



Standard Specification for Fuel System Icing Inhibitors¹

This standard is issued under the fixed designation D4171; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers additives for aviation fuels (see Specifications D910 and D1655) used to inhibit ice formation in aircraft fuel systems.

1.2 The values stated in SI units are to be regarded as standard.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:²

D56 Test Method for Flash Point by Tag Closed Cup Tester

D93 Test Methods for Flash Point by Pensky-Martens Closed Cup Tester

D268 Guide for Sampling and Testing Volatile Solvents and Chemical Intermediates for Use in Paint and Related Coatings and Material

D891 Test Methods for Specific Gravity, Apparent, of Liquid Industrial Chemicals

D910 Specification for Aviation Gasolines

D1078 Test Method for Distillation Range of Volatile Organic Liquids

D1209 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)

D1296 Test Method for Odor of Volatile Solvents and Diluents

D1353 Test Method for Nonvolatile Matter in Volatile Solvents for Use in Paint, Varnish, Lacquer, and Related Products

D1364 Test Method for Water in Volatile Solvents (Karl Fischer Reagent Titration Method)

D1476 Test Method for Heptane Miscibility of Lacquer Solvents

D1613 Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish, Lacquer, and Related Products

D1655 Specification for Aviation Turbine Fuels

D1722 Test Method for Water Miscibility of Water-Soluble Solvents

D3828 Test Methods for Flash Point by Small Scale Closed Cup Tester

D4052 Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter

D5006 Test Method for Measurement of Fuel System Icing Inhibitors (Ether Type) in Aviation Fuels

E1 Specification for ASTM Liquid-in-Glass Thermometers

E70 Test Method for pH of Aqueous Solutions With the Glass Electrode

E203 Test Method for Water Using Volumetric Karl Fischer Titration

E300 Practice for Sampling Industrial Chemicals

E450 Method for Measurement of Color of Low-Colored Clear Liquids Using the Hunterlab Color Difference Meter³

E1064 Test Method for Water in Organic Liquids by Coulometric Karl Fischer Titration

3. Classification

3.1 Two types of fuel system icing inhibitors are provided as follows:

3.1.1 *Type I*—Ethylene glycol monomethyl ether is used as an anti-icing additive in both aviation gasoline and aviation turbine fuels.

NOTE 1—Ethylene glycol monomethyl ether (EGME) was previously included in this specification, last appearing in D4171–94. EGME is considered technically satisfactory for this application, but has been generally replaced by DiEGME due to availability, reduced toxicological concerns, and lack of widely available methodology to determine FSII

¹ This specification is under the jurisdiction of ASTM Committee D02 on Petroleum Products and Lubricants and is the direct responsibility of Subcommittee D02.J0.04 on Additives and Electrical Properties.

Current edition approved Dec. 1, 2003. Published January 2004. Originally approved in 1982. Last previous edition approved in 1998 as D4171–98. DOI: 10.1520/D4171-03.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Withdrawn.

concentration in aviation fuels when a mixture is known to be present, or when the identity of the FSII present in the fuel is not clearly known.

3.2 *Type II*—Anhydrous isopropanol, also described as 99 % grade 2-Propanol or isopropyl alcohol, is used as an anti-icing additive in aviation gasoline. (**Warning**—Isopropanol (2-Propanol) is both flammable and an irritant; use with caution.)

3.3 *Type III*—Diethylene glycol monomethyl ether (DiEGME) is used as an anti-icing additive in both aviation gasoline and aviation turbine fuel. (**Warning**—Diethylene glycol monomethyl ether, (DiEGME). Combustible, toxic material.)

3.3.1 Test Method **D5006** can be used to determine the concentration of DiEGME in aviation fuels.

4. Properties

4.1 *Type II*—Isopropanol anti-icing additive shall conform to the requirements of **Table 1**, as manufactured.

4.2 *Type III*—Diethylene glycol monomethyl ether shall conform to the requirements of **Table 2**, as manufactured.

5. Sampling

5.1 The material shall be sampled in accordance with Practice **E300**.

6. Test Methods

6.1 The properties enumerated in this specification shall be determined in accordance with the following ASTM methods:

TABLE 1 Detailed Requirements for Isopropanol (99 % Grade) (Type II) FSII

Property	Requirement	ASTM Test Method
Acidity, max, mg KOH/g	0.019	D1613
Relative density:		
20/20°C	0.785 to 0.787	D268
25/25°C	0.782 to 0.784	D268
Color, platinum-cobalt, max	10	D1209 or E450
Distillation range, max, °C	1.5 (including 82.3°C)	D1078
Nonvolatile matter, max, mg/100 mL	5	D1353
Odor	characteristic, nonresidual	D1296
Water, max, mass %	0.2	D1364
Heptane miscibility at 20°C	miscible without turbidity with 19 vol 99 % heptane	D1476
Water miscibility at 25°C	miscible without turbidity when diluted with 10 vol distilled water	D1722

TABLE 2 Detailed Requirements for Fuel System Icing Inhibitors (Type III)

Property	Requirement	
	DiEGME (Type III)	ASTM Test Method
Acid number, max, mg KOH/g	0.09	D1613
Color, platinum-cobalt, max	10	D1209 or E450
Purity, min, mass %	99.0	Annex A1
pH of 25 % solution in water (25 ± 2°C)	5.5–7.5	E70 ^A
Relative density, 20°/20°C	1.020–1.025	D891 (Method A or B) or D4052
Water, max, mass %		D1364, E1064, or E203
Point of manufacture	0.10	
Point of use	0.8	
Flash point, min, °C	85°C	D93, D56, or D3828
Antioxidant, mg/kg	50–150	^B

^A Twenty-five millilitres of the inhibitor shall be pipetted into a 100-ml volumetric flask and filled with freshly boiled and cooled distilled water having a pH of 6.5 to 7.5. The pH value shall be measured with a pH meter calibrated in accordance with Test Method **E70**.

^B Acceptable antioxidants are: 2,6-ditertiary-butyl-4-methylphenol, 2,4-dimethyl-6-tertiary-butyl phenol, 2,6-ditertiary-butyl phenol, and 75 % min 2,6-ditertiary-butyl phenol plus 25 % max tertiary and tritertiary butyl phenols.

6.1.1 *Relative Density*—Determine the relative density (that is, specific gravity) at 20 or 25°C with respect to water by a method accurate to the third decimal place. See Section 5 of Test Method **D268**, Test Method **D4052**, or Method A or B of Test Methods **D891**.

6.1.2 *Color*—Test Method **D1209** or **E450**.

6.1.3 *Distillation Range*—Test Method **D1078** using ASTM Solvents Distillation Thermometers (40C with a range from 72 to 126°C for isopropanol) conforming to the requirements of Specification **E1**.

6.1.4 *Nonvolatile Matter*—Test Method **D1353**.

6.1.5 *Odor*—Test Method **D1296**.

6.1.6 *Water*—Test Method **D1364**, **E1064**, or **E203**.

6.1.7 *Heptane Miscibility*—Test Method **D1476**.

6.1.8 *Acidity*—Test Method **D1613**.

6.1.9 *Water Miscibility*—Test Method **D1722**.

6.1.10 *Flash Point*—Test Methods **D56**, **D93**, or **D3828**.

7. Keywords

7.1 additives; aircraft fuel systems; aviation fuels; fuel system icing inhibitors; ice formation