

SLOVENSKI STANDARD SIST EN 1143-1:2005+A1:2009

01-april-2009

Varnostne shranjevalne enote - Zahteve, klasifikacija in metode preskušanja protivlomne odpornosti - 1. del: Blagajne, bankomatne blagajne, vrata trezorskih prostorov in trezorski prostori

Secure storage units - Requirements, classification and methods of test for resistance to burglary - Part 1: Safes, ATM safes, strongroom doors and strongrooms

Wertbehältnisse - Anforderungen, Klassifizierung und Methoden zur Prüfung des Widerstandes gegen Einbruchdiebstahl - Teil 1: Wertschutzschränke, Wertschutzschränke für Geldautomaten, Wertschutzraumtüren und Wertschutzräume

Unités de stockage en lieux sûrs - Exigences, classification et méthodes d'essai pour la résistance à l'effraction - Partie 13 Coffres forts, distributeurs automatiques de billets (DAB), portes fortes et chambres fortes

Ta slovenski standard je istoveten z: EN 1143-1:2005+A1:2009

ICS:

13.310 Varstvo pred kriminalom Protection against crime
35.220.99 Druge naprave za Other data storage devices

shranjevanje podatkov

SIST EN 1143-1:2005+A1:2009 en,fr

SIST EN 1143-1:2005+A1:2009

iTeh STANDARD PREVIEW (standards.iteh.ai)

EUROPEAN STANDARD NORME EUROPÉENNE

EUROPÄISCHE NORM

EN 1143-1:2005+A1

January 2009

ICS 13.310

Supersedes EN 1143-1:2005

English Version

Secure storage units - Requirements, classification and methods of test for resistance to burglary - Part 1: Safes, ATM safes, strongroom doors and strongrooms

Unités de stockage en lieux sûrs - Exigences, classification et méthodes d'essai pour la résistance à l'effraction - Partie 1: Coffres-forts, distributeurs automatiques de billets (DAB), portes fortes et chambres fortes

Wertbehältnisse - Anforderungen, Klassifizierung und Methoden zur Prüfung des Widerstandes gegen Einbruchdiebstahl - Teil 1: Wertschutzschränke, Wertschutzschränke für Geldautomaten, Wertschutzraumtüren und Wertschutzräume

This European Standard was approved by CEN on 7 July 2005 and includes Amendment 1 approved by CEN on 20 December 2008.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom. 1-2009



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Forew	vord	4
Introd	duction	5
1	Scope	6
2	Normative references	6
3	Terms and definitions	6
4	Classification and requirements	8
4.1	Classification	8
4.2	General requirements	9
4.2.1	Safes, strongroom doors and strongrooms	9
4.2.2	ATM safes	9
4.2.3	Boltwork cover plate	9
4.2.4	Cable hole	9
4.2.5	User instructions iTeh STANDARD PREVIEW	9
4.3	Additional requirements for EX designation r.d.s.itoh.ai.	9
4.4	Additional requirements for CD designation	10
5	Technical documentation SIST EN 1143-1:2005+A1:2009 https://standards.iteh.a/catalog/standards/sist/td063955-6eb1-4t64-93b6-	14
6	Test specimen	15
7	Tool attack test	15
7.1	Principle	15
7.2	Testing team	15
7.3	Apparatus	16
7.3.1	Attack tools	16
7.3.2	Clock	16
7.3.3	Test blocks	16
7.4	Test criteria	17
7.5	Testing programme	17
7.5.1	Free-standing safes	17
7.5.2	Built-in safes	18
7.5.3	Strongrooms	18
7.5.4	Grades I to VIII ATM safes	18
7.5.5	Grade L ATM safes	19
7.6	Test conditions	20
7.7	Procedure	21
7.8	Operating time measuring	22
7.9	Calculation of resistance values	23
7.10	Test record	23

8	Anchoring strength test	. 24
8.1	Free-standing safes	. 24
8.1.1	Principle	.24
8.1.2	Loading equipment	.24
8.1.3	Procedure	. 25
8.1.4	Expression of test results	. 25
8.1.5	Test criteria	. 25
8.2	ATM safes	. 25
8.2.1	Principle	. 25
8.2.2	Loading equipment	. 25
8.2.3	Procedure	. 25
8.2.4	Expression of results	. 26
8.2.5	Test criteria	. 26
9	Explosive test	. 26
9.1	Principle	.26
9.2	Test specimen	.26
9.3	Explosives	. 27
9.4	Determination of explosive charge mass. Determination of explosive charge mass.	. 27
9.5	Conditions for explosive attacktestndards.iteh.ai)	. 27
9.5.1	Safes and ATM safes	. 27
9.5.2	SIST EN 1143-1:2005+A1:2009 Strongroom doors and strongrooms hips//stantards/sisviti063955-6eb1-4f64-93b6-	. 27
9.6	Calculation of resistance values for the post-detonation tool attack	
9.7	Test record	. 28
10	A) Core drilling test	. 28
10.1	Principle	. 28
10.2	Test specimen	. 28
10.3	Apparatus	. 29
10.3.1	Safes	. 29
10.3.2	Strongroom doors and strongrooms	. 29
10.4	Test method	. 29
10.5	Calculation of resistance value	. 29
10.6	Marking (A)	. 29
11	Test report	. 30
12	Marking	. 30
Annex	A (normative) Attack tools	. 32

SIST EN 1143-1:2005+A1:2009

EN 1143-1:2005+A1:2009 (E)

Foreword

This document (EN 1143-1:2005+A1:2009) has been prepared by Technical Committee CEN/TC 263 "Secure storage of cash, valuables and data media" the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by July 2009, and conflicting national standards shall be withdrawn at the latest by July 2009.

This document includes Amendment 1, approved by CEN on 2008-12-20.

This document supersedes (A) EN 1143-1:2005 (A).

The start and finish of text introduced or altered by amendment is indicated in the text by tags [A].

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

iTeh STANDARD PREVIEW (standards.iteh.ai)

Introduction

Tests are made, the results of which are used to classify the resistance to burglary. The resistance classification can also be used for designing security systems with the provision that, depending on the criminal, the conditions at the place of the crime and the availability of tools, considerably longer times are likely to occur in real burglary attacks than in a test.

Manual tests are included whose results and repeatability is dependant on the skill of the testing team. Machine related tests are under development and may be included when this European Standard is revised.

iTeh STANDARD PREVIEW (standards.iteh.ai)

1 Scope

This European Standard establishes the basis for testing and classifying free-standing safes, built-in safes (floor and wall), ATM safes and ATM bases, strongroom doors and strongrooms (with or without a door) according to their burglary resistance. This European Standard does not cover testing and classifying Deposit Systems and ATM systems.

2 Normative references

The following referenced documents are indispensable for the application of this European Standard. For dated references, only the edition cited applies. For undated references the latest edition of the referenced document (including any amendments) applies.

EN 1300, Secure storage units — Classification for high security locks according to their resistance to unauthorized opening

Terms and definitions 3

For the purposes of this European Standard, the following terms and definitions apply.

3.1

iTeh STANDARD PREVIEW

storage unit which protects its contents against burglary and when closed has at least one internal side ≤ 1 m length (stangargs.iten.ai)

3.2

SIST EN 1143-1:2005+A1:2009 free-standing safe

safe whose protection against burglary depends only upon the materials and construction of its primary manufacture and not upon materials added or attached during installation

3.3

built-in safe

safe whose protection against burglary is partly dependent upon materials incorporated into it, or attached to it, during installation

NOTE Under floor safes and wall safes are special types of built-in safes.

3.4

strongroom

storage unit which protects against burglary and when closed has internal side lengths in all directions > 1 m

NOTE Strongrooms may be cast in-situ, constructed from pre-fabricated elements or a combination of both.

3.5

strongroom door

door with lock(s), boltwork and frame intended for giving access to a strongroom

3.6

ATM safe

safe forming part of an ATM system

3.7

ATM base

any integral part of an ATM system located between the ATM safe and the surface to which the safe is to be anchored

3.8

internal space

part of the interior of an ATM safe which is bounded by the inside surfaces and the boltwork cover plate(s) of the door of the ATM safe body

3.9

ATM (automatic teller machine)

means for holding and processing cash and/or valuables

NOTE For the purpose of this standard, automated teller machines, currency exchange machines, currency recycling machines and machines such as teller assist machines are all types of ATM.

3.10

ATM-System

assembly of sub-units which provides an ATM function and affords security to cash and/or valuables stored within the ATM safe

NOTE 1 An example of an ATM system is shown in Figure 1.



Figure 1 — Example of an ATM system

NOTE 2 Of the sub-units shown in Figure 1, the ATM mechanism and the ATM control unit are not tested according to this European Standard.

3.11

accessories

installations/devices which are in the structure or which pass through the structure of the strongroom or strongroom door(s) for ventilation or for deposit of cash and valuables

NOTE Accessories may be always open, usually open (but can be closed in case of emergency), or closed (but can be opened if necessary).

3.12

operating time

time during which a tool is used attempting to create a change in the test specimen

3.13

resistance unit (RU)

burglary resistance which results from one minute's use of a tool carrying the coefficient 1 and the basic value 0

3.14

resistance grade

classification designation for burglary resistance

3.15

resistance value

numerical value in resistance units calculated for each test

3.16

basic value (BV)

number in resistance units allocated to a particular tool

The basic value represents problems in obtaining, transporting, using and operating the relevant tool at the site in question and the necessary knowledge and experience for its efficient use.

3.17

tool coefficient

number in resistance units per minute allocated to a group of tools

The tool coefficient represents factors such as noise, smoke, fumes and other effects, which increase the likelihood of a burglary attack being detected.

3.18

boltwork

mechanism by which a shut door is held such that until it is in the withdrawn position the door cannot be opened

3.19

lock

device able to recognize a coded input and which performs a blocking function on the boltwork or the door

iTeh STANDARD PREVIEW 3.20

relocking device

relocking device system comprising blocking and detecting elements which will prevent the boltwork from being withdrawn if a burglary attack is detected

SIST EN 1143-1:2005+A1:2009

NOTE A relocking device can be part of the locking mechanism (e.g. active or live relocker) or an independent unit (e.g. 186c8768d374/sist-en-1143-1-2005a1-2009 passive relocker).

3.21

to move the door so it becomes possible to bolt it

3.22

to bolt

to throw the boltwork or the bolt of the lock (if there is no boltwork) to a position where it fixes the door in closed position

3.23

to lock

to block a thrown boltwork by action of a lock

Classification and requirements

4.1 Classification

Safes are classified to a resistance grade according to Table 1.

ATM safes are classified to a resistance grade according to Table 2.

Strongroom doors and strongrooms (with or without door) are classified to a resistance grade according to Table 3.

All products shall meet general requirements (4.2) and products with EX and CD designation shall meet additional requirements (4.3 and 4.4).

4.2 General requirements

4.2.1 Safes, strongroom doors and strongrooms

There shall be no holes through the protection material other than those necessary for locks, cables or anchoring, or for the fitting of accessories to strongroom doors and strongrooms.

Cable openings in safes, strongroom doors and strongrooms (with or without a door) shall not exceed 100 mm². Unused cable entry openings shall be obstructed or plugged by the manufacturer by means which cannot be removed from the outside without leaving visible traces.

Free-standing safes with a mass of less than 1 000 kg shall have at least one hole by which they can be anchored. The anchoring assembly for each anchoring hole shall sustain the force given in Table 1.

4.2.2 ATM safes

ATM safes shall have means for plugging unused openings. These means shall be impossible to remove from the outside without leaving visible traces.

- NOTE 1 Openings through the protection material for ATM functioning are permitted in ATM safes.
- NOTE 2 Cable entry openings in ATM safes may be larger than 100 mm².

ATM safes shall have a fixing capability by which they can be anchored and which shall sustain the required force given in Table 2.

4.2.3 Boltwork cover plate (standards.iteh.ai)

Safes, ATM safes and strongroom doors shall have an internal boltwork cover plate which prevents unauthorized viewing of the locks and boltwork and access to them; when the door is open; Boltwork cover plates shall be secured so that they cannot be opened or removed without leaving visible traces.

4.2.4 Cable hole

Safes, strongroom doors and strongrooms of grade III and higher shall either have a hole for a cable or a preparation enabling a connection to be made to an alarm system after the secure storage unit has been installed.

4.2.5 User instructions

Safes, strongrooms and ATM safes shall be provided with operating and maintenance instructions, including instructions in respect of the locks. Free-standing safes and ATM safes shall have instructions for anchoring. For built-in safes, strongroom doors and strongrooms, installation instructions shall be provided.

4.3 Additional requirements for EX designation

When tested in accordance with Clause 9, safes of resistance grades II to X designated 'EX' shall achieve the minimum post-detonation resistance values given in Table 1. EX designation is not applicable to safes of resistance grade 0 to I.

When tested in accordance with Clause 9, ATM safes of resistance grades II to VIII designated 'EX' shall achieve the minimum post-detonation resistance values given in Table 2. EX designation is not applicable to ATM safes of resistance grades L and I.

When tested in accordance with Clause 9, strongroom doors and strongrooms (with or without doors) of resistance grades II to XIII designated 'EX' shall achieve the minimum post-detonation resistance values given in Table 3. EX designation is not applicable to strongroom doors and strongrooms of resistance grades 0 and I.

When tested in accordance with Clause 9, the cable-entry openings of safes, strongroom doors and strongrooms (with or without doors) shall not permit the entry of explosives (e.g. fuses or charges).

SIST EN 1143-1:2005+A1:2009

EN 1143-1:2005+A1:2009 (E)

4.4 Additional requirements for CD designation

When tested in accordance with Clause 10, safes of resistance grades IV to X designated "CD" shall achieve the minimum resistance values given in Table 1. CD designation is not applicable to safes of resistance grades 0 to III and ATM safes.

When tested in accordance with Clause 10, strongroom doors and strongrooms (with or without door) of resistance grades V to XIII designated "CD" shall achieve the minimum resistance values given in Table 3. CD designation is not applicable to strongroom doors and strongrooms of resistance grades 0 to III.

iTeh STANDARD PREVIEW (standards.iteh.ai)