

ETSI TS 125 101 V9.2.0 (2010-02)

Technical Specification

Universal Mobile Telecommunications System (UMTS); User Equipment (UE) radio transmission and reception (FDD) (3GPP TS 25.101 version 9.2.0 Release 9)



iteh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/0d3aa4de-dd6f-43a1-8561-ee263b26b056/etsi-ts-125-101-v9.2.0-2010-02>

Reference

RTS/TSGR-0425101v920

Keywords

UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™, TIPHON™, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered
for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

iteh STANDARD PRE-TEXT
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/0d3a1-8561-ee263b26b056/etsi-ts-125-101-v9.2.0>
2010-02

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	10
1 Scope	11
2 References	11
3 Definitions, symbols and abbreviations	11
3.1 Definitions.....	11
3.2 Abbreviations	12
4 General	14
4.1 Relationship between Minimum Requirements and Test Requirements	14
4.2 Power Classes.....	15
4.3 Control and monitoring functions	15
4.3.1 Minimum requirement	15
4.4 RF requirements in later releases	15
5 Frequency bands and channel arrangement.....	15
5.1 General	15
5.2 Frequency bands.....	15
5.3 TX-RX frequency separation	16
5.4 Channel arrangement.....	17
5.4.1 Channel spacing.....	17
5.4.2 Channel raster	17
5.4.3 Channel number	17
5.4.4 UARFCN	19
6 Transmitter characteristics	19
6.1 General	19
6.2 Transmit power	20
6.2.1 UE maximum output power.....	20
6.2.2 UE maximum output power with HS-DPCCH and E-DCH.....	20
6.2.2A UE maximum output power for DC-HSUPA	21
6.2.3 UE Relative code domain power accuracy	21
6.3 Frequency Error.....	22
6.3A Frequency Error for DC-HSUPA	22
6.4 Output power dynamics.....	23
6.4.1 Open loop power control	23
6.4.1.1 Minimum requirement	23
6.4.1.1A Additional requirement for DC-HSUPA	23
6.4.2 Inner loop power control in the uplink.....	23
6.4.2.1 Power control steps	23
6.4.2.1.1 Minimum requirement	23
6.4.3 Minimum output power	24
6.4.3.1 Minimum requirement	24
6.4.3.1A Additional requirement for DC-HSUPA	24
6.4.4 Out-of-synchronization handling of output power.....	24
6.4.4.1 Minimum requirement	25
6.4.4.2 Test case.....	25
6.5 Transmit ON/OFF power	27
6.5.1 Transmit OFF power.....	27
6.5.1.1 Minimum requirement	27
6.5.1.1A Additional requirement for DC-HSUPA	27
6.5.2 Transmit ON/OFF Time mask	28
6.5.2.1 Minimum requirement	28
6.5.3 Change of TFC	31

6.5.3.1	Minimum requirement	31
6.5.4	Power setting in uplink compressed mode.....	32
6.5.4.1	Minimum requirement	32
6.5.5	HS-DPCCH.....	34
6.5.5.1	Minimum requirement	34
6.6	Output RF spectrum emissions.....	35
6.6.1	Occupied bandwidth	35
6.6.1A	Occupied bandwidth for DC-HSUPA.....	36
6.6.2	Out of band emission	36
6.6.2.1	Spectrum emission mask.....	36
6.6.2.1.1	Minimum requirement	36
6.6.2.1A	Additional Spectrum emission mask for DC-HSUPA	37
6.6.2.1A.1	Minimum requirement.....	37
6.6.2.1A.2	Additional requirement for band II, IV, V and X	38
6.6.2.2	Adjacent Channel Leakage power Ratio (ACLR).....	38
6.6.2.2.1	Minimum requirement	38
6.6.2.2.1A	Additional requirement for DC-HSUPA	39
6.6.3	Spurious emissions	39
6.6.3.1	Minimum requirement	39
6.6.3.1A	Additional requirement for DC-HSUPA	41
6.7	Transmit intermodulation	45
6.7.1	Minimum requirement	45
6.7.1A	Additional requirement for DC-HSUPA.....	45
6.8	Transmit modulation	45
6.8.1	Transmit pulse shape filter.....	45
6.8.2	Error Vector Magnitude.....	46
6.8.2.1	Minimum requirement	46
6.8.2.1A	Additional requirement for DC-HSUPA.....	47
6.8.3	Peak code domain error	47
6.8.3.1	Minimum requirement	47
6.8.3a	Relative code domain error.....	47
6.8.3a.1	Relative Code Domain Error.....	47
6.8.3a.1.1	Minimum requirement	48
6.8.3b	In-band emission for DC-HSUPA	49
6.8.3b.1	Minimum requirement for DC-HSUPA	49
6.8.4	Phase discontinuity for uplink DPCH.....	49
6.8.4.1	Minimum requirement	49
6.8.5	Phase discontinuity for HS-DPCCH.....	50
6.8.5.1	Minimum requirement	50
6.8.6	Phase discontinuity for E-DCH	50
6.8.6.1	Minimum requirement	51
6.8.7	Time alignment error for DC-HSUPA	51
6.8.7.1	Minimum requirement	52
7	Receiver characteristics	52
7.1	General	52
7.2	Diversity characteristics	52
7.3	Reference sensitivity level.....	52
7.3.1	Minimum requirement	53
7.3.2	Additional requirement for DC-HSDPA.....	53
7.3.3	Additional requirement for DB-DC-HSDPA	54
7.4	Maximum input level	55
7.4.1	Minimum requirement for DPCH reception	55
7.4.2	Minimum requirement for HS-PDSCH reception.....	55
7.4.2.1	Minimum requirement for 16QAM.....	55
7.4.2.2	Minimum requirement for 64QAM.....	56
7.4.3	Additional requirement for DC-HSDPA and DB-DC-HSDPA	56
7.4.3.1	Additional requirement for 16QAM.....	56
7.4.3.2	Additional requirement for 64QAM.....	57
7.5	Adjacent Channel Selectivity (ACS).....	58
7.5.1	Minimum requirement	58
7.5.2	Additional requirement for DC-HSDPA and DB-DC-HSDPA	58

7.6	Blocking characteristics	59
7.6.1	Minimum requirement (In-band blocking)	59
7.6.1A	Additional requirement for DC-HSDPA and DB-DC-HSDPA	60
7.6.2	Minimum requirement (Out of-band blocking)	62
7.6.2A	Additional requirement for DC-HSDPA (Out of-band blocking).....	64
7.6.2B	Additional requirement for DB-DC-HSDPA (Out of-band blocking).....	66
7.6.3	Minimum requirement (Narrow band blocking)	67
7.6.3A	Additional requirement for DC-HSDPA and DB-DC-HSDPA (Narrow band blocking)	68
7.7	Spurious response.....	68
7.7.1	Minimum requirement	68
7.7.2	Additional requirement for DC-HSDPA and DB-DC-HSDPA	69
7.8	Intermodulation characteristics	69
7.8.1	Minimum requirement	69
7.8.1A	Additional requirement for DC-HSDPA and DB-DC-HSDPA	69
7.8.2	Minimum requirement (Narrow band).....	70
7.8.2A	Additional requirement for DC-HSDPA and DB-DC-HSDPA (Narrow band).....	70
7.9	Spurious emissions	71
7.9.1	Minimum requirement	71
8	Performance requirement	75
8.1	General	75
8.2	Demodulation in static propagation conditions	75
8.2.1	(void)	75
8.2.2	(void)	75
8.2.3	Demodulation of Dedicated Channel (DCH)	75
8.2.3.1	Minimum requirement	75
8.3	Demodulation of DCH in multi-path fading propagation conditions	76
8.3.1	Single Link Performance	76
8.3.1.1	Minimum requirement	76
8.4	Demodulation of DCH in moving propagation conditions	79
8.4.1	Single link performance	79
8.4.1.1	Minimum requirement	79
8.5	Demodulation of DCH in birth-death propagation conditions	80
8.5.1	Single link performance	80
8.5.1.1	Minimum requirement	80
8.5A.1	General.....	80
8.5A.2	Minimum requirement	80
8.6	Demodulation of DCH in downlink Transmit diversity modes.....	81
8.6.1	Demodulation of DCH in open-loop transmit diversity mode	81
8.6.1.1	Minimum requirement	81
8.6.2	Demodulation of DCH in closed loop transmit diversity mode	82
8.6.2.1	Minimum requirement	82
8.6.3	(void)	83
8.7	Demodulation in Handover conditions.....	83
8.7.1	Demodulation of DCH in Inter-Cell Soft Handover	83
8.7.1.1	Minimum requirement	83
8.7.2	Combining of TPC commands from radio links of different radio link sets.....	84
8.7.2.1	Minimum requirement	84
8.7.3	Combining of reliable TPC commands from radio links of different radio link sets	85
8.7.3.1	Minimum requirement	85
8.8	Power control in downlink	85
8.8.1	Power control in the downlink, constant BLER target	86
8.8.1.1	Minimum requirements	86
8.8.2	Power control in the downlink, initial convergence.....	87
8.8.2.1	Minimum requirements	87
8.8.3	Power control in downlink, wind up effects	88
8.8.3.1	Minimum requirements	88
8.8.4	Power control in the downlink, different transport formats	89
8.8.4.1	Minimum requirements	89
8.8.5	Power control in the downlink for F-DPCH	90
8.8.5.1	Minimum requirements	90
8.9	Downlink compressed mode	91

8.9.1	Single link performance	91
8.9.1.1	Minimum requirements	91
8.10	Blind transport format detection.....	92
8.10.1	Minimum requirement	92
8.11	Detection of Broadcast channel (BCH).....	93
8.11.1	Minimum requirement without transmit diversity	93
8.11.2	Minimum requirement with open loop transmit diversity	93
8.12	Demodulation of Paging Channel (PCH)	93
8.12.1	Minimum requirement	94
8.13	Detection of Acquisition Indicator (AI)	94
8.13.1	Minimum requirement	94
8.13A	Detection of E-DCH Acquisition Indicator (E-AI)	95
8.13A.1	Minimum requirement	95
8.14	UE UL power control operation with discontinuous UL DPCCH transmission operation	95
8.14.1	Minimum requirement	95
8.15	(void)	97
8.16	(void)	97
9	Performance requirement (HSDPA)	97
9.1	(void)	97
9.2	Demodulation of HS-DSCH (Fixed Reference Channel).....	97
9.2.1	Single Link performance	105
9.2.1.1	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 1/2/3/3A	106
9.2.1.2	Requirement 16QAM, Fixed Reference Channel (FRC) H-Set 1/2/3	107
9.2.1.3	Minimum requirement QPSK, Fixed Reference Channel (FRC) H-Set 4/5	108
9.2.1.4	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 6/6A	109
9.2.1.5	Requirement 16QAM, Fixed Reference Channel (FRC) H-Set 6/6A	111
9.2.1.6	Requirement 64QAM, Fixed Reference Channel (FRC) H-Set 8/8A	113
9.2.1.7	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 10/10A	114
9.2.1.8	Requirement 16QAM, Fixed Reference Channel (FRC) H-Set 10/10A	115
9.2.2	Open Loop Diversity performance	116
9.2.2.1	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 1/2/3/3A	116
9.2.2.2	Requirement 16QAM, Fixed Reference Channel (FRC) H-Set 1/2/3/3A	117
9.2.2.3	Minimum requirement QPSK, Fixed Reference Channel (FRC) H-Set 4/5	118
9.2.3	Closed Loop Diversity Performance	119
9.2.3.1	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 1/2/3	119
9.2.3.2	Requirement 16QAM, Fixed Reference Channel (FRC) H-Set 1/2/3	121
9.2.3.3	Minimum requirement QPSK, Fixed Reference Channel (FRC) H-Set 4/5	122
9.2.3.4	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 6	123
9.2.3.5	Requirement 16QAM, Fixed Reference Channel (FRC) H-Set 6	123
9.2.4	MIMO Performance.....	124
9.2.4.1	Requirement Fixed Reference Channel (FRC) H-Set 9/9A	124
9.2.4.2	Requirement Fixed Reference Channel (FRC) H-Set 11/11A	125
9.2.4A	MIMO only with single-stream restriction Performance	126
9.2.4A.1	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 1/1A	126
9.2.4A.2	Requirement 16QAM, Fixed Reference Channel (FRC) H-Set 1/1A	127
9.3	Reporting of Channel Quality Indicator	128
9.3.1	Single Link Performance	129
9.3.1.1	AWGN propagation conditions	129
9.3.1.1.1	Minimum Requirement – UE HS-DSCH categories 1-20	129
9.3.1.1.2	Minimum Requirement – UE HS-DSCH categories 13,14,17,18, 19 and 20	130
9.3.1.1.3	Additional Requirements – UE HS-DSCH categories 21, 22, 23, 24, 25, 26, 27 and 28	131
9.3.1.2	Fading propagation conditions	132
9.3.1.2.1	Minimum Requirement – UE HS-DSCH categories 1-20	132
9.3.1.2.2	Minimum Requirement – UE HS-DSCH categories 13,14,17,18, 19 and 20	133
9.3.1.2.3	Additional Requirements – UE HS-DSCH categories 21, 22, 23, 24, 25, 26, 27 and 28	134
9.3.1.3	Periodically varying radio conditions.....	135
9.3.1.3.1	Minimum Requirement – UE HS-DSCH categories 1-20	135
9.3.2	Open Loop Diversity Performance	137
9.3.2.1	AWGN propagation conditions	137
9.3.2.1.1	Minimum Requirement – UE HS-DSCH categories 1-20	137
9.3.2.1.2	Additional Requirements – UE HS-DSCH categories 21, 22, 23, 24, 25, 26, 27 and 28	138

9.3.2.2	Fading propagation conditions	139
9.3.2.2.1	Minimum Requirement – UE HS-DSCH categories 1-20	139
9.3.2.2.2	Additional Requirements – UE HS-DSCH categories 21, 22, 23, 24, 25, 26, 27 and 28	140
9.3.2.3	Periodically varying radio conditions.....	141
9.3.2.3.1	Minimum Requirement – UE HS-DSCH categories 1-20.....	141
9.3.3	Closed Loop Diversity Performance.....	142
9.3.3.1	AWGN propagation conditions	142
9.3.3.1.1	Minimum Requirement – UE HS-DSCH categories 1-20.....	142
9.3.3.2	Fading propagation conditions	143
9.3.3.2.1	Minimum Requirement – UE HS-DSCH categories 1-20.....	143
9.3.3.3	Periodically varying radio conditions.....	144
9.3.3.3.1	Minimum Requirement – UE HS-DSCH categories 1-20.....	144
9.3.4	MIMO Performance.....	146
9.3.4.1	MIMO Single Stream Fading Conditions	146
9.3.4.1.1	Minimum Requirement - UE HS-DSCH categories 15-20.....	147
9.3.4.1.2	Additional Requirement – UE HS-DSCH categories 25-28	148
9.3.4.2	MIMO Dual Stream Fading Conditions	150
9.3.4.2.1	Minimum Requirement – UE HS-DSCH categories 15-20.....	150
9.3.4.2.2	Minimum Requirement – UE HS-DSCH categories 19-20.....	151
9.3.4.2.3	Additional Requirement – UE HS-DSCH categories 25-28	153
9.3.4.2.4	Additional Requirement – UE HS-DSCH categories 27-28	154
9.3.4.3	MIMO Dual Stream Static Orthogonal Conditions.....	157
9.3.4.3.1	Minimum Requirement –UE HS-DSCH categories 15-20.....	157
9.3.4.3.2	Minimum Requirement –UE HS-DSCH categories 19-20	158
9.3.4.3.3	Additional Requirement – UE HS-DSCH categories 25-28	158
9.3.4.3.4	Additional Requirement – UE HS-DSCH categories 27-28	159
9.3.5	MIMO only with single-stream restriction Performance	160
9.3.5.1	MIMO only with single-stream restriction Fading Conditions	160
9.3.5.1.1	Minimum Requirement	160
9.4	HS-SCCH Detection Performance	162
9.4.1	HS-SCCH Type 1 Single Link Performance	162
9.4.2	HS-SCCH Type 1 Open Loop Diversity Performance	163
9.4.3	HS-SCCH Type 3 Performance	163
9.4.4	HS-SCCH Type 3 Performance for MIMO only with single-stream restriction.....	164
9.5	HS-SCCH-less demodulation of HS-DSCH (Fixed Reference Channel).....	165
9.5.1	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 7	166
9.6	Requirements for HS-DSCH and HS-SCCH reception in CELL_FACH state	166
9.6.1	HS-DSCH demodulation requirements (Single Link)	166
9.6.1.1	Requirement QPSK, Fixed Reference Channel (FRC) H-Set 3	166
9.6.2	HS-SCCH Detection Performance.....	167
9.6.2.1	HS-SCCH Type 1 Single Link Performance	167
10	Performance requirement (E-DCH)	168
10.1	General	168
10.2	Detection of E-DCH HARQ ACK Indicator Channel (E-HICH)	168
10.2.1	Single link performance.....	168
10.2.1.1	Performance requirement	168
10.2.2	Detection in Inter-Cell Handover conditions	169
10.2.2.1	Performance requirement for RLS not containing the Serving E-DCH cell	169
10.2.2.2	Performance requirement for RLS containing the serving E-DCH cell	171
10.3	Detection of E-DCH Relative Grant Channel (E-RGCH)	172
10.3.1	Single link performance	172
10.3.1.1	Performance requirement	172
10.3.2	Detection in Inter-Cell Handover conditions	174
10.3.2.1	Performance requirement for Non-serving E-DCH RL	174
10.4	Demodulation of E-DCH Absolute Grant Channel (E-AGCH)	175
10.4.1	Single link performance	175
10.4.1.1	Performance requirement	175
11	Performance requirement (MBMS).....	175
11.1	Demodulation of MCCH	176
11.1.1	Minimum requirement	176

11.1.2	Minimum requirement for MBSFN	176
11.2	Demodulation of MTCH	176
11.2.1	Minimum requirement	177
11.2.2	Minimum requirement for MBSFN	177
11.3	Demodulation of MTCH and cell identification.....	178
11.3.1	Minimum requirement	178

Annex A (normative): Measurement channels..... **179**

A.1	General	179
A.2	UL reference measurement channel	179
A.2.1	UL reference measurement channel (12.2 kbps)	179
A.2.2	UL reference measurement channel (64 kbps)	180
A.2.3	UL reference measurement channel (144 kbps)	181
A.2.4	UL reference measurement channel (384 kbps)	182
A.2.5	UL reference measurement channel (768 kbps)	183
A.2.6	UL E-DCH reference measurement channel for DC-HSUPA.....	184
A.3	DL reference measurement channel	184
A.3.0	DL reference measurement channel (0 kbps)	184
A.3.1	DL reference measurement channel (12.2 kbps)	185
A.3.2	DL reference measurement channel (64 kbps)	186
A.3.3	DL reference measurement channel (144 kbps)	187
A.3.4	DL reference measurement channel (384 kbps)	188
A.3.5	DL reference measurement channel 2 (64 kbps)	189
A.4	DL reference measurement channel for BTFD performance requirements	190
A.4A	Reference parameters for discontinuous UL DPCCH transmission.....	193
A.5	DL reference compressed mode parameters.....	193
A.6	DL reference parameters for PCH tests.....	195
A.7	DL reference channel parameters for HSDPA tests	195
A.7.1	Fixed Reference Channel (FRC)	195
A.7.1.1	Fixed Reference Channel Definition H-Set 1/1A	195
A.7.1.2	Fixed Reference Channel Definition H-Set 2	196
A.7.1.3	Fixed Reference Channel Definition H-Set 3/3A	197
A.7.1.4	Fixed Reference Channel Definition H-Set 4	198
A.7.1.5	Fixed Reference Channel Definition H-Set 5	199
A.7.1.6	Fixed Reference Channel Definition H-Set 6/6A	200
A.7.1.7	Fixed Reference Channel Definition H-Set 7	201
A.7.1.8	Fixed Reference Channel Definition H-Set 8/8A	202
A.7.1.9	Fixed Reference Channel Definition H-Set 9/9A	203
A.7.1.10	Fixed Reference Channel Definition H-Set 10/10A	204
A.7.1.11	Fixed Reference Channel Definition H-Set 11/11A	205
A.7.1.12	Fixed Reference Channel Definition H-Set 12	207
A.8	DL reference parameters for MBMS tests.....	208
A.8.1	MCCH	208
A.8.1	MTCH	208
A.9	DL reference parameters for combined MTCH demodulation and cell identification.....	209

Annex B (normative) : Propagation conditions..... **210**

B.1	(void)	210
B.2	Propagation Conditions	210
B.2.1	Static propagation condition.....	210
B.2.2	Multi-path fading propagation conditions	210
B.2.3	Moving propagation conditions.....	213
B.2.4	Birth-Death propagation conditions	214
B.2.5	High speed train condition.....	214

B.2.6	MIMO propagation conditions	217
B.2.6.1	MIMO Single Stream Fading Conditions	217
B.2.6.2	MIMO Dual Stream Fading Conditions.....	218
B.2.6.3	MIMO Dual Stream Static Orthogonal Conditions	219
Annex C (normative): Downlink Physical Channels.....		220
C.1	General	220
C.2	Connection Set-up	220
C.3	During connection	220
C.3.1	Measurement of Rx Characteristics.....	220
C.3.2	Measurement of Performance requirements	221
C.3.3	Connection with open-loop transmit diversity mode.....	222
C.3.4	Connection with closed loop transmit diversity mode.....	222
C.3.5	(void)	223
C.4	W-CDMA Modulated Interferer	223
C.5	HSDPA DL Physical channels	224
C.5.1	Downlink Physical Channels connection set-up.....	224
C.5.2	OCNS Definition.....	230
C.5.3	Test Definition for Enhanced Performance Type 3i	231
C.5.3.1	Transmitted code and power characteristics for serving cell.....	231
C.5.3.2	Transmitted code and power characteristics for interfering cells	233
C.5.3.3	Model for power control sequence generation	234
C.6	MBMS DL Physical channels	235
C.6.1	Downlink Physical Channels connection set-up.....	235
C.6.2	Downlink Physical Channels connection set-up for MBSFN.....	235
Annex D (normative) : Environmental conditions.....		236
D.1	General	236
D.2	Environmental requirements	236
D.2.1	Temperature	236
D.2.2	Voltage	236
D.2.3	Vibration.....	237
Annex E (informative): UARFCN numbers		238
E.1	General	238
E.2	List of UARFCN used for UTRA FDD bands	238
Annex F (informative): Change history		241
History		243

Foreword

This Technical Specification (TS) has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iteh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/002/2a4de-dd6f-43a1-8561-ee263b26b056/etsi-ts-125-101-v9.2.0-2010-02>

1 Scope

The present document establishes the minimum RF characteristics of the FDD mode of UTRA for the User Equipment (UE).

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] (void)
- [2] ITU-R Recommendation SM.329: "Unwanted emissions in the spurious domain".
- [3] (void)
- [4] 3GPP TS 25.433: "UTRAN Iub Interface NBAP Signalling".
- [5] ETSI ETR 273: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement of radiated methods of measurement (using test sites) and evaluation of the corresponding measurement uncertainties; Part 1: Uncertainties in the measurement of mobile radio equipment characteristics; Sub-part 2: Examples and annexes".
- [6] 3GPP TS 45.004: "Modulation".
- [7] 3GPP TS 25.331: "Radio Resource Control (RRC); Protocol Specification".
- [8] 3GPP TS 25.214: "Physical layer procedures (FDD)".
- [9] 3GPP TS 25.307: "Requirements on User Equipments (UEs) supporting a release-independent frequency band".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following definitions apply:

Enhanced performance requirements type 1: This defines performance requirements which are optional for the UE. The requirements are based on UEs which utilise receiver diversity.

Enhanced performance requirements type 2: This defines performance requirements which are optional for the UE. The requirements are based on UEs which utilise a chip equaliser receiver structure.

Enhanced performance requirements type 3: This defines performance requirements which are optional for the UE. The requirements are based on UEs which utilise a chip equaliser receiver structure with receiver diversity.

Enhanced performance requirements type 3i: This defines performance requirements which are optional for the UE. The requirements are based on UEs which utilise an interference-aware chip equaliser receiver structure with receiver diversity.

Power Spectral Density: The units of Power Spectral Density (PSD) are extensively used in this document. PSD is a function of power versus frequency and when integrated across a given bandwidth, the function represents the mean power in such a bandwidth. When the mean power is normalised to (divided by) the chip-rate it represents the mean energy per chip. Some signals are directly defined in terms of energy per chip, (DPCH_E_c, E_c, OCNS_E_c and S-CCPCH_E_c) and others defined in terms of PSD (I_o, I_{oc}, I_{or} and \hat{I}_{or}). There also exist quantities that are a ratio of energy per chip to PSD (DPCH_E_c/I_{or}, E_c/I_{or} etc.). This is the common practice of relating energy magnitudes in communication systems.

It can be seen that if both energy magnitudes in the ratio are divided by time, the ratio is converted from an energy ratio to a power ratio, which is more useful from a measurement point of view. It follows that an energy per chip of X dBm/3.84 MHz can be expressed as a mean power per chip of X dBm. Similarly, a signal PSD of Y dBm/3.84 MHz can be expressed as a signal power of Y dBm.

Maximum Output Power: This is a measure of the maximum power the UE can transmit (i.e. the actual power as would be measured assuming no measurement error) in a bandwidth of at least $(1 + \alpha)$ times the chip rate of the radio access mode. The period of measurement shall be at least one timeslot.

Mean power: When applied to a W-CDMA modulated signal this is the power (transmitted or received) in a bandwidth of at least $(1 + \alpha)$ times the chip rate of the radio access mode. The period of measurement shall be at least one timeslot unless otherwise stated.

Nominal Maximum Output Power: This is the nominal power defined by the UE power class.

RRC filtered mean power: The mean power as measured through a root raised cosine filter with roll-off factor α and a bandwidth equal to the chip rate of the radio access mode.

NOTE 1: The RRC filtered mean power of a perfectly modulated W-CDMA signal is 0.246 dB lower than the mean power of the same signal.

NOTE 2: The roll-off factor α is defined in section 6.8.1.

Throughput: Number of information bits per second excluding CRC bits successfully received on HS-DSCH by a HSDPA capable UE.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACLR	Adjacent Channel Leakage power Ratio
ACS	Adjacent Channel Selectivity
AICH	Acquisition Indication Channel
BER	Bit Error Ratio
BLER	Block Error Ratio
CQI	Channel Quality Indicator
CW	Continuous Wave (un-modulated signal)
DB-DC-HSDPA	Dual Band Dual Cell HSDPA
DC-HSDPA	Dual Cell HSDPA
DC-HSUPA	Dual Cell HSUPA
DCH	Dedicated Channel, which is mapped into Dedicated Physical Channel.
DIP	Dominant Interferer Proportion ratio
DL	Down Link (forward link)
DTX	Discontinuous Transmission
DPCCH	Dedicated Physical Control Channel
DPCH	Dedicated Physical Channel
DPCH_E _c	Average energy per PN chip for DPCH.
$\frac{\text{DPCH}_E_c}{I_{or}}$	The ratio of the transmit energy per PN chip of the DPCH to the total transmit power spectral density at the Node B antenna connector.
DPDCH	Dedicated Physical Data Channel