

---

---

**Rolling bearings — Measuring methods  
for vibration —**

Part 4:

**Radial cylindrical roller bearings with  
cylindrical bore and outside surface**

**iTeh STANDARD PREVIEW**  
*Roulements — Méthodes de mesurage des vibrations —*

*(standards) iTeh.ai*  
*Partie 4: Roulements radiaux à rouleaux cylindriques, à alésage et  
surface extérieure cylindriques*

ISO 15242-4:2007

<https://standards.itih.ai/catalog/standards/sist/b9acc01f-ccc5-4379-acc1-6e5c34422945/iso-15242-4-2007>



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 15242-4:2007](https://standards.iteh.ai/catalog/standards/sist/b9aec01f-ccc5-4379-ae1-6e5c34422945/iso-15242-4-2007)

<https://standards.iteh.ai/catalog/standards/sist/b9aec01f-ccc5-4379-ae1-6e5c34422945/iso-15242-4-2007>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

Foreword.....	iv
Introduction .....	v
1 Scope .....	1
2 Normative references .....	1
3 Terms and definitions.....	1
4 Measurement process .....	2
4.1 Speed of rotation .....	2
4.2 Bearing radial and axial loads .....	2
5 Measurement and evaluation methods .....	3
5.1 Physical quantity measured .....	3
5.2 Frequency range .....	3
5.3 Peak measurement .....	3
5.4 Testing sequence.....	3
6 Conditions for measurement.....	4
6.1 Bearing conditions for measurement .....	4
6.2 Conditions of the test environment .....	4
6.3 Conditions for the test device .....	4
6.4 Requirements for the operator .....	8
Annex A (normative) Measurement of external radial loading alignment.....	9
Annex B (normative) Measurement of external axial loading alignment .....	10

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 15242-4 was prepared by Technical Committee ISO/TC 4, *Rolling bearings*.

ISO 15242 consists of the following parts, under the general title *Rolling bearings — Measuring methods for vibration*:

- *Part 1: Fundamentals*
- *Part 2: Radial ball bearings with cylindrical bore and outside surface*
- *Part 3: Radial spherical and tapered roller bearings with cylindrical bore and outside surface*
- *Part 4: Radial cylindrical roller bearings with cylindrical bore and outside surface*

ITeH STANDARD PREVIEW  
(standards.iteh.ai)

ISO 15242-4:2007  
<https://standards.iteh.ai/catalog/standards/sist/b9acc01f-ccc5-4379-ae1-6e5e34422945/iso-15242-4-2007>

## Introduction

Vibration of rotating rolling bearings is a complex physical phenomenon dependent on the conditions of operation. Measuring the vibration output of an individual bearing under a certain set of conditions does not necessarily characterize the vibration output under a different set of conditions or when the bearing becomes part of a larger assembly. Assessment of the audible sound generated by the mechanical system incorporating the bearing is complicated further by the influence of the interface conditions, the location and orientation of the sensing device, and the acoustical environment in which the system operates. Assessment of airborne noise, which for the purpose of ISO 15242 (all parts) can be defined as any disagreeable and undesired sound, is further complicated by the subjective nature of the terms “disagreeable” and “undesired”. Structure-borne vibration can be considered the driving mechanism that ultimately results in the generation of airborne noise. Only selected methods for the measurement of the structure-borne vibration of rotating rolling bearings are addressed in the current edition of ISO 15242 (all parts).

Vibration of rotating rolling bearings can be assessed by any of a number of means using various types of transducers and test conditions. No simple set of values characterizing vibration of a bearing is adequate for the evaluation of the vibratory performance in all possible applications. Ultimately, a knowledge of the type of bearing, its application and the purpose of the vibration testing (e.g. as a manufacturing process diagnostic or an assessment of the product quality) is required to select the most suitable method for testing. The field of application for standards on bearing vibration is, therefore, not universal. However, certain methods have established a wide enough level of application to be considered as standard methods for the purposes of this part of ISO 15242.

This part of ISO 15242 serves to define the detailed method for assessing vibration of single-row and double-row radial cylindrical roller bearings with cylindrical bore and outside surface on a test rig.

[ISO 15242-4:2007](https://standards.iteh.ai/catalog/standards/sist/b9aec01f-ccc5-4379-aec1-6e5c34422945/iso-15242-4-2007)

<https://standards.iteh.ai/catalog/standards/sist/b9aec01f-ccc5-4379-aec1-6e5c34422945/iso-15242-4-2007>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 15242-4:2007](https://standards.iteh.ai/catalog/standards/sist/b9acc01f-ccc5-4379-acc1-6e5c34422945/iso-15242-4-2007)

<https://standards.iteh.ai/catalog/standards/sist/b9acc01f-ccc5-4379-acc1-6e5c34422945/iso-15242-4-2007>

# Rolling bearings — Measuring methods for vibration —

## Part 4:

# Radial cylindrical roller bearings with cylindrical bore and outside surface

## 1 Scope

This part of ISO 15242 specifies vibration measuring methods for single-row and double-row radial cylindrical roller bearings, under established test conditions.

It covers single-row and double-row radial cylindrical roller bearings with cylindrical bore and outside surface.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 286-2, *ISO system of limits and fits — Part 2: Tables of standard tolerance grades and limit deviations for holes and shafts*

ISO 554, *Standard atmospheres for conditioning and/or testing — Specifications*

ISO 558, *Conditioning and testing — Standard atmospheres — Definitions*

ISO 1132-1, *Rolling bearings — Tolerances — Part 1: Terms and definitions*

ISO 2041, *Vibration and shock — Vocabulary*

ISO 3205, *Preferred test temperatures*

ISO 3448, *Industrial liquid lubricants — ISO viscosity classification*

ISO 5593, *Rolling bearings — Vocabulary*

ISO 15242-1:2004, *Rolling bearings — Measuring methods for vibration — Part 1: Fundamentals*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 1132-1, ISO 2041, ISO 5593 and ISO 15242-1 apply.

## 4 Measurement process

### 4.1 Speed of rotation

The default speed of rotation shall be  $30 \text{ s}^{-1}$  (1 800 r/min) for bearings with outside diameter up to 100 mm and  $15 \text{ s}^{-1}$  (900 r/min) for outside diameters larger than 100 up to 200 mm. Tolerance of the speed of rotation shall be  ${}_{-2}^{+1}$  % of the specified nominal value.

Other speeds and tolerances may be used by agreement between the manufacturer and the customer; e.g. it may be necessary to use a higher speed for bearings in the smaller size range [ $40 \text{ s}^{-1}$  to  $60 \text{ s}^{-1}$  (2 400 r/min to 3 600 r/min)] in order to obtain an adequate vibration signal. Conversely, it may be necessary to use a lower speed for bearings in the larger size range [ $7,5 \text{ s}^{-1}$  to  $10 \text{ s}^{-1}$  (450 r/min to 600 r/min)] to avoid possible roller and raceway damage.

### 4.2 Bearing radial and axial loads

The bearing load shall be in the radial direction with default values as specified in Table 1.

Table 1 — Default values for bearing radial load

Bearing outside diameter $D$		Single-row radial cylindrical roller bearings		Double-row radial cylindrical roller bearings	
		Default values for bearing radial load			
$>$	$\leq$	min.	max.	min.	max.
mm		N		N	
30	50	135	165	165	195
50	70	165	195	225	275
70	100	225	275	315	385
100	140	315	385	430	520
140	170	430	520	565	685
170	200	565	685	720	880

Other radial loads and tolerances may be used by agreement between the manufacturer and the customer; e.g. depending on bearing design and lubricant used, it may be necessary to use a higher load to prevent roller/raceway slip, or a lower load to avoid possible roller, rib and raceway damage.

For bearings capable of taking axial load, an axial load of up to 30 N shall be applied on the outer ring to ensure stable operation.

The method of applying the radial and axial loads is described in 6.3.3.

NOTE Default values for radial loads are resultant values. Actual values depend on load angle used (see Figure 3).



## 5 Measurement and evaluation methods

### 5.1 Physical quantity measured

The default physical quantity to be measured is vibration velocity,  $v_{r.m.s.}$  ( $\mu\text{m/s}$ ), in the radial direction.

### 5.2 Frequency range

The velocity signal shall be measured in one or more bands with default frequency ranges as specified in Table 2.

Table 2 — Default frequency ranges

Speed of rotation		Low band (L) <sup>a</sup>		Medium band (M) <sup>a</sup>		High band (H) <sup>a</sup>	
min.	max.	$f_{low}$	$f_{high}$	$f_{low}$	$f_{high}$	$f_{low}$	$f_{high}$
r/min		Hz		Hz		Hz	
882	909	50	150	150	900	900	5 000
1 764	1 818	50	300	300	1 800	1 800	10 000

<sup>a</sup> For rotational speeds other than the nominal 900 r/min or 1 800 r/min, the frequency range should be adjusted in proportion to the speed. For practical reasons, frequencies lower than 50 Hz or higher than 10 000 Hz should not be used, unless agreed upon between the manufacturer and the customer.

(standards.iteh.ai)

NOTE Other frequency ranges may be considered by agreement between the manufacturer and the customer in those instances where specific ranges have greater importance to successful operation of the bearing.

<https://standards.iteh.ai/catalog/standards/sist/b9acc01f-ccc5-4379-acc1->

The use of spectral analysis of the vibration signal is an alternative.

### 5.3 Peak measurement

Detection of peaks or spikes in the time domain velocity signal, usually due to surface defects and/or contamination in the test bearing, may be considered as a supplementary option by agreement between the manufacturer and the customer. Various evaluation methods exist depending on the bearing type and the application.

### 5.4 Testing sequence

Single-row and double-row radial cylindrical roller bearings shall be tested with the radial load applied in a radial direction on the outer ring and perpendicular to the inner ring axis. An axial load may be necessary to ensure stable operation. If the axial load is used, it is applied from one side of the outer ring. For double-row radial cylindrical roller bearings the test should be repeated, if the design allows, with the axial load on the other side of the outer ring.

For diagnostic purposes, performing multiple measurements with the outer ring in different angular positions relative to the pick-up is appropriate.

For acceptance of the bearing, the highest vibration reading for the appropriate frequency band shall be within the limits mutually agreed between the manufacturer and the customer.

For test duration, see ISO 15242-1:2004, 6.5.