



SLOVENSKI STANDARD
SIST EN 1993-1-10:2005/AC:2009
01-junij-2009

Evrokod 3: Projektiranje jeklenih konstrukcij - 1-10. del: Izbira kakovosti jekla glede na žilavost in lamelarni lom

Eurocode 3: Design of steel structures - Part 1-10: Material toughness and through-thickness properties

Eurocode 3: Bemessung und Konstruktion von Stahlbauten - Teil 1-10: Stahlsortenauswahl im Hinblick auf Bruchzähigkeit und Eigenschaften in Dickenrichtung

Eurocode 3 - Calcul des structures en acier - Partie 1-10 : Choix des qualités d'acier

[SIST EN 1993-1-10:2005/AC:2009](https://standards.iteh.ai/catalog/standards/sist/9b4d2146-8e09-426a-8880-c24b2974596/sist-en-1993-1-10-2005-ac-2009)

Ta slovenski standard je istoveten z: **EN 1993-1-10:2005/AC:2009**

ICS:

91.010.30	V [^] @ã}ãããã	Technical aspects
91.080.10	Kovinske konstrukcije	Metal structures

SIST EN 1993-1-10:2005/AC:2009 en,fr

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 1993-1-10:2005/AC:2009

<https://standards.iteh.ai/catalog/standards/sist/9b4d2146-8e09-426a-8880-c24f52974596/sist-en-1993-1-10-2005-ac-2009>

EUROPEAN STANDARD

EN 1993-1-10:2005/AC

NORME EUROPÉENNE

March 2009

EUROPÄISCHE NORM

Mars 2009

März 2009

ICS 91.010.30

English version
Version Française
Deutsche Fassung

Eurocode 3: Design of steel structures - Part 1-10: Material toughness and through-thickness properties

Eurocode 3 - Calcul des structures en acier
- Partie 1-10 : Choix des qualités d'acier

Eurocode 3: Bemessung und Konstruktion
von Stahlbauten - Teil 1-10:
Stahlsortenauswahl im Hinblick auf
Bruchzähigkeit und Eigenschaften in
Dickengerichtung

This corrigendum becomes effective on 25 March 2009 for incorporation in the three official language versions of the EN.

Ce corrigendum prendra effet le 25 mars 2009 pour incorporation dans les trois versions linguistiques officielles de la EN.

Die Berichtigung tritt am 25. März 2009 zur Einarbeitung in die drei offiziellen Sprachfassungen der EN in Kraft.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

© 2009 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.
Tous droits d'exploitation sous quelque forme et de quelque manière que ce soit réservés dans le monde entier aux membres nationaux du CEN.
Alle Rechte der Verwertung, gleich in welcher Form und in welchem Verfahren, sind weltweit den nationalen Mitgliedern von CEN vorbehalten.

Ref. No.: EN 1993-1-10:2005/AC:2009 D/E/F

EN 1993-1-10:2005/AC:2009 (E)**Modifications due to EN 1993-1-10:2005/AC:2005****1) Modifications to Subclause 2.1**

The corrections are to add a "P" after the clause number and replace "should" with "shall" where appropriate. The corrections are underlined as shown.

'2.1 General'

"(3)P The rules shall be applied to the properties of materials specified for the toughness quality in the relevant steel product standard. Material of a less onerous grade shall not be used even though test results show compliance with the specified grade."

Modifications due to EN 1993-1-10:2005/AC:2009**2) Modification to Subclause 1.2**

Paragraph '(1)', delete:

"

EN 10155 Structural steels with improved atmospheric corrosion resistance - Technical delivery conditions;

".

iTeh STANDARD PREVIEW

3) Modifications to Subclause 1.3.1

(standards.iteh.ai)

Change " K_V -value" into: "**KV**-value".

SIST EN 1993-1-10:2005/AC:2009

Change "The K_V (Charpy V-Notch) value..." into: "The **KV** (Charpy V-Notch) value..."

http://standards.iteh.ai/catalog/standards/sist/en-1993-1-10-2005-ac-2009/c24f52974596/sist-en-1993-1-10-2005-ac-2009

Delete: " $A_V(T)$ ".

4) Modification to Subclause 1.3.2

Change " $A_V(T)$ " into: "**KV(T)**".

5) Modification to Subclause 1.3.3

'Figure 1.1', change " $A_V(T)$ " into: "**KV(T)**".

6) Modification to Subclause 1.3.4

Change " A_V " into: "**KV**".

7) Modifications to Subclause 1.4

Change " $A_V(T)$ " into: "**KV(T)**".

Add:

"

K stress intensity factor

"

Change the definition for 'K_{IC}' into:

"

K_{IC} plane strain fracture toughness for linear elastic behaviour measured in N/mm^{3/2}

"

(to be consistent with 1.3.6).

8) Modification to Subclause 2.2

Paragraph '(5)', 'NOTE 2', change "stress intensity function" into: "stress intensity factor function" at the two occurrences of this expression in the note.

9) Modification to Subclause 2.3.1

Paragraph '(1)', change "K_V-value" into: "KV-value".

Paragraph '(2)', delete: "EN 10155,".

10) Modifications to Subclause 2.3.2

'Table 2.1', 1st row, 3rd column, change "Charpy energy CVN" into: "KV"

'Table 2.1', 'NOTE 2', change "T_{AV}" into: "T_{KV}".

'Table 2.1', 'NOTE 3', change "Charpy energy values CVN" into: "KV-values".

<https://standards.iteh.ai/catalog/standards/sist/9b4d2146-8e09-426a-8880-1993-1-10-2005-ac-2009>

11) Modifications to Subclause 2.4

Paragraph '(1)', change "K_V-values" into: "KV-values".

Paragraph '(2)', change Equation '(2.7)' into: " $T_{Ed} \geq T_{Rd}$ ".

Paragraph '(3)', change "The assumed flaw should be located at the position of adverse stress concentration" into: "The assumed flaw should be located at the position of the most adverse stress concentration".

12) Modification to Subclause 3.1

Paragraph '(3)', change "if the strain in the joint acts" into: "if the strain in the connection acts".

13) Modification to Subclause 3.2

'Table 3.2', 3rd column, 1st row at the top, heading, delete: "=" and divide this cell into two cells with a vertical line continuing the one subdividing the rows below, so that the new cell on the left bears the title "Effective weld depth a_{eff} (see Figure 3.2)" and the new cell on the right bears the title "Throat thickness a of fillet welds", thus:

"

EN 1993-1-10:2005/AC:2009 (E)

Table 13.1: Criteria affecting the target value of Z_{Ed}

a)	Weld depth relevant for straining from metal shrinkage	Effective weld depth a_{eff} (see Figure 3.2)	Throat thickness a of fillet welds	Z_i
		$a_{eff} \leq 7\text{mm}$	$a = 5\text{ mm}$	$Z_a = 0$
		$7 < a_{eff} \leq 10\text{mm}$	$a = 7\text{ mm}$	$Z_a = 3$
		$10 < a_{eff} \leq 20\text{mm}$	$a = 14\text{ mm}$	$Z_a = 6$
		$20 < a_{eff} \leq 30\text{mm}$	$a = 21\text{ mm}$	$Z_a = 9$
		$30 < a_{eff} \leq 40\text{mm}$	$a = 28\text{ mm}$	$Z_a = 12$
		$40 < a_{eff} \leq 50\text{mm}$	$a = 35\text{ mm}$	$Z_a = 15$
		$50 < a_{eff}$	$a > 35\text{ mm}$	$Z_a = 15$

(...)

“

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 1993-1-10:2005/AC:2009](https://standards.iteh.ai/catalog/standards/sist/9b4d2146-8e09-426a-8880-c24f52974596/sist-en-1993-1-10-2005-ac-2009)

<https://standards.iteh.ai/catalog/standards/sist/9b4d2146-8e09-426a-8880-c24f52974596/sist-en-1993-1-10-2005-ac-2009>