## INTERNATIONAL STANDARD

ISO 3764

Third edition 2000-04-15

### Timekeeping instruments — Movements — Types, dimensions and nomenclature

Instruments horaires — Mouvements — Formes, dimensions et nomenclature

### iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 3764:2000 https://standards.iteh.ai/catalog/standards/sist/203e26d2-a65f-49c2-94ec-a6b53a9f7203/iso-3764-2000



#### **PDF** disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 3764:2000 https://standards.iteh.ai/catalog/standards/sist/203e26d2-a65f-49c2-94ec-a6b53a9f7203/iso-3764-2000

#### © ISO 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 734 10 79
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

#### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 3764 was prepared by Technical Committee ISO/TC 114, *Horology*, Subcommittee SC 7, *Overall dimensions*.

This third edition cancels and replaces the second edition (ISO 3764:1997), of which it constitutes a minor revision.

(standards.iteh.ai)

ISO 3764:2000 https://standards.iteh.ai/catalog/standards/sist/203e26d2-a65f-49c2-94ec-a6b53a9f7203/iso-3764-2000

© ISO 2000 – All rights reserved iii

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 3764:2000 https://standards.iteh.ai/catalog/standards/sist/203e26d2-a65f-49c2-94ec-a6b53a9f7203/iso-3764-2000

### Timekeeping instruments — Movements — Types, dimensions and nomenclature

#### 1 Scope

This International Standard specifies the types and fitting dimensions of mechanical and electromechanical watchmovements.

This International Standard is applicable to the four following types of movements:

- Type 1: round;
- Type 2: shaped round;
- Type 3: 5 ½"";
- Type 4: 6 ¾ × 8". iTeh STANDARD PREVIEW (standards.iteh.ai)

#### 2 Normative references

ISO 3764:2000

The following normative documents contain provisions which through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 286-1, ISO system of limits and fits — Part 1: Bases of tolerances, deviations and fits

ISO 6426-2, Horological vocabulary — Part 2: Technico-commercial definitions.

#### 3 Terms and definitions

For the purposes of this International Standard, the terms and definitions given in ISO 286-1 and ISO 6426-2, and the following, apply.

#### 3.1 Diameters of movement

#### 3.1.1

#### casing diameter

 $d_1$ 

diameter of a plate, or an equivalent part or an assembly unit, by which the movement is located in the watch-case

NOTE The protruding elements of movement parts are not included in the casing diameter if the protrusion does not exceed 1,5 % of a diameter value and if in length it is no more than 10 % of the plate perimeter.

© ISO 2000 – All rights reserved

#### 3.1.2

#### outer diameter

da

largest diameter of the movement, on the flange of the plate, of an equivalent part or of an assembly unit

#### 3.2 Thickness of movements

#### 3.2.1 Mechanical type

#### 3.2.1.1

#### total thickness of the movement

l,

thickness embracing all the movement parts, including the distance between the dial support surface and the lowest protruding part of the movement

#### 3.2.2 Electromechanical type

#### 3.2.2.1

#### total thickness of the movement without a battery

 $l_1$ 

thickness embracing all the movement parts, including the distance between the dial support surface and the lowest protruding part of the movement

#### 3.2.2.2

### total thickness of the movement with a pattery NDARD PREVIEW

 $l_2$ 

distance between the dial support surface and the lower battery surface 1)

NOTE If the battery is not the most protruding part, the total movement thickness is determined as  $l_1$ .

#### 3.2.2.3

https://standards.iteh.ai/catalog/standards/sist/203e26d2-a65f-49c2-94ec-

a6b53a9f7203/iso-3764-2000

#### total thickness of the movement including a battery and its fastening clamp

 $l_3$ 

distance between the dial support surface and the lower surface of the clamp


NOTE 1 If the battery with its clamp is not the most protruding part, the total movement thickness is determined as  $l_1$ .

NOTE 2 For watches with analog display, the total thickness of the movement does not include the projection of the hand-fastening elements nor the elements providing electrical contact with the case.

#### 4 Nomenclature of movements and their dimensions

#### 4.1 Type 1: Round movement

See Figure 1 and Table 1.



#### Key

- $d_1$  is the casing diameter
- $d_2$  is the outer diameter

Figure 1 —Round movement (view from the side of the bridges)


Table 1 — Type 1: Round movements ITEM STANDARD PREVIEW Dimensions in millimetres

	(S <sub>l</sub> andards.iten.ai <sub>d</sub>					
	tol. h8 tol. h8					
https://standard	ds.iten:a/catalog/standar	15/2000 15/203e26d2-465f-49c2-94ec-				
	12,06b53a9f7203/isp-3764-2000 12,4					
	13,0	13,4				
	15,3 *	15,7				
	16,0	16,4				
	17,2 *	17,6				
	19,4 *	20,0				
	21,0	21,6				
	22,0	22,6				
	23,3 *	23,9				
	24,0	24,6				
	25,6 *	26,2				
	28,0	28,6				
	30,0	30,6				
	36,0	36,8				
	40,0	40,8				
NOTE 1	NOTE 1 The values $d_1$ with an asterisk are the preferred values.					
NOTE 2	The tolerances only apply to metallic movements.					
NOTE 3	See ISO 286-1 for definition of the tolerances.					

© ISO 2000 – All rights reserved

#### 4.2 Type 2: Shaped round movement

See Figure 2 and Table 2.



#### Key

- a is the width
- $d_1$  is the casing diameter
- $d_2$  is the outer diameter

Figure 2 — Shaped round movement (view from the side of the bridges)

(standards.iteh.ai)

Table 2 — Type 2: Shaped round movements

https://standards.iteh.ai/catalog/standards/sig/103a26d2-a65f3a9f7203/iso-3764-2000

h8
),4
5,7
7,6
7,9
0,0
3,9
5,2
7


NOTE 1 The tolerances only apply to metallic movements.

NOTE 2 Width a is not specified.

NOTE 3 See ISO 286-1 for definition of the tolerances.

#### 4.3 Type 3: 5 1/2" movement

See Figure 3 and Table 3.



#### Key

- a is the width
- $b_1$  is the fitting length
- $b_2$  is the overall length
- f is the offset of the radius centre ch STANDARD PREVIEW
- r is the oval radius

### (standards.iteh.ai)

Figure 3 — 5 ½" movement (view from the side of the bridges)

https://standards.iteh.ai/catalog/standards/sist/203e26d2-a65f-49c2-94ec-a6b53a9f7203/iso-3764-2000

Table 3 — Type 3: 5 1/2" movements

Dimensions in millimetres

a tol. h9	b <sub>1</sub> tol. h8	<i>b</i> <sub>2</sub> tol. h9	f	r	
13,0	15,15	15,55	2,3	8,8	
NOTE 1 The tolerances only apply to metallic movements.					
NOTE 2 Se	OTE 2 See ISO 286-1 for definition of the tolerances.				

© ISO 2000 – All rights reserved 5