INTERNATIONAL STANDARD



First edition 2002-06-01

Reciprocating internal combustion engines — Determination and method for the measurement of engine power — Additional requirements for exhaust emission tests in accordance with ISO 8178

Teh Moteurs alternatifs à combustion interne — Détermination et méthode de mesurage de la puissance — Exigences supplémentaires pour les essais d'émissions de gaz d'échappement suivant l'ISO 8178

ISO 14396:2002 https://standards.iteh.ai/catalog/standards/sist/3d6b93ec-5bfa-49ce-bd8a-43525d8c72d2/iso-14396-2002



Reference number ISO 14396:2002(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 14396:2002 https://standards.iteh.ai/catalog/standards/sist/3d6b93ec-5bfa-49ce-bd8a-43525d8c72d2/iso-14396-2002

© ISO 2002

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.ch Web www.iso.ch

Printed in Switzerland

Contents

Forev	word	iv
Intro	duction	v
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Symbols	2
5	Standard reference conditions	2
6 6.1 6.2 6.3	Tests Test method Test conditions Test procedure	3 3 4
7	Method of power correction	4
8	Measurement of exhaust emission	4
9 9.1 9.2	Test report	5 5 7
10	Tolerance for measuring engine power	8
Biblic	150 14390.2002 ographyhttps://standards.itely.ai/catalog/standards/sist/3d6b93ee+5bfa+49ee+bd8a+	9
	43525d8c72d2/iso-14396-2002	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 14396 was prepared by Technical Committee ISO/TC 70, Internal combustion engines.

This first edition of ISO 14396 cancels and replaces ISO/TR 14396 1996 which has been technically revised.

(standards.iteh.ai)

ISO 14396:2002 https://standards.iteh.ai/catalog/standards/sist/3d6b93ec-5bfa-49ce-bd8a-43525d8c72d2/iso-14396-2002

Introduction

This International Standard establishes one "Satellite" standard of the ISO engine power measurement standards, the use of which enables one to avoid the disadvantages due to the existance of many similar, but different, ISO standards for the definition and determination of engine power. It uses the "Core" and "Satellite" approach.

The "Core" standard, ISO 15550 contains the requirements that are common to all engine applications whereas this International Standard contains as a "Satellite" standard those requirements that are necessary to tailor power measurement and declaration to suit the particular engine application as defined in clause 1.

This International Standard is intended to be applied only in conjunction with the "Core" standard ISO 15550 in order to completely specify the requirements for the particular engine application. The "Satellite" standard therefore is not a document that can stand alone but is intended to be accomplished by the requirements laid down in the "Core" standard ISO 15550 to become a complete standard.

The structure of both, the "Core" and the "Satellite" standard have been drafted in a very similar way to ensure easy use.

The advantage of this approach is that the use of standards for the same or similar engines used in different applications will be rationalized and the harmonization of standards in the course of revision or development will be ensured.

In comparison with engines for on-road applications, engines for off-road use are made in a much wider range of power outputs and configurations as they are used in a large number of different applications.

The objective of ISO 8178 is to rationalize the gaseous and particulate emission test procedures for off-road engines in order to simplify and make more cost effective the drafting of legislation, the development of engine specifications and engine certification. 43525d8c72d2/iso-14396-2002

One of the concepts that has been adopted to achieve this objective is to calculate the specific emissions (g/kWh) on the basis of the engine power when only the essential dependent auxiliaries are fitted.

ISO 8178 has been used in legislation and the authorities have set limit values that vary according to the power of the engine. This International Standard defines the procedure to be used to determine the power of the engine for testing in accordance with the requirements of ISO 8178.

The calculation of specific emissions in accordance with ISO 8178 is based upon uncorrected power measurement values, since the emissions vary with ambient conditions but cannot be corrected at the time of measurement. The permissible range of ambient conditions in this International Standard is therefore very small in order to minimize this effect.

This International Standard, which uses power correction procedures so that a wide range of ambient test conditions can be met, is intended to be used to determine the engine power prior to performing an emission test.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 14396:2002 https://standards.iteh.ai/catalog/standards/sist/3d6b93ec-5bfa-49ce-bd8a-43525d8c72d2/iso-14396-2002

Reciprocating internal combustion engines — Determination and method for the measurement of engine power — Additional requirements for exhaust emission tests in accordance with ISO 8178

1 Scope

This International Standard specifies the additional and method requirements for determining the power of reciprocating internal combustion (RIC) engines when presented for an exhaust emission test in accordance with ISO 8178, to the basic requirements defined in the "Core" standard ISO 15550.

It also specifies the power correction method for the confirmation of engine power for pre-set engines under variable atmospheric conditions. These corrections do not apply to the definition of the exhaust emission values which are in all cases only related to the uncorrected engine power.

This International Standard applies to RIC engines for land, rail traction and marine use excluding engines for motor vehicles primarily designed for on-road use. It may be applied to engines used to propel e.g. road construction and earth-moving machines, industrial trucks and for other applications.

This International Standard is a "Satellite" standard and shall be applied in conjunction with the "Core" standard ISO 15550 only, in order to completely specify the requirements for the particular engine application. https://standards.iteh.avcatalog/standards/sist/3d6b93ec-5bfa-49ce-bd8a-

43525d8c72d2/iso-14396-2002

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 3104:1994, Petroleum products — Transparent and opaque liquids — Determination of kinematic viscosity and calculation of dynamic viscosity

ISO 3675:1998, Crude petroleum and liquid petroleum products — Laboratory determination of density — Hydrometer method

ISO 5164:1990, Motor fuels — Determination of knock characteristics — Research method

ISO 5165:1998, Petroleum products — Determination of the ignition quality of diesel fuels — Cetane engine method

ISO 15550:2002, Reciprocating internal combustion engines — Determination and method for the measurement of engine power — General requirements

ASTM D240-00, Standard Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimeter

ASTM D3338-00, Standard Test Method for Estimation of Net Heat of Combustion of Aviation Fuels

3 Terms and definitions

For the purposes of this International Standard, the terms and definitions given in ISO 15550 listed in Table 1 apply.

Term	Definition		
(listed alphabetically)	see ISO 15550 Subclause No.		
declared engine speed	3.2.4		
declared intermediate engine speed	3.2.5		
declared power	3.3.1		
engine adjustment	3.2.1		
engine power for ISO 8178	3.3.3.3		
engine speed	3.2.3		
engine speed at maximum torque	3.2.7		
fuel delivery	3.4.2		
load	3.3.11		
power correction	3.3.10		
production conformity test iTeh STANDARD PI	EVIEW 3.5.4		
special test (standards, iteh	3.5.3		
For the declaration of the intermediate engine speed the following requirements shall b	e taken into account:		
- for engines which are designed to operate over a specific speed range of the full load torque curve, the intermediate engine speed shall be			

Table 1 — Terms and definitions

- for engines which are designed to operate over a specific speed range of the full load torque curve, the intermediate engine speed shall be the declared engine speed at maximum torque if it occurs between 60 % and 75 % of the declared speed d8a-

If the declared engine speed at maximum torque is less than 60% of the declared speed, then the intermediate engine speed shall be 60 % of the declared speed.

If the declared engine speed at maximum torque is greater than 75 % of the declared speed, then the intermediate engine speed shall be 75 % of the declared speed.

- for engines which are not designed to operate over a speed range of the full load torque curve at steady conditions, the intermediate engine speed will typically be between 60 % and 70 % of the declared speed.

4 Symbols

For the symbols used in this International Standard see Table 2 of ISO 15550:2002; for the meanings of subscripts see Table 3 of ISO 15550:2002.

5 Standard reference conditions

The requirements of ISO 15550:2002 clause 5 apply.

6 Tests

6.1 Test method

Test method 2 in accordance with 6.3 of ISO 15550:2002 applies.

6.2 Test conditions

The requirements of ISO 15550:2002 sublauses 6.3.4.1 to 6.3.4.14 apply with the following additions:

a) The settings for the engine power test depend upon whether the engine is 'pre-set' and will run at full fuel delivery under all conditions, or if the engine is adjustable and will be adjusted to produce a specified power output.

For adjustable compression-ignition (diesel) engines the engine power test shall consist of a run at the required fuel system settings to produce the manufacturer's specified power, the engine being equipped as specified in ISO 15550:2002, Table 1, column 5.

All equipment and auxiliaries not required by ISO 15550:2002, Table 1, column 5, should be removed before the test.

Certain accessories, necessary only for the operation of the machine to which the engine will be connected and which may be mounted on the engine, should be removed for the test. The following non-exhaustive list is given as an example:

- air compressors for brakes;
- power-steering pump;

ISO 14396:2002

(standards.iteh.ai)

- suspension compressor; 43525d8c72d2/iso-14396-2002
- air-conditioning system compressor;
- mounted gearbox.

Where accessories cannot be removed, the power absorbed by them in the unloaded condition shall be determined and added to the measured engine power. If this value is greater than 3 % of the maximum power at the test speed it may be verified by the test authority.

b) The fuel selected for the ISO 8178 power test shall be the same as that for the ISO 8178 emission test. Unless otherwise agreed by the parties involved the fuel shall be selected in accordance with the requirements of Table 12 of ISO 15550:2002.

For compression ignition (diesel) engines operating on distillate fuel, the fuel temperature values given in ISO 15550:2002, subclause 6.3.4.11 b) do not apply. For these engines the fuel temperature shall be $313 \text{ K}_{-7}^{+3} \text{ K}^{(1)(2)}$.

¹⁾ The tolerances shown are in conformity with the non-road engine emission legislative requirements.

²⁾ If other than diesel fuels are used, the fuel temperature may vary.