



SLOVENSKI STANDARD
SIST ISO 17485:2006

01-december-2006

Glčy Ugh]ncVb]_]E`G]ghYa `lc`YfUbWdc`=GC

Bevel gears -- ISO system of accuracy

iTeh STANDARD PREVIEW

Engrenages coniques -- Système ISO d'exactitude

(standards.iTeh.ai)

Ta slovenski standard je istoveten z: **ISO 17485:2006**

SIST ISO 17485:2006
<https://standards.iTeh.ai/catalog/standards/sist/10716555-b7a4-4c96-ae22-c13d89abc936/sist-iso-17485-2006>

ICS:

21.200

Gonila

Gears

SIST ISO 17485:2006

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 17485:2006

<https://standards.iteh.ai/catalog/standards/sist/f07f6553-b7a4-4c96-ae22-c13d89abc936/sist-iso-17485-2006>

INTERNATIONAL STANDARD

ISO
17485

First edition
2006-06-15

Bevel gears — ISO system of accuracy

Engrenages coniques — Système ISO d'exactitude

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 17485:2006](https://standards.iteh.ai/catalog/standards/sist/f07f6553-b7a4-4c96-ae22-c13d89abc936/sist-iso-17485-2006)

<https://standards.iteh.ai/catalog/standards/sist/f07f6553-b7a4-4c96-ae22-c13d89abc936/sist-iso-17485-2006>



Reference number
ISO 17485:2006(E)

© ISO 2006

ISO 17485:2006(E)**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 17485:2006](https://standards.iteh.ai/catalog/standards/sist/f07f6553-b7a4-4c96-ae22-c13d89abc936/sist-iso-17485-2006)

<https://standards.iteh.ai/catalog/standards/sist/f07f6553-b7a4-4c96-ae22-c13d89abc936/sist-iso-17485-2006>

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	2
3 Terms, definitions and symbols	2
3.1 Terms and definitions.....	2
3.2 Fundamental terms and symbols.....	6
4 Application of classification system.....	7
4.1 General.....	7
4.2 Accuracy grade classification	7
4.3 Tolerance direction.....	8
4.4 Additional characteristics	8
5 Tolerances	8
5.1 Tolerance values.....	8
5.2 Step factor	8
5.3 Rounding rules.....	9
5.4 Tolerance equations	9
6 Application of measuring methods.....	11
6.1 Methods of measurement	11
6.2 Recommended measurement control methods	12
6.3 Measurement data filtering	12
6.4 Tooth contact pattern inspections.....	12
Annex A (informative) Example tolerance tables.....	14
Annex B (informative) Single-flank composite measuring method	16
Annex C (informative) Accuracy of small module bevel gears.....	21
Annex D (informative) Interpretation of composite data	24
Bibliography	32

ISO 17485:2006(E)**Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 17485 was prepared by Technical Committee ISO/TC 60, *Gears*.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 17485:2006](https://standards.iteh.ai/catalog/standards/sist/f07f6553-b7a4-4c96-ae22-c13d89abc936/sist-iso-17485-2006)

<https://standards.iteh.ai/catalog/standards/sist/f07f6553-b7a4-4c96-ae22-c13d89abc936/sist-iso-17485-2006>

Introduction

The measurement and tolerance specification of bevel gears are very complex subjects that were in need of international standardization. For these and other reasons, ISO/TC 60 approved the project based on a proposed document, ANSI/AGMA 2009-B01, *Bevel Gear Classification, Tolerances, and Measuring Methods*.

At an early stage it was decided to develop two documents: this International Standard, with accuracy grades and definitions, and a separate Technical Report, ISO/TR 10064-6, containing inspection practice and measuring methods. These practices and measuring methods include topics such as manufacturing considerations, CMM measurements, contact pattern checking, and advanced topics such as bevel gear flank form analysis.

Prior to the development of this International Standard, the accuracy grades described in ISO 1328, for cylindrical gears, were often used for bevel gears. However, this use was not always consistent with the specific requirements and general practices followed within the bevel gear industry. This International Standard contains items that are distinctly different from ISO 1328-1:1995:

- the definitions, tolerance diameter and measuring directions are specifically for bevel gears;
- accuracy grade tolerances are based on equations and not on tables;
- there is approximately one grade difference in tolerance level between bevel and cylindrical gears, similar to that used by the DIN system of tolerances.

The use of the definitions and accuracy grades within this International Standard should improve the consistent application of bevel gear geometrical tolerances for the general benefit of industry.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 17485:2006

<https://standards.iteh.ai/catalog/standards/sist/f07f6553-b7a4-4c96-ae22-c13d89abc936/sist-iso-17485-2006>

Bevel gears — ISO system of accuracy

1 Scope

This International Standard establishes a classification system that can be used to communicate geometrical accuracy specifications of unassembled bevel gears, hypoid gears, and gear pairs. It defines gear tooth accuracy terms and specifies the structure of the gear accuracy grade system and allowable values.

This International Standard provides the gear manufacturer and the gear buyer with a mutually advantageous reference for uniform tolerances. Ten accuracy grades are defined, numbered 2 to 11 in order of decreasing precision. Equations for tolerances and their ranges of validity are provided in 5.4 for the defined accuracy of gearing. In general, these tolerances cover the following ranges:

$$1,0 \text{ mm} \leq m_{mn} \leq 50 \text{ mm}$$

$$5 \leq z \leq 400$$

$$5 \text{ mm} \leq d_T \leq 2\,500 \text{ mm}$$

iTeh STANDARD PREVIEW
(standards.iteh.ai)

where

- d_T is the tolerance diameter; [SIST ISO 17485:2006
https://standards.iteh.ai/catalog/standards/sist/f07f6553-b7a4-4c96-ae22-c13d89abc936/sist-iso-17485-2006](https://standards.iteh.ai/catalog/standards/sist/f07f6553-b7a4-4c96-ae22-c13d89abc936/sist-iso-17485-2006)
- m_{mn} is the mean normal module;
- z is the number of teeth.

See Clause 6 for required and optional measuring methods. As tolerances are calculated from the actual dimensions of a bevel gear, tolerance tables are not provided. In order to provide an overview, example values of tolerances and graphs are given in Annex A.

This International Standard does not apply to enclosed gear unit assemblies, including speed reducers or increasers, gear motors, shaft mounted reducers, high speed units, or other enclosed gear units manufactured for a given power, speed, ratio or application.

Gear design is beyond the scope of this International Standard. The use of the accuracy grades for the determination of gear performance requires extensive experience with specific applications. Therefore, the users of this International Standard are cautioned against the direct application of tolerance values to a projected performance of unassembled (loose) gears when they are assembled.

Tolerance values for gears outside the limits stated in this International Standard will need to be established by determining the specific application requirements. This could require the setting of a tolerance other than that calculated by the formulas in this International Standard.

ISO 17485:2006(E)

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1122-1:1998, *Vocabulary of gear terms — Part 1: Definitions related to geometry*

ISO 23509¹⁾, *Bevel and hypoid gear geometry*

3 Terms, definitions and symbols

For the purposes of this document, the terms and definitions given in ISO 1122-1, ISO 23509 and the following terms, definitions and symbols apply.

Some of the symbols and terminology contained in this document could differ from those used in other documents and standards. Users of this International Standard should assure themselves that they are using the symbols, terminology and definitions in the manner indicated herein.

3.1 Terms and definitions

3.1.1

index deviation

 F_x

displacement of any tooth flank from its theoretical position, relative to a datum tooth flank

iTeh STANDARD PREVIEW
(standards.iteh.ai)

3.1.2

mean normal module

 m_{mn}

ratio of the mean pitch diameter in millimetres to the number of teeth in a normal plane at the mean cone distance

SIST ISO 17485:2006

<https://standards.iteh.ai/catalog/standards/sist/f07ff6553-b7a4-4c96-ae22-144e201644e0/iso-17485-2006>

$$m_{mn} = \frac{d_m}{z} \cos \beta_m = \frac{R_m}{R_e} m_{et} \cos \beta_m \quad (1)$$

where

d_m is the mean pitch diameter,

z is the number of teeth,

β_m is the mean spiral angle,

R_m is the mean cone distance,

R_e is the outer cone distance, and

m_{et} is the outer transverse module

3.1.3

reference gear

gear of known accuracy that is designed specifically to mesh with the gear to be inspected for composite deviation and contact marking tests

1) To be published.

3.1.4**total runout deviation** F_r

difference between the maximum and minimum distance perpendicular to the pitch cone, of a probe (ball or cone) placed successively in each tooth space, with the probe contacting both the right and left flanks at the tolerance circle approximately mid tooth-depth

NOTE Tolerances are provided in 5.4.4.

3.1.5**tooth mesh component single-flank composite deviation** f_{is}

value of the greatest single-flank composite deviation over any one pitch ($360^\circ/z$), after removal of the long-term component (sinusoidal effect of eccentricity), during a single-flank composite test, when the wheel is moved through one revolution

NOTE This International Standard specifies the tolerance direction for tooth mesh component single-flank composite deviation to be along the arc of the tolerance diameter circle in a transverse section. Tolerances are provided in 5.4.5.

3.1.6**total single-flank composite deviation** F_{is}

total deviation, measured from minimum to maximum, during a single-flank composite test, when the wheel is moved through one revolution

NOTE This International Standard specifies the tolerance direction for total single-flank composite deviation to be along the arc of the tolerance diameter circle in a transverse section. See Annex B. Tolerances are provided in 5.4.6.


3.1.7**single pitch deviation** f_{pt}

displacement of any tooth flank from its theoretical position relative to the corresponding flank of an adjacent tooth, measured by a probe from a point on a flank, to a point on the adjacent flank, on the same measurement circle

See Figure 1.

NOTE 1 Distinction is made as to the algebraic sign of the measured value. Thus, a condition wherein the actual tooth flank position was nearer to the adjacent tooth flank than the theoretical position would be considered a minus (–) deviation. A condition wherein the actual tooth flank position was farther from the adjacent tooth flank than the theoretical position would be considered a plus (+) deviation.

NOTE 2 This International Standard specifies the tolerance direction of measurement for single pitch deviation to be along the arc of the tolerance diameter circle in the transverse section. Tolerances are provided in 5.4.2.

**Key**

- 1 theoretical tooth flank position
- 2 actual tooth flank position
- 3 theoretical circular pitch
- 4 measurement circle

Figure 1 — Pitch deviations**3.1.8****tolerance diameter** d_T

diameter where the mean cone distance, R_m , and the midpoint of the working depth intersect

See Figure 2.

SIST ISO 17485:2006

NOTE The midpoint of the mean working depth is one half the depth of engagement of the two gears at the mean cone distance. The value of d_T can be determined by Equations (2) or (3).

$$d_{T1} = d_{m1} + 2(0,5 h_{mw} - h_{am2}) \cos \delta_1 = d_{m1} + (h_{am1} - h_{am2}) \cos \delta_1 \quad (2)$$

$$d_{T2} = d_{m2} - 2(0,5 h_{mw} - h_{am2}) \cos \delta_2 = d_{m2} + (h_{am2} - h_{am1}) \cos \delta_2 \quad (3)$$

where

$d_{m1,2}$ is the mean pitch diameter (pinion, wheel);

h_{mw} is the mean working depth;

$h_{am1,2}$ is the mean addendum;

$\delta_{1,2}$ is the pitch angle (pinion, wheel).

These values can be obtained from manufacturing summary sheets or by calculations shown in ISO 10300 or in ISO 23509.




Figure 2 — Tolerance diameter

3.1.9


total cumulative pitch deviation

 F_p

largest algebraic difference between any two index deviation values for a specified flank (left or right), without distinction as to the direction or algebraic sign of this reading

See Figure 3.

NOTE This International Standard specifies the tolerance direction of for total cumulative pitch deviation to be along the arc of the tolerance diameter circle in the transverse section. Tolerances are provided in 5.4.2.



- F_x = index deviation
- f_{pt} = single pitch deviation
- F_p = total cumulative pitch deviation
- z = tooth number

Figure 3 — Pitch data from single probe device