

SLOVENSKI STANDARD
SIST EN 301 502 V9.2.1:2010

01-december-2010

Globalni sistem mobilnih komunikacij (GSM) - Harmonizirani EN za opremo za bazne postaje, ki zajema bistvene zahteve člena 3.2 direktive R&TTE

Global System for Mobile communications (GSM) - Harmonized EN for Base Station Equipment covering the essential requirements of article 3.2 of the R&TTE Directive

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: [SIST EN 301 502 V9.2.1:2010
https://standards.iteh.ai/catalog/standards/sist/471d1474-fb16-4b8d-a8ce-33ac3c63536c/sist-en-301-502-v9-2-1-2010](https://standards.iteh.ai/catalog/standards/sist/471d1474-fb16-4b8d-a8ce-33ac3c63536c/sist-en-301-502-v9-2-1-2010)

ICS:

33.070.50	Globalni sistem za mobilno telekomunikacijo (GSM)	Global System for Mobile Communication (GSM)
-----------	---	--

SIST EN 301 502 V9.2.1:2010 **en**

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 502 V9.2.1:2010](#)

<https://standards.iteh.ai/catalog/standards/sist/471d1474-fb16-4b8d-a8ce-33ac3c63536c/sist-en-301-502-v9-2-1-2010>

ETSI EN 301 502 V9.2.1 (2010-10)

Harmonized European Standard (Telecommunications series)

**Global System for Mobile communications (GSM);
Harmonized EN for Base Station Equipment
covering the essential requirements
of article 3.2 of the R&TTE Directive**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 502 V9.2.1:2010](#)

<https://standards.iteh.ai/catalog/standards/sist/471d1474-fb16-4b8d-a8ce-33ac3c63536c/sist-en-301-502-v9-2-1-2010>



Reference
REN/MSG-00005
Keywords
GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse 06 N° 7303/88

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 502 V9.2.1:2010](#)
<https://standards.iteh.ai/catalog/standards/sist/471d1474-fb16-4b8d-a8ce-33ac3c6357a4/standards/sist/en/2010-10-01/v9-2-1-2010>
Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™, TIPHON™, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	7
Foreword.....	7
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	10
3 Definitions and abbreviations.....	10
3.1 Definitions.....	10
3.2 Abbreviations	12
4 Technical requirements specifications	13
4.1 Environmental profile.....	13
4.2 Conformance requirements	13
4.2.1 Modulation accuracy.....	14
4.2.1.1 Definition	14
4.2.1.2 Limit.....	14
4.2.1.3 Conformance	15
4.2.2 Mean transmitted RF carrier power	15
4.2.2.1 Definition	15
4.2.2.2 Limit.....	15
4.2.2.3 Conformance	16
4.2.3 Transmitted RF carrier power versus time.....	16
4.2.3.1 Definition	16
4.2.3.2 Limit.....	16
4.2.3.3 Conformance	19
4.2.4 Adjacent channel power.....	19
4.2.4.1 Spectrum due to modulation and wideband noise.....	20
4.2.4.1.1 Definition.....	20
4.2.4.1.2 Limit	20
4.2.4.1.3 Conformance	22
4.2.4.2 Switching transients spectrum.....	22
4.2.4.2.1 Definition.....	22
4.2.4.2.2 Limit	22
4.2.4.2.3 Conformance	22
4.2.5 Spurious emissions from the transmitter antenna connector.....	22
4.2.5.1 Conducted spurious emissions from the transmitter antenna connector, inside the BTS transmit band.....	22
4.2.5.1.1 Definition.....	22
4.2.5.1.2 Limit	22
4.2.5.1.3 Conformance	22
4.2.5.2 Conducted spurious emissions from the transmitter antenna connector, outside the BTS transmit band.....	22
4.2.5.2.1 Definition.....	23
4.2.5.2.2 Limit	23
4.2.5.2.3 Conformance	24
4.2.5.3 Conducted spurious emissions from the transmitter antenna connector, in 3G bands outside the BTS transmit band	24
4.2.5.3.1 Definition.....	24
4.2.5.3.2 Limit	24
4.2.5.3.3 Conformance	24
4.2.6 Intermodulation attenuation	24
4.2.6.1 Definition	24
4.2.6.2 Limit.....	24

4.2.6.2.1	For all BTSs except multicarrier BTS	24
4.2.6.2.2	For multicarrier BTS	25
4.2.6.3	Conformance	25
4.2.7	Intra Base Station System intermodulation attenuation	25
4.2.7.1	Definition	25
4.2.7.2	Limit.....	25
4.2.7.2.1	For all BTSs except multicarrier BTS	25
4.2.7.2.2	For multicarrier BTS	25
4.2.7.3	Conformance	25
4.2.8	Wideband noise and intra BSS intermodulation attenuation in multicarrier operation.....	25
4.2.8.1	Definition	25
4.2.8.2	Limit.....	26
4.2.9	Static Reference Sensitivity Level	27
4.2.9.1	Definition	27
4.2.9.2	Limit.....	27
4.2.9.3	Conformance	30
4.2.10	Multipath Reference Sensitivity Level	30
4.2.10.1	Definition	30
4.2.10.2	Limit.....	30
4.2.10.3	Conformance	37
4.2.11	Reference Interference Level.....	37
4.2.11.1	Definition	37
4.2.11.2	Limit.....	38
4.2.11.3	Conformance	51
4.2.12	Blocking Characteristics	51
4.2.12.1	Definition	51
4.2.12.2	Limit.....	51
4.2.12.2.1	Blocking	51
4.2.12.2.2	Spurious response	52
4.2.12.3	Conformance	52
4.2.13	Intermodulation characteristics	52
4.2.13.1	Definition	52
4.2.13.2	Limit.....	53
4.2.13.3	Conformance	53
4.2.14	AM suppression	53
4.2.14.1	Definition	53
4.2.14.2	Limit.....	53
4.2.14.3	Conformance	53
4.2.15	Spurious emissions from the receiver antenna connector	53
4.2.15.1	Definition	53
4.2.15.2	Limit.....	54
4.2.15.3	Conformance	54
4.2.16	Radiated spurious emissions	54
4.2.16.1	Definition	54
4.2.16.2	Limit.....	54
4.2.16.3	Conformance	54
5	Testing for compliance with technical requirements.....	54
5.1	Environmental conditions for testing	54
5.2	Interpretation of the measurement results	55
5.3	Essential radio test suites.....	56
5.3.1	Modulation accuracy.....	56
5.3.1.1	Test case.....	56
5.3.1.2	Test Environment.....	57
5.3.2	Mean transmitted RF carrier power	57
5.3.2.1	Test case.....	57
5.3.2.2	Test Environment.....	58
5.3.3	Transmitted RF carrier power versus time.....	58
5.3.3.1	Test case.....	58
5.3.3.2	Test Environment.....	59
5.3.4	Adjacent channel power.....	59
5.3.4.1	Spectrum due to modulation and wideband noise	59

5.3.4.1.1	Test case	59
5.3.4.1.2	Test Environment	60
5.3.4.2	Switching transients spectrum.....	60
5.3.4.2.1	Test case	60
5.3.4.2.2	Test Environment	61
5.3.5	Spurious emissions from the transmitter antenna connector.....	62
5.3.5.1	Conducted spurious emissions from the transmitter antenna connector, inside the BTS transmit band.....	62
5.3.5.1.1	Test case	62
5.3.5.1.2	Test Environment	62
5.3.5.2	Conducted spurious emissions from the transmitter antenna connector, outside the BTS transmit band.....	62
5.3.5.2.1	All base stations except multicarrier BTS	62
5.3.5.2.2	Multicarrier BTS	63
5.3.5.3	Conducted spurious emissions from the transmitter antenna connector, in 3G bands outside the BTS transmit band	65
5.3.5.3.1	Test case	65
5.3.5.3.2	Test Environment	66
5.3.6	Intermodulation attenuation.....	66
5.3.6.1	Test case.....	66
5.3.6.2	Test Environment.....	68
5.3.7	Intra Base Station System intermodulation attenuation.....	68
5.3.7.1	Test case.....	68
5.3.7.2	Test Environment.....	69
5.3.8	Wideband noise and intra BSS intermodulation attenuation in multicarrier operation.....	69
5.3.8.1	Test case.....	69
5.3.8.2	Test Environment.....	71
5.3.9	Static reference sensitivity level	71
5.3.9.1	Test case.....	71
5.3.9.2	Test Environment.....	73
5.3.10	Multipath Reference Sensitivity Level	73
5.3.10.1	Test case.....	73
5.3.10.2	Test Environment.....	78
5.3.11	Reference Interference Level 3c63536c:sist-en-301-502-v9.2-1-2010.....	78
5.3.11.1	Test case.....	78
5.3.11.2	Test Environment.....	85
5.3.12	Blocking Characteristics	85
5.3.12.1	Test case.....	86
5.3.12.2	Test Environment.....	89
5.3.13	Intermodulation characteristics	89
5.3.13.1	Test case.....	89
5.3.13.2	Test Environment.....	91
5.3.14	AM suppression	91
5.3.14.1	Test case.....	91
5.3.14.2	Test Environment.....	92
5.3.15	Spurious emissions from the receiver antenna connector	92
5.3.15.1	Test case.....	93
5.3.15.2	Test Environment.....	93
5.3.16	Radiated spurious emissions	93
5.3.16.1	Test case.....	94
5.3.16.2	Test Environment.....	95
Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT).....	96
Annex B (normative):	General test conditions and declarations.....	98
B.1	Declaration by manufacturer	98
B.1.1	Output power and determination of power class	98
B.1.2	Specified frequency range	98
B.1.3	Frequency hopping	99
B.1.4	RF power control.....	99

B.1.5	Downlink discontinuous transmission (DTX)	99
B.2	BTS Configurations.....	99
B.2.1	Receiver diversity.....	100
B.2.2	Duplexers	100
B.2.3	Power supply options	101
B.2.4	Ancillary RF amplifiers.....	101
B.2.5	BSS using antenna arrays	101
B.2.6	BTS supporting 8-PSK modulation.....	103
B.2.7	BTS supporting additional modulations in EGPRS2.....	103
B.2.8	Supported Symbol Rate.....	103
B.2.9	Support of RTTI and/or FANR	103
B.2.10	Multicarrier BTS	103
Annex C (normative):	Test environments.....	105
C.1	Normal test environment	105
C.2	Extreme test environment.....	105
C.2.1	Extreme temperature	106
C.3	Vibration.....	106
C.4	Power supply	106
Annex D (informative):	The EN title in the official languages	107
Annex E (informative):	Bibliography	108
History	iTeh STANDARD PREVIEW (standards.iteh.ai)	109

[SIST EN 301 502 V9.2.1:2010](#)

<https://standards.iteh.ai/catalog/standards/sist/471d1474-fb16-4b8d-a8ce-33ac3c63536c/sist-en-301-502-v9-2-1-2010>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Mobile Standards Group (MSG).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [i.1] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [i.2] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

The requirements relevant to Directive 1999/5/EC [i.2] are summarized in annex A.

SIST EN 301 502 V9.2.1:2010	
https://standards.iteh.ai/itstdn1/standards/itstdn1/171d1474fb16-4b8d-a8ce-33ae3c63536c/ist_en_301_502_v9_2_1_2010	
Date of adoption of this EN:	19 October 2010
Date of latest announcement of this EN (doa):	31 January 2011
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 July 2011
Date of withdrawal of any conflicting National Standard (dow):	31 July 2012

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive. The modular structure is shown in EG 201 399 [i.3].

Figure 1: Void

1 Scope

The present document applies to the following {radio}{telecommunications terminal} equipment types:

- 1) GSM base stations.

Table 1-1: GSM Base Station System frequency bands

GSM band	Direction of transmission	GSM Base Station System relevant frequency bands
P-GSM 900	Transmit	935 MHz to 960 MHz
	Receive	890 MHz to 915 MHz
E-GSM 900	Transmit	925 MHz to 960 MHz
	Receive	880 MHz to 915 MHz
R-GSM 900	Transmit	921 MHz to 960 MHz
	Receive	876 MHz to 915 MHz
DCS 1 800	Transmit	1 805 MHz to 1 880 MHz
	Receive	1 710 MHz to 1 785 MHz
GSM 450	Transmit	460,4 MHz to 467,6 MHz
	Receive	450,4 MHz to 457,6 MHz
GSM 480	Transmit	488,8 MHz to 496 MHz
	Receive	478,8 MHz to 486 MHz

The present document is intended to cover the provisions of Directive 1999/5/EC [i.2] (R&TTE Directive), article 3.2, which states that "..... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In regards to interference to systems operating in adjacent bands guidance for single carrier BTS and multicarrier BTS is provided in ECC Report 146 [i.4].

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements https://standards.etsi.org/catalog/standards/sist/4/1d14/4_1b16-4b8d-a8ce-33ac3c63336c/sist-en-301-502-v9-2-1-2010 under other parts of article 3 of the R&TTE Directive [i.2] may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org>.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TR 121 905 (V8.8.0): "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Vocabulary for 3GPP Specifications (3GPP TR 21.905 version 8.8.0 Release 8)".
- [2] ETSI TS 151 021 (V8.7.0): "Digital cellular telecommunications system (Phase 2+); Base Station System (BSS) equipment specification; Radio aspects (3GPP TS 51.021 version 8.7.0 Release 8)".

- [3] ETSI TS 145 002 (V8.0.0): "Digital cellular telecommunications system (Phase 2+); Multiplexing and multiple access on the radio path (3GPP TS 45.002 version 8.0.0 Release 8)".
- [4] ETSI TS 145 004 (V8.0.0): "Digital cellular telecommunications system (Phase 2+); Modulation (3GPP TS 45.004 version 8.0.0 Release 8)".
- [5] ETSI TS 145 005 (V8.9.0): "Digital cellular telecommunications system (Phase 2+); Radio Transmission and reception (3GPP TS 45.005 version 8.9.0 Release 8)".
- [6] Void.
- [7] ETSI TS 145 010 (V8.5.0): "Digital cellular telecommunications system (Phase 2+); Radio subsystem synchronization (3GPP TS 45.010 version 8.5.0 Release 8)".
- [8] ETSI TS 144 060 (V8.9.0): "Digital cellular telecommunications system (Phase 2+); General Packet Radio Service (GPRS); Mobile Station (MS) - Base Station System (BSS) interface; Radio Link Control/Medium Access Control (RLC/MAC) protocol (3GPP TS 44.060 version 8.9.0 Release 8)".
- [9] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [10] ETSI EN 300 019-1 (V2.1.2): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-0: Classification of environmental conditions; Introduction".
- [11] ETSI EN 300 019-1-3 (V2.3.2): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-3: Classification of environmental conditions; Stationary use at weatherprotected locations".

THE STANDARD REVIEW

- [12] ETSI EN 300 019-1-4 (V2.1.2): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-4: Classification of environmental conditions; Stationary use at non-weatherprotected locations".
- [13] IEC 60068-2-2007: "Environmental testing procedures; Part 2-20: Tests - 33ac3c63536c/sist-en-301-502-v9-2-1-2010"
- [14] IEC 60721 (2002): "Classification of environmental conditions".
- [15] ETSI TS 124 022 (V8.0.0): "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Radio Link Protocol (RLP) for circuit switched bearer and teleservices (3GPP TS 24.022 version 8.0.0 Release 8)".
- [16] ETSI TS 148 020 (V8.0.0): "Digital cellular telecommunications system (Phase 2+); Rate Adaptation on the Base Station System - Mobile Service Switching Centre (BSS-MSC) Interface (3GPP TS 48.020 version 8.0.0 Release 8)".
- [17] ITU-T Recommendation O.153 (1992): "Basic Parameters for the measurement of error performance at bit rates below the primary rate".
- [18] ITU-R Recommendation SM.329-10 (2003): "Unwanted emissions in the spurious domain".
- [19] ETSI TS 145 001 (V8.1.0): "Digital cellular telecommunications system (Phase 2+); Physical layer on the radio path; General description (3GPP TS 45.001 version 8.1.0 Release 8)".
- [20] ITU-T Recommendation O.151 (1992): "Error performance measuring equipment operating at the primary rate and above".
- [21] CEPT/ERC/Recommendation 74-01E: "Unwanted emissions in the spurious domain".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.2] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.3] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the R&TTE Directive".
- [i.4] ECC Report 146: "Compatibility between GSM MCBTS and other services (TRR, RSBN/PRMG, HC-SDMA, GSM-R, DME, MIDS, DECT) operating in the 900 and 1800 MHz frequency bands", 6th July 2010.
- [i.5] ETSI EN 301 908-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Base Stations (BS), Repeaters and User Equipment (UE) for IMT-2000 Third-Generation cellular networks; Part 1: Harmonized EN for IMT-2000, introduction and common requirements, covering the essential requirements of article 3.2 of the R&TTE Directive".
- [i.6] ETSI EN 301 908-18: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Base Stations (BS), Repeaters and User Equipment (UE) for IMT-2000 Third-Generation cellular networks; Part 18: Harmonized EN for E-UTRA, UTRA and GSM/EDGE Multi-Standard Radio (MSR) Base Station (BS) covering the essential requirements of article 3.2 of the R&TTE Directive".

THE STANDARD PREVIEW

(standards.iteh.ai)

3 Definitions and abbreviations

<https://standards.iteh.ai/catalog/standards/sist/471d1474-fb16-4b8d-a8ce-33ac3c63536c/sist-en-301-502-v9-2-1-2010>

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 121 905 [1] and the following apply:

8-PSK: modulation type as defined in TS 145 004 [4], clause 3

16-QAM: modulation type as defined in TS 145 004 [4], clause 4 for EGPRS2-A and clause 5 for EGRPS2-B

32-QAM: modulation type as defined in TS 145 004 [4], clause 4 for EGPRS2-A and clause 5 for EGRPS2-B

ancillary RF amplifier: piece of equipment, which when connected by RF coaxial cables to the BTS, has the primary function to provide amplification between the transmit and/or receive antenna connector of a BTS and an antenna without requiring any control signal to fulfil its amplifying function

base station RF bandwidth: instantaneous bandwidth in which a multicarrier BTS transmits or receives multiple carriers simultaneously

BSS: in the present document, the term BSS (or base station subsystem) applies to both a BTS and integrated BSS

NOTE: If a separate BSC is required to perform tests on a BTS, the BSC may be regarded as test equipment and the environmental conditions of the BSC need not be controlled.

Base Station System Test Equipment (BSSTE): See annex B in TS 151 021 [2].

carrier frequency: centre of the ARFCN under test

circuit switched logical channels: all the standard GSM logical channels, including traffic channels (TCH), common control channels (RACH) and dedicated control channels (SDCCH, SACCH)

E-GSM: extended GSM 900 band (includes P-GSM band)

ECSD: any subset of the E-TCH traffic channels and related control channels

EGPRS: any subset of the packet traffic channels PDTCH/MCS-1 to MCS-9 and related control channels

EGPRS2: any of EGPRS2-A and EGPRS2-B

EGPRS2-A: packet traffic channels utilizing any subset of the packet traffic channels MCS-1 to 6 and PDTCH/UAS-7 to UAS-11 in uplink, together with MCS-1 to 4 and PDTCH/DAS-5 to DAS-12 in downlink, and related control channels

NOTE In addition, MCS-7 and MCS-8 may be used in downlink when either the USF or the PAN or both are addressed to one or more EGPRS mobile stations.

EGPRS2-B: packet traffic channels utilizing any subset of the packet traffic channels MCS-1 to 4 and PDTCH/UBS-5 to UBS-12 in uplink, together with MCS-1 to 4 and PDTCH/DBS-5 to DBS-12 in downlink, and related control channels

NOTE: In addition, MCS-6 to MCS-9, DAS-5, DAS-6, DAS-8, DAS-9, DAS-10 pad, DAS-11, and DAS-12 pad may be used in downlink under the conditions specified in TS 144 060 [8].

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

GMSK: modulation type as defined by TS 145 004 [4], clause 2

GPRS: any subset of the packet traffic channels PDTCH/CS-1 to CS-4 and related control channels

GSM: unless otherwise specified, references to GSM include GSM 400, GSM 900 and DCS1800

GSM 400: unless otherwise specified, references to GSM 400 include GSM 450 and GSM 480 band

GSM 900: unless otherwise specified, references to GSM 900 include P-GSM, E-GSM and R-GSM band

manufacturer: in the present document, a reference to a manufacturer shall also apply to an agent of the manufacturer

[SIST EN 301 502 V9.2.1:2010](#)

maximum base station RF bandwidth: maximum bandwidth in which a multicarrier BTS transmits or receives multiple carriers simultaneously

maximum transmit filter bandwidth: maximum bandwidth of the duplexer or the transmit filter used in a multicarrier BTS transmitting carriers simultaneously

micro-BTS: low-power BTS with performance requirements defined in TS 145 005 [5]

NOTE: In the present document, this also includes a BSS which incorporates a micro-BTS.

multicarrier BTS: class of BTS, characterized by the ability to, in addition to single carrier operation, process two or more carriers in common active components simultaneously, either in multicarrier transmitter only or, in both multicarrier transmitter and multicarrier receiver

normal BTS: any BTS or BSS as defined by TS 145 005 [5] which is not a micro-BTS or pico-BTS

operating band: transmit and receive operating bands together comprise the frequency band supported by the BSS

NOTE: As defined in clause B.1.2.

P-GSM: primary GSM 900 band

packet switched logical channels: all the General Packet Radio Services (GPRS) packet data logical channels, including packet traffic channels (PDTCH and PACCH) and packet common control channels (PRACH)

pico-BTS: low-power BTs with performance requirements defined in TS 145 005 [5]

NOTE: In the present document, this also includes a BSS which incorporates a pico-BTS.

QPSK: modulation type as defined TS 145 004 clause 5 [4], used in EGPRS2-B

R-GSM: Railways GSM 900 band (includes P-GSM band and E-GSM band)

relevant RX band (or relevant receive band): receive band for the frequency band of BTS declared by the manufacturer

NOTE: As defined in clause 1.

relevant TX band (or relevant transmit band): transmit band for the frequency band of BTS declared by the manufacturer

NOTE: As defined in clause 1.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 121 905 [1] and the following apply:

AGC	Automatic Gain Control
AMR	Adaptive Multi-rate
AMR-WB	Adaptive - Wideband
ARFCN	Absolute Radio Frequency Channel Number
B	Bottom
BCCH	Broadcast Control Channel
BER	Bit Error Ratio
BLER	BLock Error Ratio
BSC	Base Station Controller
BSS	Base Station System
BSSTE	Base Station System Test Equipment
BTS	Base Tranceiver Station
BTI	Basic Transmission Time Interval
BW	Bandwidth
DAS	EGPRS2 Downlink Level A modulation and coding Scheme
DBS	EGPRS2 Downlink Level B modulation and coding Scheme
DC	Direct Current
DCS	Digital Cellular System SIST EN 301 502 V9.2.1:2010
ECSD	Enhanced Circuit Switched Data http://standards.etsi.org/standards/sist/471d1474-fb16-4b8d-a8ce-33ac3c63536c/sist-en-301-502-v9-2-1-2010
EGPRS	Enhanced GPRS http://standards.etsi.org/standards/sist/471d1474-fb16-4b8d-a8ce-33ac3c63536c/sist-en-301-502-v9-2-1-2010
EGPRS2	Enhanced GPRS phase 2
ESIDR	Erased SID frame Rate
E-TCH	Enhanced Traffic Channel
EVM	Error Vector Magnitude
EVFR	Erased Valid RATSCCH Frame Rate
EVSIDR	Erased Valid SID frame Rate
EVSIDUR	Erased Valid SID_UPDATE frame Rate associated to an adaptive speech traffic channel
FANR	Fast Ack/Nack Reporting
FER	Frame Erasure Ratio
GMSK	Gaussian Minimum Shift Keying
GPRS	General Packet Radio Service
IM	InterModulation
M	Middle
MCBTS	multicarrier BTS
MFS	Multipath Fading Simulator
MSC	Mobile service Switching Centre
MSE	Mean Square Error
O-FACCH	Octal Fast Associated Control Channel
PAN	Piggy-backed Ack/Nack message
PDTCH	Packet Data Traffic Channel
PSK	Phase Shift Keying
RACH	Random Access Channel
RBER	Residual Bit Error Ratio
RF	Radio Frequency
RTTI	Reduced Transmission Time Interval
RX	Reception
SACCH	Slow associated Control Channel
SDCCH	Stand alone Dedicated Control Channel

SFH	Slow Frequency Hopping
T	Top
TCH	Traffic Channel
TRX	Transceiver
TSC	Training Sequence Code
TX	Transmission
UAS	EGPRS2 Uplink level A modulation and coding Scheme
UBS	EGPRS2 Uplink level B modulation and coding Scheme
UFR	Unreliable Frame Rate
WFS	Wideband AMR full rate codec based on GMSK

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile.

For guidance on how a supplier can declare the environmental profile see annex C.

4.2 Conformance requirements

The STANDARD PREVIEW

Support of certain functions of a BTS are optional in the GSM specifications. When specified in a test, the manufacturer shall declare the nominal value of a parameter, or whether an option is supported. A summary of such functions are included in annex B.

SIST EN 301 502 V9.2.1:2010
<https://standards.etsi.org/catalog/standards/sist/4/101474/fb16-4b8d-asce-33ac3cb6333bc/sist-en-301-502-v9.2.1-2010>
For a multicarrier BTS additionally conforming to EN 301 908-1 [i.5] and EN 301 908-18 [i.6], conformance with the technical requirements listed in table 4.2-1 can equally be demonstrated through the corresponding technical requirements and test suites in EN 301 908-1 [i.5] and EN 301 908-18 [i.6], as listed in table 4.2-1.

When conformance is demonstrated through the test suites in EN 301 908-1 [i.5] and EN 301 908-18 [i.6] for these technical requirements, the corresponding test suites in the present document need not be performed.

Table 4.2-1: Alternative technical requirements and test suites in EN 301 908-1 [i.5] and EN 301 908-18 [i.6] that can equally be used for demonstrating conformance for MCBTS

Technical requirement in the present document	Corresponding technical requirements in EN 301 908	Corresponding test suites in EN 301 908
4.2.5.2 Conducted spurious emissions from the transmitter antenna connector, outside the BTS transmit band (Note 1)	4.2.4 Transmitter spurious emissions (in EN 301 908-18 [i.6])	5.3.3 Transmitter spurious emissions (in EN 301 908-18 [i.6])
4.2.5.3 Conducted spurious emissions from the transmitter antenna connector, in 3G bands outside the BTS transmit band	4.2.4 Transmitter spurious emissions (in EN 301 908-18 [i.6])	5.3.3 Transmitter spurious emissions (in EN 301 908-18 [i.6])
4.2.12 Blocking Characteristics (Note 2)	4.2.9 Out-of-band blocking (in EN 301 908-18 [i.6])	5.3.8 Out-of-band blocking (in EN 301 908-18 [i.6])
4.2.15 Spurious emissions from the receiver antenna connector	4.2.7 Receiver spurious emissions (in EN 301 908-18 [i.6])	5.3.6 Receiver spurious emissions (in EN 301 908-18 [i.6])
4.2.16 Radiated spurious emissions	4.2.3 Radiated emissions (BS and repeater) (in EN 301 908-1 [i.5])	5.3.2 Radiated emissions (BS and repeater) (in EN 301 908-1 [i.5])
NOTE 1: Applicable for frequency offsets larger than 10 MHz outside the relevant transmit band.		
NOTE 2: Applicable for frequency offsets outside the relevant inband frequencies, as defined in table 5.12-2 in the present document.		