

ETSI EN 300 086-2 V1.3.1 (2010-06)

Harmonized European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Land Mobile Service;
Radio equipment with an internal or external RF
connector intended primarily for analogue speech;
Part 2: Harmonized EN covering the essential requirements
of article 3.2 of the R&TTE Directive**

ITeH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/4180cca5-8849-414b-8c1b-5cd4ee046b43/etsi-en-300-086-2-v1.3.1-2010-06>



ReferenceREN/ERM-TGDMR-288-2

Keywordsanalogue, antenna, mobile, PMR, radio,
regulation, speech**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Introduction	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	7
3 Definitions, symbols and abbreviations	7
3.1 Definitions.....	7
3.2 Symbols.....	7
3.3 Abbreviations	7
4 Technical requirements specifications	7
4.1 Environmental profile.....	7
4.2 Transmitter requirements	7
4.2.1 Frequency error.....	7
4.2.1.1 Definition	7
4.2.1.2 Limit.....	8
4.2.1.3 Conformance.....	8
4.2.2 Transmitter power (conducted).....	8
4.2.2.1 Definition	8
4.2.2.2 Limit.....	8
4.2.2.3 Conformance.....	8
4.2.3 Maximum effective radiated power	8
4.2.3.1 Definition	8
4.2.3.2 Limit.....	8
4.2.3.3 Conformance.....	8
4.2.4 Adjacent and alternate channel power	8
4.2.4.1 Definition	8
4.2.4.2 Limit.....	8
4.2.4.3 Conformance.....	8
4.2.5 Unwanted emissions in the spurious domain	8
4.2.5.1 Definition	8
4.2.5.2 Limit.....	9
4.2.5.3 Conformance.....	9
4.2.6 Intermodulation attenuation	9
4.2.6.1 Definition	9
4.2.6.2 Limit.....	9
4.2.6.3 Conformance.....	9
4.3 Receiver requirements	9
4.3.1 Maximum usable receiver sensitivity	9
4.3.1.1 Definition	9
4.3.1.2 Limit.....	9
4.3.1.3 Conformance.....	9
4.3.2 Co-channel rejection	9
4.3.2.1 Definition	9
4.3.2.2 Limit.....	9
4.3.2.3 Conformance.....	10
4.3.3 Adjacent channel selectivity	10
4.3.3.1 Definition	10
4.3.3.2 Limit.....	10
4.3.3.3 Conformance.....	10
4.3.4 Spurious response rejection	10
4.3.4.1 Definition	10
4.3.4.2 Limit.....	10

4.3.4.3	Conformance	10
4.3.5	Intermodulation response rejection	10
4.3.5.1	Definition	10
4.3.5.2	Limit	10
4.3.5.3	Conformance	10
4.3.6	Blocking or desensitization	11
4.3.6.1	Definition	11
4.3.6.2	Limit	11
4.3.6.3	Conformance	11
4.3.7	Spurious radiations	11
4.3.7.1	Definition	11
4.3.7.2	Limit	11
4.3.7.3	Conformance	11
5	Testing for compliance with technical requirements	11
5.1	Environmental conditions for testing	11
5.1.1	Normal and extreme test-conditions	11
5.1.2	Test power source	11
5.1.3	Choice of samples for test suites	11
5.2	Interpretation of the measurement results	12
5.3	Essential radio test suites	12
5.3.1	Frequency error	12
5.3.2	Transmitter power (conducted)	12
5.3.3	Maximum effective radiated power	12
5.3.4	Adjacent and alternate channel power	12
5.3.5	Unwanted emissions in the spurious domain	12
5.3.6	Intermodulation attenuation	12
5.3.7	Receiver Spurious radiations	12
5.3.8	Maximum usable receiver sensitivity	13
5.3.9	Co-channel rejection	13
5.3.10	Adjacent channel selectivity	13
5.3.11	Spurious response rejection	13
5.3.12	Intermodulation response rejection	13
5.3.13	Receiver blocking or desensitization	13
Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT)	14
Annex B (informative):	The EN title in the official languages	16
History		17

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC (as amended) [i.2] laying down a procedure for the provision of information in the field of technical standards and regulations.

The present document is intended to become a Harmonized Standard, the reference of which will be published in the Official Journal of the European Communities referencing the Directive 1999/5/EC [i.1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity ("the R&TTE Directive").

Technical specifications relevant to Directive 1999/5/EC [i.1] are given in annex A.

The present document is part 2 of a multi-part deliverable covering the Land Mobile Service; Radio equipment with an internal or external RF connector intended primarily for analogue speech, as identified below:

Part 1: "Technical characteristics and methods of measurement";

Part 2: "Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".

National transposition dates

Date of adoption of this EN:	24 June 2010
Date of latest announcement of this EN (doa):	30 September 2010
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 March 2011
Date of withdrawal of any conflicting National Standard (dow):	31 March 2012

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive. The modular structure is shown in EG 201 399 [i.3].

1 Scope

The present document covers the technical requirements for radio transmitters and receivers used in stations in the Private Mobile Radio (PMR) service.

It applies to use in the land mobile service, operating on radio frequencies between 30 MHz and 1 GHz, with channel separations of 12,5 kHz, 20 kHz and 25 kHz, primarily intended for analogue speech.

Table 1: Radiocommunications service frequency bands

Radiocommunications service frequency bands	
Transmit	30 MHz to 1 000 MHz
Receive	30 MHz to 1 000 MHz

The equipment comprises a transmitter and associated modulator and/or a receiver and associated demodulator. The types of equipment covered by the present document are as follows:

- base station (equipment fitted with an antenna connector, intended for use in a fixed location);
- mobile station (equipment fitted with an antenna connector, normally used in a vehicle or as a transportable); and
- those hand portable stations:
 - a) fitted with an antenna connector; or
 - b) without an external antenna connector, but fitted with a permanent internal or a temporary internal 50 Ω Radio Frequency (RF) connector which allows access to the transmitter output and the receiver input.

Hand portable equipment without an external or internal RF connector and without the possibility of having a temporary internal 50 Ω RF connector is not covered by the present document.

NOTE: Hand portable equipment without an external or internal RF connector and without the possibility of having a temporary internal 50 Ω RF connector is not covered by the present document (integral antenna equipment is covered by EN 300 296 [i.4]).

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 086-1 (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land Mobile Service; Radio equipment with an internal or external RF connector intended primarily for analogue speech; Part 1: Technical characteristics and methods of measurement".
- [2] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.2] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.3] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of candidate Harmonized Standards for application under the R&TTE Directive".
- [i.4] ETSI EN 300 296 (all parts): "ElectroMagnetic Compatibility and Radio Spectrum Matters (ERM); Land Mobile Service; Radio equipment using integral antennas intended primarily for analogue speech".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in EN 300 086-1 [1] apply.

3.2 Symbols

For the purposes of the present document, the symbols given in EN 300 086-1 [1] apply.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in EN 300 086-1 [1] apply.

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the manufacturer of the equipment. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile.

4.2 Transmitter requirements

4.2.1 Frequency error

4.2.1.1 Definition

The frequency error is defined in EN 300 086-1 [1], clause 7.1.1.

4.2.1.2 Limit

The frequency error shall not exceed the limits in EN 300 086-1 [1], clause 7.1.3.

4.2.1.3 Conformance

Conformance tests as defined in clause 5.3.1 shall be carried out.

4.2.2 Transmitter power (conducted)

4.2.2.1 Definition

The transmitter power (conducted) is defined in EN 300 086-1 [1], clause 7.2.1.

4.2.2.2 Limit

The transmitter power (conducted) shall not exceed the limits in EN 300 086-1 [1], clause 7.2.3.

4.2.2.3 Conformance

Conformance tests as defined in clause 5.3.2 shall be carried out.

4.2.3 Maximum effective radiated power

4.2.3.1 Definition

The maximum effective radiated power is defined in EN 300 086-1 [1], clause 7.3.1.

4.2.3.2 Limit

The maximum effective radiated power shall not exceed the limits in EN 300 086-1 [1], clause 7.3.3.

4.2.3.3 Conformance

Conformance tests as defined in clause 5.3.3 shall be carried out.

4.2.4 Adjacent and alternate channel power

4.2.4.1 Definition

The adjacent and alternate channel power is defined in EN 300 086-1 [1], clause 7.5.1.

4.2.4.2 Limit

The adjacent and alternate channel power shall not exceed the limits in EN 300 086-1 [1], clause 7.5.3.

4.2.4.3 Conformance

Conformance tests as defined in clause 5.3.4 shall be carried out.

4.2.5 Unwanted emissions in the spurious domain

4.2.5.1 Definition

The unwanted emissions in the spurious domain are defined in EN 300 086-1 [1], clause 7.6.1.

4.2.5.2 Limit

The unwanted emissions in the spurious domain shall not exceed the limits in EN 300 086-1 [1], clause 7.6.4.

4.2.5.3 Conformance

Conformance tests as defined in clause 5.3.5 shall be carried out.

4.2.6 Intermodulation attenuation

4.2.6.1 Definition

The intermodulation attenuation is defined in EN 300 086-1 [1], clause 7.7.1.

4.2.6.2 Limit

The intermodulation attenuation shall not exceed the limits in EN 300 086-1 [1], clause 7.7.3.

4.2.6.3 Conformance

Conformance tests as defined in clause 5.3.6 shall be carried out.

4.3 Receiver requirements

4.3.1 Maximum usable receiver sensitivity

4.3.1.1 Definition

The maximum usable receiver sensitivity is defined in EN 300 086-1 [1], clause 8.1.1 (conducted) and clause 8.2.1 (field strength).

In addition, for duplex equipment (equipment providing simultaneous transmission and reception), the receiver desensitization is defined in EN 300 086-1 [1], clause 9.1.1.

4.3.1.2 Limit

The sensitivity shall not exceed the limits in EN 300 086-1 [1], clause 8.1.3 (conducted) and clause 8.2.3 (field strength).

In addition, for duplex equipment (equipment providing simultaneous transmission and reception), the receiver desensitization shall meet the requirements of EN 300 086-1 [1], clause 9.1.4.

4.3.1.3 Conformance

Conformance tests as defined in clause 5.3.9 may be carried out.

4.3.2 Co-channel rejection

4.3.2.1 Definition

The co-channel rejection is defined in EN 300 086-1 [1], clause 8.3.1.

4.3.2.2 Limit

The co-channel rejection shall not exceed the limits in EN 300 086-1 [1], clause 8.3.3.