

SLOVENSKI STANDARD
oSIST prEN 302 372-1 V1.2.1:2010
01-november-2010

**Elektromagnetna združljivost in zadeve v zvezi z radijskim spektrom (ERM) -
Naprave kratkega dosega (SRD) - Oprema za odkrivanje in premikanje - Radar za
sondiranje nivoja v rezervoarjih (TLPR), ki deluje v frekvenčnih pasovih 5,8 GHz,
10 GHz, 25 GHz, 61 GHz in 77 GHz - 1. del: Tehnične karakteristike in preskusne
metode**

Electromagnetic compatibility and Radio spectrum Matters (ERM) - Short Range Devices (SRD) - Equipment for Detection and Movement - Tanks Level Probing Radar (TLPR) operating in the frequency bands 5,8 GHz, 10 GHz, 25 GHz, 61 GHz and 77 GHz - Part 1: Technical characteristics and test methods

[SIST EN 302 372-1 V1.2.1:2011](https://standards.iteh.ai/catalog/standards/sist/c1f8038e-3be7-4835-bc2d-68875af28afe/sist-en-302-372-1-v1-2-1-2011)

<https://standards.iteh.ai/catalog/standards/sist/c1f8038e-3be7-4835-bc2d-68875af28afe/sist-en-302-372-1-v1-2-1-2011>

Ta slovenski standard je istoveten z: EN 302 372-1 Version 1.2.1

ICS:

33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment
33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general

oSIST prEN 302 372-1 V1.2.1:2010 **en**

Draft ETSI EN 302 372-1 V1.2.1 (2010-08)

European Standard (Telecommunications series)

**Electromagnetic compatibility
and Radio spectrum Matters (ERM);
Short Range Devices (SRD);
Equipment for Detection and Movement;
Tanks Level Probing Radar (TLPR) operating in the
frequency bands 5,8 GHz, 10 GHz, 25 GHz, 61 GHz and 77 GHz;
Part 1: Technical characteristics and test methods**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 302 372-1 V1.2.1:2011

<https://standards.iteh.ai/catalog/standards/sist/c1f8038e-3be7-4835-bc2d-68875af28afe/sist-en-302-372-1-v1-2-1-2011>



Reference

REN/ERM-TGTLPR-0117-1

Keywords

EHF, radar, regulation, SHF, short range,
SRD, testing, UWB

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 302 372-1 V1.2.1:2011

[https://standards.iteh.ai/catalog/standards/sist-en-302-372-1-v1-2-1-2011](https://standards.iteh.ai/catalog/standards/sist/en-302-372-1-v1-2-1-2011)

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	7
3 Definitions, symbols and abbreviations	7
3.1 Definitions.....	7
3.2 Symbols.....	8
3.3 Abbreviations	8
4 Technical requirements specifications	9
4.1 Presentation of equipment for testing purposes.....	9
4.2 Choice of model for testing	9
4.3 Mechanical and electrical design.....	9
4.3.1 Marking (equipment identification).....	10
4.3.1.1 Equipment identification.....	10
4.4 Auxiliary test equipment and product information.....	10
4.5 General requirements for RF cables	10
4.6 RF waveguides	11
4.6.1 Wave Guide Attenuators	12
4.7 External harmonic mixers	12
4.7.1 Introduction.....	12
4.7.2 Signal identification.....	13
4.7.3 Measurement hints.....	13
4.8 Preamplifier.....	13
4.9 Interpretation of the measurement results	14
5 Test conditions, power sources and ambient temperatures	14
5.1 Normal and extreme test conditions	14
5.2 External test power source.....	14
5.3 Normal test conditions.....	14
5.3.1 Normal temperature and humidity.....	14
5.3.2 Normal test power source	15
5.3.2.1 Mains voltage.....	15
5.3.2.2 Regulated lead-acid battery power source.....	15
5.3.2.3 Other power sources.....	15
6 General conditions.....	15
6.1 Radiated measurement arrangements	15
6.2 Measuring receiver	16
7 Measurement uncertainty	16
7.1 Conversion loss data and measurement uncertainty.....	17
8 Methods of measurement and limits.....	18
8.1 Frequency band of operation	18
8.1.1 Definition.....	18
8.1.2 Method of measurement	18
8.1.3 Limits.....	19
8.2 Duty cycle	19
8.2.1 Duty cycle resulting from application.....	19
8.2.2 Duty cycle resulting from modulation	20
8.2.2.1 Method of measurement.....	20
8.3 Equivalent isotropically radiated power (e.i.r.p.)	20
8.3.1 Definition.....	20

8.3.2	Method of measurement	21
8.3.3	Limits.....	22
8.4	Emissions	22
8.4.1	Definition.....	22
8.4.2	Method of measurement	22
8.4.3	Limits.....	25
8.5	Range of modulation parameters.....	25
Annex A (normative): Radiated measurement.....		26
A.1	Test sites and general arrangements for measurements involving the use of radiated fields	26
A.1.1	Anechoic Chamber	26
A.1.2	Anechoic Chamber with a conductive ground plane	27
A.1.3	Open Area Test Site (OATS)	28
A.1.4	Minimum requirements for test sites for measurements above 18 GHz.....	29
A.1.5	Test antenna.....	31
A.1.6	Substitution antenna	31
A.1.7	Measuring antenna	31
A.2	Guidance on the use of radiation test sites	31
A.2.1	Verification of the test site	31
A.2.2	Preparation of the EUT.....	32
A.2.3	Power supplies to the EUT.....	32
A.2.4	Range length.....	32
A.2.5	Site preparation	33
A.3	Coupling of signals.....	33
A.3.1	General	33
Annex B (normative): Installation requirements of Tank Level Probing Radar (TLPR) Equipment		34
Annex C (informative): Measurement antenna and preamplifier specifications		35
Annex D (informative): Electromagnetic leakage from a EUT		36
D.1	General	36
D.2	Survey of sources of leakage.....	36
Annex E (normative): Requirements on Test Tank.....		38
Annex F (informative): Practical test distances for accurate measurements		39
F.1	Introduction	39
F.2	Conventional near-field measurements distance limit	39
F.3	Near-field conditions outside a test tank	39
Annex G (normative): Range of modulation parameters		40
G.1	Pulse modulation	40
G.1.1	Definition	40
G.1.2	Operating parameters	41
G.2	Frequency modulated continuous wave	41
G.2.1	Definition	41
G.2.2	Operating parameters	42
Annex H (informative): Atmospheric absorptions and material dependent attenuations.....		43
H.1	Atmospheric absorptions.....	43
H.2	Material dependent attenuations.....	45
History		47

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM), and is now submitted for the Public Enquiry phase of the ETSI standards Two-step Approval Procedure.

For non-EU countries, the present document may be used for regulatory (Type Approval) purposes.

The present document is part 1 of a multi-part deliverable covering Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Equipment for Detection and Movement; Tanks Level Probing Radar (TLPR) operating in the frequency bands 5,8 GHz, 10 GHz, 25 GHz, 61 GHz and 77 GHz, as identified below:

Part 1: "Technical characteristics and test methods";

Part 2: "Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

1 Scope

The present document specifies the requirements for Tank Level Probing Radar (TLPR) applications based on pulse RF, FMCW, or similar wideband techniques, operating in the following frequency bands or part hereof as specified in table 1.

Table 1: Frequency bands designated to Tank Level Probing Radars (TLPR)

	Frequency Bands/frequencies (GHz)
Transmit and Receive	4,5 to 7
Transmit and Receive	8,5 to 10,6
Transmit and Receive	24,05 to 26,5
Transmit and Receive	57 to 64
Transmit and Receive	75 to 85

Table 1 shows a list of the frequency bands as designated to Tank Level Probing Radars in the EC-Decision 2009/381 [i.4] and Recommendation CEPT/ERC/REC 70-03 [i.1] as known at the date of publication of the present document. TLPRs are used for tank level measurement applications.

The scope is limited to TLPRs operating as Short Range Devices, in which the devices are installed in closed metallic tanks or reinforced concrete tanks, or similar enclosure structures made of comparable attenuating material, holding a substance, liquid or powder.

The radar applications in the present document are not intended for communications purposes. Their intended usage excludes any intended radiation into free space.

The present document applies to TLPRs radiating RF signals directly from the tank top downwards to the surface of a substance contained in a closed tank. Any radiation outside of the tank is caused by leakage and is considered as unintentional emission. It applies only to TLPRs fitted with dedicated antennas. The present document does not necessarily include all the characteristics, which may be required by a user, nor does it necessarily represent the optimum performance achievable.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] CISPR 16 (2006) (parts 1-1, 1-4 and 1-5): "Specification for radio disturbance and immunity measuring apparatus and methods; Part 1: Radio disturbance and immunity measuring apparatus".
- [2] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [3] ANSI C63.5 (2006): "American National Standard for Calibration of Antennas Used for Radiated Emission Measurements in Electro Magnetic Interference".

- [4] ETSI TR 102 273 (all parts) (V1.2.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [5] ETSI EN 302 372-2 (V1.2.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Equipment for Detection and Movement; Tanks Level Probing Radar (TLPR) operating in the frequency bands 5,8 GHz, 10 GHz, 25 GHz, 61 GHz and 77 GHz; Part 2: Harmonized EN under article 3.2 of the R&TTE Directive".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] CEPT/ERC/Recommendation 70-03: "Relating to the use of Short Range Devices (SRD)".
- [i.2] ITU-R Recommendation SM.1754: "Measurement techniques of Ultra-wideband transmissions".
- [i.3] ETSI TS 103 051: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Expanded measurement uncertainty for the measurement of radiated electromagnetic fields".
- [i.4] Commission Decision 2006/771/EC on harmonization of the radio spectrum for use by short range devices as amended by commission decision 2009/381/EC.
- [i.5] ETSI TS 103 052: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Radiated measurement methods and general arrangements for test sites up to 100 GHz".
- [i.6] ITU-R Recommendation P.676-5 (2001): "Attenuation by atmospheric gases".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

dedicated antenna: antenna that is designed as an indispensable part of the equipment

Device Under Test (DUT): TLPR under test without a test tank

DU: Activity Factor which is used to describe different modulation parameters and activity levels of TLPR devices and defined as the ratio of active measurement periods (bursts, sweeps, scans) within the overall repetitive measurement cycle, i.e. $T_{\text{meas}}/T_{\text{meas_cycle}}$

duty cycle: ratio of the total on time of the transmitter to the total time in any one-hour period reflecting normal operational mode

emissions: signals that leaked or are scattered into the air within the frequency range (that includes harmonics) which depend on equipment's frequency band of operation

NOTE: For TLPRs there is no intended emission outside the tank.

Equipment Under Test (EUT): TLPR under test mounted on a test tank

equivalent isotropically radiated power (e.i.r.p.): total power transmitted, assuming an isotropic radiator

NOTE: e.i.r.p. is conventionally the product of "power into the antenna" and "antenna gain". e.i.r.p. is used for both peak and average power.

Frequency Modulated Continuous Wave (FMCW) radar: radar where the transmitter power is fairly constant but possibly zero during periods giving a big duty cycle (such as 0,1 to 1)

NOTE: The frequency is modulated in some way giving a very wideband spectrum with a power versus time variation which is clearly not pulsed.

integral antenna: permanent fixed antenna, which may be built-in, designed as an indispensable part of the equipment

operating frequency (operating centre frequency): nominal frequency at which equipment is operated

pulsed radar (or here simply "pulsed TLPR"): radar where the transmitter signal has a microwave power consisting of short RF pulses

power spectral density (psd): amount of the total power inside the measuring receiver bandwidth expressed in dBm/MHz

Pulse Repetition Frequency (PRF): inverse of the Pulse Repetition Interval, averaged over a sufficiently long time to cover all PRF variations

radiated measurements: measurements that involve the absolute measurement of a radiated field

radiation: signals emitted intentionally inside a tank for level measurements

3.2 Symbols

For the purposes of the present document, the following symbols apply:

f	Frequency
f_C	Frequency at which the emission is the peak power at maximum
f_H	Highest frequency of the frequency band of operation
f_L	Lowest frequency of the frequency band of operation
t	Time
k	Boltzmann constant
T	Temperature
G	Efficient antenna gain of radiating structure
G_a	Declared measurement antenna gain
d	Largest dimension of the antenna aperture of the TLPR
d_1	Largest dimension of the DUT/dipole after substitution (m)
d_2	Largest dimension of the test antenna (m)
D	Duty cycle
D_U	Duty cycle determined by the users transmission time
D_X	Duty cycle determined by the transmitters modulation type
P_s	Output power of the signal generator measured by power meter
Δf	Bandwidth
X	Minimum radial distance (m) between the DUT and the test antenna
λ	Wavelength

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

dB	deciBel
dBi	antenna gain in decibels relative to an isotropic antenna
DUT	Device Under Test
e.i.r.p.	equivalent isotropically radiated power
EMC	ElectroMagnetic Compatibility
ERC	European Radiocommunication Committee
EUT	Equipment Under Test
FMCW	Frequency Modulated Continuous Wave
IF	Intermediate Frequency
LNA	Low Noise Amplifier
LO	Local Oscillator
OATS	Open Area Test Site

PRF	Pulse Repetition Frequency
PRI	Pulse Repetition Interval
PSD	Power Spectral Density
R&TTE	Radio and Telecommunications Terminal Equipment
RBW	Resolution BandWidth
RF	Radio Frequency
RMS	Root Mean Square
SA	Spectrum Analyser
SRD	Short Range Device
TLPR	Tank Level Probing Radar
Tx	Transmitter
UWB	Ultra WideBand
VBW	Video BandWidth
VSWR	Voltage Standing Wave Ratio

4 Technical requirements specifications

4.1 Presentation of equipment for testing purposes

Equipment submitted for testing, where applicable, shall fulfil the requirements of the present document on all frequencies over which it is intended to operate.

The provider shall submit one or more samples of the equipment as appropriate for testing.

Additionally, technical documentation and operating manuals, sufficient to allow testing to be performed, shall be supplied.

The performance of the equipment submitted for testing shall be representative of the performance of the corresponding production model. In order to avoid any ambiguity in that assessment, the present document contains instructions for the presentation of equipment for testing purposes (clause 4), conditions of testing (clauses 5 and 6) and the measurement methods (clause 8).

The provider shall offer equipment complete with any auxiliary equipment needed for testing. The provider shall also submit a suitable test tank, as described in annex E.

The provider shall declare the frequency range(s), the range of operation conditions and power requirements, as applicable, in order to establish the appropriate test conditions.

4.2 Choice of model for testing

If an equipment has several optional features, considered not to affect the RF parameters then the tests need only to be performed on the equipment configured with that combination of features considered to create the highest unintentional emissions outside the tank structure.

In addition, when a device has the capability of using different dedicated antennas, tank connections or other features that affect the RF parameters, at least the worst combination of features from an emission point of view as agreed between the provider and the test laboratory shall be tested.

The choice of model(s) for testing shall be recorded in the test report.

4.3 Mechanical and electrical design

The equipment submitted by the provider shall be designed, constructed and manufactured in accordance with good engineering practice and with the aim of minimizing harmful interference to other equipment and services.

4.3.1 Marking (equipment identification)

The equipment shall be marked in a visible place. This marking shall be legible and durable. Where this is not possible due to physical constraints, the marking shall be included in the user's manual.

4.3.1.1 Equipment identification

The marking shall include as a minimum:

- the name of the manufacturer or his trademark;
- the type designation.

4.4 Auxiliary test equipment and product information

All necessary set-up information shall accompany the TLPR equipment when it is submitted for testing.

The following product information shall be provided by the manufacturer:

- the type of UWB technology implemented in the TLPR equipment (e.g. FMCW or pulsed);
- the operating frequency range(s) of the equipment;
- the intended combination of the TLPR transceiver and its antenna and their corresponding e.i.r.p. levels;
- the nominal power supply voltages of the TLPR radio equipment;
- for FMCW, FH, FSK, stepped frequency hopping or similar carrier based modulation schemes, it is important to describe the modulation parameters in order to ensure that the right settings of the measuring receiver are used. Important parameters are the modulation period, deviation or dwell times within a modulation period, rate of modulation (Hz/s);
- the implementation of features such as gating;
- for pulsed equipment, the Pulse Repetition Frequency PRF is to be stated.

All necessary test signal sources, set-up information, and the test tank shall accompany the equipment when it is submitted for testing.

4.5 General requirements for RF cables

All RF cables including their connectors at both ends used within the measurement arrangements and set-ups shall be of coaxial or waveguide type featuring within the frequency range they are used:

- a VSWR of less than 1,2 at either end;
- a shielding loss in excess of 60 dB.

When using coaxial cables for frequencies above 40 GHz attenuation features increase significantly and decrease of return loss due to mismatching caused by joints at RF connectors and impedance errors shall be considered.

All RF cables and waveguide interconnects shall be routed suitably in order to reduce impacts on antenna radiation pattern, antenna gain, antenna impedance. Table 2 provides some information about connector systems that can be used in connection with the cables.

Table 2: Connector systems

Connector System	Frequency	Recommended coupling torque
N	18 GHz	0,68 Nm to 1,13 Nm
SMA	18 GHz (some up to 26 GHz)	~ 0,56 Nm
3,50 mm	26,5 GHz	0,8 Nm to 1,1 Nm
2,92 mm	40 GHz (some up to 46 GHz)	0,8 Nm to 1,1 Nm
2,40 mm	50 GHz (some up to 60 GHz)	0,8 Nm to 1,1 Nm
1,85 mm	65 GHz (some up to 75 GHz)	0,8 Nm to 1,1 Nm

4.6 RF waveguides

Wired signal transmission in the millimeter range is preferably realized by means of waveguides because they offer low attenuation and high reproducibility. Unlike coaxial cables, the frequency range in which waveguides can be used is limited also towards lower frequencies (highpass filter characteristics). Wave propagation in the waveguide is not possible below a certain cutoff frequency where attenuation of the waveguide is very high. Beyond a certain upper frequency limit, several wave propagation modes are possible so that the behaviour of the waveguide is no longer unambiguous. In the unambiguous range of a rectangular waveguide, only H10 waves are capable of propagation.

The dimensions of rectangular and circular waveguides are defined by international standards such as 153-IEC for various frequency ranges. These frequency ranges are also referred to as waveguide bands. They are designated using different capital letters depending on the standard. Table 3 provides an overview of the different waveguide bands together with the designations of the associated waveguides and flanges.

For rectangular waveguides, which are mostly used in measurements, harmonic mixers with matching flanges are available for extending the frequency coverage of measuring receivers. Table 3 provides some information on waveguides.

Table 3: Waveguide bands and associated waveguides

Band	Frequency in GHz	Designations				Internal dimensions of waveguide		Designations of frequently used flanges		
		MIL-W-85	EIA	153-IEC	RCSC (British)	in mm	in inches	MIL-F-3922	UG-XXX/U equivalent (reference)	Remarks
Ka	26,5 to 40,0	3-006	WR-28	R320	WG-22	7,11 x 3,56	0,280 x 0,140	54-006 68-002 67B-005	UG-559/U - UG-381/U	Rectangular Rectangular Round
Q	33,0 to 55,0	3-010	WR-22	R400	WG-23	5,69 x 2,84	0,224 x 0,112	67B-006	UG-383/U	Round
U	40,0 to 60,0	3-014	WR-19	R500	WG-24	4,78 x 2,388	0,188 x 0,094	67B-007	UG-383/U-M	Round
V	50,0 to 75,0	3-017	WR-15	R620	WG-25	3,759 x 1,879	0,148 x 0,074	67B-008	UG-385/U	Round
E	60,0 to 90,0	3-020	WR-12	R740	WG-26	3,099 x 1,549	0,122 x 0,061	67B-009	UG-387/U	Round
W	75,0 to 110,0	3-023	WR-10	R900	WG-27	2,540 x 1,270	0,100 x 0,050	67B-010	UG-383/U-M	Round

As waveguides are rigid, it is unpractical to set up connections between antenna and measuring receiver with waveguides. Either a waveguide transition to coaxial cable is used or - at higher frequencies - the harmonic mixer is used for frequency extension of the measuring receiver and is directly mounted at the antenna.