

# ETSI TS 102 890-1 V1.1.1 (2017-05)



## **Intelligent Transport Systems (ITS); Facilities layer function; Part 1: Services Announcement (SA) specification**

**STANDARD PREVIEW**  
Full standard/catalog/standards/070701/etsi-ts-102-890-1-v1-1-17-05  
<https://standards.iteh.ai/catalog/standards/070701/etsi-ts-102-890-1-v1-1-17-05>  
459b-87af-b464361cbdb

---

Reference

DTS/ITS-0020044

---

Keywords

interoperability, ITS, service, validation

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSI/DeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.

All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ and LTE™ are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	4
Foreword.....	4
Modal verbs terminology.....	4
Introduction .....	4
1 Scope .....	5
2 References .....	5
2.1 Normative references .....	5
2.2 Informative references.....	5
3 Definitions, symbols and abbreviations .....	6
3.1 Definitions .....	6
3.2 Symbols.....	7
3.3 Abbreviations .....	7
4 SA functional description .....	8
4.1 SA functional architecture.....	8
4.2 Interfaces of the SA service.....	9
4.2.1 Interface between Application entity and Management entity.....	9
4.2.2 Interface between Facilities layer and the Management entity .....	10
4.2.3 Interface between Facilities layer and the Security entity.....	11
4.2.4 Interface between Facilities layer and the Networking & Transport layer .....	11
5 SAEM format .....	11
5.1 General .....	11
5.2 Service info component.....	12
5.3 Channel info component .....	12
5.4 IPv6 routing advertisement.....	12
6 SAEM dissemination.....	13
6.1 Identification .....	13
6.2 SA service trigger, update, repetition and termination .....	13
6.3 SA service communication requirements.....	13
6.4 SA Application Identifier (AID).....	14
6.5 SA Service Specific Permissions (SSP) .....	14
<b>Annex A (normative): ASN.1 specification of SAEM .....</b>	<b>15</b>
<b>Annex B (normative): ASN.1 specification of extensions .....</b>	<b>16</b>
B.1 General .....	16
B.2 <i>ChannellInfo</i> extensions.....	16
B.2.1 <i>ProtocolType</i> extension.....	16
History .....	17

---

# Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Intelligent Transport Systems (ITS).

The present document is part 1 of a multi-part deliverable covering Intelligent Transport Systems; Facilities layer function, as identified below:

**Part 1: "Services Announcement (SA) specification";**

Part 2: "Position and time facility specification".

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

Some of the applications of the Basic Set of Applications (see ETSI TR 102 638 [i.1]) require ITS stations (Service Users) to have knowledge of a certain service of interest that is provided by other ITS stations (Service Providers) via defined communication access technologies.

The C-ITS protocol stack supports push and pull mechanisms in order to allow an ITS station to identify the availability of ITS services. The push mechanism is named "ITS service announcement" which is also known as "ITS service advertisement" (see ETSI EN 302 665 [i.2]). Throughout this document this service is referred to as service announcement service (SA service).

The ITS SA service is a functionality agnostic to the medium and the announced service that can be used by specific services to provide the push functionality mentioned above. In this sense, each specification of an ITS service will tailor the ITS service announcement to its needs. This means that ITS service definitions (e.g. in other standards or technical specifications) should make use of the provisions of the present document to define its service-specific use of ITS service announcement, i.e. to profile the ITS service announcement appropriately (for example the use of service announcement in a Platooning service). The present document defines therefore a general framework which needs to be followed whenever a specific service is specified. Compliance should be tested according to this service specification that defines the application-specific requirements for the service announcement.

---

# 1 Scope

The present document provides the specification of the Services Announcement (SA) service, including its protocol functions, based on ISO/TS 16460 [1].

The definition of the interface between Service Provider and Service Announcer ITS stations (ITS-S) as well as of the communication steps following the service announcement protocol procedure and related protocol details between Service Announcer and Service User ITS-S are application-specific and are not covered by the present document.

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ISO/TS 16460:2016: "Intelligent transport systems -- Communications access for land mobiles (CALM) -- Communications protocol messages for global usage".
- [2] ETSI TS 102 894-2: "Intelligent Transport Systems (ITS); Users and applications requirements; Part 2: Applications and facilities layer common data dictionary".
- [3] ETSI EN 302 636-4-1: "Intelligent Transport Systems (ITS); Vehicular Communications; GeoNetworking; Part 4: Geographical addressing and forwarding for point-to-point and point-to-multipoint communications; Sub-part 1: Media-Independent Functionality".
- [4] ETSI TS 103 097 (V1.2.1): "Intelligent Transport Systems (ITS); Security; Security header and certificate formats".
- [5] ETSI EN 302 931 (V1.1.1): "Intelligent Transport Systems (ITS); Vehicular Communications; Geographical Area Definition".
- [6] Recommendation ITU-T X.691/ISO/IEC 8825-2 (2015): "Information technology - ASN.1 encoding rules: Specification of Packed Encoding Rules (PER)".
- [7] ETSI TS 102 965: "Intelligent Transport Systems (ITS); Application Object Identifier (ITS-AID); Registration".
- [8] ETSI TS 103 248: "Intelligent Transport Systems (ITS); GeoNetworking; Port Numbers for the Basic Transport Protocol (BTP)".
- [9] IEEE 1609.3™ - 2016: "IEEE Standard for Wireless Access in Vehicular Environments (WAVE) - Networking Services".

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 102 638 (V1.1.1): "Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Definitions".
- [i.2] ETSI EN 302 665 (V1.1.1): "Intelligent Transport Systems (ITS); Communications Architecture".
- [i.3] ISO/TS 17423:2014: "Intelligent transport systems -- Cooperative systems -- ITS application requirements and objectives for selection of communication profiles".
- [i.4] ETSI TS 102 723-11: "Intelligent Transport Systems (ITS); OSI cross-layer topics; Part 11: Interface between networking and transport layer and facilities layer".
- [i.5] ETSI TS 102 723-5 (V1.1.1): "Intelligent Transport Systems (ITS); OSI cross-layer topics; Part 5: Interface between management entity and facilities layer".
- [i.6] ETSI EN 302 636-5-1: "Intelligent Transport Systems (ITS); Vehicular Communications; GeoNetworking; Part 5: Transport Protocols; Sub-part 1: Basic Transport Protocol".
- [i.7] ETSI TS 103 301: "Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Facilities layer protocols and communication requirements for infrastructure services".

---

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**ITS application:** association of two or more complementary ITS-S applications

**ITS-S application:** fragment of an ITS application available at an ITS-S that uses ITS-S services to connect to one or more other fragments of the same ITS application

**ITS-S gateway:** gateway functionality based on the ITS-S reference architecture

**ITS-S router:** routing functionality based on the ITS-S reference architecture

**ITS service:** service provided by an ITS application to the user of ITS

**ITS-S service:** communication functionality offered by an ITS-S to an ITS-S application

**Services announcement:** provision, via an ITS communication functionality, of information about an ITS service

NOTE: Such information can include the ITS service identity, availability and communication details.

**Service announcer ITS-S:** ITS-S that announces services on behalf of the service provider ITS-S by transmitting SAEM

**Service provider ITS-S:** ITS-S that provides remote or local ITS services

**Service user ITS-S:** consumer of ITS services monitoring SAEM for an announced ITS service opportunity of interest

NOTE: These definitions are in line with ETSI EN 302 665 [i.2].

## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

<i>changeCount</i>	Component of <i>samBody</i>
<i>channelIndex</i>	Component of <i>ServiceInfo</i> pointer to <i>ChannelInfo</i>
<i>ChannelInfo</i>	Datatype of <i>channelInfos</i> list entry
<i>channelInfos</i>	Component of <i>samBody</i>
<i>chOptions</i>	Component of <i>ServiceInfo</i>
<i>contentCount</i>	Component of <i>changeCount</i>
<i>defaultGateway</i>	Component of <i>routingAdvertisement</i>
<i>ExtendedChannelInfos</i>	Component of <i>extensions</i> of <i>samBody</i>
<i>extensions</i>	Component of <i>samBody</i>
<i>GatewayMACAddress</i>	Component of <i>routingAdvertisement</i>
<i>IPv6Address</i>	Component of <i>chOptions</i>
<i>ItsPduHeader</i>	Header component of the SAEM
<i>messageID</i>	Component of the <i>ItsPduHeader</i>
<i>protocolType</i>	Component of <i>chOptions</i>
<i>protocolVersion</i>	Component of the <i>ItsPduHeader</i>
<i>ProviderMACAddress</i>	Component of <i>chOptions</i>
<i>routingAdvertisement</i>	Component of <i>samBody</i>
<i>saID</i>	Component of <i>changeCount</i>
<i>sam</i>	Component of the SAEM
<i>Sam</i>	Datatype specified in ISO/TS 16460 [1]
<i>samBody</i>	Component of <i>sam</i>
<i>serviceID</i>	Component of <i>ServiceInfo</i>
<i>ServiceInfo</i>	Datatype of <i>serviceInfos</i> list entry
<i>serviceInfos</i>	Component of <i>samBody</i>
<i>serviceProviderPort</i>	Unused component of <i>chOptions</i>
<i>SrvAdvChangeCount</i>	Datatype of <i>changeCount</i>
<i>stationID</i>	Component of the <i>ItsPduHeader</i>
<i>systemService</i>	Unused component of <i>chOptions</i>

## 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AID	Application Identifier
API	Application Programming Interface
ASN	Abstract Syntax Notation
BTP	Basic Transport Protocol
C-ITS	Cooperative ITS
GN	GeoNetworking
ID	Identifier
IETF	Internet Engineering Task Force
IP	Internet Protocol
IPv6	Internet Protocol Version 6
ISO	International Organization for Standardization
ITS	Intelligent Transport System
ITS-S	ITS Station
ITU-T	International Telecommunication Union - Telecommunication Standardization Sector
MAC	Medium Access Control
MA-SAP	Management to Application Service Access Point
MDA	Minimum Dissemination Area
MF	Management to Facilities
MF-SAP	Management to Facilities Service Access Point
NF	Networking & Transport to Facilities
NF-SAP	Networking & Transport to Facilities Service Access Point
PER	Packed Encoding Rules
RX	Reception
SA	Services Announcement

SAEM	Services Announcement Extended Message
SAM	Service Announcement
SAP	Service Access Point
SfCH	Safety channel (logical)
SSP	Service Specific Permissions
TX	Transmission

---

## 4 SA functional description

### 4.1 SA functional architecture

The Services Announcement (SA) service is a protocol service that is distributed over the facilities layer and the management entity of the ITS-S reference architecture as defined in ETSI EN 302 665 [i.2]. The SA service provides information on available services, applying the Services Announcement protocol with the following functions:

- The SA message processing function of the facility layer is responsible for the periodic transmission and/or reception of SAEM. It shall offer the following functionalities:
  - For the SAEM transmission (TX) service:
    - message encoding;
    - transmission management.
  - For the SAEM reception (RX) service:
    - message decoding;
    - reception management.
- The SA management function of the management entity is responsible for the registration / update / deregistration of applications.

The SA service is implemented in a Service Provider, Service Announcer, or Service User ITS-S.

Figure 1 presents the SA service in the context of the ITS-S reference architecture and its logical interfaces with other entities and layers.

The SA service supports different configurations with respect of the Service Provider role and the Service Announcer role, such as:

- Service Provider and Service Announcer functionality are implemented in the same ITS-S;
- Service Provider and Service Announcer functionality are implemented in separate ITS-S;
- and other configurations.






Figure 1: SA in the context of the ITS-S reference architecture

## 4.2 Interfaces of the SA service

### 4.2.1 Interface between Application entity and Management entity

A Service Provider ITS-S application may register / update / deregister its offered ITS service at the management entity using the parameters specified in table 1.

A Service User ITS-S application may register / update / deregister potential services of interest at the management entity using the parameters specified in table 2.

A Service User ITS-S application may be notified of the reception of an SAEM corresponding to one of the registered services of interest by the management entity using the parameters specified in table 3.

This interface may be implemented as an API or as MA-SAP.

Table 1: Parameters for the service primitive of a SA provider request via the MA-SAP

Category	Data	Definition
Data passed from service provider application to SA management	Request type	SA Provider registration / update / deregistration
	ITS-AID	ITS-AID to be indicated in an SAEM, identifying the service provider application (see ETSI TS 102 965 [7])
	Dissemination parameter	See table 7
	Traffic class	If GeoNetworking / BTP (ETSI EN 302 636-5-1 [i.6]) is used for transmission of SAEM, then the GN traffic class as defined in ETSI EN 302 636-4-1 [3] shall be used for message prioritization
	Payload	Application-specific service announcement data to be contained in SAEM, see clause 5.2
SA data returned to the requesting application	saID	See clause 6.1
	contentCount	See clause 6.1
	Response code	Code indicating the status of the SA Provider announcement registration