



SLOVENSKI STANDARD

SIST EN 13087-2:2012

01-julij-2012

Nadomešča:

SIST EN 13087-2:2000

SIST EN 13087-2:2000/A1:2002

Varovalne čelade - Preskusne metode - 2. del: Absorpcija udarca

Protective helmets - Test methods - Part 2: Shock absorption

Schutzhelme - Prüfverfahren - Teil 2: Stoßdämpfung

Casques de protection - Méthodes d'essai - Partie 2: Absorption des chocs

Ta slovenski standard je istoveten z: EN 13087-2:2012

SIST EN 13087-2:2012
<https://standards.iteh.ai/catalog/standards/sist/en-13087-2-2012/4d15-8947-d8b10006cac8/sist-en-13087-2-2012>

ICS:

13.340.20 Varovalna oprema za glavo Head protective equipment

SIST EN 13087-2:2012

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 13087-2:2012

<https://standards.iteh.ai/catalog/standards/sist/2220c397-e438-4d15-8947-d8b10006cac8/sist-en-13087-2-2012>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 13087-2

February 2012

ICS 13.340.20

Supersedes EN 13087-2:2000

English Version

Protective helmets - Test methods - Part 2: Shock absorption

Casques de protection - Méthodes d'essai - Partie 2:
Absorption des chocs

Schutzhelme - Prüfverfahren - Teil 2: Stoßdämpfung

This European Standard was approved by CEN on 17 December 2011.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

SIST EN 13087-2:2012

<https://standards.iteh.ai/catalog/standards/sist/2220c397-e438-4d15-8947-d8b10006cac8/sist-en-13087-2-2012>



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Prerequisites	5
5 Test methods.....	6
5.1 General.....	6
5.2 Falling mass method	6
5.2.1 Principle.....	6
5.2.2 Apparatus	6
5.2.3 Procedure	7
5.2.4 Test report	7
5.3 Falling headform method.....	7
5.3.1 Principle.....	7
5.3.2 Apparatus	7
5.3.3 Procedure	9
5.3.4 Test report	9
Annex A (normative) Test results – Uncertainty of measurement.....	10
Annex B (informative) Significant technical changes between this European Standard and EN 13087-2:2000.....	11
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 89/686/EEC Personal Protective Equipment.....	12

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 13087-2:2012

[https://standards.iteh.ai/catalog/standards/sist/2220c597-c458-4d19-8947-](https://standards.iteh.ai/catalog/standards/sist/2220c597-c458-4d19-8947-d8b10006cac6/sist-en-13087-2-2012)

[d8b10006cac6/sist-en-13087-2-2012](https://standards.iteh.ai/catalog/standards/sist/2220c597-c458-4d19-8947-d8b10006cac6/sist-en-13087-2-2012)

Foreword

This document (EN 13087-2:2012) has been prepared by Technical Committee CEN/TC 158 "Head protection", the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by August 2012, and conflicting national standards shall be withdrawn at the latest by August 2012.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 13087-2:2000.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EU Directive(s), see informative Annex ZA, which is an integral part of this document.

Annex B provides details of significant technical changes between this European Standard and the previous edition.

This European Standard consists of the following ten parts

Part 1 : Conditions and conditioning;

[SIST EN 13087-2:2012](https://standards.iteh.ai/catalog/standards/sist/2220c397-e438-4d15-8947-d8b10006cac8/sist-en-13087-2-2012)

Part 2 : Shock absorption;

<https://standards.iteh.ai/catalog/standards/sist/2220c397-e438-4d15-8947-d8b10006cac8/sist-en-13087-2-2012>

Part 3 : Resistance to penetration;

Part 4 : Retention system effectiveness;

Part 5 : Retention system strength;

Part 6 : Field of vision;

Part 7 : Flame resistance;

Part 8 : Electrical properties;

Part 9 : Mechanical rigidity¹;

Part 10 : Resistance to radiant heat.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

¹ To be published.

Introduction

This European Standard is intended as a supplement to the specific product standards for protective helmets (helmet standards). This method or other test methods may be applicable to complete helmets or parts thereof, and may be referenced in the appropriate helmet standards.

Performance requirements are given in the appropriate helmet standard, as are such prerequisites as the number of samples, preconditioning, preparation of samples for the tests, sequence and duration of testing and assessment of test results. If deviations from the test method given in this standard are necessary, these deviations will be specified in the appropriate helmet standard.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 13087-2:2012](https://standards.iteh.ai/catalog/standards/sist/2220c397-e438-4d15-8947-d8b10006cac8/sist-en-13087-2-2012)

<https://standards.iteh.ai/catalog/standards/sist/2220c397-e438-4d15-8947-d8b10006cac8/sist-en-13087-2-2012>

1 Scope

The European Standard specifies methods of test for protective helmets. The purpose of these tests is to enable assessment of the performance of the helmet as specified in the appropriate helmet standard.

This European Standard specifies the method for determination of shock absorption.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 960:2006, *Headforms for use in the testing of protective helmets*

EN 13087-1, *Protective helmets — Test methods — Part 1: Conditions and conditioning*

ISO 6487, *Road vehicles — Measurement techniques in impact tests — Instrumentation*

3 Terms and definitions

For the purposes of this document, the terms and definitions used in this standard can be found in the appropriate helmet standard.

(standards.iteh.ai)

4 Prerequisites

[SIST EN 13087-2:2012](https://standards.iteh.ai/catalog/standards/sist/2220c397-e438-4d15-8947-1b13087-2012)

<https://standards.iteh.ai/catalog/standards/sist/2220c397-e438-4d15-8947-1b13087-2012>

In order to implement this part of EN 13087, at least the following parameters need to be specified in the appropriate helmet standard:

- a) performance requirements;
- b) number of samples;
- c) preparation of samples;
- d) sequence of conditioning;
- e) sequence of tests;
- f) method of test - 5.2 or 5.3;
- g) sizes of headforms;
- h) type of striker or anvil;
- i) fitting instructions;
- j) number and location of impact points on helmets;
- k) for each impact, the impact energy, including tolerance, of the falling mass for the falling mass method, or the impact speed, including tolerance, of the helmet/headform assembly for the falling headform method.

EN 13087-2:2012 (E)**5 Test methods****5.1 General**

Testing shall be performed in the ambient conditions specified in EN 13087-1. When the test method specifies that the helmet shall be fitted to a headform, this shall be done in accordance with the appropriate helmet standard. Two test methods are specified. The appropriate helmet standard will state which of these methods is applicable. Annex A refers to the uncertainty of measurement.

5.2 Falling mass method**5.2.1 Principle**

A specified striker is allowed to fall with specified energy on to a helmet which is fitted to a rigidly mounted headform. The transmitted force is measured by means of a force transducer located beneath the headform.

5.2.2 Apparatus**5.2.2.1 Base**

The base shall be solid, made of steel or a combination of steel and concrete and have a mass of not less than 500 kg. At least the uppermost 25 mm shall consist of steel, which shall be firmly attached to the concrete if present. No part of the base and headform mounting assembly shall have a resonant frequency liable to affect the measurements.

NOTE See 5.2.2.6.2 regarding frequency response.

5.2.2.2 Test headforms

The headforms shall comply with EN 960:2006, 2.2, 3.1.2 and 3.2. The sizes to be used are specified in the helmet standard, but shall be selected from size designations 495, 535, 575, 605 and 625 (equivalent to codes A, E, J, M and O, respectively, EN 960:1994). When in the upright position, the headform shall be positioned so that its central vertical axis coincides with those of the force transducer and striker.

5.2.2.3 Striker

Two types of striker are specified - a flat one and a hemispherical one. The type of striker to be used is specified in the appropriate helmet standard.

The striker shall be made of steel and have a mass of $(5 \pm 0,05)$ kg.

The flat striker shall have a flat striking face of diameter (100 ± 2) mm, with the edge of its circumference radiused to nominally 2 mm.

The hemispherical striker shall have a hemispherical striking face of radius (50 ± 1) mm.

5.2.2.4 Guidance system

Means shall be provided for the striker to be dropped in free or guided fall.

The guidance system shall be such as to ensure that the striker:

- shall be positioned above the headform so that its central axis coincides with the central vertical axis of the force transducer; and
- falls on to the required impact point with an impact speed of not less than 95% of that which would theoretically obtain for a free fall.

5.2.2.5 Means to measure impact speed

Unless free fall is employed, means shall be provided to measure the striker speed at a distance of no more than 60 mm prior to impact, to within an accuracy of $\pm 1\%$.

The impact speed shall be measured during the commissioning of the apparatus. It need not be done for each impact, but has to be sufficiently regular to comply with 5.2.2.4.

5.2.2.6 Instrumentation to record and analyse the data

5.2.2.6.1 Force transducer

The non-inertial force transducer shall be firmly attached to the base and arranged so that its sensitive axis coincides with the vertical axis passing through the centre of gravity of the headform and the centre of the striker. The transducer shall be capable of withstanding a compressive force of 40 kN without damage.

5.2.2.6.2 Signal conditioning instrumentation

The instrumentation shall provide for the complete measuring channel to have a frequency response in accordance with channel frequency class (CFC) 600 of ISO 6487. If digital sampling is employed, a sample rate of at least 6 kHz shall be used. The required low pass filter may be included within the computer software.

Means shall be provided to record the maximum force transmitted during impact, to the nearest 10 N.

5.2.3 Procedure

iTeh STANDARD PREVIEW

(standards.iteh.ai)

Within 1 min of its removal from conditioning (this time applies to temperature conditioning only), fit the helmet to the appropriate headform in the manner in which it is intended to be worn on the head and allow the striker to fall on to the specified impact point. The impact energy shall be as specified in the appropriate helmet standard.

If the design of the helmet permits direct contact between the striker and the headform, the test shall not be performed and the result shall be declared a failure.

5.2.4 Test report

Record and report the maximum force transmitted during the impact to the nearest 10 N.

5.3 Falling headform method

5.3.1 Principle

The helmet to be tested is fitted to a headform and the assembly is allowed to fall with specified speed on to a rigidly mounted anvil. The deceleration of the headform is measured by means of a tri-axial accelerometer located within the headform.

5.3.2 Apparatus

5.3.2.1 Base

The base shall be solid, made of steel or a combination of steel and concrete and have a mass of not less than 500 kg. At least the uppermost 25 mm shall consist of steel, which shall be firmly attached to the concrete if present. No part of the base and anvil assembly shall have a resonant frequency liable to affect the measurements.

NOTE See 5.3.2.6.2 regarding frequency response.