
**Information technology — 8 mm wide
magnetic tape cartridge for information
interchange — Helical scan recording AIT-1
with MIC format**

*Technologies de l'information — Cartouche à bande magnétique de 8 mm
de large pour l'échange d'information — Enregistrement par balayage en
spirale AIT-1 avec format MIC*

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

ISO/IEC 18809:2000

<https://standards.iteh.ai/catalog/standards/sist/1ceed255-6785-4f95-be90-71d161f044ea/iso-iec-18809-2000>

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 18809:2000

<https://standards.iteh.ai/catalog/standards/sist/1ceed255-6785-4f95-be90-71d161f044ea/iso-iec-18809-2000>

© ISO/IEC 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Contents

Section 1 - General	1
1 Scope.....	1
2 Conformance.....	1
2.1 Magnetic tape cartridge.....	1
2.2 Generating drive.....	1
2.3 Receiving drive.....	1
3 Normative references.....	2
4 Terms and definitions.....	2
4.1 Absolute Frame Number (AFN).....	2
4.2 a.c. erase.....	2
4.3 Access.....	2
4.4 algorithm.....	2
4.5 Area ID.....	2
4.6 Automatic Track Finding (ATF).....	2
4.7 Average Signal Amplitude.....	2
4.8 azimuth.....	2
4.9 back surface.....	2
4.10 byte.....	2
4.11 cartridge.....	2
4.12 Channel bit.....	2
4.13 Codeword.....	2
4.14 Early Warning Point (EWP).....	2
4.15 End of Data (EOD).....	2
4.16 Entity.....	2
4.17 Error Correcting Code (ECC).....	2
4.18 flux transition position.....	2
4.19 flux transition spacing.....	2
4.20 Frame.....	3
4.21 Housekeeping Frame.....	3
4.22 Logical Beginning of Tape (LBOT).....	3
4.23 magnetic tape.....	3
4.24 Master Standard Amplitude Calibration Tape.....	3
4.25 Master Standard Reference Tape.....	3
4.26 Memory In Cartridge (MIC).....	3
4.27 Partition Boundary.....	3
4.28 Physical Beginning of Tape (PBOT).....	3
4.29 Physical End of Tape (PEOT).....	3
4.30 physical recording density.....	3
4.31 pre-recording condition.....	3
4.32 processing.....	3
4.33 processed data.....	3
4.34 Processed Record.....	3
4.35 record.....	3
4.36 Reference Field.....	3
4.37 Secondary Standard Amplitude Calibration Tape.....	3
4.38 Secondary Standard Reference Tape.....	3
4.39 Separator Mark.....	3
4.40 Standard Reference Amplitude (SRA).....	3
4.41 Tape Reference Edge.....	4
4.42 Typical Field.....	4
4.43 Standard Reference Current.....	4
4.44 Test Recording Current.....	4
4.45 track.....	4

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 18809:2000
<https://standards.iteh.ai/catalog/standards/sist/1ceed255-6785-4f95-be90-71d161f044ea/iso-iec-18809-2000>

4.46	unprocessed data.....	4
4.47	Unprocessed Record.....	4
5	Conventions and Notations.....	4
5.1	Representation of numbers.....	4
5.2	Names.....	4
6	Acronyms.....	4
7	Environment and safety.....	4
7.1	Test environment.....	4
7.2	Operating environment.....	5
7.3	Storage environment.....	5
7.4	Transportation.....	5
7.5	Safety.....	5
7.6	Flammability.....	5
Section 2 - Requirements for the case.....		6
8	Dimensional and mechanical characteristics of the case.....	6
8.1	General.....	6
8.2	Overall dimension (figures 5 and 6).....	6
8.3	Holding areas.....	7
8.4	Cartridge insertion.....	7
8.5	Window (figure 1).....	8
8.6	Loading grips (figures 5 and 7).....	8
8.7	Label areas (figures 6 and 8).....	8
8.8	Datum areas and Datum holes.....	8
8.9	Support areas (figure 9).....	9
8.10	Recognition holes (figures 10, 11 and 12).....	10
8.11	Write-inhibit hole (figure 11).....	10
8.12	Pre-positioning surfaces (figures 4 and 10).....	11
8.13	Cartridge lid (figures 6, 13 and 15).....	11
8.14	Cartridge reel lock (figures 10 and 16).....	12
8.15	Reel access holes (figure 10).....	13
8.16	Interface between the reels and the drive spindles.....	13
8.17	Light path (figures 10, 12, 20 and 21).....	14
8.18	Position of the tape in the case (figure 21).....	15
8.19	Tape path zone.....	15
8.20	Tape access cavity (figure 10).....	16
8.21	Tape access cavity clearance (figure 24).....	16
8.22	Requirements for the MIC (figures 25 and 26).....	16
8.23	Recognition recesses (figures 8 and 10).....	17
Section 3 - Requirements for the unrecorded tape.....		38
9	Mechanical, physical and dimensional characteristics of the tape.....	38
9.1	Materials.....	38
9.2	Tape length.....	38
9.2.1	Length of the magnetic tape.....	38
9.2.2	Length of the leader and trailer tapes.....	38
9.2.3	Length of the splicing tapes.....	38
9.3	Tape width.....	38
9.3.1	Width of the magnetic, leader and trailer tapes.....	38
9.3.2	Width and position of the splicing tape.....	38
9.4	Discontinuities.....	39
9.5	Tape thickness.....	39
9.5.1	Thickness of the magnetic tape.....	39
9.5.2	Thickness of the leader and trailer tapes.....	39
9.5.3	Thickness of the splicing tape.....	39
9.6	Longitudinal curvature.....	39

9.7	Cupping.....	39
9.8	Coating adhesion.....	39
9.9	Layer-to-layer adhesion.....	40
9.10	Tensile strength.....	40
9.10.1	Breaking strength.....	40
9.10.2	Yield strength.....	40
9.11	Residual elongation.....	40
9.12	Electrical resistance of the recording surface.....	40
9.13	Tape winding.....	41
9.14	Light transmittance of the tape.....	41
10	Magnetic recording characteristics.....	41
10.1	Typical Field	42
10.2	Signal Amplitude	42
10.3	Resolution	42
10.4	Overwrite	42
10.5	Ease of erasure	42
10.6	Tape quality.....	42
10.6.1	Missing pulses.....	42
10.6.2	Missing pulse zone.....	43
10.7	Signal-to-Noise Ratio (SNR) characteristic	43
Section 4 - Requirements for an interchanged tape.....		43
11	Format	43
11.1	General.....	43
11.2	Basic Groups.....	43
11.2.1	Entity.....	44
11.2.2	Group Information Table	45
11.2.3	Block Access Table (BAT)	47
11.3	Sub-Groups	50
11.3.1	G1 Sub-Group	50
11.3.2	G2 Sub-Group - Randomizing	51
11.3.3	G3 Sub-Group	52
11.4	Data Block.....	53
11.4.1	ID information.....	54
11.4.2	Recording of the ID Information in the Data Block Headers.....	56
12	Method of recording.....	62
12.1	Physical recording density	62
12.2	Long-term average bit cell length	62
12.3	Short-term average bit cell length	62
12.4	Rate of change.....	62
12.5	Bit shift.....	63
12.6	Read signal amplitude	63
12.7	Maximum recorded levels.....	63
13	Track geometry	63
13.1	Track configuration.....	63
13.2	Average track pitch	63
13.3	Variations of the track pitch.....	64
13.4	Track width	64
13.5	Track angle.....	64
13.6	Track edge straightness	64
13.7	Track length	64
13.8	Azimuth angles.....	64
14	Recorded patterns.....	64
14.1	Recorded Data Block	64

14.2	Margin blocks	64
15	Format of a track.....	64
15.1	Track structure.....	64
15.2	Positioning accuracy.....	65
15.3	Tracking scheme.....	66
16	Layout of the tape	66
16.1	Device Area	67
16.2	Reference Area	67
16.3	Position Tolerance Band No. 1.....	68
16.4	System Area.....	68
16.4.1	System Preamble	68
16.4.2	System Log.....	68
16.4.3	System Postamble.....	72
16.4.4	Position Tolerance Band No. 2.....	72
16.4.5	Vendor Group Preamble.....	72
16.5	Data Area.....	72
16.5.1	Vendor Group.....	72
16.5.2	Recorded Data Group	72
16.5.3	ECC3	72
16.5.4	Multiple Recorded Instances	73
16.5.5	Repeated Frames.....	73
16.5.6	Appending and overwriting.....	74
16.6	EOD Area	75
16.7	Optional Device Area	75
16.8	Logical End Of Tape (LEOT).....	76
16.9	Logical Beginning of Tape (LBOT).....	76
16.10	Early Warning Point - EWP.....	76
16.11	Empty Partition.....	76
16.12	Initialization.....	76
17	Housekeeping Frames.....	77
17.1	Amble Frames.....	77
17.2	System Amble Frames.....	77
18	Content of the MIC.....	77

Annexes

A	- Measurement of light transmittance.....	79
B	- Measurement of Signal-to-Noise Ratio.....	82
C	- Method for determining the nominal and the maximum allowable recorded levels	83
D	- Representation of 8-bit bytes by 10-bit patterns	84
E	- Measurement of bit shift	96
F	- Method of measuring the straightness of track edges.....	98
G	- ECC calculation	99
H	- Recommendations for transportation.....	102
J	- Read-After-Write	103
K	- Example of the content of a Basic Group No. 0	104
L	- Examples of MIC chip	105

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

This International Standard was prepared by ECMA (as ECMA-291) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval of national bodies of ISO and IEC.

Annexes A to G form a normative part of this International Standard, annexes H to L are for information only.

[ISO/IEC 18809:2000](https://standards.iteh.ai/catalog/standards/sist/1ceed255-6785-4f95-be90-71d161f044ea/iso-iec-18809-2000)

<https://standards.iteh.ai/catalog/standards/sist/1ceed255-6785-4f95-be90-71d161f044ea/iso-iec-18809-2000>

Introduction

This International Standard constitutes a further development of the magnetic tape cartridge specified in International Standard ISO/IEC 14833. A higher capacity is achieved by using a thinner, thus longer tape.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 18809:2000](https://standards.iteh.ai/catalog/standards/sist/1ceed255-6785-4f95-be90-71d161f044ea/iso-iec-18809-2000)
<https://standards.iteh.ai/catalog/standards/sist/1ceed255-6785-4f95-be90-71d161f044ea/iso-iec-18809-2000>

Information technology — 8 mm wide magnetic tape cartridge for information interchange — Helical scan recording AIT-1 with MIC format

Section 1 - General

1 Scope

This International Standard specifies the physical and magnetic characteristics of an 8 mm wide magnetic tape cartridge containing a memory chip to enable physical interchange of such cartridges between drives. It also specifies the quality of the recorded signals, the recording method and the recorded format - called Advanced Intelligent Tape No. 1 with Memory In Cartridge (AIT-1 with MIC) - thereby allowing data interchange between drives by means of such magnetic tape cartridges. The System Log is recorded in the MIC.

This International Standard specifies two types of cartridge depending on the thickness of the magnetic tape contained in the case.

Information interchange between systems also requires, at a minimum, agreement between the interchange parties upon the interchange code(s) and the specifications of the structure and labelling of the information on the interchanged cartridge.

2 Conformance

2.1 Magnetic tape cartridge

A tape cartridge shall be in conformance with this International Standard if it meets all the mandatory requirements specified herein. The tape requirements shall be satisfied throughout the extent of the tape.

2.2 Generating drive

A drive generating a magnetic tape cartridge for interchange shall be in conformance with this International Standard if all recordings on the tape meet the mandatory requirements of this International Standard, and if either or both methods of appending and overwriting are implemented. In addition, such a drive shall be able to record the System Log in the MIC.

A claim of conformance shall state which of the following optional features are implemented and which are not

- the performing of a Read-After-Write check and the recording of any necessary repeated frames;
- the generation of ECC3 Frames.

In addition a claim of conformance shall state

- whether or not one, or more, registered algorithm(s) are implemented within the system and are able to compress data received from the host prior to collecting the data into Basic Groups, and
- the registered identification number(s) of the implemented compression algorithm(s).

2.3 Receiving drive

A drive receiving a magnetic tape cartridge for interchange shall be in conformance with this International Standard if it is able to handle any recording made on the tape according to this International Standard. In particular it shall

- be able to read the System Log recorded in the MIC,
- be able to recognise repeated frames, and to make available to the host, data and Separator Marks from only one of these frames;
- be able to recognise multiple representations of the same Basic Group, and to make available to the host, data and Separator Marks from only one of these representations;
- be able to recognise an ECC3 frame, and ignore it if the system is not capable of using ECC3 check bytes in a process of error correction;
- be able to recognise processed data within an Entity, identify the algorithm used, and make its registered identification number available to the host;
- be able to make processed data available to the host.
- In addition a claim of conformance shall state

- whether or not the system is capable of using ECC3 check bytes in a process of error correction;
- whether or not one or more de-compression algorithm(s) are implemented within the system, and are able to be applied to compressed data prior to making such data available to the host;
- the registered identification number(s) of the compression algorithm(s) for which a complementary de-compression algorithm is implemented.

3 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 527-3:1995	<i>Plastics – Determination of tensile properties – Part 3: Test conditions for films and sheets.</i>
ISO 1302:1992	<i>Technical drawings – Method of indicating surface texture on drawings.</i>
ISO/IEC 11576:1994	<i>Information technology – Procedure for the registration of algorithms for the lossless compression of data.</i>
IEC 60950:1999	<i>Safety of information technology equipment.</i>

4 Terms and definitions

For the purposes of this International Standard, the following terms and definitions apply.

- 4.1 Absolute Frame Number (AFN):** A sequence number encoded in a Frame.
- 4.2 a.c. erase:** A process of erasure utilizing magnetic fields of decaying intensity.
- 4.3 Access:** A read or write pass over a partition.
- 4.4 algorithm:** A set of rules for transforming the logical representation of data.
- 4.5 Area ID:** An identifier defining the area of the tape and specifying the types of Frame written.
- 4.6 Automatic Track Finding (ATF):** The method by which tracking is achieved.
- 4.7 Average Signal Amplitude:** The average peak-to-peak value of the output signal from the read head at the fundamental frequency of the specified physical recording density over a minimum of 20,0 mm of track, exclusive of missing pulses.
- 4.8 azimuth:** The angular deviation made by the mean flux transition line with a line normal to the centreline of the recorded track.
- 4.9 back surface:** The surface of the tape opposite to the magnetic coating which is used to record data.
- 4.10 byte:** An ordered set of bits acted upon as a unit.
- 4.11 cartridge:** A case containing magnetic tape stored on twin hubs.
- 4.12 Channel bit:** A bit after 8-10 transformation.
- 4.13 Codeword:** A word generated by a compression algorithm. The number of bits in a Codeword is variable, and is not specified by this International Standard.
- 4.14 Early Warning Point (EWP):** A point along the length of the tape at which warning is given of the approach, in the forward direction of the tape motion, of the Partition Boundary or of the Physical End of Tape.
- 4.15 End of Data (EOD):** The point on the tape at the end of the group which contains the last user data.
- 4.16 Entity:** A unit of recorded data, comprising an Entity Header and a Record sequence.
- 4.17 Error Correcting Code (ECC):** A mathematical computation yielding check bytes used for the detection and correction of errors.
- 4.18 flux transition position:** That point which exhibits maximum free-space flux density normal to the tape surface.
- 4.19 flux transition spacing:** The distance along a track between successive flux transitions.

- 4.20 Frame:** A pair of adjacent tracks with azimuths of opposite polarity, in which the track with the positive azimuth precedes that with the negative azimuth.
- 4.21 Housekeeping Frame:** A Frame which contains no user data and which is identified as such by the setting of the Data Fields therein.
- 4.22 Logical Beginning of Tape (LBOT):** The point along the length of the tape where a recording of data for interchange commences.
- 4.23 magnetic tape:** A tape which will accept and retain the magnetic signals intended for input, output and storage purposes on computers and associated equipment.
- 4.24 Master Standard Amplitude Calibration Tape:** A pre-recorded tape on which the standard signal amplitudes have been recorded in the tracks of positive and negative azimuth recorded at a track pitch of 11,0 μm , on an a.c. erased tape.

NOTE 1 - The tape includes recording at 1 428,6 ftpmm, 1 904,8 ftpmm, 2 857,1 ftpmm and 3 809,5 ftpmm.

NOTE 2 - The Master Standard Amplitude Calibration Tape has been established by Sony Corporation.

- 4.25 Master Standard Reference Tape:** A tape selected as the standard for the Reference Recording Field, Signal Amplitude, Resolution, Overwrite and Signal-to-Noise ratio.

NOTE - The Master Standard Reference Tape has been established by Sony Corporation.

- 4.26 Memory In Cartridge (MIC):** A chip within the case containing information about the cartridge and its recordings.
- 4.27 Partition Boundary:** The point along the length of a magnetic tape at which a Partition ends and the next Partition commences.
- 4.28 Physical Beginning of Tape (PBOT):** The point where the leader tape is joined to the magnetic tape.
- 4.29 Physical End of Tape (PEOT):** The point where the trailer tape is joined to the magnetic tape.
- 4.30 physical recording density:** The number of recorded flux transitions per unit length of track, expressed in flux transitions per millimetre (ftpmm).
- 4.31 pre-recording condition:** The recording levels above which a tape intended for interchange shall not previously have been recorded.
- 4.32 processing:** The use of an algorithm to transform host data into Codewords.
- 4.33 processed data:** A sequence of Codewords which results from the application of processing to data.
- 4.34 Processed Record:** A sequence of Codewords which results from the application of processing to an Unprocessed Record.
- 4.35 record:** Related data treated as a unit of information.
- 4.36 Reference Field:** The Typical Field of the Master Standard Reference Tape.
- 4.37 Secondary Standard Amplitude Calibration Tape:** A tape pre-recorded as specified for the Master Standard Amplitude Calibration Tape the outputs of which are related to those of the Master Standard Amplitude Calibration Tape by calibration factors.

NOTE - Secondary Standard Amplitude Calibration Tapes can be ordered under Part No. SSCT-AIT-1 from Sony Corporation, RME Company, Data Media Marketing Div., 6-7-35 Kitashinagawa, Shinagawa-ku, Tokyo 141, Japan. In principle such Secondary Standard Amplitude Calibration Tapes will be available for a period of 10 years from the publication of the first Edition of this International Standard. However, by agreement between ISO/IEC and Sony Corporation, this period can be shortened or extended to take into account the demand for such Secondary Standard Amplitude Calibration Tapes.

- 4.38 Secondary Standard Reference Tape:** A tape the outputs of which are related to those of the Master Standard Reference Tape by calibration factors.

NOTE - Secondary Standard Reference Tapes can be ordered under Part No. SSRT-AIT-1 from Sony Corporation, RME Company, Data Media Marketing Div., 6-7-35 Kitashinagawa, Shinagawa-ku, Tokyo 141, Japan. In principle such Secondary Standard Reference Tapes will be available for a period of 10 years from the publication of the first Edition of this International Standard. However, by agreement between ISO/IEC and Sony Corporation, this period can be shortened or extended to take into account the demand for such Secondary Standard Reference Tapes.

It is intended that these be used for calibrating tertiary reference tapes for use in routine calibration.

- 4.39 Separator Mark:** A record containing no user data, which is used to separate data.
- 4.40 Standard Reference Amplitude (SRA):** The Average Signal Amplitude from the tracks of positive azimuth of the Master Standard Amplitude Calibration Tape at a specified physical recording density.

- 4.41 Tape Reference Edge:** The bottom edge of the tape when viewing the recording side of the tape, with the PEOT to the observer's right.
- 4.42 Typical Field:** In the plot of Average Signal Amplitude against the recording field at the physical recording density of 2 857,1 ftpmm, the field that causes an Average Signal Amplitude equal to 90% of the maximum Average Signal Amplitude.
- 4.43 Standard Reference Current:** The current that produces the Reference Field.
- 4.44 Test Recording Current:** The current used to record an SRA. It is 1,5 times the Standard Reference Current.
- 4.45 track:** A diagonally positioned area on the tape along which a series of magnetic signals may be recorded.
- 4.46 unprocessed data:** Data which has not been subjected to processing.
- 4.47 Unprocessed Record:** A record of unprocessed data, comprising an integral number of bytes.

5 Conventions and Notations

5.1 Representation of numbers

A measured value is rounded off to the least significant digit of the corresponding specified value. This implies that, for example, a specified value of 1,26 with a positive tolerance of +0,01 and a negative tolerance of -0,02 allows a range of measured values from 1,235 to 1,275.

The setting of a bit is denoted by ZERO or ONE.

Bit patterns and numbers in binary notation are represented by strings of digits 0 and 1. Within such strings, X may be used to indicate that the setting of a bit is not specified within the string.

Bit patterns and numbers in binary notation are shown with the most significant bit to the left and the least significant bit to the right.

The most significant bit of an 8-bit byte is denoted by b8 and the least significant by b1.

5.2 Names

The names of basic elements, e.g. specific fields, are given with a capital initial letter.

6 Acronyms

AEWP	After Early Warning Point
AFN	Absolute Frame Number
ATF	Automatic Tracking Finding
BAT	Block Access Table
ECC	Error Correcting Code
EOD	End of Data
EWPP	Early Warning Point
GIT	Group Information Table
LBOT	Logical Beginning of Tape
LEOT	Logical End of Tape
LSB	Least Significant Byte
LF-ID	Logical Frame Identifier
MIC	Memory in Cartridge
MSB	Most Significant Byte
MSRT	Master Standard Reference Tape
PBOT	Physical Beginning of Tape
PEOT	Physical End of Tape
RAW	Read-After-Write
SNR	Signal-to-Noise Ratio
msb	Most significant bit

7 Environment and safety

7.1 Test environment

Tests and measurements made on the tape cartridge to check the requirements of this International Standard shall be carried out in the following ambient conditions of the air immediately surrounding the drive.

temperature : 23 °C ± 2 °C
 relative humidity : 40 % to 60 %
 conditioning period before testing : 24 h min.

7.2 Operating environment

Cartridges used for data interchange shall be capable of operating under the following conditions, as measured within 10 mm of the tape exit from the drum of the generating or receiving drive:

temperature : 5 °C to 45 °C
 relative humidity : 20 % to 80 %
 wet bulb temperature : 26 °C max.

There shall be no deposit of moisture on or in the cartridge.

The above conditions include any temperature rise that may occur while operating the drive.

Conditioning before operating:

If a cartridge has been exposed during storage and/or transportation to a condition outside the above values, before use the cartridge shall be conditioned in the operating environment for a time at least equal to the period during which it has been out of the operating environment, up to a maximum of 24 h.

NOTE - Rapid variations of temperature should be avoided.

7.3 Storage environment

The following conditions shall be observed during storage

temperature : 5°C to 32°C
 relative humidity : 20 % to 60 %

The stray magnetic field at any point on the tape shall not exceed 4000 A/m. There shall be no deposit of moisture on or in the cartridge.

7.4 Transportation

Recommended limits for the environment to which a cartridge may be subjected during transportation, and the precautions to be taken to minimize the possibility of damage, are provided in annex H.

7.5 Safety

The cartridge and its components shall satisfy the requirements of Standard IEC 60950. The cartridge and its components shall not constitute any safety or health hazard when used in the intended manner, or through any foreseeable misuse in an information processing system.

7.6 Flammability

The cartridge and its components shall be made from materials, which if ignited from a match flame, do not continue to burn in a still carbon dioxide atmosphere.

Section 2 - Requirements for the case

8 Dimensional and mechanical characteristics of the case

8.1 General

Dimensional characteristics are specified for those parameters deemed to be mandatory for interchange and compatible use of the cartridge. Where there is freedom of design, only the functional characteristics of the elements described are indicated. In the figures a typical implementation is represented in third angle projection.

Figure 1	is a perspective view of the cartridge seen from the top.
Figure 2	is a perspective view of the cartridge seen from the bottom.
Figure 3	is a perspective view of Reference Planes X, Y and Z.
Figure 4	shows the front side with the lid closed.
Figure 5	shows the left side with the lid closed.
Figure 6	shows the top side with the lid closed.
Figure 7	shows the right side with the lid closed.
Figure 8	shows the rear side with the lid closed.
Figure 9	shows the bottom side, Datum and Support areas.
Figure 10	shows the bottom side with the lid removed.
Figure 11	shows an enlarged view of the Datum and Recognition holes.
Figure 12	shows the cross-sections through the light path holes, the Recognition holes and the Write-inhibit hole.
Figure 13	shows details of the lid when closed, rotating and open.
Figure 14	shows the details of the lid release insertion channel.
Figure 15	shows the lid lock release requirements.
Figure 16	shows the reel lock release requirements.
Figure 17	shows the reel unlock force direction.
Figure 18	shows the lid release force direction.
Figure 19	shows the lid opening force direction.
Figure 20	shows the light path and light window.
Figure 21	shows the internal tape path and light path.
Figure 22	shows the cartridge reel and a cross-section of the cartridge reel.
Figure 23	shows a cross-section of the interface of the cartridge reel with the drive spindle.
Figure 24	shows the tape access cavity clearance.
Figure 25	shows the Access Holes of the MIC on the rear side.
Figure 26	shows the Access Holes of the MIC on the bottom side.

The dimensions are referred to three orthogonal Reference Planes X, Y and Z (see figure 3).

Plane X is perpendicular to Plane Z and passes through the centres of the Datum holes A and B.

Plane Y is perpendicular to Plane X and Plane Z and passes through the centre of Datum hole A.

Datum areas A, B and C lie in Plane Z.

8.2 Overall dimension (figures 5 and 6)

The length of the case shall be

$$l_1 = 62,5 \text{ mm} \pm 0,3 \text{ mm}$$

The width of the case shall be

$$l_2 = 95,0 \text{ mm} \pm 0,2 \text{ mm}$$

The distance from the top side of the case to Reference Plane Z shall be

$$l_3 = 15,0 \text{ mm} \pm 0,2 \text{ mm}$$

The distance from the rear side to Plane X shall be

$$l_4 = 47,35 \text{ mm} \pm 0,15 \text{ mm}$$

The distance from the right side to Plane Y shall be

$$l_5 = 13,0 \text{ mm} \pm 0,1 \text{ mm}$$

8.3 Holding areas

The holding areas shown shaded in figure 6 shall be the areas along which the cartridge shall be held down when inserted into the drive. The distance of the holding areas from Plane X shall be

$$l_6 = 12,0 \text{ mm max.}$$

The width when measured from the edges of the case shall be

$$l_7 = 3,0 \text{ mm min.}$$

8.4 Cartridge insertion

The cartridge shall have asymmetrical features to prevent insertion into the drive in other than the correct orientation. These consist of a channel, a recess and an incline.

The channel (figures 4 and 14) shall provide for an unobstructed path, when the lid is closed and locked, to unlock the lid. The distance of the channel from Plane Y shall be

$$l_8 = 79,6 \text{ mm} \pm 0,2 \text{ mm}$$

There shall be a chamfer at the beginning of the channel defined by

$$l_9 = 1,0 \text{ mm} \pm 0,1 \text{ mm}$$

$$l_{16} = 1,5 \text{ mm} \pm 0,1 \text{ mm}$$

An additional chamfer further into the channel shall be defined by

$$l_{10} = 0,7 \text{ mm} \pm 0,1 \text{ mm}$$

$$l_{17} = 1,9 \text{ mm} \pm 0,1 \text{ mm}$$

$$l_{18} = 3,65 \text{ mm} \pm 0,10 \text{ mm}$$

The innermost width of the channel shall be

$$l_{11} = 1,0 \text{ mm min.}$$

ISO/IEC 18809:2000

<https://standards.iteh.ai/catalog/standards/sist/1ceed255-6785-4f95-be90-71d161f044ea/iso-iec-18809-2000>

There shall be a chamfer on the lid defined by

$$l_{12} = 1,2 \text{ mm} \pm 0,1 \text{ mm}$$

$$l_{13} = 0,8 \text{ mm} \pm 0,1 \text{ mm}$$

$$l_{14} = 1,2 \text{ mm} \pm 0,1 \text{ mm}$$

$$l_{15} = 0,5 \text{ mm} \pm 0,1 \text{ mm}$$

The distance from the left side of the case to the release pin shall be

$$l_{19} = 0,2 \text{ mm} \pm 0,2 \text{ mm}$$

The height of the insertion area shall be

$$l_{20} = 2,3 \text{ mm min.}$$

$$l_{21} = 2,5 \text{ mm} \begin{matrix} + 0,2 \text{ mm} \\ - 0,0 \text{ mm} \end{matrix}$$

The recess is located on the right side of the cartridge. The position and dimensions (figures 7 and 10) shall be defined by

$$l_{22} = 7,5 \text{ mm max.}$$

$$l_{23} = 11,0 \text{ mm} \pm 0,2 \text{ mm}$$

$$l_{24} = 1,5 \text{ mm} \pm 0,1 \text{ mm}$$

The depth of the recess shall be

$$l_{25} = 1,5 \text{ mm} \pm 0,1 \text{ mm}$$