
**Information technology — 8 mm wide
magnetic tape cartridge for information
interchange — Helical scan recording —
MammothTape-2 format**

*Technologies de l'information — Cartouche de bande magnétique de 8 mm
de large pour l'échange d'information — Enregistrement par balayage en
spirale — Format «MammothTape-2»*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 18836:2001](https://standards.iteh.ai/catalog/standards/sist/fb23d614-e589-4015-9efa-783463bca425/iso-iec-18836-2001)

<https://standards.iteh.ai/catalog/standards/sist/fb23d614-e589-4015-9efa-783463bca425/iso-iec-18836-2001>

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 18836:2001](https://standards.iteh.ai/catalog/standards/sist/fb23d614-e589-4015-9efa-783463bca425/iso-iec-18836-2001)

<https://standards.iteh.ai/catalog/standards/sist/fb23d614-e589-4015-9efa-783463bca425/iso-iec-18836-2001>

© ISO/IEC 2001

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Contents

Section 1 - General	1
1 Scope	1
2 Conformance	1
2.1 Magnetic tape cartridges	1
2.2 Generating drive	1
2.3 Receiving drive	1
3 References	1
4 Definitions	1
4.1 a.c. erase	1
4.2 algorithm	1
4.3 Average Signal Amplitude	1
4.4 azimuth	2
4.5 back surface	2
4.6 bit cell	2
4.7 byte	2
4.8 cartridge	2
4.9 Channel bit	2
4.10 Cyclic Redundancy Check (CRC) character	2
4.11 Error Correcting Code (ECC)	2
4.12 File Mark	2
4.13 Logical Beginning of Partition (LBOP)	2
4.14 Logical Block	2
4.15 magnetic tape	2
4.16 Master Standard Reference Tape	2
4.17 Partition	2
4.18 Physical Beginning of Partition (PBOP)	2
4.19 Physical Beginning of Tape (PBOT)	2
4.20 Physical End of Partition (PEOP)	2
4.21 Physical End of Tape (PEOT)	2
4.22 physical recording density	2
4.23 Read Back Check (RBC)	2
4.24 Reference Field	2
4.25 Secondary Standard Reference Tape (SSRT)	2
4.26 Set Mark	2
4.27 Standard Reference Amplitude (SRA)	2
4.28 Standard Reference Current (Ir)	2
4.29 Tape Reference Edge	2
4.30 Test Recording Current (TRC)	2
4.31 Track	3
4.32 Typical Field	3
5 Conventions and Notations	3
5.1 Representation of numbers	3
5.2 Names	3
6 Acronyms	3

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 18836:2001](https://standards.iteh.ai/catalog/standards/sist/fb23d614-e589-4015-9efa-783463bca425/iso-iec-18836-2001)

<https://standards.iteh.ai/catalog/standards/sist/fb23d614-e589-4015-9efa-783463bca425/iso-iec-18836-2001>

ISO/IEC 18836:2001(E)

7	Environment and Safety	4
7.1	Testing environment	4
7.2	Operating environment	4
7.3	Storage environment	4
7.4	Transportation	4
7.5	Safety	4
7.6	Flammability	4
Section 2 - Requirements for the case		5
8	Dimensional and mechanical characteristics of the case	5
8.1	General	5
8.2	Overall dimension	5
8.3	Holding areas	6
8.4	Cartridge insertion	6
8.5	Window	7
8.6	Loading grips	7
8.7	Label areas	7
8.8	Datum areas and datum holes	7
8.9	Support areas	8
8.10	Recognition holes	9
8.11	Write-inhibit hole	9
8.12	Pre-positioning surfaces	10
8.13	Cartridge lid	10
8.14	Cartridge reel lock	11
8.15	Reel access holes	12
8.16	Interface between the reels and the drive spindles	12
8.17	Light path	14
8.18	Position of the tape in the case	14
8.19	Tape path zone	14
8.20	Tape access cavity	15
8.21	Tape access cavity clearance requirements	15
Section 3 - Requirements for the Unrecorded Tape		32
9	Mechanical, physical and dimensional characteristics of the tape	32
9.1	Materials	32
9.2	Tape length	32
9.2.1	Length of the magnetic tape	32
9.2.2	Length of leader and trailer tapes	32
9.2.3	Length of the cleaning tape	32
9.2.4	Length of the splicing tape	32
9.3	Width	32
9.3.1	Width of magnetic, cleaning, leader and trailer tape	32
9.3.2	Width and position of the splicing tape	33
9.3.3	Edge weave	33
9.4	Discontinuities	34
9.5	Thickness	34
9.5.1	Thickness of the magnetic tape	34
9.5.2	Thickness of the cleaning tape	34
9.5.3	Thickness of leader and trailer tape	34
9.5.4	Thickness of the splice tape	35
9.6	Longitudinal curvature	35
9.7	Cupping	35
9.8	Coating adhesion	35
9.9	Layer-to-layer adhesion	36
9.10	Tensile strength	36

9.10.1	Breaking strength	36
9.10.2	Yield strength	36
9.11	Residual elongation	36
9.12	Electrical resistance of the recording surface	36
9.13	Tape winding	37
9.14	Light transmittance of tape	37
9.15	Abrasivity	37
10	Magnetic recording characteristics	37
10.1	Test conditions	37
10.2	Typical Field	37
10.3	Signal Amplitude	38
10.4	Resolution	38
10.5	Signal-to-Noise Ratio	38
10.6	Ease of erasure	39
10.7	Tape quality	39
10.7.1	Missing pulses	39
10.7.2	Missing pulse zone	39
10.7.3	Overwrite	39
Section 4 - Requirements for an Interchanged Tape		40
11	Track Format	40
11.1	General	40
11.2	Physical block format	41
11.2.1	Logical Transfer Segment (LTS)	41
11.2.2	Compression Unit	42
11.2.3	Physical block	43
11.2.4	Information Matrix	50
11.2.5	Recorded patterns	51
11.3	Search field format	51
11.3.1	Search field data	51
11.3.2	Search field CRC and ECC	53
11.3.3	Search field recording patterns	53
11.4	Servo area	53
11.5	Track layout	53
12	Method of recording	56
12.1	Physical Recording Density	56
12.1.1	Long Term Average Bit Cell Length	56
12.1.2	Short Term Average Bit Cell Length	56
12.1.3	Rate of Change	56
12.2	Bit Shift	57
12.3	Amplitude of Data Signals	57
13	Track geometry	57
13.1	General	57
13.2	Track pitch	57
13.3	Average track pitch	57
13.4	Track width	57
13.5	Track angle	58
13.6	Track length	58
13.7	Guard band	58
13.8	Azimuth angles	58
13.9	Track linearity	58

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 18836:2001](https://standards.iteh.ai/catalog/standards/sist/fb23d614-e589-4015-9efa-783463bca425/iso-iec-18836-2001)

<https://standards.iteh.ai/catalog/standards/sist/fb23d614-e589-4015-9efa-783463bca425/iso-iec-18836-2001>

ISO/IEC 18836:2001(E)

14	Layout of a tape	58
14.1	General	58
14.2	Tape History Log (THL)	58
14.3	Physical Beginning of Partition	59
14.4	Logical Beginning of Partition	59
14.5	Data area	59
14.5.1	General	59
14.5.2	Short File Mark	59
14.5.3	Long File Mark	59
14.5.4	Set Mark	59
14.6	End of Data	59
14.7	Physical End of Partition (PEOP)	59
Annexes		
A	(normative) - Measurement of Light Transmittance of Tape and Leaders	60
B	(normative) - Tape abrasivity measurement procedure	63
C	(normative) - Generation of the Logical Block CRC	65
D	(normative) - ECC3 Check Bytes	66
E	(normative) - Generation of the Data Area CRC	67
F	(normative) - Generation of the ECC	68
G	(normative) - Pre-coder	69
H	(normative) - Representation of 8-bit bytes by 10-bit patterns	70
J	(normative) - Randomisation	77
K	(normative) - Generation of the Search Field CRC	78
L	(normative) - The Search Field ECC	79
M	(normative) - Measurement of bit shift	80
N	(informative) - Recommendations for transportation	82

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 18836:2001](https://standards.iteh.ai/catalog/standards/sist/fb23d614-e589-4015-9efa-783463bca425/iso-iec-18836-2001)

standards.iteh.ai/catalog/standards/sist/fb23d614-e589-4015-9efa-783463bca425/iso-iec-18836-2001

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

This International Standard was prepared by ECMA (as ECMA-293) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

Annexes A to M form a normative part of this International Standard. Annex N is for information only.

[ISO/IEC 18836:2001](https://standards.iteh.ai/catalog/standards/sist/fb23d614-e589-4015-9efa-783463bca425/iso-iec-18836-2001)

<https://standards.iteh.ai/catalog/standards/sist/fb23d614-e589-4015-9efa-783463bca425/iso-iec-18836-2001>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 18836:2001](#)

<https://standards.iteh.ai/catalog/standards/sist/fb23d614-e589-4015-9efa-783463bca425/iso-iec-18836-2001>

Information technology - 8 mm wide magnetic tape cartridge for information interchange - Helical scan recording - MammothTape-2 format

Section 1 - General

1 Scope

This International Standard specifies the physical and magnetic characteristics of an 8 mm wide magnetic tape cartridge to enable physical interchange of such cartridges between drives. It also specifies the quality of the recorded signals, the recording method and the recorded format called MammothTape-2, and thereby allowing data interchange between drives by means of such magnetic tape cartridges.

Information interchange between systems also requires, at a minimum, agreement between the interchange parties upon the interchange code(s) and the specifications of the structure and labelling of the information on the interchanged cartridge.

2 Conformance

2.1 Magnetic tape cartridges

A magnetic tape cartridge shall be in conformance with this International Standard if it satisfies all mandatory requirements of this International Standard throughout the extent of the tape.

2.2 Generating drive

A drive generating a magnetic tape cartridge for interchange shall be entitled to claim conformance with this International Standard if all the recordings that it makes on a tape meet the mandatory requirements of this International Standard. A claim of conformance shall state whether or not one or more registered compression algorithm(s) are implemented within the system to process data from the host prior to allocating data to physical blocks.

2.3 Receiving drive

A system receiving a magnetic tape cartridge for interchange shall be entitled to claim conformance with the International Standard if it is able to handle any recording on this tape according to this International Standard. A receiving drive shall be able to recognise the use of a data compression algorithm and make the algorithm registration number available to the host.

3 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

IEC 60950:1999	<i>Safety of information technology equipment.</i>
ISO 527-3:1995	<i>Plastics - Determination of tensile properties - Part 3: Test conditions for films and sheets.</i>
ISO 1302:1992	<i>Technical Drawings - Method of indicating surface texture.</i>
ISO/IEC 11576:1994	<i>Information technology - Procedure for the registration of algorithms for the lossless compression of data.</i>
ISO/IEC 15200:1996	<i>Information technology - Adaptive Lossless Data Compression algorithm (ALDC).</i>

4 Terms and definitions

For the purposes of this International Standard, the following terms and definitions apply.

4.1 a.c. erase: A process of erasure utilising alternating magnetic fields of decaying intensity.

4.2 algorithm: A set of rules for transforming the logical representation of data.

4.3 Average Signal Amplitude: The average peak-to-peak value of the output signal from the read head at a density of 3 704 fpmmm measured over a distance of 3000 mm, exclusive of missing pulses.

- 4.4 **azimuth:** The angular deviation, in degrees of arc, of the recorded flux transitions on a track from a line normal to the track centreline.
- 4.5 **back surface:** The surface of the tape opposite to the magnetic coating used to record data.
- 4.6 **bit cell:** A distance along the track allocated for the recording of a Channel bit.
- 4.7 **byte:** An ordered set of bits acted upon as a unit.
- 4.8 **cartridge:** A case containing magnetic tape stored on twin reels.
- 4.9 **Channel bit:** A bit after 8-10 transformation.
- 4.10 **Cyclic Redundancy Check (CRC) character:** A character derived from information contained in data bytes that is used for error detection.
- 4.11 **Error Correcting Code (ECC):** A mathematical procedure yielding bytes used for the detection and correction of errors.
- 4.12 **File Mark:** A mark recorded on the tape at the request of the host system to separate files or to provide an append point. This format provides for Long or Short File Marks.
- 4.13 **Logical Beginning of Partition (LBOP):** The point in a partition where a recording of data for interchange commences.
- 4.14 **Logical Block:** Information (data, file marks, or set marks) sent to the tape drive to be recorded.
- 4.15 **magnetic tape:** A tape that accepts and retains magnetic signals intended for input, output, and storage of data for information processing.
- 4.16 **Master Standard Reference Tape:** A tape selected as the standard for Signal Amplitude, Typical Field, Overwrite and Resolution.

Note - The Master Standard Reference Tape has been established by Pericomp Corporation.

- 4.17 **Partition:** A formatted length of tape used to record data.
- 4.18 **Physical Beginning of Partition (PBOP):** The point along the length of tape at which a partition begins.
- 4.19 **Physical Beginning of Tape (PBOT):** The transition from the tape leader to an opaque area of the splice by which a translucent leader tape is joined to the magnetic tape.
- 4.20 **Physical End of Partition (PEOP):** The point along the length of tape at which a partition ends.
- 4.21 **Physical End of Tape (PEOT):** The transition from an opaque area of the splice to a translucent trailer tape.
- 4.22 **physical recording density:** The number of recorded flux transitions per unit length of track, expressed in flux transitions per millimetre (ftpmm).
- 4.23 **Read Back Check (RBC):** A Read Back Check occurs when, while writing, the data is read by trailing heads and checked for errors.
- 4.24 **Reference Field:** The Typical Field of the Master Standard Reference Tape.
- 4.25 **Secondary Standard Reference Tape (SSRT):** A tape the performance of which is known and stated in relation to that of the Master Standard Reference Tape.

Note - Secondary Standard Reference Tapes can be ordered under the Part Number *SSRT/M.AME/PC97*, from Pericomp Corporation, 14 Huron Drive, Natick, MA 01760, USA.

In principle, such tapes will be available for a period of 10 years from the publication of the first edition of this International Standard. However, by agreement between ISO/IEC and Pericomp, this period may be shortened or extended to take account of demand for such tapes.

It is intended that these be used for calibrating Tertiary Reference Tapes for use in routine calibration.

- 4.26 **Set Mark:** A mark recorded on the tape at the request of the host system to separate a set of data or to provide an append point.
- 4.27 **Standard Reference Amplitude (SRA):** The Average Signal Amplitude derived from the Master Standard Reference Tape, using the Test Recording Current at 3 704 ftpmm.
- 4.28 **Standard Reference Current (Ir):** The current that produces the Reference Field.
- 4.29 **Tape Reference Edge:** The lower edge of tape as seen when viewing the recording surface of the tape with the supply reel to the observer's right.
- 4.30 **Test Recording Current (TRC):** The current used to record the SRA. The TRC is 1,5 times the Standard Reference Current.

4.31 Track: A diagonally positioned area on the tape along which a series of magnetic transitions may be recorded.

4.32 Typical Field: In the plot of the Average Signal Amplitude against the recording field at the physical recording density of 3 704 ft/mm, the minimum field that causes an Average Signal Amplitude equal to 90% of the maximum Average Signal Amplitude.

5 Conventions and Notations

5.1 Representation of numbers

A measured value is rounded off to the least significant digit of the corresponding specified value. It implies that a specific value of 1,26 with a positive tolerance of +0,01, and a negative tolerance of -0,02 allows a range of measured values from 1,235 to 1,275.

- Letters and digits in parentheses represent numbers in hexadecimal notation.
- The setting of a bit is denoted by ZERO or ONE.
- Numbers in binary notation and bit combinations are represented by strings of digits 0 and 1.
- Numbers in binary notation and bit combinations are shown with the most significant byte to the left, and with the most significant bit in each byte to the left.
- Negative values of numbers in binary notation are given in Two's complement.
- In each field the data is processed so that the most significant byte (byte 0) is processed first. Within each byte the most significant bit (numbered 7 in an 8-bit byte) is processed first, least significant bit is numbered 0 and is processed last. This order of processing applies also to the data input to the Error Detection and Correction circuits and to their output, unless otherwise stated.

5.2 Names

The names of entities, e.g. specific tracks, fields, etc., are given with a capital initial.

iTeh STANDARD PREVIEW
(standards.itteh.ai)

6 Acronyms

ABID	Augmentative Block Identifier	ISO/IEC 18836:2001
BID	Block Identifier	https://standards.itteh.ai/catalog/standards/sist/fb23d614-e589-4015-9efa-783463bca425/iso-iec-18836-2001
CRC	Cyclic Redundancy Check	
CUH	Compression Unit Header	
CUID	Compression Unit Identifier	
ECC	Error Correction Code	
EOD	End of Data	
FID	File Identifier	
LBOP	Logical Beginning of Partition	
LID	Logical Block Identifier	
lsb	Least Significant Bit	
LSB	Least Significant Byte	
LTS	Logical Transfer Segment	
msb	Most Significant Bit	
MSB	Most significant Byte	
PBOP	Physical Beginning of Partition	
PBOT	Physical Beginning of Tape	
PEOP	Physical End of Partition	
PEOT	Physical End of Tape	
PID	Physical Identifier	
RBC	Read Back Check	
SID	Stream Identifier	
SMID	Set Mark Identifier	
SRA	Standard Reference Amplitude	
SSRT	Secondary Standard Reference Tape	
THL	Tape History Log	
TRC	Test Recording Current	

7 Environment and Safety

The conditions specified below refer to the ambient conditions immediately surrounding the cartridge.

Cartridges exposed to environments outside these limits may still be able to function usefully; however, such exposure may cause permanent damage.

7.1 Testing environment

Unless otherwise specified, tests and measurements made on the cartridge to check the requirements of this International Standard shall be carried out under the following conditions

temperature: 23 °C ± 2 °C
relative humidity: 40 % to 60 %
conditioning period before testing: 24 h min.

7.2 Operating environment

Cartridges used for data interchange shall be capable of operating under the following conditions

temperature: 5 °C to 45 °C
relative humidity: 20 % to 80 %
wet bulb temperature: 26 °C max.

The average temperature of the air immediately surrounding the tape shall not exceed 45°C.

If a cartridge has been exposed during storage and/or transportation to conditions outside the above values, before use the cartridge shall be conditioned in the operating environment for a time at least equal to the period during which it has been out of the operating environment, up to a maximum of 24 h.

7.3 Storage environment

The following conditions shall be observed during storage

temperature: 5 °C to 32 °C
relative humidity: 20 % to 60 %
stray magnetic field: shall not exceed 4 000 A/m at any point on the tape.

There shall be no deposit of moisture on or in the cartridge.

7.4 Transportation

Recommended limits for the environments, to which a cartridge may be subjected during transportation, and the precautions to be taken to minimise the possibility of damage, are provided in annex N.

7.5 Safety

The cartridge shall satisfy the safety requirements of IEC 60950 when used in the intended manner or in any foreseeable use in an information processing system.

7.6 Flammability

The cartridge shall be made from materials that comply with the flammability class for HB materials, or better, as specified in IEC 60950.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
<https://standards.iteh.ai/catalog/standards/sist/fb23d614-e589-4015-9efa-783463bca425/iso-iec-18836-2001>

Section 2 - Requirements for the case

8 Dimensional and mechanical characteristics of the case

8.1 General

The cartridge shall consist of the following elements:

- a case
- recognition holes
- a write inhibit mechanism
- twin reels containing magnetic tape
- a locking mechanism for the reels

Dimensional characteristics are specified for those parameters deemed to be mandatory for interchange and compatible use of the cartridge. Where there is freedom of design, only the functional characteristics of the elements described are indicated. In the figures a typical implementation is represented in third angle projections.

- Figure 1 shows a perspective view of the cartridge seen from the top.
 Figure 2 shows a perspective view of the cartridge seen from the bottom.
 Figure 3 shows a perspective view of Reference Planes X, Y and Z.
 Figure 4 shows the front side with the lid closed.
 Figure 5 shows the left side with the lid closed.
 Figure 6 shows the top side with the lid closed.
 Figure 7 shows the right side with the lid closed.
 Figure 8 shows the rear side with the lid closed.
 Figure 9 shows the bottom side, datum and support areas.
 Figure 10 shows the bottom side with the lid removed.
 Figure 11 shows the enlarged view of the datum and recognition holes.
 Figure 12 shows cross-sections through the light path holes, the recognition holes and the write-inhibit hole.
 Figure 13 shows details of the lid when closed, rotating and open.
 Figure 14 shows details of the lid release insertion channel.
 Figure 15 shows the lid lock release requirements.
 Figure 16 shows the reel lock release requirements.
 Figure 17 shows the reel unlock force direction.
 Figure 18 shows the lid release force direction.
 Figure 19 shows the lid opening force direction.
 Figure 20 shows the light path and light window.
 Figure 21 shows the internal tape path and light path.
 Figure 22 shows the cartridge reel and a cross-section view of the cartridge reel.
 Figure 23 shows a cross-section view of the cartridge reel interface with the drive spindle.
 Figure 24 shows the tape access cavity clearance requirements.

The dimensions are referred to three orthogonal Reference Planes X, Y and Z (see figure 3).

Plane X is perpendicular to Plane Z and passes through the centres of the Datum Holes A and B.

Plane Y is perpendicular to Plane X and Plane Z and passes through the centre of Datum Hole A.

Datum area A, B and C shall lie in Plane Z.

8.2 Overall dimension (figures 5 and 6)

The length of the case shall be

$$l_1 = 62,5 \text{ mm} \pm 0,3 \text{ mm}$$

The width of the case shall be

$$l_2 = 95,0 \text{ mm} \pm 0,2 \text{ mm}$$

The distance from the top of the case to Plane Z shall be

$$l_3 = 15,0 \text{ mm} \pm 0,2 \text{ mm}$$

The distance from the rear side to Plane X shall be

$$l_4 = 47,35 \text{ mm} \pm 0,15 \text{ mm}$$

The distance from the right side to Plane Y shall be

$$l_5 = 13,0 \text{ mm} \pm 0,1 \text{ mm}$$

8.3 Holding areas

The holding areas shown hatched in figure 6 shall be the areas along which the cartridge shall be held down when inserted into the drive. The distance of the holding areas from Plane X shall be

$$l_6 = 12,0 \text{ mm max.}$$

The width when measured from the edge of the case shall be

$$l_7 = 3,0 \text{ mm min.}$$

8.4 Cartridge insertion

The cartridge shall have asymmetrical features to prevent insertion into the drive in other than the correct orientation. These consist of an insertion channel, a recess and an incline.

The insertion channel (figures 4 and 14) shall provide for an unobstructed path, when the lid is closed and locked, to unlock the lid. The distance of the insertion channel from Plane Y shall be

$$l_8 = 79,7 \text{ mm} \pm 0,2 \text{ mm}$$

There shall be a chamfer at the beginning of the insertion channel defined by

$$l_9 = 1,0 \text{ mm} \pm 0,1 \text{ mm}$$

$$l_{16} = 1,5 \text{ mm} \pm 0,1 \text{ mm}$$

An additional chamfer further into the insertion channel shall be defined by

$$l_{10} = 0,7 \text{ mm} \pm 0,1 \text{ mm}$$

$$l_{17} = 1,0 \text{ mm} \pm 0,1 \text{ mm}$$

$$l_{18} = 3,8 \text{ mm} \pm 0,1 \text{ mm}$$

The innermost width of the insertion channel shall be

$$l_{11} = 1,0 \text{ mm min.}$$

The thickness of the lid shall be

$$l_{12} = 1,2 \text{ mm} \pm 0,1 \text{ mm}$$

There shall be a chamfer on the lid defined by

$$l_{13} = 0,8 \text{ mm} \pm 0,1 \text{ mm}$$

$$l_{14} = 1,2 \text{ mm} \pm 0,1 \text{ mm}$$

The lid shall extend from the case a distance of

$$l_{15} = 0,5 \text{ mm} \pm 0,1 \text{ mm}$$

The distance from the left side of the case to the lid lock shall be

$$l_{19} = 0,2 \text{ mm} \pm 0,2 \text{ mm}$$

The height of the insertion area shall be

$$l_{20} = 2,3 \text{ mm min.}$$

$$l_{21} = 2,5 \text{ mm} \pm 0,2 \text{ mm}$$

The recess is located on the right side of the cartridge. The position and dimensions (figures 5, 7 and 10) shall be defined by

$$l_{22} = 7,5 \text{ mm max.}$$

$$l_{23} = 11,0 \text{ mm} \pm 0,2 \text{ mm}$$

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 18836:2001
<https://standards.iteh.ai/catalog/standards/sist/fb23d614-e589-4015-9efa-783463bca425/iso-iec-18836-2001>

$$l_{24} = 1,5 \text{ mm} \pm 0,1 \text{ mm}$$

The depth of the recess shall be

$$l_{25} = 1,5 \text{ mm} \pm 0,1 \text{ mm}$$

The incline (figure 13a) is part of the lid structure. The distance of the incline from Plane X shall be defined by

$$l_{26} = 7,7 \text{ mm} \begin{array}{l} + 0,0 \text{ mm} \\ - 2,5 \text{ mm} \end{array}$$

The angle of the incline shall be

$$a_1 = 20^\circ \pm 1^\circ$$

The incline shall end when it intersects the radius r_3 (see clause 8.13).

8.5 Window (figure 1)

A window may be provided on the top side so that parts of the reels are visible. The window, if provided, shall not extend beyond the height of the cartridge.

8.6 Loading grips (figures 5 and 7)

The cartridge shall have recessed loading grips on each side to aid an automatic loading mechanism.

The distance from Plane X to the centreline of the loading grip shall be

$$l_{28} = 39,35 \text{ mm} \pm 0,20 \text{ mm};$$

The distance from Plane Z on the bottom side and from the top side shall be

$$l_{29} = 1,5 \text{ mm} \pm 0,1 \text{ mm};$$

The width of the indent shall be

$$l_{30} = 5,0 \text{ mm} \pm 0,3 \text{ mm};$$

The depth of the indent shall be <https://standards.iteh.ai/catalog/standards/sist/fb23d614-e589-4015-9efa-783463bca425/iso-iec-18836-2001>

$$l_{31} = 2,0 \text{ mm} \pm 0,2 \text{ mm};$$

and the angle of the indent

$$a_2 = 90^\circ \pm 5^\circ.$$

8.7 Label areas (figures 6 and 8)

A portion of the rear side of the cartridge and a portion of the top side of the cartridge may be used for labels. The position and the size of the labels shall not interfere with the operation or clearance requirements of the cartridge component parts.

The area used for labels on the top side shall not extend beyond the inner edge of the holding areas defined by l_6 and l_7 .

The position and dimensions of the label area on the rear side shall be defined by

$$l_{32} = 0,5 \text{ mm min.}$$

$$l_{33} = 1,5 \text{ mm min.}$$

$$l_{34} = 80,0 \text{ mm max.}$$

The depth of the top side label area shall be 0,3 mm max. The depth of the rear side label area shall be $0,30 \text{ mm} \pm 0,05 \text{ mm}$.

8.8 Datum areas and datum holes

The annular datum areas A, B and C shall lie in Plane Z (see figures 9, 10 and 11). They determine the vertical position of the cartridge in the drive. Each shall have a diameter d_1 equal to $6,0 \text{ mm} \pm 0,1 \text{ mm}$ and be concentric with the respective datum hole.

The centres of datum holes A and B lie in Plane X.

The centre of the circular datum hole A shall be at the intersection of planes X and Y (see figure 10).