

SLOVENSKI STANDARD
oSIST prEN ISO 21007-2:2011
01-junij-2011

Plinske jeklenke - Označevanje in prepoznavanje s pomočjo radiofrekvenčne identifikacije - 2. del: Oštevilčenje sistemov za radiofrekvenčno identifikacijo (ISO/DIS 21007-2:2011)

Gas cylinders - Identification and marking using radio frequency identification technology - Part 2: Numbering schemes for radio frequency identification (ISO/DIS 21007-2:2011)

Gasflaschen - Identifizierung und Kennzeichnung mittels Hochfrequenzidentifizierungstechnologie - Teil 2: Nummerierungssysteme für die Hochfrequenzidentifizierung (ISO/DIS 21007-2:2011)

Bouteilles à gaz - Identification et marquage à l'aide de la technologie d'identification par radiofréquences - Partie 2: Schémas de numérotage pour identification par radiofréquences (ISO/DIS 21007-2:2011)

Ta slovenski standard je istoveten z: prEN ISO 21007-2

ICS:

23.020.30	Tlačne posode, plinske jeklenke	Pressure vessels, gas cylinders
-----------	---------------------------------	---------------------------------

oSIST prEN ISO 21007-2:2011

en,fr,de

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

DRAFT
prEN ISO 21007-2

February 2011

ICS 23.020.30

Will supersede EN ISO 21007-2:2005

English Version

Gas cylinders - Identification and marking using radio frequency identification technology - Part 2: Numbering schemes for radio frequency identification (ISO/DIS 21007-2:2011)

Bouteilles à gaz - Identification et marquage à l'aide de la technologie d'identification par radiofréquences - Partie 2: Schémas de numérotage pour identification par radiofréquences (ISO/DIS 21007-2:2011)

Gasflaschen - Identifizierung und Kennzeichnung mittels Hochfrequenztechnologie - Teil 2: Identifikationssysteme für die Hochfrequenztechnik (ISO/DIS 21007-2:2011)

This draft European Standard is submitted to CEN members for parallel enquiry. It has been drawn up by the Technical Committee CEN/TC 23.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents	Page
Foreword.....	3

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN ISO 21007-2:2013

<https://standards.iteh.ai/catalog/standards/sist/2b52b385-6236-4146-8e67-10dd47fad6b7/sist-en-iso-21007-2-2013>

Foreword

This document (prEN ISO 21007-2:2011) has been prepared by Technical Committee ISO/TC 58 "Gas cylinders" in collaboration with Technical Committee CEN/TC 23 "Transportable gas cylinders" the secretariat of which is held by BSI.

This document is currently submitted to the parallel Enquiry.

This document will supersede EN ISO 21007-2:2005.

Endorsement notice

The text of ISO/DIS 21007-2:2011 has been approved by CEN as a prEN ISO 21007-2:2011 without any modification.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN ISO 21007-2:2013](https://standards.iteh.ai/catalog/standards/sist/2b52b385-6236-4146-8e67-10dd47fad6b7/sist-en-iso-21007-2-2013)

<https://standards.iteh.ai/catalog/standards/sist/2b52b385-6236-4146-8e67-10dd47fad6b7/sist-en-iso-21007-2-2013>



DRAFT INTERNATIONAL STANDARD ISO/DIS 21007-2

ISO/TC 58/SC 4

Secretariat: ANSI

Voting begins on
2011-02-03Voting terminates on
2011-07-03

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Gas cylinders — Identification and marking using radio frequency identification technology —

Part 2: Numbering schemes for radio frequency identification

*Bouteilles à gaz — Identification et marquage à l'aide de la technologie d'identification par radiofréquences —
Partie 2: Schémas de numérotage pour identification par radiofréquences*

[Revision of first edition (ISO 21007-2:2005)]

ICS 23.020.30

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/CEN PARALLEL PROCESSING

This draft has been developed within the International Organization for Standardization (ISO), and processed under the **ISO-lead** mode of collaboration as defined in the Vienna Agreement.

This draft is hereby submitted to the ISO member bodies and to the CEN member bodies for a parallel five-month enquiry.

Should this draft be accepted, a final draft, established on the basis of comments received, will be submitted to a parallel two-month approval vote in ISO and formal vote in CEN.

In accordance with the provisions of Council Resolution 15/1993 this document is circulated in the English language only.

Conformément aux dispositions de la Résolution du Conseil 15/1993, ce document est distribué en version anglaise seulement.

To expedite distribution, this document is circulated as received from the committee secretariat. ISO Central Secretariat work of editing and text composition will be undertaken at publication stage.

Pour accélérer la distribution, le présent document est distribué tel qu'il est parvenu du secrétariat du comité. Le travail de rédaction et de composition de texte sera effectué au Secrétariat central de l'ISO au stade de publication.

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW

(standards.iteh.ai)

[SIST EN ISO 21007-2:2013](https://standards.iteh.ai/catalog/standards/sist/2b52b385-6236-4146-8e67-10dd47fad6b7/sist-en-iso-21007-2-2013)

<https://standards.iteh.ai/catalog/standards/sist/2b52b385-6236-4146-8e67-10dd47fad6b7/sist-en-iso-21007-2-2013>

Copyright notice

This ISO document is a Draft International Standard and is copyright-protected by ISO. Except as permitted under the applicable laws of the user's country, neither this ISO draft nor any extract from it may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission being secured.

Requests for permission to reproduce should be addressed to either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Reproduction may be subject to royalty payments or a licensing agreement.

Violators may be prosecuted.

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms, definitions and numerical notations	1
4 Data presentation	2
5 Gas cylinder identification structure	4
6 Gas cylinder identification data schemes	5
7 Air interface specifications	15
8 Transponder memory addressing	16
Annex A (normative) Technical solution	18
Annex B (informative) List of codes for registration bodies	19
Annex C (informative) List of codes for gas cylinder manufacturers	20
Annex D (informative) Gas quantity units code	44
Annex E (informative) Host to interrogator to MODBUS communication protocol	45

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 21007-2 was prepared by Technical Committee ISO/TC 58, *Gas cylinders*, Subcommittee SC 4, *Operational requirements for cylinders*.

This second edition cancels and replaces the first edition (ISO 21007-2:2005), Annex C of which has been technically revised.

ISO 21007 consists of the following parts, under the general title *Gas cylinders — Identification and marking using radio frequency identification technology*:

- *Part 1: Reference architecture and terminology*
- *Part 2: Numbering schemes for radio frequency identification*

Introduction

Throughout industry and in commerce, trade and the domestic sector, the employment of gas cylinders (referred to as GC in this part of ISO 21007) to enable the local consumption and use of gases and liquids, without the need for in-situ high cost permanent pressure vessel installations, is an important part of modern practice.

Such cylinders may provide complex gas mixes for medical, industrial or research use.

As the cylinders may contain a wide variety of gases, identification is of paramount importance. It is mandatory to be able to uniquely identify each cylinder. As many contents are of limited life, and for product quality and liability tracking and tracing, in some circumstances it may be necessary or desirable to identify not only the type of gas or liquid, but also such details as filling station, batch and date of fill.

Various methods and technologies such as physical identification through indentation; paper, card, metal, and plastic labeling; colour code identification; bar coding and, in some circumstances, vision systems are already used to make or assist such identifications.

The technology of radio frequency identification (RFID) involves a reader/interrogator station that transmits a predetermined signal of inductive, radio or microwave energy to one or many transponders located within a read zone. The transponder returns the signal in a modified form to the reader/interrogator and the data is decoded. The data component in a portable gas or liquid cylinder environment provides the basis for unambiguous identification of the transponder and may also provide a medium for a bi-directional interactive exchange of data between the host and transponder. The signal may be modulated or unmodulated according to architecture of the system.

In many cases it will be necessary or desirable to use one air carrier frequency and protocol, but this will not always be possible or even desirable in all situations, and it may be useful to separate fundamentally different cylinders by the response frequency.

However, there is benefit in using a standard common core data structure that is capable of upwards integration and expandable from the simplest low cost cylinder identification system to more complex functions. Such a structure will have to be flexible and enabling rather than prescriptive, thus enabling different systems degrees of interoperability within and between their host systems.

The use of Abstract Syntax Notation One (ASN.1, as defined in the ISO/IEC 8824 series) from ISO/IEC 8824-1 as a notation to specify data and its associated Packed Encoding Rules (PER) from ISO/IEC 8825-2 is widely used and gaining popularity. Its usage will provide maximum interoperability and conformance to existing standards and will meet the specifically defined requirements for a generic standard model for portable gas cylinder identification in that it

- enables and uses existing standard coding,
- is adaptable and expandable,
- does not include unnecessary information for a specific application, and
- has a minimum of overhead in storage and transmission.

ISO 21007-1 provides a framework reference architecture for such systems. This supporting Part 2 provides a standardized yet flexible and interoperable framework for numbering schemes. This part of ISO 21007 details individual numbering schemes within the framework for the automatic identification of gas cylinders.

ISO/DIS 21007-2

Central to the effective use of many of the constructs is a structure to provide unambiguous identification. This part of ISO 21007 provides a standardized data element construct for the automatic identification of gas cylinders.

DRAFT 2011

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN ISO 21007-2:2013](https://standards.iteh.ai/catalog/standards/sist/2b52b385-6236-4146-8e67-10dd47fd677/sist-en-iso-21007-2-2013)
<https://standards.iteh.ai/catalog/standards/sist/2b52b385-6236-4146-8e67-10dd47fd677/sist-en-iso-21007-2-2013>

Gas cylinders — Identification and marking using radio frequency identification technology — Part 2: Numbering schemes for radio frequency identification

1 Scope

This part of ISO 21007 establishes a common framework for data structure to enable the unambiguous identification in gas cylinder (GC) applications and for other common data elements in this sector.

This part of ISO 21007 enables a structure to allow some harmonization between different systems. However, it does not prescribe any one system and has been written in a non-mandatory style so as not to make it obsolete as technology changes.

The main body of this part of ISO 21007 excludes any data elements that form any part of transmission or storage protocols such as headers and checksums.

For details of cylinder/tag operations see Annex A.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3166-1, *Codes for the representation of names of countries and their subdivisions — Part 1: Country codes*

ISO 13769, *Gas cylinders — Stamp marking*

ISO 21007-1, *Gas cylinders — identification and marking using radio frequency identification technology — Part 1: Reference architecture and terminology*¹⁾

ISO/IEC 8824-1:2002, *Information technology — Abstract Syntax Notation One (ASN.1): Specification of basic notation*

ISO/IEC 8825-2:2002, *Information technology — ASN.1 encoding rules: Specification of Packed Encoding Rules (PER)*

3 Terms, definitions and numerical notations

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 21007-1 and the following apply.

3.1.1

bit rates

number of bits per second, independent of the data coding

1) To be published.

ISO/DIS 21007-2**3.1.2****carrier frequency**

centre frequency of the downlink/uplink band

3.1.3**construct**

one or more primitive constructs to form an ASN.1 message

3.1.4**data coding**

coding that determines the baseband signal presentation i.e., a mapping of logical bits to physical signals

NOTE Examples are bi-phase schemes (Manchester, Miller, FM0, FM1, differential Manchester), NRZ and NRZ1.

3.1.5**modulation**

keying of the carrier wave by coded data described in accordance with commonly understood methodologies (amplitude shift keying, frequency shift keying)

3.1.6**octet**

set of eight binary digits (bits)

3.1.7**power limits within communication zone**

limits that determine the minimum and maximum values of incident power referred to a 0 dB antenna in front of the tag

NOTE These two values also specify the dynamic range of the tag receiver. Power values are measured without any additional losses due to rain or misalignment.

3.1.8**registration body**

organization entitled to issue and keep track of issuer identification

NOTE For examples, see Annex A.

3.1.9**tolerance of carrier frequency**

maximum deviation of the carrier frequency expressed as a percentage

3.2 Numerical notations

The numerical notations used in this part of ISO 21007 are as follows:

- Decimal (“normal”) notation has no subscript, e.g. 127;
- Hexadecimal numbers are noted by subscript 16, e.g. 7F₁₆;
- Binary numbers are noted by subscript 2, e.g. 01111111₂.

4 Data presentation**4.1 General requirements**

The data element construct determined in this part of ISO 21007 is an “enabling” structure. It is designed to accommodate within its framework, data element constructs for a variety of GC applications, from simple GC identification to more complex transactions with a wide variety of uses, and to allow combinations of data elements to be used in a composite data construct. It is designed to allow as much interoperability of the data

elements within an electronic data interchange/electronic data transfer (EDI/EDT) environment as is possible and has to provide a capability for a significant expansion of the number of GC applications in the future.

This part of ISO 21007 takes cognizance of and accommodates the operation of systems of different capabilities and will enable within its structure the interoperability of one transponder in any country, even though the operator systems themselves may be significantly different, so long as there is a common air interface (at reference point Delta) and protocol. Even where information has to be collected by a separate interrogator because air carrier compatibility does not exist, the data once collected is in a commonly interoperable format and so may be used accurately and effectively within an EDI/EDT environment.

The data element structure defined in this part of ISO 21007 specifies the general presentation rules for transfer of ASN.1 data schemes. It is also the purpose of this part of ISO 21007 to determine how ASN.1 will be used for data transmission in GC applications.

Excluding transfers in a predefined context, the first level of identification required in ASN.1 messages identifies the context of the message. This part of ISO 21007 determines that in GC applications this is achieved by using an object identifier that shall be determined in accordance with an arc determined in Annex B of ISO/IEC 8824-1.

The objective of this part of ISO 21007 is therefore to establish a basis where the message can always be identified simply by reference to the relevant standard and without the requirement of central registration authorities (except where those are specifically required in the referred to document).

4.2 ASN.1 messages

Where there is a simple message where no further subdivision according to ASN.1 rules is possible, the message is called an ASN.1 "primitive message". Such messages will have only one identification and length statement. The GC identification structure defined in Clause 3 of ISO 21007-1:—²⁾ is an ASN.1 primitive message.

4.3 Message identification requirements

The data constructs shall conform to ISO/IEC 8824-1.

With the exception of transfers in a predetermined context (see 4.4):

- All GC standard ASN.1 messages shall commence with a unique object identifier that shall be determined in accordance with the arc 2 (joint ITU-T), followed by the object class indicating a standard arc 0, followed by the reference to the standard:

```
{ITU-T}(2) standard(0) standardxxx(yyy) }
```

- Where the data content relates to standards produced by other identified organizations, they shall commence with a unique object identifier that shall be determined in accordance with the arc 2 (joint ITU-T) followed by the identification of an identified organization arc 3, followed by the identification of the identified organization (as provided in Annex B), followed by the object class indicating a standard arc 0, followed by the reference to the standard:

```
{ ITU-T.(2) identified-organization (3) organization-identity(xxx) standard(0) standardxxx(zzz) }
```

4.4 Predetermined context and the use of packed encoding rules

Where the context of a transfer is known, the data constructs determined in this part of ISO 21007 may be assumed to be in accordance with the rules determined in ISO/IEC 8825-2.

In respect of any identification of an item using an ISO ASN.1 message, the data necessary for unambiguous identification shall reside on the on-board equipment associated with the item being identified.

2) To be published.