



# SLOVENSKI STANDARD

## SIST ISO 12233:2011

01-julij-2011

---

### Fotografija - Digitalne kamere za mirujoče slike - Merjenje ločljivosti

Photography - Electronic still-picture cameras - Resolution measurements

Photographie - Appareils de prises de vue électroniques - Mesurages de la résolution

Ta slovenski standard je istoveten z: **ISO 12233:2000**

[SIST ISO 12233:2011](https://standards.iteh.ai/catalog/standards/sist/9bde1d8c-d0ca-49eb-ad08-aca8817ab369/sist-iso-12233-2011)

<https://standards.iteh.ai/catalog/standards/sist/9bde1d8c-d0ca-49eb-ad08-aca8817ab369/sist-iso-12233-2011>

#### **ICS:**

37.040.10	Fotografska oprema. Projektorji	Photographic equipment. Projectors
-----------	------------------------------------	---------------------------------------

**SIST ISO 12233:2011**

**en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 12233:2011](#)

<https://standards.iteh.ai/catalog/standards/sist/9bde1d8c-d0ca-49eb-ad08-aca8817ab369/sist-iso-12233-2011>

INTERNATIONAL  
STANDARD

ISO  
12233

First edition  
2000-09-01

---

---

**Photography — Electronic still-picture  
cameras — Resolution measurements**

*Photographie — Appareils de prises de vue électroniques — Mesurages  
de la résolution*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 12233:2011](https://standards.iteh.ai/catalog/standards/sist/9bde1d8c-d0ca-49eb-ad08-aca8817ab369/sist-iso-12233-2011)

<https://standards.iteh.ai/catalog/standards/sist/9bde1d8c-d0ca-49eb-ad08-aca8817ab369/sist-iso-12233-2011>



Reference number  
ISO 12233:2000(E)

© ISO 2000

**ISO 12233:2000(E)****PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 12233:2011](https://standards.iteh.ai/catalog/standards/sist/9bde1d8c-d0ca-49eb-ad08-aca8817ab369/sist-iso-12233-2011)

<https://standards.iteh.ai/catalog/standards/sist/9bde1d8c-d0ca-49eb-ad08-aca8817ab369/sist-iso-12233-2011>

© ISO 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.ch](mailto:copyright@iso.ch)  
Web [www.iso.ch](http://www.iso.ch)

Printed in Switzerland

## Contents

Page

Foreword.....	iv
<b>0 Introduction.....</b>	<b>v</b>
<b>0.1 Purpose.....</b>	<b>v</b>
<b>0.2 Technical background.....</b>	<b>v</b>
<b>1 Scope.....</b>	<b>1</b>
<b>2 Normative references.....</b>	<b>1</b>
<b>3 Terms and definitions.....</b>	<b>1</b>
<b>4 Test chart.....</b>	<b>5</b>
<b>4.1 Introduction.....</b>	<b>5</b>
<b>4.2 Material.....</b>	<b>6</b>
<b>4.3 Size.....</b>	<b>6</b>
<b>4.4 Test patterns.....</b>	<b>6</b>
<b>4.5 Test-pattern modulation.....</b>	<b>6</b>
<b>4.6 Units.....</b>	<b>6</b>
<b>4.7 Features.....</b>	<b>6</b>
<b>4.8 Positional tolerance.....</b>	<b>6</b>
<b>5 Test conditions.....</b>	<b>10</b>
<b>5.1 Test-chart illumination.....</b>	<b>10</b>
<b>5.2 Camera framing and lens focal-length setting.....</b>	<b>10</b>
<b>5.3 Camera focusing.....</b>	<b>10</b>
<b>5.4 Camera settings.....</b>	<b>10</b>
<b>5.5 White balance.....</b>	<b>11</b>
<b>5.6 Luminance and colour measurements.....</b>	<b>11</b>
<b>5.7 Gamma correction.....</b>	<b>11</b>
<b>6 Test measurements.....</b>	<b>11</b>
<b>6.1 Visual resolution.....</b>	<b>11</b>
<b>6.2 Limiting resolution.....</b>	<b>12</b>
<b>6.3 Spatial frequency response.....</b>	<b>12</b>
<b>6.4 Aliasing ratio.....</b>	<b>15</b>
<b>7 Presentation of results.....</b>	<b>15</b>
<b>7.1 Introduction.....</b>	<b>15</b>
<b>7.2 Visual resolution.....</b>	<b>15</b>
<b>7.3 Limiting resolution.....</b>	<b>15</b>
<b>7.4 Spatial frequency response (SFR).....</b>	<b>15</b>
<b>7.5 Aliasing ratio.....</b>	<b>16</b>
<b>Annex A (informative) SFR measurement algorithm C-code.....</b>	<b>17</b>
<b>Annex B (informative) Test-chart dimensions.....</b>	<b>28</b>
<b>Annex C (normative) Spatial frequency response (SFR) algorithm.....</b>	<b>29</b>
<b>Annex D (informative) Relationships between resolution metrics.....</b>	<b>31</b>
<b>Bibliography.....</b>	<b>32</b>

**ISO 12233:2000(E)****Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 12233 was prepared by Technical Committee ISO/TC 42, *Photography*.

Annex C forms a normative part of this International Standard. Annexes A, B and D are for information only.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 12233:2011](https://standards.iteh.ai/catalog/standards/sist/9bde1d8c-d0ca-49eb-ad08-aca8817ab369/sist-iso-12233-2011)

<https://standards.iteh.ai/catalog/standards/sist/9bde1d8c-d0ca-49eb-ad08-aca8817ab369/sist-iso-12233-2011>

## 0 Introduction

### 0.1 Purpose

The spatial resolution capability is an important attribute of an electronic still-picture camera. Resolution measurement standards allow users to compare and verify spatial resolution measurements. This International Standard defines terminology, test charts and test methods for performing resolution measurements for analog and digital electronic still-picture cameras.

### 0.2 Technical background

One of the most important characteristics of an electronic still-picture camera is the ability of the camera to capture fine detail found in the original scene. This ability to resolve detail is determined by a number of factors, including the performance of the camera lens, the number of addressable photoelements in the optical imaging device, and the electrical circuits in the camera, which may include image compression and gamma correction functions. Different measurement methods can provide different metrics to quantify the resolution of an imaging system, or a component of an imaging system, such as a lens. Resolution measurement metrics include resolving power, limiting resolution (at some specified contrast), spatial frequency response, MTF and OTF.

The first step in measuring resolution is to capture an image of a suitable test chart with the camera under test. The test chart should include patterns with sufficiently fine detail, such as edges, lines, square waves, or sine wave patterns. The test chart defined in this International Standard has been designed specifically to evaluate electronic still-picture cameras. It has not been designed to evaluate other electronic imaging equipment such as input scanners, CRT displays, hard-copy printers, or electrophotographic copiers, nor individual components of an electronic still-picture camera, such as the lens.

<https://standards.iteh.ai/catalog/standards/sist/9bde1d8c-d0ca-49eb-ad08->

The resolution measurements described in this International Standard are performed in the digital domain, using digital analysis techniques. For electronic still-picture cameras that include only analog outputs, the analog signal needs to be digitized, so that the digital measurement can be performed. The digitizing equipment is characterized, so that the effects of the digitization process can be removed from the measurement results. When this is not possible, the type of digitizing equipment used shall be reported along with the measurement results.

The spatial frequency response (SFR) measurement method described in this International Standard uses a computer algorithm to analyse digital image data from the electronic still-picture camera. Digitized image values near slanted vertical and horizontal black to white edges are digitized and used to compute the SFR values. The use of a slanted edge allows the edge gradient to be measured at many phases relative to the image sensor photoelements, in order to eliminate the effects of aliasing. This technique is mathematically equivalent to performing a moving knife edge measurement.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 12233:2011](#)

<https://standards.iteh.ai/catalog/standards/sist/9bde1d8c-d0ca-49eb-ad08-aca8817ab369/sist-iso-12233-2011>



# Photography — Electronic still-picture cameras — Resolution measurements

## 1 Scope

This International Standard specifies methods for measuring the resolution of electronic still-picture cameras. It is applicable to the measurement of both monochrome and colour cameras which output digital data or analog video signals.

## 2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 7589:1984, *Photography — Illuminants for sensitometry — Specifications for daylight and incandescent tungsten.*

ISO 14524:1999, *Photography — Electronic still-picture cameras — Methods for measuring opto-electronic conversion functions (OECFs).*

## 3 Terms and definitions

For the purposes of this International Standard, the following terms and definitions apply.

### 3.1

#### **addressable photoelements**

number of active photoelements in an image, which is equal to the number of active lines of photoelements multiplied by the number of active photoelements per line

**NOTE** It is possible that the number of addressable photoelements may be different for the different colour records of an image. When the signal values of the photoelements are digitized, the digitized code values may be referred to as picture elements, or pixels.

### 3.2

#### **aliasing**

output image artifacts that occur in a sampled imaging system for input images having significant energy at frequencies higher than the Nyquist frequency of the system

### 3.3

#### **cycles per millimetre**

#### **cy/mm**

unit used for specifying resolution characteristics in terms of the response of an imaging system to a linear radiance sine wave input, as a function of the frequency of the sine wave

**NOTE 1** A range of input sine wave frequencies is obtained in this International Standard through the use of a sharp edged target.

**ISO 12233:2000(E)**

NOTE 2 Most pictorial imaging systems exhibit non-linear behaviour, which may result in the nature of the target affecting the measured resolution characteristics. Distance units other than millimetres may also be used.

**3.4****aliasing ratio**

value equal to the "maximum minus minimum" modulation divided by the "average" modulation of an electronic still-picture camera when imaging a frequency burst of constant spatial frequency

NOTE The aliasing ratio is described in 6.4.

**3.5****edge spread function****ESF**

normalized spatial signal distribution in the linearized output of an imaging system resulting from imaging a theoretical infinitely sharp edge

**3.6****effectively spectrally neutral**

having spectral characteristics which result in a specific imaging system producing the same output as for a spectrally neutral object

**3.7****electronic still-picture camera**

camera incorporating an image sensor that outputs an analog or digital signal representing a still-picture, or records an analog or digital signal representing a still-picture on a removable media, such as a memory card or magnetic disc

**iTeh STANDARD PREVIEW**

**3.8****gamma correction**

process that alters the image data in order to modify the tone reproduction

[SIST ISO 12233:2011](https://standards.iteh.ai/catalog/standards/sist/9bde1d8c-d0ca-49eb-ad08-aca8817ab369/sist-iso-12233-2011)

**3.9****horizontal resolution**

resolution value measured in the longer image dimension, corresponding to the horizontal direction for a "landscape" image orientation, typically using a vertically oriented test-chart feature

<https://standards.iteh.ai/catalog/standards/sist/9bde1d8c-d0ca-49eb-ad08-aca8817ab369/sist-iso-12233-2011>

**3.10****image aspect ratio**

ratio of the image width to the image height

**3.11****image compression**

process that alters the way digital image data is encoded in order to reduce the size of an image file

**3.12****image sensor**

electronic device that converts an optical image into an electronic signal; for example a charge coupled device (CCD) array

**3.13****limiting resolution**

value of that portion of a specified resolution test pattern, measured in line widths per picture height, that corresponds to an average modulation value equal to some specified percentage of the modulation value at a specified reference frequency

EXAMPLE The limiting resolution may be the test pattern value, in line widths per picture height (LW/PH), corresponding to a camera output modulation level of 5 % of the camera output modulation level at a reference frequency of 10 LW/PH.

**3.14****line pairs per millimetre****lp/mm**

metric for specifying resolution in terms of the number of equal width black and white line pairs per millimetre that can be resolved according to some criterion, such as visual resolution or limiting resolution

NOTE distance units other than millimetres may also be used.

**3.15****lines per millimetre****lines/mm**

metric for specifying resolution in terms of the number of equal-width black and white lines per millimetre that can be resolved according to some criterion, such as visual resolution or limiting resolution

NOTE Distance units other than millimetres may also be used.

**3.16****line spread function****LSF**

normalized spatial signal distribution in the linearized output of an imaging system resulting from imaging a theoretical infinitely thin line

NOTE If the imaging system is operating in an isoplanatic region and in its linear range, the LSF is equal to the first derivative of the ESF.

**3.17****line widths per picture height****LW/PH**

metric for specifying the width of a solid line on a test chart, relative to the height of the active area of the chart, which is equal to the height of the active area of the test chart divided by the width of a black line, that is equal to the total number of lines of the same width which can be placed edge to edge within the height of a test target, or within the vertical field of view of a camera

NOTE If the height of the active area of the chart equals 20 cm, a black line of 1 000 LW/PH has a width equal to 20/1 000 cm.

**3.18****linearized**

digital signal conversion performed to invert the camera opto-electronic conversion function (OECF) so that the resulting signal is approximately linearly proportional to the scene luminance

**3.19****modulation**

difference between the minimum and maximum signal levels divided by the sum of these levels

**3.20****modulation transfer function****MTF**

modulus of the optical transfer function

**3.21****normalized spatial frequency**

unit used for expressing spatial frequency response, where the distance dimension has been removed by multiplying the spatial frequency in cycles per millimetre by the sampling period in millimetres

NOTE Normalized spatial frequency is particularly appropriate for comparing the spatial frequency response of imaging systems where the rendering magnification is unknown, and the total number of samples is equal.

**3.22****Nyquist limit**

spatial frequency equal to 1/2 times the inverse of the sampling period

NOTE Energy at an input spatial frequency above the Nyquist limit will alias to a spatial frequency below the Nyquist limit in the output image. The Nyquist limit may be different in the two orthogonal directions.

**ISO 12233:2000(E)****3.23****optical transfer function****OTF**

two-dimensional Fourier transform of the imaging system's point spread function

NOTE 1 For the OTF to have significance, it is necessary that the imaging system be operating in an isoplanatic region and in its linear range.

NOTE 2 The OTF is a complex function whose modulus has unity value at zero spatial frequency.

**3.24****point spread function****PSF**

normalized spatial signal distribution in the linearized output of an imaging system resulting from imaging a theoretical infinitely small point source

**3.25****resolution**

measure of the ability of a camera system, or a component of a camera system, to depict picture detail

NOTE Resolution measurement metrics include resolving power, limiting resolution, spatial frequency response (SFR), MTF and OTF.

**3.26****sampling aspect ratio**

ratio of the sample spacing in the two orthogonal sampling directions

NOTE If the sample spacing is equal, the aspect ratio of the sampling grid is 1:1 or "square", so that the sampling aspect ratio provides "square pixels".

**3.27****sampled imaging system**

imaging system or device which generates an image signal by sampling an image at an array of discrete points, or along a set of discrete lines, rather than a continuum of points

NOTE The sampling at each point is done using a finite size sampling aperture or area.

**3.28****sample spacing**

physical distance between sampling points or sampling lines

NOTE The sample spacing may be different in the two orthogonal sampling directions.

**3.29****spatial frequency response****SFR**

measured amplitude response of an imaging system as a function of relative input spatial frequency

NOTE 1 The SFR is normally represented by a curve of the output response to an input signal of unit amplitude, over a range of spatial frequencies.

NOTE 2 The SFR is normalized to yield a value of unity at a spatial frequency of 0.

**3.30****spectrally neutral**

test chart is spectrally neutral if the relative spectral power distributions of the incident and reflected (or transmitted) light are equal

**3.31****test chart**

arrangement of test patterns designed to test particular aspects of an imaging system

**3.32****test pattern**

specified arrangement of spectral reflectance or transmittance characteristics used in measuring an image quality attribute

The test pattern spectral characteristics include the following types:

**3.32.1****bi-tonal pattern**

pattern that is spectrally neutral or effectively spectrally neutral, and consists exclusively of two reflectance or transmittance values in a prescribed spatial arrangement

NOTE Bi-tonal patterns are typically used to measure resolving power, limiting resolution and SFR.

**3.32.2****grey scale pattern**

pattern that is spectrally neutral or effectively spectrally neutral, and consists of a large number of different reflectance or transmittance values in a prescribed spatial arrangement

NOTE Grey scale patterns are typically used to measure opto-electronic conversion functions.

**3.32.3****spectral pattern**

pattern that is specified by the spatial arrangement of features with differing spectral reflectance or transmittance values

NOTE Spectral patterns are typically used to measure colour reproduction.

**3.33****vertical resolution**

resolution value measured in the shorter image dimension, corresponding to the vertical direction for a "landscape" image orientation, typically using a horizontally oriented test-chart feature

<https://standards.iteh.ai/catalog/standards/sist/9bde1d8c-d0ca-49eb-ad08-aca8817ab369/sist-iso-12233-2011>

**3.34****visual resolution**

spatial frequency at which the individual black and white lines of a test pattern reproduced on a display or print can no longer be distinguished by human observers, or are reproduced at a spatial frequency lower than the spatial frequency of the corresponding area of the test chart, as a result of aliasing

**4 Test chart****4.1 Introduction**

A reproduction of a test chart for measuring the resolution of an electronic still-picture camera is shown in Figure 1. Figure 2 is a diagram showing the locations of particular features of the test chart, which may be either a reflective or transmissive chart. The purpose of each test pattern element is listed in Table 1. A complete spreadsheet specification of the test chart is given for information in annex A.

The measurements described in clause 6 can be performed using test charts other than the chart shown in Figure 1. For example, the test patterns present in the test chart can be separated and rearranged, if required, for specific test objectives. The framing and the reproduction scale of the patterns can also be varied, if required, for specific test objectives.

The chart shown in Figure 1 is designed to measure cameras having a limiting resolution of less than 2 000 LW/PH. Nevertheless, it is possible to use the chart to measure the visual resolution or limiting resolution of an electronic still camera having a limiting resolution greater than 2 000 LW/PH. This is accomplished by adjusting the camera to target distance, or the focal length of the camera lens, so that the test-chart active area fills only a fraction of the vertical image height of the camera. This fraction is then measured in the digital image, by dividing the number of image lines in the camera image by the number of lines in the active chart area. The values of all test-chart features, in LW/PH, printed on the chart or specified in this International Standard, are multiplied by this