

SLOVENSKI STANDARD SIST EN ISO 286-2:2010

01-september-2010

Nadomešča: SIST EN 20286-2:2000 SIST EN 20286-2:2000/prA1:2008 SIST ISO 286-2:1999

Specifikacija geometrijskih veličin izdelka - Sistem ISO za tolerance dolžinskih mer - 2. del: Preglednice standardnih toleranc in mejnih odstopkov za luknje in gredi (ISO 286-2:2010)

Geometrical product specifications (GPS)-/ISQ code system for tolerances on linear sizes - Part 2: Tables of standard tolerance classes and limit deviations for holes and shafts (ISO 286-2:2010)

SIST EN ISO 286-2:2010

Geometrische Produktspezifikation (GRS) ISO-Toleranzsystem für Längenmaße - Teil 2: Tabellen der Grundtoleranzgrade und Grenzabmaße für Bohrungen und Wellen (ISO 286-2:2010)

Spécification géométrique des produits (GPS) - Système de codification ISO pour les tolérances sur les tailles linéaires - Partie 2: Tableaux des classes de tolérance normalisées et des écarts limites des alésages et des arbres (ISO 286-2:2010)

Ta slovenski standard je istoveten z: EN ISO 286-2:2010

<u>ICS:</u>

17.040.10	Tolerance in ujemi
17.040.40	Specifikacija geometrijskih veličin izdelka (GPS)

Limits and fits Geometrical Product Specification (GPS)

SIST EN ISO 286-2:2010

en,fr



iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN ISO 286-2:2010

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN ISO 286-2

June 2010

ICS 17.040.10

Supersedes EN 20286-2:1993

English Version

Geometrical product specifications (GPS) - ISO code system for tolerances on linear sizes - Part 2: Tables of standard tolerance classes and limit deviations for holes and shafts (ISO 286-2:2010)

Spécification géométrique des produits (GPS) - Système de codification ISO pour les tolérances sur les tailles linéaires - Partie 2: Tableaux des classes de tolérance normalisées et des écarts limites des alésages et des arbres (ISO 286-2:2010) Geometrische Produktspezifikation (GPS) - ISO-Toleranzsystem für Längenmaße - Teil 2: Tabellen der Grundtoleranzgrade und Grenzabmaße für Bohrungen und Wellen (ISO 286-2:2010)

This European Standard was approved by CEN on 15 May 2010.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

https://standards.iteh.ai/catalog/standards/sist/93a404c7-a493-4630-9dac-

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Oroatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

© 2010 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.

Ref. No. EN ISO 286-2:2010: E

Contents

Page

iTeh STANDARD PREVIEW (standards.iteh.ai)

Foreword

This document (EN ISO 286-2:2010) has been prepared by Technical Committee ISO/TC 213 "Dimensional and geometrical product specifications and verification" in collaboration with Technical Committee CEN/TC 290 "Dimensional and geometrical product specification and verification" the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by December 2010, and conflicting national standards shall be withdrawn at the latest by December 2010.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 20286-2:1993.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom, ARD PREVIEW



The text of ISO 286-2:2010 has been approved by CEN as a EN ISO 286-2:2010 without any modification. https://standards.iteh.avcatalog/standards/sist/93a404c7-a493-4630-9dac-8a4c27db7029/sist-en-iso-286-2-2010



iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN ISO 286-2:2010

INTERNATIONAL STANDARD

ISO 286-2

Second edition 2010-06-15

Geometrical product specifications (GPS) — ISO code system for tolerances on linear sizes —

Part 2:

Tables of standard tolerance classes and limit deviations for holes and shafts iTeh STANDARD PREVIEW

Spécification géométrique des produits (GPS) — Système de codification ISO pour les tolérances sur les tailles linéaires —

Partie 2: Tableaux des classes de tolérance normalisées et des écarts limites des alésages et des arbres https://standards.iteh.avcatalog/standards/sist/93a404c7-a493-4630-9dac-

8a4c27db7029/sist-en-iso-286-2-2010



Reference number ISO 286-2:2010(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN ISO 286-2:2010 https://standards.iteh.ai/catalog/standards/sist/93a404c7-a493-4630-9dac-8a4c27db7029/sist-en-iso-286-2-2010



COPYRIGHT PROTECTED DOCUMENT

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

Contents

Forew	ord	iv
Introdu	uction	v
1	Scope	1
2	Normative references	3
3	Standard tolerances	3
4	Limit deviations for holes	4
5	Limit deviations for shafts	4
6	Presentation of Tables 2 to 32	4
Annex	A (informative) Graphical review of tolerance intervals for holes and shafts	45
Annex	B (informative) Relationship to the GPS matrix model	50
Bibliog	graphy	52

iTeh STANDARD PREVIEW (standards.iteh.ai)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 286-2 was prepared by Technical Committee ISO/TC 213, *Dimensional and geometrical product specifications and verification.*

This second edition cancels and replaces the first edition (ISO 286-2:1988), which has been technically revised. It also incorporates the Technical Corrigendum ISO 286-2:1988/Cor.1:2006.

ISO 286 consists of the following parts, under the general title *Geometrical product specifications (GPS)* — ISO code system for tolerances on linear sizes: <u>SISTEN ISO 286-2:2010</u>

https://standards.iteh.ai/catalog/standards/sist/93a404c7-a493-4630-9dac-

— Part 1: Basis of tolerances, deviations⁸⁴⁶²7ftb^{7029/sist-en-iso-286-2-2010}

— Part 2: Tables of standard tolerance classes and limit deviations for holes and shafts

Introduction

This part of ISO 286 is a geometrical product specification (GPS) standard and is to be regarded as a general GPS standard (see ISO/TR 14638). It influences chain links 1 and 2 of the chain of standards on size in the general GPS matrix.

For more detailed information on the relationship of this part of ISO 286 to the GPS matrix model, see Annex B.

The need for limits and fits for machined workpieces was brought about mainly by the requirement for interchangeability between mass-produced parts and the inherent inaccuracy of manufacturing methods, coupled with the fact that "exactness" of size was found to be unnecessary for most workpiece features. In order that the fit function could be satisfied, it was found sufficient to manufacture a given workpiece so that its size lay within two permissible limits, i.e. a tolerance, this being the variation in size acceptable in manufacture while ensuring the functional fit requirements of the product.

Similarly, where a specific fit condition is required between mating features of two different workpieces, it is necessary to ascribe an allowance, either positive or negative, to the nominal size to achieve the required clearance or interference. ISO 286 gives the internationally accepted code system for tolerances on linear sizes. It provides a system of tolerances and deviations suitable for two types of feature: "cylinder" and "two parallel opposite surfaces". The main intention of this code system is the fulfilment of the function fit.

The terms "hole", "shaft" and "diameter" are used to designate the types of feature of cylinders (e.g. for the tolerancing of the diameter of a hole or shaft). For simplicity, they are also used for two parallel opposite surfaces (e.g. for the tolerancing of the thickness of a key or the width of a slot).

The pre-condition for the application of the ISO code system for tolerances on linear sizes for the features forming a fit is that the nominal sizes of the hole and the shaft are identical.

The previous edition of ISO 286-2 (published in 1988) had the envelope criterion as the default association criterion for the size of a feature; however, ISO 14405-1 changes this default association criterion to the two-point size criterion. This means that form is no longer controlled by the default specification of size.

In many cases, the diameter tolerances specified in this part of ISO 286 are not sufficient for effective control of the intended function of the fit. The envelope criterion specified in ISO 14405-1 may be required. In addition, the use of geometrical form tolerances and surface texture requirements may improve the control of the intended function.

A general graphical representation of the relationship between the respective tolerance classes and their deviations is given in Annex A.



iTeh STANDARD PREVIEW (standards.iteh.ai)

Geometrical product specifications (GPS) — ISO code system for tolerances on linear sizes —

Part 2: Tables of standard tolerance classes and limit deviations for holes and shafts

1 Scope

This part of ISO 286 gives values of the limit deviations for commonly used tolerance classes for holes and shafts calculated from the tables given in ISO 286-1. This part of ISO 286 covers values for the upper limit deviations *ES* (for holes) and *es* (for shafts), and the lower limit deviations *EI* (for holes) and *ei* (for shafts) (see Figures 1 and 2).

NOTE In the tables of limit deviations, the values of the upper limit deviation *ES* or *es* are shown above the values of the lower limit deviation *EI* or *ei* except for tolerance classes JS and js which are symmetrical about the zero line.

The ISO system for tolerances on linear size provides a system of tolerances and deviations suitable for features of the following types:

- a) cylinders; SIST EN ISO 286-2:2010 https://standards.iteh.ai/catalog/standards/sist/93a404c7-a493-4630-9dac-8a4c27db7029/sist-en-iso-286-2-2010
- b) two parallel opposite surfaces.

For simplicity, and also because of the importance of cylindrical workpieces of circular section, only these are referred to explicitly. It should be clearly understood, however, that the tolerances and deviations given in this part of ISO 286 equally apply to workpieces of other than circular sections.

In particular, the term "hole" or "shaft" is used to designate features of the cylinder type (e.g. for the tolerancing of the diameter of a hole or shaft) and, for simplicity, these terms are also used for two parallel opposite surfaces (e.g. for the tolerancing of the thickness of a key or the width of a slot).

For further information on terminology, symbols, the basis of the system, etc., see ISO 286-1.



Key

https://standards.iteh.ai/catalog/standards/sist/93a404c7-a493-4630-9dac-8a4c27db7029/sist-en-iso-286-2-2010

1 K1 to K3, and also K4 to K8 for sizes for which — < nominal size ≤ 3 mm (for the significance of the dash, see e.g. footnote "b" to Table 2)

- 2~ K4 to K8 for sizes for which 3 mm < nominal size \leqslant 500 mm
- 3 K9 to K18
- 4 M1 to M6
- 5 M9 to M18
- 6 N1 to N8
- 7 N9 to N18

Figure 1 — Upper and lower limit deviations for holes (internal features)



https://standards.iteh.ai/catalog/standards/sist/93a404c7-a493-4630-9dac-8a4c27db7029/sist-en-iso-286-2-2010

1 j5, j6

Key

- 2 k1 to k3, and k4 to k7 for sizes for which < nominal size ≤ 3 mm (for the significance of the dash, see e.g. footnote "b" to Table 2)
- 3 k4 to k7 for sizes for which 3 mm < nominal size \leqslant 500 mm
- 4 k8 to k18

Figure 2 — Upper and lower limit deviations for shafts (external features)

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 286-1:2010, Geometrical product specifications (GPS) — ISO code system for tolerances of linear sizes — Part 1: Basis of tolerances, deviations and fits

3 Standard tolerances

The values of standard tolerance grades IT01 to IT18, inclusive, are given in Table 1.