



SLOVENSKI STANDARD SIST ISO/TS 17450-2:2003

01-julij-2003

GdYWZ_UWY[Yca Yf]g_l 'j Y]]b]nXY_U!`Gd`cýb]`_cbWdh]!'&"XY.`Cgbcj bU
bU YUžgdYWZ_UWYžcdYfUcf]']b`bY[cfcj cgh]

Geometrical product specifications (GPS) -- General concepts -- Part 2: Basic tenets, specifications, operators and uncertainties

iTeh STANDARD PREVIEW

Spécification géométrique des produits (GPS) -- Concepts généraux -- Partie 2: Principes de base, spécifications, opérateurs et incertitudes

[SIST ISO/TS 17450-2:2003](https://standards.iteh.ai/catalog/standards/sist/3bd6a981-c73b-464f-a52e-810550a1506c/sist-iso-ts-17450-2-2003)

Ta slovenski standard je istoveten z: [ISO/TS 17450-2:2002](https://standards.iteh.ai/catalog/standards/sist/3bd6a981-c73b-464f-a52e-810550a1506c/sist-iso-ts-17450-2-2003)

ICS:

17.040.01	Linearne in kotne meritve na splošno	Linear and angular measurements in general
-----------	--------------------------------------	--

SIST ISO/TS 17450-2:2003

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO/TS 17450-2:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/3bd6a981-c73b-464f-a52e-8f6330af306c/sist-iso-ts-17450-2-2003>

TECHNICAL
SPECIFICATION

ISO/TS
17450-2

First edition
2002-10-15

**Geometrical product specifications
(GPS) — General concepts —**

Part 2:

**Basic tenets, specifications, operators and
uncertainties**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

*Spécification géométrique des produits (GPS) — Concepts généraux —
Partie 2: Principes de base, spécifications, opérateurs et incertitudes*

[SIST ISO/TS 17450-2:2003](https://standards.iteh.ai/catalog/standards/sist/3bd6a981-c73b-464f-a52e-8f6330af306c/sist-iso-ts-17450-2-2003)

<https://standards.iteh.ai/catalog/standards/sist/3bd6a981-c73b-464f-a52e-8f6330af306c/sist-iso-ts-17450-2-2003>



Reference number
ISO/TS 17450-2:2002(E)

© ISO 2002

ISO/TS 17450-2:2002(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO/TS 17450-2:2003](https://standards.iteh.ai/catalog/standards/sist/3bd6a981-c73b-464f-a52e-8f6330af306c/sist-iso-ts-17450-2-2003)

<https://standards.iteh.ai/catalog/standards/sist/3bd6a981-c73b-464f-a52e-8f6330af306c/sist-iso-ts-17450-2-2003>

© ISO 2002

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Contents

	Page
Foreword	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions	2
3.1 Generic term	2
3.2 Terms related to operations.....	2
3.3 Terms related to operators.....	4
3.4 Terms related to uncertainty.....	7
3.5 Terms related to specifications	10
4 Basic tenets	11
5 Impact of uncertainty on basic tenets.....	12
5.1 Impact of correlation and specification uncertainties.....	12
5.2 Impact of method and implementation uncertainties.....	12
6 Specification process	13
7 Verification process	13
Annex A (informative) Concept diagram	14
Annex B (informative) Drawing indications.....	15
Annex C (informative) Relationship to the GPS matrix model.....	16
Bibliography.....	17

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO/TS 17450-2:2003](https://standards.iteh.ai/catalog/standards/sist/3bd6a981-c73b-464f-a52e-8f6330af306c/sist-iso-ts-17450-2-2003)

<https://standards.iteh.ai/catalog/standards/sist/3bd6a981-c73b-464f-a52e-8f6330af306c/sist-iso-ts-17450-2-2003>

ISO/TS 17450-2:2002(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In other circumstances, particularly when there is an urgent market requirement for such documents, a technical committee may decide to publish other types of normative document:

- an ISO Publicly Available Specification (ISO/PAS) represents an agreement between technical experts in an ISO working group and is accepted for publication if it is approved by more than 50 % of the members of the parent committee casting a vote;
- an ISO Technical Specification (ISO/TS) represents an agreement between the members of a technical committee and is accepted for publication if it is approved by 2/3 of the members of the committee casting a vote.

An ISO/PAS or ISO/TS is reviewed after three years with a view to deciding whether it should be confirmed for a further three years, revised to become an International Standard, or withdrawn. In the case of a confirmed ISO/PAS or ISO/TS, it is reviewed again after six years at which time it has to be either transposed into an International Standard or withdrawn.

Attention is drawn to the possibility that some of the elements of this part of ISO/TS 17450 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/TS 17450-2 was prepared by Technical Committee ISO/TC 213, *Dimensional and geometrical product specifications and verification*.

ISO/TS 17450 consists of the following parts, under the general title *Geometrical product specifications (GPS) — General concepts*:

- *Part 1: Model for geometric specification and verification*
- *Part 2: Basic tenets, specifications, operators and uncertainties*

Annexes A, B and C of this part of ISO/TS 17450 are for information only.

Introduction

This part of ISO/TS 17450 is a geometrical product specification (GPS) document and is to be regarded as a global GPS document (see ISO/TR 14638). It influences all chain links of the chains of standards.

For more detailed information on the relationship of this part of ISO/TS 17450 to other standards and to the GPS matrix model, see annex C.

This part of ISO/TS 17450 covers several fundamental issues common to all the GPS standards developed by ISO/TC 213 and, by presenting GPS's basic tenets and specification and verification processes, explains some of the underlying ideas and indicates the starting point for the standards developed by this technical committee.

It must be pointed out that these ideas — and, for that matter, all the other ideas and concepts applied by ISO/TC 213 — are subject to development and refinement, as the TC's recognition and understanding of them further evolves during its ongoing standards work.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO/TS 17450-2:2003](https://standards.iteh.ai/catalog/standards/sist/3bd6a981-c73b-464f-a52e-8f6330af306c/sist-iso-ts-17450-2-2003)

<https://standards.iteh.ai/catalog/standards/sist/3bd6a981-c73b-464f-a52e-8f6330af306c/sist-iso-ts-17450-2-2003>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO/TS 17450-2:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/3bd6a981-c73b-464f-a52e-8f6330af306c/sist-iso-ts-17450-2-2003>

Geometrical product specifications (GPS) — General concepts —

Part 2:

Basic tenets, specifications, operators and uncertainties

1 Scope

This part of ISO/TS 17450 defines terms related to specifications, operators (and operations) and uncertainties used in geometrical product specifications (GPS) standards, presents the basic tenets of the GPS philosophy while discussing the impact of uncertainty on those tenets, and examines the processes of specification and verification as they apply to GPS.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO/TS 17450. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO/TS 17450 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO/TS 14253-2:1999, *Geometrical Product Specifications (GPS) — Inspection by measurement of workpieces and measuring equipment — Part 2: Guide to the estimation of uncertainty in GPS measurement, in calibration of measuring equipment and in product verification*

ISO 14660-1:1999, *Geometrical Product Specifications (GPS) — Geometrical features — Part 1: General terms and definitions*

ISO 14978:—¹⁾, *Geometrical Product Specifications (GPS) — General concepts and requirements for GPS measurement equipment*

ISO/TS 17450-1:2001, *Geometrical product specifications (GPS) — General concepts — Part 2: Model for geometric specification and verification*

Guide to the Expression of Uncertainty in Measurement (GUM). BIPM, IEC, IFCC, ISO, IUPAC, IUPAP, OIML, 1st edition, 1993, corrected and reprinted, 1995

International Vocabulary of Basic and General Terms in Metrology (VIM). BIPM, IEC, IFCC, ISO, IUPAC, IUPAP, OIML, 2nd edition, 1993

1) To be published.

ISO/TS 17450-2:2002(E)

3 Terms and definitions

For the purposes of this part of ISO/TS 17450, the terms and definitions given in ISO/TS 14253-2, ISO 14660-1, ISO 14978, ISO/TS 17450-1, GUM, VIM and the following apply. See annex A, Figure A.1, for a concept diagram giving an overview of the relationships between these terms, which it is recommended be read first.

3.1 Generic term

3.1.1

metrological characteristic deviation

deviation from a ideal metrological characteristic value

See ISO/TS 17450-1.

NOTE The metrological characteristic deviation of measuring equipment includes those originating from scales, guideways, software, magnification, non-stiffness of the equipment, etc.

3.2 Terms related to operations

3.2.1

specification operation

operation formulated using only mathematical or geometrical expressions or algorithms, or all these

NOTE 1 Specification operations are used in the geometrical field of mechanical engineering to specify a requirement to a product as part of a **specification operator** (3.3.3).

NOTE 2 Specification operation is a theoretical concept.

EXAMPLE 1 The association of a minimum circumscribed cylinder in the specification of the diameter of a shaft.

EXAMPLE 2 The filtration by a Gaussian filter in the specification of surface texture.

3.2.2

default specification operation

specification operation (3.2.1) required by standards, regulations etc. when the ISO **basic GPS specification** (3.5.4) is used without modifiers in the **actual GPS specification** (3.5.6)

NOTE 1 The default specification operation may be a global default (ISO default), company default or drawing default specification operation.

EXAMPLE 1 The evaluation of a two-point diameter in the specification of the diameter of a shaft using the default indication $\varnothing 30 \pm 0,1$.

EXAMPLE 2 The filtration by a Gaussian filter (default filter) with the default cut-off length given by the default rules in ISO 4288 in the specification of R_a for a surface.

3.2.3

special specification operation

specification operation (3.2.1) specifically required when the ISO **basic GPS specification** (3.5.4) is used with modifiers, thus overriding a **default specification operation** (3.2.2)

NOTE A special specification is a non-default specification.

EXAMPLE 1 The association of a minimum circumscribed cylinder in the specification of the diameter of a shaft, when the modifier symbol, \textcircled{E} , for envelope, is used (see ISO 14405).

EXAMPLE 2 The filtration by a Gaussian filter (default filter) with a special cut-off length of 2,5 mm in the specification of R_a for a surface, when the appropriate indication is used to override the default rules in ISO 4288.

3.2.4**actual specification operation**

specification operation (3.2.1) indicated implicitly or explicitly in the technical product documentation at hand

NOTE An actual specification operation can be

- indicated implicitly by an ISO **basic GPS specification** (3.5.5),
- indicated explicitly by a **GPS specification element** (3.5.1),
- missing.

EXAMPLE 1 The evaluation of a two-point default diameter in an actual specification operation, such as when the specification $\varnothing 30 \pm 0,1$ is used (see ISO 14405).

EXAMPLE 2 The filtration by a Gaussian filter (default filter) with a special cut-off length of 2,5 mm and the calculation by the R_a algorithm are two actual specification operations, when the specification indicates $R_a 1,5$ using a 2,5 mm filter.

3.2.5**verification operation**

operation implemented in a measurement or measurement apparatus, or both, of the corresponding **actual specification operation** (3.2.4)

NOTE Verification operations are used in the geometrical field of mechanical engineering to verify a product to the corresponding **specification operation** (3.2.1).

EXAMPLE 1 The evaluation of a two-point diameter when verifying the diameter of a shaft — using a micrometer, for instance.

EXAMPLE 2 The extraction of data points from a surface for surface finish verification using a nominal stylus tip radius of 2 μm and a sample spacing of 0,5 μm .

3.2.6**perfect verification operation**

verification operation (3.2.5) with no intentional deviations from the corresponding **actual specification operation** (3.2.4)

NOTE 1 The only measurement uncertainty contributions from a perfect verification operation are from **metrological characteristic deviation(s)** (3.1.1) in the implementation of the operation.

NOTE 2 The purpose of calibration is generally to evaluate the magnitude of these measurement uncertainty contributors originating from the measuring equipment.

EXAMPLE The extraction of data points from a surface using a nominal stylus tip radius of 2 μm and a sample spacing of 0,5 μm during the verification of the surface finish, when this is the extraction operation indicated in the specification.

3.2.7**simplified verification operation**

verification operation (3.2.5) with intentional deviations from the corresponding **actual specification operation** (3.2.4)

NOTE These intentional deviations cause measurement uncertainty contributions in addition to the measurement uncertainty contributions from the **metrological characteristic deviation(s)** (3.1.1) in the implementation of the operation.

EXAMPLE The association of a two-point diameter in the verification of the size of a shaft — using a micrometer, for instance — when the specification indicates that the minimum circumscribed cylinder association is to be used.

3.2.8**actual verification operation**

verification operation (3.2.5) used in the actual measurement process