

transforme

ISO

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION

ISO RECOMMENDATION

R 2150

CONTINUOUS MECHANICAL HANDLING EQUIPMENT FOR UNIT LOADS

OVERHEAD TWIN RAIL CHAIN CONVEYORS (POWER AND FREE)

SAFETY CODE

1st EDITION

November 1971

COPYRIGHT RESERVED

The copyright of ISO Recommendations and ISO Standards belongs to ISO Member Bodies. Reproduction of these documents, in any country, may be authorized therefore only by the national standards organization of that country, being a member of ISO.

For each individual country the only valid standard is the national standard of that country.

Printed in Switzerland

Also issued in French and Russian. Copies to be obtained through the national standards organizations.

BRIEF HISTORY

The ISO Recommendation R 2150, *Continuous mechanical handling equipment for unit loads – Overhead twin rail chain conveyors (power and free) – Safety code*, was drawn up by Technical Committee ISO/TC 101, *Continuous mechanical handling equipment*, the Secretariat of which is held by the Association Française de Normalisation (AFNOR).

Work on this question led to the adoption of Draft ISO Recommendation No. 2150, which was circulated to all the ISO Member Bodies for enquiry in October 1970.

The Draft has been approved, subject to a few modifications of an editorial nature, by the following Member Bodies :

Australia	Japan	Thailand
Austria	Korea, Rep. of	U.A.R.
Belgium	Netherlands	United Kingdom
Czechoslovakia	New Zealand	U.S.A.
France	South Africa, Rep. of	U.S.S.R.
Germany	Spain	
India	Sweden	

No Member Body opposed the approval of the Draft .

This Draft ISO Recommendation was then submitted by correspondence to the ISO Council, which decided to accept it as an ISO RECOMMENDATION.

ISO Recommendation

R 2150

November 1971

CONTINUOUS MECHANICAL HANDLING EQUIPMENT FOR UNIT LOADS

OVERHEAD TWIN RAIL CHAIN CONVEYORS (POWER AND FREE)

SAFETY CODE

1. SCOPE

This ISO Recommendation specifies, in addition to the general safety rules set out in ISO Recommendation R 1819, *Continuous mechanical handling equipment – Safety code – General rules*, the special safety rules for the following continuous mechanical handling equipment for unit loads : overhead twin rail chain conveyors (power and free).

2. FIELD OF APPLICATION

The safety rules laid down in this ISO Recommendation apply regardless of the use for which the equipment is intended.

These safety rules limit the supplier's responsibility to continuous mechanical handling equipment proper, excluding the structures to which such equipment is affixed.

3. SPECIAL SAFETY RULES

The construction and operation for overhead twin rail chain conveyors (power and free), should meet :

- the legal and local requirements relating to safety in general*,
- the principles laid down in section 1 of ISO Recommendation R 1819,
- the general rules laid down in section 2 of ISO Recommendation R 1819,
- the following special rules :

3.1 In the construction stage (design and manufacture)

3.1.1 All traction mechanism drives (main sections and branch lines) should be equipped with load limiters (with or without motor cut-out), i.e. independently of the thermal cut-out devices of the electrical switchgear.

If several drives operate in one group, the entire group should be cut out when the load limiter of one drive responds.

3.1.2 Load carriers, hangers and load traversing gear must be connected to each other and to the pusher equipment in such a way that they cannot become detached by themselves.

* See Appendix Z of ISO Recommendation R 1819.