



SLOVENSKI STANDARD
SIST ISO 11271:2006

01-september-2006

U_cj cghHJ`È'8 c`c Yj Ub^fYXc_g'dchYbWUUE`HYfYbg_Ua YrcXU

Soil quality -- Determination of redox potential -- Field method

iTeh STANDARD PREVIEW

Qualité du sol -- Détermination du potentiel d'oxydoréduction -- Méthode de terrain
(standards.iTeh.si)

Ta slovenski standard je istoveten z: ISO 11271:2002

SIST ISO 11271:2006
<https://standards.iTeh.si/catalog/standards/sist/1ae1c0d5-85dc-4727-8352-0fb1beb824025/sist-iso-11271-2006>

ICS:

13.080.20 Fizikalne lastnosti tal Physical properties of soils

SIST ISO 11271:2006 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 11271:2006

<https://standards.iteh.ai/catalog/standards/sist/1ae1c0d3-85dc-4727-8352-0f1beb824025/sist-iso-11271-2006>

INTERNATIONAL
STANDARD

ISO
11271

First edition
2002-10-01

**Soil quality — Determination of redox
potential — Field method**

*Qualité du sol — Détermination du potentiel d'oxydoréduction — Méthode
de terrain*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 11271:2006](https://standards.iteh.ai/catalog/standards/sist/1ae1c0d3-85dc-4727-8352-0f1beb824025/sist-iso-11271-2006)

[https://standards.iteh.ai/catalog/standards/sist/1ae1c0d3-85dc-4727-8352-
0f1beb824025/sist-iso-11271-2006](https://standards.iteh.ai/catalog/standards/sist/1ae1c0d3-85dc-4727-8352-0f1beb824025/sist-iso-11271-2006)



Reference number
ISO 11271:2002(E)

© ISO 2002

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 11271:2006](https://standards.iteh.ai/catalog/standards/sist/1ae1c0d3-85dc-4727-8352-0fb824025/sist-iso-11271-2006)

<https://standards.iteh.ai/catalog/standards/sist/1ae1c0d3-85dc-4727-8352-0fb824025/sist-iso-11271-2006>

© ISO 2002

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Contents

	Page
1 Scope	1
2 Normative reference	1
3 Term and definition	1
4 Principle	1
5 Apparatus	2
6 Reagents	3
7 Site selection and sampling	3
8 Procedure	3
9 Evaluation	4
10 Expression of results	4
11 Test report	4

Annexes

A Description of the construction of redox electrodes, of the salt bridge, and their arrangement during measurement	5
B Potentials of platinum electrodes in different solutions	9
C Potentials of reference electrodes	10
D Soil moisture status.....	11
Bibliography.....	12

ISO 11271:2002(E)**Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 11271 was prepared by Technical Committee ISO/TC 190, *Soil quality*, Subcommittee SC 3, *Chemical methods and soil characteristics*.

Annexes A, B, C and D of this International Standard are for information only.

ITEH STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 11271:2006](https://standards.iteh.ai/catalog/standards/sist/1ae1c0d3-85dc-4727-8352-0f1beb824025/sist-iso-11271-2006)

<https://standards.iteh.ai/catalog/standards/sist/1ae1c0d3-85dc-4727-8352-0f1beb824025/sist-iso-11271-2006>

Introduction

The redox potential is a physicochemical parameter used to characterize soil aeration status in a global way. Under field conditions, it gives information on the condition of oxidation or reduction of those compounds which, depending on the case, play an important part in plant nutrition, can induce toxicity phenomena or intervene in gas transfer to the atmosphere (greenhouse effect). It can also be used to a certain extent to follow soil performances in case of sludge disposal or composting, and to adjust applications accordingly. Under laboratory conditions, it can be used in order to study oxygen diffusion phenomena to aggregate level.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 11271:2006](https://standards.iteh.ai/catalog/standards/sist/1ae1c0d3-85dc-4727-8352-0f1beb824025/sist-iso-11271-2006)

<https://standards.iteh.ai/catalog/standards/sist/1ae1c0d3-85dc-4727-8352-0f1beb824025/sist-iso-11271-2006>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 11271:2006

<https://standards.iteh.ai/catalog/standards/sist/1ae1c0d3-85dc-4727-8352-0fb824025/sist-iso-11271-2006>

Soil quality — Determination of redox potential — Field method

1 Scope

This International Standard specifies a field method for the determination of soil redox potential (E_h).

NOTE The electrochemical measurement of redox potential described here is possible only if the relevant soil horizon has a moisture status defined as fresh or wetter according to the classes presented in annex D.

2 Normative reference

The following normative document contains provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, this publication do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the normative document indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 3696:1987, *Water for analytical laboratory use — Specification and test methods*

3 Term and definition

For the purposes of this International Standard, the following term and definition apply.

3.1


redox potential

E_h

electrochemical potential reflecting the oxidation-reduction status of a liquid chemical system (in this case of the soil solution)

4 Principle

Redox potential is an electrochemical equivalent of the free energy of redox reactions, and for an equilibrated single redox system of the general form:



is given by the Nernst equation:

$$E_h = E^0 + \frac{RT}{nF} \ln \frac{A_{\text{ox}}}{A_{\text{red}}} - \frac{2,303mRT}{nF} \text{pH} \quad (2)$$

where

A_{ox} and A_{red} are the activities of the oxidized and reduced forms of the element, respectively;

e^- refers to the electron(s) involved in the reaction;

H^+ refers to the proton(s) involved in the reaction;

ISO 11271:2002(E)

n and m	are the numbers of electrons and protons involved in the reaction, respectively;
E^0	is the standard value of the potential, i.e. when $A_{\text{ox}} = A_{\text{red}}$ and $\text{pH} = 0$;
R	is the universal gas constant ($8,314 \text{ J} \cdot \text{mol}^{-1} \cdot \text{K}^{-1}$);
T	is the absolute temperature;
F	is the Faraday constant ($96 \text{ 500 C} \cdot \text{mol}^{-1}$);
2,303	is the natural log of 10.

Redox potential is related to electron activity (e^-) in the system as follows:

$$E_h = - \frac{RT}{F} \ln(e^-) \quad (3)$$

NOTE Users of this International Standard unfamiliar with these electrochemical concepts should consult appropriate texts, or seek professional advice.

The electrometric determination of redox potential is analogous to the determination of pH. The determination of E_h follows the principle of measuring potential differences between an inert measuring electrode (usually a platinum electrode), i.e. an electrode not reacting with the solution *per se*, with respect to the standard hydrogen electrode used as the reference electrode. Many redox systems are involved in the soil solution, and the resulting potential is a mixed potential depending on the existing electroactive redox couples. For practical reasons, a silver-silver chloride electrode is usually used as the reference electrode, the potential of which is added to the measured potential difference (see annex C) in order to obtain the values expressed on the basis of the standard hydrogen electrode.

5 Apparatus

SIST ISO 11271:2006

[https://standards.iteh.ai/catalog/standards/sist/1ae1c0d3-85dc-4727-8352-](https://standards.iteh.ai/catalog/standards/sist/1ae1c0d3-85dc-4727-8352-0f1beb824025/sist-iso-11271-2006)

[0f1beb824025/sist-iso-11271-2006](https://standards.iteh.ai/catalog/standards/sist/1ae1c0d3-85dc-4727-8352-0f1beb824025/sist-iso-11271-2006)

5.1 Millivoltmeter, with an input resistance not less than $10 \text{ G}\Omega$ and sensitivity of 1 mV .

5.2 A set of redox-electrodes, constructed as in A.1.

All electrodes should be sufficiently robust for field use.

5.3 Reference electrode: silver/silver chloride reference electrode in 1 mol/l or 3 mol/l potassium chloride solution.

Other reference electrodes such as the calomel electrode can also be used, but are not recommended because of the health hazard connected with the use of mercury. The potential of such reference electrodes with respect to the standard hydrogen electrode is given in annex B. Reference electrodes should be stored in a potassium chloride solution (6.4) of the same concentration as that present in the electrode, or directly in the salt bridge (5.5) containing the same concentration of potassium chloride. It should be noted that lower concentrations of potassium chloride will reduce contamination of the soil with this salt.

5.4 Rigid rod, (stainless steel has been found suitable), 20 cm to 100 cm in length, with a diameter 2 mm greater than that of the redox electrodes (5.2).

The rod shall have a length which allows the redox electrodes to be inserted to the desired depth in the soil.

5.5 Salt bridge, to connect the reference electrode with the soil (see A.2).

5.6 Hand auger, with a diameter 3 mm to 5 mm greater than that of the salt bridge.

5.7 Electrode cleaning materials: finest grade of steel wool, scouring powder and some cotton cloth have been found suitable.

5.8 Thermometer, to measure the temperature at the location of the reference electrode (see clause 8) with an accuracy of 1 °C.

6 Reagents

6.1 Redox buffer solution, to calibrate the redox electrodes.

Use either buffered quinhydrone solution (prepared by adding quinhydrone to a pH buffer to obtain a suspension), or an equimolar solution of potassium hexacyanoferrate(III) and potassium hexacyanoferrate(II) (see annex B).

6.2 Water, conforming to grade 2 of ISO 3696.

6.3 Agar, $\rho = 0,5 \%$, in a potassium chloride solution of the same concentration as that in the reference electrode.

6.4 Potassium chloride solution, of the same concentration as that chosen in 5.3.

NOTE This solution is used to store the reference electrode and to add to the salt bridge, as needed.

7 Site selection and sampling

The selection and description of the place of measurement, and of samples for laboratory measurement, should follow the guidelines given in ISO 10381-1 and ISO 11464.

8 Procedure

8.1 Care, cleaning and testing of the redox electrode system

The platinum electrodes shall be stored in air and kept clean. They shall be inspected for damage and/or contamination at intervals of not more than one year, and every time they are used. Oils, fats and waxes, and other chemicals likely to adhere are particularly damaging to electrode performance. If contaminated with soil material they shall be cleaned gently with a cotton cloth, and rinsed with distilled water. In cases of severe contamination, e.g. with oils, etc. (above), an appropriate solvent followed by scouring material (5.7) shall be used (see Note below).

The reference electrode(s) shall also be inspected at the same time as the platinum electrode(s). Any visible change in the colour or transparency of the potassium chloride electrolyte solution indicates probable trouble. In such cases the reference electrode shall not be used. Crystals of potassium chloride are, however, a normal feature of saturated potassium chloride solutions, and are no reason to reject the electrode in question.

The electrodes shall be checked prior to each series of measurements, by determining their response in the redox buffer solution (6.1). The measured redox potential values shall be as given in annex B. Any electrode differing by more than 10 mV from the required value shall be cleaned and tested again, and discarded if cleaning fails to correct the problem.

NOTE Experience has shown that the use of strong oxidizing agents, e.g. nitric acid or hydrogen peroxide solution, as cleaning agents for platinum electrodes can result in high redox potentials. The use of such agents is therefore not recommended.

In practical terms, the reference electrode potentials can be checked against each other. An electrode which gives a reading differing by more than 10 mV from the other(s) is likely to be faulty, and should be discarded. This check procedure requires a minimum of three reference electrodes, connected in turn.

Reference electrodes can be checked in absolute terms only against a standard hydrogen electrode. This can be done only in specialist laboratories. It is usually more convenient to buy electrodes only from a reputable source.