

SLOVENSKI STANDARD
SIST EN 301 908-20 V5.2.1:2011
01-november-2011

Celična omrežja IMT - Harmonizirani EN, ki zajema bistvene zahteve člena 3.2 direktive R&TTE - 20. del: Bazne postaje TDD OFDMA TDD WMAN (mobilni WiMAX)

IMT cellular networks - Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive - Part 20: OFDMA TDD WMAN (Mobile WiMAX) TDD Base Stations (BS)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 908-20 V5.2.1:2011](#)

Ta slovenski standard je istoveten z: [EN 301 908-20 Version 5.2.1](https://standards.iteh.ai/catalog/standards/sist/03436bc2-ddc2-4ba3-a8a6-1a63aacab22/sist-en-301-908-20-v5.2.1-2011)

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
-----------	---------------------------------------	---

SIST EN 301 908-20 V5.2.1:2011

en

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 908-20 V5.2.1:2011

<https://standards.iteh.ai/catalog/standards/sist/03436bc2-ddc2-4ba3-a8a6-affc5aacab22/sist-en-301-908-20-v5-2-1-2011>

ETSI EN 301 908-20 v5.2.1 (2011-09)



**IMT cellular networks;
Harmonized EN covering the essential requirements
of article 3.2 of the R&TTE Directive;
Part 20: OFDMA TDD WMAN (Mobile WiMAX)**

SIST EN 301 908-20 V5.2.1:2011
<https://standards.etsi.org/EN/301-908-20-v5-2-1-2011>

Reference

DEN/MSG-TFES-009-20

Keywordsbroadband, IMT, IMT-2000, mobile, OFDMA,
radio, regulation, TDD, WiMAX, WMAN***ETSI***

650 Route des Lucioles
 F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
 Association à but non lucratif enregistrée à la
 Sous-Préfecture de Grasse 06 N° 7303/88

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 908-20 V5.2.1:2011

<https://standards.iteh.ai/catalog/standards/sist/03436bc2-ddc2-4ba3-a8a6-affc5aacab2> Important notice
v5.2.1-2011

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
 The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
 All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
 of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	8
3 Definitions, symbols and abbreviations	9
3.1 Definitions	9
3.2 Symbols.....	10
3.3 Abbreviations	10
4 Essential requirements specification	11
4.1 Environmental profile.....	11
4.2 Conformance requirements	11
4.2.1 Introduction.....	11
4.2.2 Transmitter Spectrum Emission Mask.....	11
4.2.2.1 Definition	11
4.2.2.2 Limits	11
4.2.2.2.1 Spectrum emission mask for 5 MHz channel bandwidth	12
4.2.2.2.2 Spectrum emission mask for 10 MHz channel bandwidth	12
4.2.2.3 Conformance	12
4.2.3 Transmitter Adjacent Channel Leakage power Ratio (ACLR)	12
4.2.3.1 Definition	12
4.2.3.2 Limits	12
4.2.3.2.1 ACLR requirements for 5 MHz channel bandwidth.....	12
4.2.3.2.2 ACLR requirements for 10 MHz channel bandwidth.....	13
4.2.3.3 Conformance	13
4.2.4 Transmitter spurious emissions.....	13
4.2.4.1 Definition	13
4.2.4.2 Limits	13
4.2.4.2.1 General requirements.....	13
4.2.4.2.2 Additional Spurious Emission Requirements	14
4.2.4.3 Conformance	14
4.2.5 Base station maximum output power.....	14
4.2.5.1 Definition	14
4.2.5.2 Limits	14
4.2.5.3 Conformance.....	15
4.2.6 Transmit intermodulation	15
4.2.6.1 Definition	15
4.2.6.2 Limits	15
4.2.6.3 Conformance	15
4.2.7 Receiver spurious emissions	15
4.2.7.1 Definition	15
4.2.7.2 Limits	15
4.2.7.3 Conformance	16
4.2.8 Receiver blocking characteristics	16
4.2.8.1 Definition	16
4.2.8.2 Limits	16
4.2.8.3 Conformance	16
4.2.9 Receiver intermodulation characteristics	17
4.2.9.1 Definition	17
4.2.9.2 Limits	17
4.2.9.3 Conformance.....	17

4.2.10	Receiver Adjacent Channel Selectivity.....	17
4.2.10.1	Definition	17
4.2.10.2	Limits	18
4.2.10.3	Conformance	18
5	Testing for compliance with technical requirements.....	18
5.1	Environmental conditions for testing	18
5.2	Product information.....	18
5.3	Interpretation of the measurement results	19
5.4	Essential radio test suites.....	20
5.4.1	Transmitter Spectrum Emission Mask.....	20
5.4.1.1	Method of measurement.....	20
5.4.1.1.1	Initial conditions.....	20
5.4.1.1.2	Procedure.....	20
5.4.1.2	Test requirements	21
5.4.2	Transmitter Adjacent Channel Leakage Power Ratio (ACLR).....	21
5.4.2.1	Method of measurement.....	21
5.4.2.1.1	Initial conditions.....	22
5.4.2.1.2	Procedure.....	22
5.4.2.2	Test requirements	22
5.4.3	Transmitter spurious emissions.....	22
5.4.3.1	Method of measurement.....	23
5.4.3.1.1	Initial conditions.....	23
5.4.3.1.2	Procedure.....	23
5.4.3.2	Test requirements	23
5.4.4	Base Station maximum output power	24
5.4.4.1	Method of measurement.....	24
5.4.4.1.1	Initial conditions.....	24
5.4.4.1.2	Procedure.....	24
5.4.4.2	Test requirements	25
5.4.5	Transmit Intermodulation	25
5.4.5.1	Method of measurement.....	25
5.4.5.1.1	Initial conditions.....	25
5.4.5.1.2	Procedure.....	25
5.4.5.2	Test requirements	26
5.4.6	Receiver spurious emissions	26
5.4.6.1	Method of measurement.....	26
5.4.6.1.1	Initial conditions.....	26
5.4.6.1.2	Procedure.....	26
5.4.6.2	Test requirements	26
5.4.7	Receiver blocking characteristics	27
5.4.7.1	Method of Measurement	27
5.4.7.1.1	Initial conditions.....	28
5.4.7.1.2	Procedure.....	28
5.4.7.2	Test requirements	28
5.4.8	Receiver Intermodulation characteristics	28
5.4.8.1	Method of measurement.....	28
5.4.8.1.1	Initial conditions.....	29
5.4.8.1.2	Procedure.....	29
5.4.8.2	Test requirements	30
5.4.9	Receiver adjacent channel selectivity	30
5.4.9.1	Method of measurement.....	30
5.4.9.1.1	Initial conditions.....	30
5.4.9.1.2	Procedure.....	30
5.4.9.2	Test requirements	31
Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT).....	32
Annex B (normative):	Environmental profile	34
Annex C (informative):	The EN title in the official languages	35

Annex D (informative):	Bibliography	36
History		37

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 908-20 V5.2.1:2011

<https://standards.iteh.ai/catalog/standards/sist/03436bc2-ddc2-4ba3-a8a6-affc5aacab22/sist-en-301-908-20-v5-2-1-2011>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [i.1] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.2].

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**
See article 5.1 of Directive 1999/5/EC [i.2] for information on presumption of conformity and Harmonised Standards or parts thereof the references of which have been published in the Official Journal of the European Union.

The requirements relevant to Directive 1999/5/EC [i.2] are summarised in annex A.

SIST EN 301 908-20 V5.2.1:2011
The present document is part 20 of a multi-part deliverable covering the essential requirements under article 3.2 of Directive 1999/5/EC [i.2] for Base Stations (BS), Repeaters and User Equipment (UE) for IMT cellular networks, as identified below:

- Part 1: "Introduction and common requirements";
- Part 2: "CDMA Direct Spread (UTRA FDD) User Equipment (UE)";
- Part 3: "CDMA Direct Spread (UTRA FDD) Base Stations (BS)";
- Part 4: "CDMA Multi-Carrier (cdma2000) User Equipment (UE)";
- Part 5: "CDMA Multi-Carrier (cdma2000) Base Stations (BS)";
- Part 6: "CDMA TDD (UTRA TDD) User Equipment (UE)";
- Part 7: "CDMA TDD (UTRA TDD) Base Stations (BS)";
- Part 8: "Harmonized EN for IMT-2000, TDMA Single-Carrier (UWC 136) (UE) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 9: "Harmonized EN for IMT-2000, TDMA Single-Carrier (UWC 136) (BS) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 10: "Harmonized EN for IMT-2000, FDMA/TDMA (DECT) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 11: "CDMA Direct Spread (UTRA FDD) (Repeaters)";
- Part 12: "Harmonized EN for IMT-2000, CDMA Multi-Carrier (cdma2000) (Repeaters) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 13: "Evolved Universal Terrestrial Radio Access (E-UTRA) User Equipment (UE)";

- Part 14: "Evolved Universal Terrestrial Radio Access (E-UTRA) Base Stations (BS)";
- Part 15: "Evolved Universal Terrestrial Radio Access (E-UTRA) (FDD Repeaters)";
- Part 16: "Harmonized EN for IMT-2000, Evolved CDMA Multi-Carrier Ultra Mobile Broadband (UMB) (UE) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 17: "Harmonized EN for IMT-2000, Evolved CDMA Multi-Carrier Ultra Mobile Broadband (UMB) (BS) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 18: "E-UTRA, UTRA and GSM/EDGE Multi-Standard Radio (MSR) Base Stations (BS)";
- Part 19: "OFDMA TDD WMAN (Mobile WiMAX) TDD User Equipment (UE)";
- Part 20: "OFDMA TDD WMAN (Mobile WiMAX) TDD Base Stations (BS)";**
- Part 21: "OFDMA TDD WMAN (Mobile WiMAX) FDD User Equipment (UE)";
- Part 22: "OFDMA TDD WMAN (Mobile WiMAX) FDD Base Stations (BS)".

National transposition dates	
Date of adoption of this EN:	12 September 2011
Date of latest announcement of this EN (doa):	31 December 2011
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2012
Date of withdrawal of any conflicting National Standard (dow):	30 June 2013

Introduction

<https://standards.iteh.ai/catalog/standards/sist/03436bc2-ddc2-4ba3-a8a6-affc5aacab22/sist-en-301-908-20-v5-2-1-2011>

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.2]. The modular structure is shown in EG 201 399 [i.3].

1 Scope

The present document applies to the following radio equipment type:

- Base stations for IMT-2000 OFDMA TDD WMAN (Mobile WiMAX) operating in TDD mode.

This radio equipment type is capable of operating in all or any part of the frequency bands given in table 1-1.

Table 1-1: OFDMA TDD WMAN Base Station frequency bands

Mobile WiMAX Band Class Index	IMT-2000 OFDMA TDD WMAN service operating bands	Channel Bandwidth
1B	2 300 MHz to 2 400 MHz	5 MHz and 10 MHz

The requirements in the present document apply to both Wide Area Base Stations and Local Area Base Stations unless otherwise stated.

The present document is intended to cover the provisions of Directive 1999/5/EC [i.2], (R&TTE Directive) article 3.2, which states that "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the Directive 1999/5/EC [i.2] may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site <http://www.newapproach.org>.

(standards.iteh.ai)

2 References

[SIST EN 301 908-20 V5.2.1:2011](#)

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 301 908-1 (V5.2.1): "IMT cellular networks; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive; Part 1: Introduction and common requirements".
- [2] CEPT/ERC/REC 74-01E (Siófok 1998, Nice 1999, Sesimbra 2002, Hradec Kralove 2005): "Unwanted emissions in the spurious domain".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.

- [i.2] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.3] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the R&TTE Directive".
- [i.4] ETSI TR 102 215 (V1.3.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Recommended approach, and possible limits for measurement uncertainty for the measurement of radiated electromagnetic fields above 1 GHz".
- [i.5] ETSI EN 300 019-1-0: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-0: Classification of environmental conditions; Introduction".
- [i.6] ETSI TR 100 028 (all parts) (V1.4.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.7] ITU-R Recommendation SM.329-10 (2003): "Unwanted emissions in the spurious domain".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [i.2] and the following apply:

~~THE STANDARD PREVIEW~~

burst: period during which radio waves are intentionally transmitted, preceded and succeeded by periods during which no intentional transmission is made

environmental profile: declared range of environmental conditions under which equipment within the scope of the present document is required to be compliant
<https://standards.iteh.ai/catalog/standards/sist-en-301-908-20-v5-2-1-2011>

integral antenna: antenna which is declared to be part of the radio equipment by the manufacturer

NOTE: Even when equipment with an integral antenna is concerned, it might still be possible to separate the antenna from the equipment using a special tool. In such cases the assessment of the radio equipment and of the antenna against requirements of the present document may be done separately.

maximum output power: mean power level per carrier of the base station measured at the antenna connector in a specified reference condition

mean power: when applied to a modulated signal, this is the power (transmitted or received) in a bandwidth

nominal maximum output power: maximum nominal mean power level per carrier of the user equipment available at the antenna connector declared by the manufacturer; for equipment implementing dynamic change of modulation format, it is intended as the maximum nominal mean power associated to the modulation format delivering the highest power

receiver thermal noise power: equal to $k \times T \times BW \times F$

WiMAX: trade marked name for the OFDMA TDD WMAN IMT technology

3.2 Symbols

For the purposes of the present document, the following symbols apply:

A_{BS}	Base Station Interface A
A_{MS}	Mobile Station Interface A
A_{UUT}	Unit Under Test Interface A
BW	Assigned channel bandwidth
dB	decibel
dBc	decibel relative to carrier
dBm	decibel relative to 1 milliwatt
f	Frequency of measurement
f_c	centre frequency of the assigned channel
F	Receiver noise figure
k	Boltzmann's constant
M_{BS}	Base Station Interface M
M_{MS}	Mobile Station Interface M
N_{th}	Receiver thermal noise power expressed in dBm
P_{SENS}	Receiver sensitivity level at $BER \leq 10^{-6}$ (or equivalent PER) performance, corresponding to the most robust modulation and coding rate supported by the technology
P_{SENS5}	Receiver sensitivity level at $BER 10^{-6}$ for a 5 MHz channelized system, corresponding to the most robust modulation and coding rate supported by the technology
P_{SENS10}	Receiver sensitivity level at $BER 10^{-6}$ for a 10 MHz channelized system, corresponding to the most robust modulation and coding rate supported by the technology
Pnom	declared nominal maximum output Power
T	Ambient temperature in Kelvin

3.3 Abbreviations

SIST EN 301 908-20 V5.2.1:2011

<http://standards.iteh.ai/catalog/standards/sist/03436bc2-ddc2-4ba3-a8a6-affc5aacab22/sist-en-301-908-20-v5-2-1-2011>

For the purposes of the present document, the following abbreviations apply:

ACLR	Adjacent Channel Leakage power Ratio
ACS	Adjacent Channel Selectivity
BER	Bit Error Ratio
BS	Base Station
CW	Continuous Wave
ERM	Electromagnetic compatibility and Radio spectrum Matters
GHz	GigaHertz
IMT	International Mobile Telecommunications
MHz	MegaHertz
MSG	Mobile Standards Group
OFDMA	Orthogonal Frequency Division Multiple Access
PER	Packet Error Ratio
RF	Radio Frequency
R&TTE	Radio equipment and Telecommunications Terminal Equipment
RMS	Root Mean Square
TDD	Time Division Duplexing
TFES	Task Force for European Standards for IMT
TPC	Transmit Power Control
Tx	Transmit, Transmitter
UE	User Equipment
UEE	User Equipment Emulator
UUT	Unit Under Test
WMAN	Wireless Metropolitan Area Network