
**Road vehicles — Test method for the
quantification of on-centre handling —
Determination of dispersion metrics for
straight-line driving**

*Véhicules routiers — Méthodes d'essai pour la quantification de la stabilité
sur l'axe — Détermination de la dispersion métrique pour la conduite en
ligne droite*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/TS 20119:2002

<https://standards.iteh.ai/catalog/standards/sist/61ed5d6e-eac0-4406-93cd-680b36345768/iso-ts-20119-2002>



Reference number
ISO/TS 20119:2002(E)

© ISO 2002

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/TS 20119:2002

<https://standards.iteh.ai/catalog/standards/sist/61ed5d6e-eac0-4406-93cd-680b36345768/iso-ts-20119-2002>

© ISO 2002

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Contents

Page

Foreword	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms, definitions and symbols	1
4 Principle	2
5 Variables	2
6 Measuring equipment	3
7 Test conditions.....	3
8 Test procedure	5
9 Data evaluation and presentation of results	6
Bibliography.....	8

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/TS 20119:2002

<https://standards.iteh.ai/catalog/standards/sist/61ed5d6e-eac0-4406-93cd-680b36345768/iso-ts-20119-2002>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In other circumstances, particularly when there is an urgent market requirement for such documents, a technical committee may decide to publish other types of normative document:

- an ISO Publicly Available Specification (ISO/PAS) represents an agreement between technical experts in an ISO working group and is accepted for publication if it is approved by more than 50 % of the members of the parent committee casting a vote;
- an ISO Technical Specification (ISO/TS) represents an agreement between the members of a technical committee and is accepted for publication if it is approved by 2/3 of the members of the committee casting a vote.

<https://standards.iteh.ai/catalog/standards/sist/61ed5d6e-eac0-4406-93cd-680b36345768/iso-ts-20119-2002>

An ISO/PAS or ISO/TS is reviewed after three years with a view to deciding whether it should be confirmed for a further three years, revised to become an International Standard, or withdrawn. In the case of a confirmed ISO/PAS or ISO/TS, it is reviewed again after six years at which time it has to be either transposed into an International Standard or withdrawn.

Attention is drawn to the possibility that some of the elements of this Technical Specification may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/TS 20119 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 9, *Vehicle dynamics and road-holding ability*.

Introduction

The dynamic behaviour of a road vehicle is a most important part of active vehicle safety. Any given vehicle, together with its driver and the prevailing environment, forms a unique closed-loop system. The task of evaluating the dynamic behaviour is therefore very difficult because of the significant interaction of these driver–vehicle–road elements, each of which is in itself complex. A complete and accurate description of the behaviour of the road vehicle must necessarily involve information obtained from a number of tests of different types.

Because they quantify only a small part of the whole handling field, the results of these tests can be considered significant only for a correspondingly small part of the overall dynamic behaviour.

Moreover, insufficient knowledge is available concerning the relationship between accident avoidance and the dynamic characteristics evaluated by these tests. A substantial amount of effort is necessary to acquire sufficient and reliable data on the correlation between accident avoidance and vehicle dynamic properties in general and the results of these tests in particular.

Therefore it is not possible to use these methods and test results for regulation purposes at present. The best that can be expected is that these on-centre handling tests are used as some among many other tests, which together describe an important part of the field of vehicle dynamic behaviour.

Finally, the role of the tyres is important and test results can be strongly influenced by the type and condition of tyres.

ITC STANDARD PREVIEW
(standards.iteh.ai)
ISO/TS 20119:2002
<https://standards.iteh.ai/catalog/standards/sist/61ed5d6e-eac0-4406-93cd-680b36345768/iso-ts-20119-2002>

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

ISO/TS 20119:2002

<https://standards.iteh.ai/catalog/standards/sist/61ed5d6e-eac0-4406-93cd-680b36345768/iso-ts-20119-2002>

Road vehicles — Test method for the quantification of on-centre handling — Determination of dispersion metrics for straight-line driving

1 Scope

This Technical Specification specifies a test schedule that addresses certain aspects of the on-centre handling characteristics of a vehicle, *on-centre handling* being used to describe the steering “feel” and precision of the vehicle during nominally straight-line driving and in negotiating large-radius bends at high speeds but low lateral accelerations. It is applicable to passenger cars in accordance with ISO 3833, and to light trucks.

NOTE The manoeuvres specified are not necessarily representative of real driving conditions but are useful for obtaining measures of vehicle on-centre handling behaviour in response to several specific types of steering input under closely controlled test conditions. Other aspects of on-centre handling are addressed in the companion ISO 13674-1 and ISO 13674-2 (under preparation).

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this Technical Specification. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this Technical Specification are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 1176, *Road vehicles — Masses — Vocabulary and codes*

ISO 2416, *Passenger cars — Mass distribution*

ISO 3833, *Road vehicles — Types — Terms and definitions*

ISO 8855, *Road vehicles — Vehicle dynamics and road-holding ability — Vocabulary*

ISO 15037-1:1998, *Road vehicles — Vehicle dynamics test methods — Part 1: General conditions for passenger cars*

3 Terms, definitions and symbols

For the purposes of this Technical Specification, the terms, definitions and symbols given in ISO 1176, ISO 2416, ISO 3833 and ISO 8855 apply.

4 Principle

On-centre handling represents that part of the straight-line directional stability characteristics of the vehicle existing at lateral acceleration levels typically no greater than 1 m/s^2 . On-centre handling is concerned primarily with features that directly influence the driver's steering input, such as steering system and tyre characteristics. Thus test schedules for the evaluation of on-centre handling behaviour seek to minimize other factors that influence the wider aspects of straight-line directional stability, such as disturbance inputs due to ambient winds and road irregularities.

This Technical Specification defines a test schedule that involves driving the vehicle in a nominally straight line at a constant forward speed. Because this is a closed-loop test procedure, the results are driver-dependent. For this reason it is essential that all vehicles or vehicle configurations be tested using the same driver or drivers. During the test, driver inputs and vehicle responses are measured and recorded. From the recorded signals, characteristic values are calculated.

5 Variables

5.1 Reference system

The variables of motion used to describe the vehicle behaviour in a test-specific driving situation relate to the intermediate axis system, X , Y , Z (see ISO 8855).

The location of the origin of the vehicle axis system, X_V , Y_V , Z_V , is the reference point and thus should be independent of the loading condition. The origin is therefore fixed in the longitudinal plane of symmetry at half-wheelbase and at the same height above ground as the centre of gravity of the vehicle at complete vehicle kerb mass (see ISO 1176).

5.2 Variables to be measured

When performing this test procedure, the following variables shall be measured:

- steering-wheel angle, δ_H ;
- yaw velocity, $\frac{d\psi}{dt}$;
- longitudinal velocity, v_X .

The following variables should also be measured:

- steering-wheel angular velocity, $\frac{d\delta_H}{dt}$;
- lateral acceleration, a_Y .

These variables are defined in ISO 8855.

6 Measuring equipment

6.1 Description

All variables shall be measured by means of appropriate transducers and their time histories shall be recorded by a multi-channel recording system. Typical operating ranges and recommended maximum errors of the combined transducer and recording system are given in Table 1.

Table 1 — Variables, typical operating ranges and recommended maximum errors

Variable	Typical operating range ^a	Recommended maximum error of combined system ^b
Steering-wheel angle	$\pm 50^\circ$	$\pm 0,1^\circ$
Yaw velocity	$\pm 10^\circ/\text{s}$	$\pm 0,1^\circ/\text{s}$
Longitudinal velocity	0 m/s to 50 m/s	$\pm 0,5 \text{ m/s}$
Lateral acceleration	$\pm 5 \text{ m/s}^2$	$\pm 0,1 \text{ m/s}^2$
Steering-wheel angular velocity	$\pm 100^\circ/\text{s}$	$\pm 1^\circ/\text{s}$
Transducers for measuring some of the listed variables are not widely available and are not in general use. Many such instruments are developed by users. If any system error exceeds the recommended maximum value, this and the actual maximum error shall be stated in the test report (see ISO 15037-1:1998, annex A).		
^a These transducer ranges are appropriate for the standard test conditions and might not be suitable for non-standard test conditions. ^b The values for maximum errors are provisional until more experience and data are available.		

6.2 Transducer installations

ISO/TS 20119:2002

<https://standards.iteh.ai/catalog/standards/sist/61ed5d6e-eac0-4406-93cd-680b36345768/iso-ts-20119-2002>

The transducers shall be installed according to the manufacturer's instructions, where such instructions exist, so that the variables corresponding to the terms and definitions of ISO 8855 can be determined.

If a transducer does not measure a variable directly, appropriate transformation into the specified reference system shall be carried out.

NOTE Lateral acceleration, as defined, is measured in the intermediate XY -plane. However, for the purpose of this test procedure, measurement of "sideways" acceleration in the vehicle $X_V Y_V$ -plane (i.e. corrupted by vehicle roll) is typically adequate, provided that the roll angle versus lateral acceleration characteristic for the vehicle is known and an appropriate correction in respect of roll angle can be made to the "sideways" acceleration.

6.3 Data processing

See ISO 15037-1:1998, 4.3.

7 Test conditions

7.1 General

See ISO 15037-1:1998, clause 5.