



**SLOVENSKI STANDARD**  
**SIST EN 301 842-1 V1.3.2:2011**  
**01-februar-2011**

---

**Radijska oprema za VHF digitalne povezave zrak-tla, 4. način - Tehnične karakteristike in merilne metode za talno opremo - 1. del: EN za talno opremo**

VHF air-ground Digital Link (VDL) Mode 4 radio equipment - Technical characteristics and methods of measurement for ground-based equipment - Part 1: EN for ground equipment

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 842-1 V1.3.2:2011](https://standards.iteh.ai/catalog/standards/sist/a44cac52-1af5-4cfe-a029-9246b5a0b76/sist-en-301-842-1-v1-3-2-2011)

Ta slovenski standard je istoveten z: [EN 301 842-1 Version 1.3.2](https://standards.iteh.ai/catalog/standards/sist/a44cac52-1af5-4cfe-a029-9246b5a0b76/sist-en-301-842-1-v1-3-2-2011)

---

**ICS:**

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
49.090	Oprema in instrumenti v zračnih in vesoljskih plovilih	On-board equipment and instruments

**SIST EN 301 842-1 V1.3.2:2011**                      **en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 301 842-1 V1.3.2:2011

<https://standards.iteh.ai/catalog/standards/sist/a44cac52-1af5-4cfe-a029-924ebb5a0b78/sist-en-301-842-1-v1-3-2-2011>

# ETSI EN 301 842-1 V1.3.2 (2010-12)

---

*European Standard (Telecommunications series)*

**VHF air-ground Digital Link (VDL) Mode 4 radio equipment;  
Technical characteristics and methods of measurement  
for ground-based equipment;  
Part 1: EN for ground equipment**

---

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 842-1 V1.3.2:2011](https://standards.iteh.ai/catalog/standards/sist/a44cac52-1af5-4cfe-a029-924ebb5a0b78/sist-en-301-842-1-v1-3-2-2011)

<https://standards.iteh.ai/catalog/standards/sist/a44cac52-1af5-4cfe-a029-924ebb5a0b78/sist-en-301-842-1-v1-3-2-2011>



## Reference

---

REN/AERO-00006-1

## Keywords

---

aeronautical, digital, radio, testing, VHF**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 301 842-1 V1.3.2:2011<https://standards.iteh.ai/catalog/standards/sist/a44cac52-1af5-4cfe-a029-924ebb5a0178/sist-en-301-842-1-v1-3-2-2011>**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**LTE™** is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	6
Foreword.....	6
Introduction .....	7
1 Scope .....	8
2 References .....	9
2.1 Normative references .....	9
2.2 Informative references.....	10
3 Definitions and abbreviations.....	10
3.1 Definitions.....	10
3.1.1 Basic reference model definitions.....	10
3.1.2 Service conventions definitions .....	10
3.1.3 General definitions.....	11
3.2 Abbreviations .....	15
4 General description and architecture of VDL Mode 4 .....	16
4.1 General .....	16
5 VDL Mode 4 physical layer functional specifications .....	16
5.1 Overview .....	16
5.1.1 Functions .....	16
5.1.2 Data reception .....	16
5.1.3 Data transmission.....	16
5.2 Modulation scheme .....	16
6 VDL Mode 4 equipment requirements.....	16
6.1 Receiver Requirements.....	17
6.1.1 Receiver operating range .....	17
6.1.2 BER requirement .....	17
6.1.3 Reference signal level.....	17
6.1.4 Sensitivity .....	17
6.1.5 Adjacent channel rejection.....	17
6.1.6 Rejection of signals within the VHF Aeronautical band.....	17
6.1.7 Rejection of signals outside the VHF Aeronautical band .....	18
6.1.8 Desired signal dynamic range.....	18
6.1.9 Symbol rate capture range .....	18
6.1.10 Frequency capture range .....	18
6.1.11 Co-channel interference .....	19
6.1.12 Conducted spurious emission .....	19
6.1.13 FM Broadcast Intermodulation.....	19
6.1.13.1 Radio frequencies in the band 117,975 MHz to 137 MHz.....	19
6.1.14 In-band Intermodulation .....	19
6.1.15 Cabinet radiation.....	19
6.2 Transmitter requirements .....	20
6.2.1 Transmitter operating range .....	20
6.2.2 Channel Bit Rate.....	20
6.2.3 Protection of the transmitter.....	20
6.2.4 Manufacturer's declared output power.....	20
6.2.5 RF power rise time.....	20
6.2.6 RF power release time .....	20
6.2.7 Conducted Spurious emissions .....	21
6.2.8 Adjacent channel power.....	21
6.2.9 Wide-band noise .....	21
6.2.10 Frequency Tolerance.....	21
6.2.11 Load VSWR capability .....	21
6.2.12 Cabinet radiation.....	21

6.3	Transceiver requirements .....	22
6.3.1	Start of transmission .....	22
6.3.2	Automatic transmitter shutdown .....	22
6.3.3	Receiver to transmitter turnaround time .....	22
6.3.4	Transmitter to receiver turnaround time .....	22
6.3.5	System timing requirements .....	22
7	General design requirements .....	22
7.1	Controls and indicators .....	22
7.2	Class of emission and modulation characteristics .....	22
7.3	Warm up .....	22
8	Test conditions, power sources and ambient temperatures .....	23
8.1	Test power source .....	23
8.2	Test channels .....	23
8.3	General conditions of measurement .....	23
8.3.1	Receiver test signal arrangement .....	23
8.3.2	Performance check .....	23
8.4	Normal and extreme test conditions .....	23
8.4.1	Normal test conditions .....	24
8.4.1.1	Normal temperature and humidity .....	24
8.4.1.2	Normal power sources .....	24
8.4.1.2.1	Mains voltage and frequency .....	24
8.4.1.2.2	Other power sources .....	24
8.4.2	Extreme test conditions .....	24
8.4.2.1	Extreme temperatures .....	24
8.4.2.2	Procedure for tests at extreme temperatures .....	24
8.4.2.2.1	General .....	24
8.4.2.2.2	High temperature .....	24
8.4.2.2.3	Low temperature .....	25
8.4.2.3	Extreme values of test power sources .....	25
8.4.2.3.1	Mains voltage and frequency .....	25
9	Detailed Test Procedures for the physical layer .....	25
9.1	Receiver .....	25
9.1.1	BER test .....	25
9.1.2	Sensitivity .....	27
9.1.3	Adjacent Channel Rejection (ACR) .....	28
9.1.4	Rejection of signals within the VHF Aeronautical band .....	29
9.1.5	Rejection of signals outside the VHF Aeronautical band .....	30
9.1.6	Desired Signal dynamic range .....	30
9.1.7	Symbol rate capture range .....	31
9.1.8	Frequency capture range .....	31
9.1.9	Co-channel interference .....	32
9.1.10	Conducted spurious emission .....	32
9.1.11	In-band Intermodulation .....	33
9.2	Transmitter .....	34
9.2.1	Channel Bit Rate .....	34
9.2.2	Manufacturer's declared output power .....	34
9.2.3	RF power rise time .....	35
9.2.4	RF power release time .....	35
9.2.5	Spurious emissions .....	36
9.2.6	Adjacent channel power .....	36
9.2.6.1	Method of measurement for the first adjacent channel .....	36
9.2.6.2	Method of measurement for the second adjacent channel .....	37
9.2.6.3	Method of measurement for the fourth adjacent channel .....	38
9.2.6.4	Alternative measurement procedure for Adjacent Channel Power (ACP) .....	38
9.2.7	Wide-band noise .....	39
9.2.8	Frequency Error .....	40
9.2.8.1	Definition .....	40
9.2.8.2	Method of measurement .....	40
9.2.8.3	Limits .....	40
9.2.9	Load VSWR capability .....	40

9.3	Physical layer, system parameters .....	41
9.3.1	Receiver to Transmitter turn-around time.....	41
9.3.2	Transmitter to Receiver turn-around time.....	42
9.3.3	Tuning Time .....	42
<b>Annex A (informative):</b>	<b>Cross reference matrix .....</b>	<b>43</b>
<b>Annex B (informative):</b>	<b>Bibliography.....</b>	<b>45</b>
History .....		47

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 842-1 V1.3.2:2011](https://standards.iteh.ai/catalog/standards/sist/a44cac52-1af5-4cfe-a029-924ebb5a0b78/sist-en-301-842-1-v1-3-2-2011)

<https://standards.iteh.ai/catalog/standards/sist/a44cac52-1af5-4cfe-a029-924ebb5a0b78/sist-en-301-842-1-v1-3-2-2011>

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Aeronautics (AERO).

The present document is part 1 of a multi-part deliverable covering the VHF air-ground Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment, as identified below:

- Part 1:** "EN for ground equipment";
- Part 2: "General description and data link layer";
- Part 3: "Additional broadcast aspects";
- Part 4: "Point-to-point functions";
- Part 5: "Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".

The present document is accompanied by an equivalent airborne standard, EN 302 842 [8] parts 1 to 4, covering the VHF air-ground Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for airborne equipment.

### National transposition dates

Date of latest announcement of this EN (doa):	31 March 2011
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 September 2011
Date of withdrawal of any conflicting National Standard (dow):	30 September 2011



---

## Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.1]. The modular structure is shown in EG 201 399 [i.2].

The present document states the technical specifications for Very High Frequency (VHF) Digital Link (VDL) Mode 4 ground-based radio transmitters, transceivers and receivers for air-ground communications operating in the VHF band, using Gaussian-filtered Frequency Shift Keying (GFSK) Modulation with 25 kHz channel spacing and capable of tuning to any of the 25 kHz channels from 118,000 MHz to 136,975 MHz as defined in ICAO VHF Digital Link (VDL) Standards and Recommended Practices (SARPs) [2].

The present document may be used to produce tests for the assessment of the performance of the equipment. The performance of the equipment submitted for type testing should be representative of the performance of the corresponding production model.

The present document has been written on the assumption that:

- the type test measurements will be performed only once, in an accredited test laboratory and the measurements accepted by the various authorities in order to grant type approval;
- if equipment available on the market is required to be checked it may be tested in accordance with the methods of measurement specified in the present document or a documented alternative approved by the certifying authority;
- equipment comply with EN 301 489-22 [6].

**ITEH STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 842-1 V1.3.2:2011](https://standards.iteh.ai/catalog/standards/sist/a44cac52-1af5-4cfe-a029-924ebb5a0b78/sist-en-301-842-1-v1-3-2-2011)

<https://standards.iteh.ai/catalog/standards/sist/a44cac52-1af5-4cfe-a029-924ebb5a0b78/sist-en-301-842-1-v1-3-2-2011>

---

# 1 Scope

The present document applies to the following radio equipment types:

- Very High Frequency (VHF) Digital Link (VDL) Mode 4 ground-based radio transmitters and receivers for air-ground communications operating in the VHF band, using Gaussian-filtered Frequency Shift Keying (GFSK) Modulation with 25 kHz channel spacing and capable of tuning to any of the 25 kHz channels from 118,000 MHz to 136,975 MHz as defined in ICAO VHF Digital Link (VDL) Standards and Recommended Practices (SARPs) [2].

The present document provides part 1 of the technical specification.

The present document is designed to ensure that equipment certified to it will be compatible with the relevant ICAO VHF Digital Link (VDL) Standards and Recommended Practices (SARPs) [2] and VDL Mode 4 Technical Manual (TM) [1].

Manufacturers should note that in future the tuning range for the ground transceivers may also cover any 25 kHz channel from 108,000 MHz to 117,975 MHz.

The scope of the present document is limited to ground stations. The equivalent specification for airborne stations is EN 302 842 [8].

The VDL Mode 4 system provides digital communication exchanges between aircraft and ground-based systems and other aircraft supporting surveillance and communication applications. The supported modes of communication include:

- broadcast and point-to-point communication;
- broadcast services including Automatic Dependent Surveillance-broadcast (ADS-B), Traffic Information Service - Broadcast (TIS-B) and Flight Information Service - Broadcast (FIS-B) capabilities;
- air-air, air-to-ground, and ground-to-air services;
- operation without ground infrastructure.

The present document is derived from the specifications:

- VDL Mode 4 standards produced under the auspices of the International Civil Aviation Organization (ICAO) [1] and [2];
- other relevant standards as defined in clause 2.

It is envisaged that manufacturers may provide equipment supporting:

- broadcast services only;
- point-to-point services only;
- both broadcast and point-to-point services.

The present document deals with tests of the physical layer necessary to support all types of equipment.

The present document includes:

- clause 2 provides references to relevant documents;
- clause 3 provides general definitions, abbreviations and symbols used;
- clause 4 refers to a general description and architecture of VDL Mode 4 contained in EN 301 842-2 [7];
- clause 5 provides functional specifications applicable to the physical layer including transmitter/receiver requirements and the modulation scheme;
- clause 6 provides general equipment requirements;

- clause 7 provides general design requirements;
- clause 8 covers general test conditions, environmental tests and calibration;
- clause 9 provides detailed test procedures for the physical layer;
- annex A provides a detailed cross-reference to the relevant requirements contained in reference [1];
- annex B provides a Bibliography;
- a document history.

The full physical layer tests are provided which correspond closely to the standard set of tests used for other VDL systems.

### Mandating and Recommendation Phrases

- "Shall"**  
The use of the word "Shall" indicates a mandated criterion; i.e. compliance with the particular procedure or specification is mandatory and no alternative may be applied.
- "Should"**  
The use of the word "Should" (and phrases such as "It is recommended that...", etc.) indicate that though the procedure or criterion is regarded as the preferred option, alternative procedures, specifications or criteria may be applied, provided that the manufacturer, installer or tester can provide information or data to adequately support and justify the alternative.

---

## 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

### 2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ICAO Doc 9816 AN/448 (First Edition 2004): "Manual on VHF Digital Link (VDL) Mode 4, Part 2: Detailed Technical Specifications".
- [2] ICAO Annex 10 to the Convention on International Civil Aviation: "Aeronautical Telecommunications, Volume III: Communication Systems, Part I: Digital Data Communication Systems, Chapter 6".
- [3] ISO/IEC 7498-1 (1994): "Information technology - Open Systems Interconnection - Basic Reference Model: The Basic Model".
- [4] ISO/IEC 10731 (1994): "Information technology - Open Systems Interconnection - Basic Reference Model - Conventions for the definition of OSI services".
- [5] ETSI EN 300 113-1 (V1.6.2): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector; Part 1: Technical characteristics and methods of measurement".

- [6] ETSI EN 301 489-22 (V1.3.1): "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 22: Specific conditions for ground based VHF aeronautical mobile and fixed radio equipment".
- [7] ETSI EN 301 842-2 (V1.6.1): "VHF air-ground Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for ground-based equipment; Part 2: General description and data link layer".
- [8] ETSI EN 302 842 (all parts): "VHF air-ground and air-air Digital Link (VDL) Mode 4 radio equipment; Technical characteristics and methods of measurement for aeronautical mobile (airborne) equipment".

## 2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.2] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the R&TTE Directive".

---

## 3 Definitions and abbreviations

### 3.1 Definitions

#### 3.1.1 Basic reference model definitions

The present document is based on the concepts developed in the open systems interconnect basic reference model and makes use of the following terms defined in ISO/IEC 7498-1 [3]:

- layer;
- sublayer;
- entity;
- service;
- service access point;
- service data unit;
- physical layer;
- data link layer.

#### 3.1.2 Service conventions definitions

The present document makes use of the following terms defined in ISO/IEC 10731 [4]:

- service provider;
- service user;
- service primitive;

- request;
- indication;
- confirm.

### 3.1.3 General definitions

For the purposes of the present document, the following terms and definitions apply:

**adjacent channel power:** amount of the modulated RF signal power which falls within a given adjacent channel

NOTE: Adjacent channel power includes discrete spurious, signal sidebands, and noise density (including phase noise) at the transmitter output.

**Adjacent Channel Rejection (ACR):** receiver's ability to demodulate the desired signal and meet the BER requirement in the presence of an interfering signal in an adjacent channel

NOTE: The ratio (in dB) between the adjacent interfering signal level and the desired signal level necessary to achieve the specified minimum BER, is the adjacent channel rejection (ACR) ratio.

**Aeronautical Mobile Service (AMS):** mobile service between aeronautical stations and aircraft stations, or between aircraft stations, in which survival craft stations may participate

**Aeronautical Telecommunications Network (ATN):** internetwork architecture that allows ground, air/ground, and aircraft data subnetworks to interoperate by adopting common interface services and protocols based on the International Organization for Standardization Open Systems Interconnection (OSI) Reference Model

**aircraft address:** unique combination of 24 bits available for assignment to an aircraft for the purpose of air-ground communications, navigation and surveillance

NOTE: An aircraft may choose not to use this unique address and can use instead a non-unique address.

**Automatic Dependent Surveillance-Broadcast (ADS-B):** surveillance application transmitting parameters, such as position, track and ground speed, via a broadcast mode data link for use by any air and ground users requiring it

NOTE: ADS-B is a surveillance service based on aircraft self-determination of position/velocity/time and automatic, periodic or random, broadcast of this information along with auxiliary data such as aircraft identity (ID), communications control parameters, etc. ADS-B is intended to support multiple high-level applications and associated services such as cockpit display of traffic information, traffic alert and collision avoidance functionality, enhanced traffic management in the air and on the ground, search and rescue support and others.

**autotune function:** function, performed by the Link Management Entity, that allows a ground VDL Mode 4 station to command an aircraft to change the operating characteristics of synchronization burst transmissions

**Bit Error Rate (BER):** expressed as the ratio between the number of erroneous bits received and the total number of bits received

**burst length:** number of slots across which the VDL Mode 4 burst is transmitted

**Co-Channel Interference (CCI):** co-channel interference protection defines the capability of a receiver to demodulate the desired signal and achieve the minimum specified BER performance in the presence of an unwanted signal at the same assigned frequency

NOTE: The ratio (in dB) between the wanted signal level and the unwanted signal level is the co-channel interference ratio. The co-channel interference ratio has a major impact on frequency re-use planning criteria.

**conducted measurements:** measurements which are made using a direct RF connection to the equipment under test

**current slot:** slot in which a received transmission begins

**Data Link Entity (DLE):** protocol state machine capable of setting up and managing a single data link connection