



SLOVENSKI STANDARD
SIST EN 300 392-12-21 V1.4.1:2011
01-julij-2011

Prizemni snopovni radio (TETRA) - Govor in podatki (V+D) - 12. del: Dopolnilne storitve stopnje 3 - 21. poddel: Poslušanje okolice (AL)

Terrestrial Trunked Radio (TETRA) - Voice plus Data (V+D) - Part 12: Supplementary services stage 3 - Sub-part 21: Ambience Listening (AL)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **EN 300 392-12-21 Version 1.4.1**

SIST EN 300 392-12-21 V1.4.1:2011
<https://standards.iteh.ai/catalog/standards/sist/9ce9155d-17a2-480a-81bd-7ce1df08417d/sist-en-300-392-12-21-v1-4-1-2011>

ICS:

33.070.10	Prizemni snopovni radio (TETRA)	Terrestrial Trunked Radio (TETRA)
-----------	---------------------------------	-----------------------------------

SIST EN 300 392-12-21 V1.4.1:2011 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 392-12-21 V1.4.1:2011

<https://standards.iteh.ai/catalog/standards/sist/9ce9153d-17a2-480a-81bd-7ce1df08417d/sist-en-300-392-12-21-v1-4-1-2011>

ETSI EN 300 392-12-21 V1.4.1 (2011-04)

European Standard

**Terrestrial Trunked Radio (TETRA);
Voice plus Data (V+D);
Part 12: Supplementary services stage 3;
Sub-part 21: Ambience Listening (AL)**

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST EN 300 392-12-21 V1.4.1:2011](https://standards.iteh.ai/catalog/standards/sist/9ce9153d-17a2-480a-81bd-7ce1df08417d/sist-en-300-392-12-21-v1-4-1-2011)

<https://standards.iteh.ai/catalog/standards/sist/9ce9153d-17a2-480a-81bd-7ce1df08417d/sist-en-300-392-12-21-v1-4-1-2011>



Reference

REN/TETRA-03211

Keywords

supplementary service, TETRA**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 392-12-21 V1.4.1:2011

<https://standards.iteh.ai/catalog/standards/sist/9ce9153d-17a2-480a-81bd-7ce1df08417d/sist-300-392-12-21-v1-4-1-2011>
Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	7
3 Definitions and abbreviations.....	8
3.1 Definitions.....	8
3.2 Abbreviations	8
4 SS-AL service description.....	8
4.1 General	8
4.2 SS-AL services offered over the TNSS-SAP	9
4.2.1 SS-AL service primitives to served user.....	9
4.2.2 SS-AL service primitives to affected user	9
4.2.3 SS-AL service primitive to second listening party	9
4.3 Service primitive descriptions	10
4.3.1 INFORMATION indication.....	10
4.3.2 INTERROGATE request.....	10
4.3.3 INTERROGATE indication.....	10
4.3.4 INVOKE1 request	11
4.3.5 INVOKE2 request.....	11
4.3.6 INVOKE indication.....	11
4.3.7 INVOKE ACK request	11
4.3.8 INVOKE1 indication.....	12
4.3.9 INVOKE2 indication.....	12
4.3.10 INVOKE3 request	12
4.3.11 INVOKE3 indication.....	13
4.3.12 STOP LISTENING request.....	13
4.4 Parameter description	13
5 Signalling protocol to support SS-AL	15
5.1 General	15
5.2 SS-AL general operational requirements	15
5.2.1 Requirements on the affected user MS	15
5.2.2 Requirements on the affected user current SwMI.....	15
5.2.3 Requirements on the SS-AL affected user home SwMI	15
5.2.4 Requirements on the served user MS/LS	15
5.2.5 Requirements on the served user SwMI	15
5.2.6 Requirements on the second listening party MS/LS.....	16
5.2.7 Requirements on the SS-AL second listening party SwMI.....	16
5.3 SS-AL coding requirements	16
5.3.1 General on SS-AL PDUs	16
5.3.2 AL-TX DEMAND PDU	16
5.3.3 AL-TX GRANTED PDU	17
5.3.4 AL-TX INFORM PDU	17
5.3.5 AL-TX INTERRUPT PDU	17
5.3.6 AL-TX REJECT PDU	18
5.3.7 INFORMATION PDU	18
5.3.8 INTERROGATE PDU	19
5.3.9 INTERROGATE ACK PDU	19
5.3.10 INVOKE1 PDU	20
5.3.11 INVOKE2 PDU	20
5.3.12 INVOKE PDU	21
5.3.13 INVOKE ACK PDU.....	21
5.3.14 INVOKE1 ACK PDU.....	21
5.3.15 INVOKE2 ACK PDU.....	22

5.4	Information element coding	22
5.4.1	AL PDU type	22
5.4.2	Affected party extension	23
5.4.3	Affected party short number	23
5.4.4	Affected party SSI	23
5.4.5	Affected party type identifier	23
5.4.6	Encryption control	23
5.4.7	Interrogated party extension	23
5.4.8	Interrogated party short number	24
5.4.9	Interrogated party SSI	24
5.4.10	Interrogated party type identifier	24
5.4.11	Listening party extension	24
5.4.12	Listening party SSI	24
5.4.13	Listening party type identifier	24
5.4.14	Range type of interrogated users	24
5.4.15	Result of interrogation	24
5.4.16	Result of invocation	25
5.4.17	Result of invocation by user	25
5.4.18	Second listening party extension	25
5.4.19	Second listening party short number	26
5.4.20	Second listening party SSI	26
5.4.21	Second listening party type identifier	26
5.4.22	Transmission grant	26
5.5	SS-AL state definitions	26
5.5.1	Protocol states of served user FE1	26
5.5.2	Protocol states of SwMI FE2	26
5.5.3	Protocol states of affected user FE5	26
5.5.4	Protocol states of FE2 in visited SwMI	26
5.5.5	Protocol states of second listening party FE6	26
5.6	SS-AL Procedures	26
5.6.1	Procedures for served user FE1	26
5.6.1.1	Interrogation	26
5.6.1.2	Invocation	27
5.6.1.3	Addition of second listening party	27
5.6.1.4	Invocation during on-going call	27
5.6.2	Procedures for SwMI FE2	27
5.6.2.1	Interrogation	27
5.6.2.2	Invocation	27
5.6.2.3	Addition of second listening party	28
5.6.2.4	Invocation during on-going call	28
5.6.3	Procedures for FE2 in visited SwMI	28
5.6.4	Procedures for affected user FE5	29
5.6.4.1	Invocation	29
5.6.4.2	Invocation during on-going call	29
5.6.4.3	Affected user request for invocation	29
5.6.5	Procedures for second listening party FE6	29
5.6.5.1	Invocation	29
5.6.5.2	Invocation during on-going call	29
5.7	Interactions with other supplementary services	30
5.7.1	General	30
5.7.2	Call Forwarding	30
5.7.3	Ambience Listening	30
Annex A (informative):	SS-AL Call request	31
Annex B (informative):	INTERROGATE ACK PDU encoding	32
Annex C (informative):	INVOKE1 and INVOKE1 ACK PDUs encoding	33
Annex D (informative):	Change requests	34
History		35

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Terrestrial Trunked Radio (TETRA).

The present document is part 12, sub-part 21 of a multi-part deliverable covering Voice plus Data (V+D), as identified below:

EN 300 392-1: "General network design";

EN 300 392-2: "Air Interface (AI)";

EN 300 392-3: "Interworking at the Inter-System Interface (ISI)";

ETS 300 392-4: "Gateways basic operation";

EN 300 392-5: "Peripheral Equipment Interface (PEI)";

EN 300 392-7: "Security";

EN 300 392-9: "General requirements for supplementary services";

EN 300 392-10: "Supplementary services stage 1";

EN 300 392-11: "Supplementary services stage 2";

EN 300 392-12: "Supplementary services stage 3";

EN 300 392-12-1: "Call Identification (CI)";

ETS 300 392-12-2: "Call Report (CR)";

EN 300 392-12-3: "Talking Party Identification (TPI)";

EN 300 392-12-4: "Call Forwarding (CF)";

ETS 300 392-12-5: "List Search Call (LSC)";

EN 300 392-12-6: "Call Authorized by Dispatcher (CAD)";

ETS 300 392-12-7: "Short Number Addressing (SNA)";

EN 300 392-12-8: "Area Selection (AS)";

ETS 300 392-12-9: "Access Priority (AP)";

EN 300 392-12-10: "Priority Call (PC)";

ETS 300 392-12-11: "Call Waiting (CW)";

EN 300 392-12-12: "Call Hold (HOLD)";

ETS 300 392-12-13: "Call Completion to Busy Subscriber (CCBS)";

EN 300 392-12-14: "Late Entry (LE)";

EN 300 392-12-16: "Pre-emptive Priority Call (PPC)";

EN 300 392-12-17: "Include Call (IC)";

EN 300 392-12-18: "Barring of Outgoing Calls (BOC)";

EN 300 392-12-19: "Barring of Incoming Calls (BIC)";

ETS 300 392-12-20: "Discreet Listening (DL)";

EN 300 392-12-21: "Ambience Listening (AL)";

EN 300 392-12-22: "Dynamic Group Number Assignment (DGNA)";

ETS 300 392-12-23: "Call Completion on No Reply (CCNR)";

ETS 300 392-12-24: "Call Retention (CRT)";

ETS 300 392-13: "SDL model of the Air Interface (AI)";

ETS 300 392-14: "Protocol Implementation Conformance Statement (PICS) proforma specification";

TS 100 392-15: "TETRA frequency bands, duplex spacings and channel numbering";

TS 100 392-16: "Network Performance Metrics";

TR 100 392-17: "TETRA V+D and DMO specifications";

TS 100 392-18: "Air interface optimized applications";

NOTE: Part 3, sub-parts 6 and 7 (Speech format implementation), part 4, sub-part 3 (Data networks gateway), part 10, sub-part 15 (Transfer of control), part 13 (SDL) and part 14 (PICS) of this multi-part deliverable are in status "historical" and are not maintained.

STANDARD PREVIEW
(standards.iteh.ai)

National transposition dates

Date of adoption of this EN:	7 April 2011
Date of latest announcement of this EN (doa):	31 July 2011
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2012
Date of withdrawal of any conflicting National Standard (dow):	31 January 2012

1 Scope

The present document defines the stage 3 specification of the Supplementary Service Ambience Listening (SS-AL) for the Terrestrial Trunked Radio (TETRA). Stage 3 defines the signalling system protocols and switching functions needed to implement the service described in stage 1 and stage 2.

Charging principles and Man-Machine Interface (MMI) are outside the scope of the present document.

The SS-AL enables the served user to place a TETRA Mobile Station (MS) into a special type of voice call whereby the called MS transmits without any action from, or indication to, the affected user. The SS-AL call can include a second listening party. The affected user can ask other user to set an SS-AL call on him.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- SIST EN 300 392-12-21 V1.4.1:2011
<https://standards.iteh.ai/catalog/standards/sist/3cc9155d-17a2-480a-b1bd-7cc1d05417d/sist-en-300-392-12-21-v1-4-1-2011>
- [1] ETSI EN 300 392-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".
 - [2] ETSI EN 300 392-1: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 1: General network design".
 - [3] ETSI EN 300 392-9: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 9: General requirements for supplementary services".
 - [4] ETSI EN 300 392-3-2: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 2: Additional Network Feature Individual Call (ANF-ISIIC)".
 - [5] ETSI EN 300 392-3-3: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 3: Interworking at the Inter-System Interface (ISI); Sub-part 3: Additional Network Feature Group Call (ANF-ISIGC)".
 - [6] ETSI EN 300 392-10-21: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 10: Supplementary services stage 1; Sub-part 21: Ambience Listening (AL)".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EN 300 392-11-21: "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 11: Supplementary services stage 2; Sub-part 21: Ambience Listening (AL)".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

affected user: user to whom the served user is listening

Ambience Listening (AL) call: call in which ambience listening functionality is requested

NOTE: During an AL call, the affected user's MS transmits without any action from, or indication to, the affected user.

second listening party: TETRA individual or group which additionally listens into the AL call

served user: user who invokes this supplementary service and listens to the affected user

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AL	Ambience Listening
CC	Call Control
CFB	Call Forwarding on Busy
CLIR	Calling Line Identification Restriction
CMCE	Circuit Mode Control Entity
FE	Functional Entity
GSSI	Group Short Subscriber Identity
ISI	Inter-System Interface
ISSI	Individual Short Subscriber Identity
ITSI	Individual TETRA Subscriber Identity
LS	Line Station
MMI	Man-Machine Interface
MS	Mobile Station
PDU	Protocol Data Unit
SAP	Service Access Point
SDL	(Functional) Specification and Description Language
SNA	Short Number Address
SS	Supplementary Service

NOTE: The abbreviation SS is only used when referring to a specific supplementary service.

SSI	Short Subscriber Identity
SwMI	Switching and Management Infrastructure
TNSS-SAP	TETRA Network layer Supplementary Service - Service Access Point
TSI	TETRA Subscriber Identity

4 SS-AL service description

4.1 General

The SS-AL enables the served user to place a TETRA Mobile Station (MS) into a special type of voice call teleservice whereby the called MS transmits without any action from, or indication to, the affected user. The affected user shall be an individual user. The SS-AL call may include a second listening party. The second listening party may be either individual user or a group.

Clauses 4.2 and 4.3 describe SS-AL specific services offered by the Circuit Mode Control Entity (CMCE) at the Supplementary Services service access point (TNSS-SAP) of the TETRA voice plus data layer 3 service boundary. The SS-AL service access point is used in conformance testing as a normative boundary in TETRA Mobile Stations (MSs).

NOTE 1: As the present document only deals with the SS-AL all the service primitives has been shown without a TNSS-AL-prefix e.g. the TNSS-AL-INVOKE request is shorten into an INVOKE request.

The services offered to users of SS-AL are defined as service primitives containing service parameters. The service primitives are defined in clauses 4.2 and 4.3 and the service parameters are defined in clause 4.4.

In addition to the defined service primitives a SwMI may respond by a service not supported or a process not supported primitives as appropriate, refer EN 300 392-9 [3].

NOTE 2: As the present document does not describe a man-machine interface nor user applications the service primitives are used to define information exchange to and from the standardized part of the MS/LS. Those primitives may not be accessible directly nor indirectly.

Examples of information flows are presented in EN 300 392-11-21 [i.1].

4.2 SS-AL services offered over the TNSS-SAP

4.2.1 SS-AL service primitives to served user

The SS-AL service primitives at the served user MS/LS (FE1) TNSS-SAP are:

- a) INTERROGATE request;
- b) INTERROGATE indication;
- c) INVOKE1 request;
- d) INVOKE1 indication;
- e) INVOKE2 request;
- f) INVOKE2 indication;
- g) INVOKE3 request;
- h) INVOKE3 indication; and
- i) STOP LISTENING request.

4.2.2 SS-AL service primitives to affected user

The SS-AL service primitives at the affected user MS/LS (FE5) TNSS-SAP are:

- a) INVOKE indication; and
- b) INVOKE ACK request.

4.2.3 SS-AL service primitive to second listening party

The SS-AL service primitive at the second listening party MS/LS (FE6) TNSS-SAP is:

- a) INFORMATION indication.

NOTE: In the present document primitives request and indication are used instead of request and confirmation as there may not be a one to one correspondence between those primitives, e.g. there can be multiple responses as indications due to a single request.

The information contained in the following argument description tables correspond to the following key:

- C/O/M: conditional/optional/mandatory;
- Remark: comment.

4.3 Service primitive descriptions

4.3.1 INFORMATION indication

The INFORMATION indication shall be presented to the application from FE6 to indicate to the second listening party that the incoming call is an ambience listening call. The primitive shall contain the SS-AL information parameters listed in table 1.

Table 1: INFORMATION indication primitive contents

Parameter	Indication	Remark
Affected user TETRA identity	M	
Listening party identity	O	See note
NOTE: This parameter is not available, when the Notification indicator is used alone.		

4.3.2 INTERROGATE request

The INTERROGATE request primitive shall be offered from application to FE1 over TNSS-SAP when a served user interrogates whether an affected user is ambience listened to. The primitive shall contain the SS-AL information parameters listed in table 2.

Interrogated TETRA identity parameter is a repeatable parameter that shall define one individual number, a list of individual numbers or a range of individual numbers. There shall be at least one defined TETRA identity in a INTERROGATE request. SNA, if used, should refer to a SNA defined for served user.

The implementation of INTERROGATE request is optional.

Table 2: INTERROGATE request primitive contents

Parameter	Request	Remark
Interrogated TETRA identity	M	Repeatable

4.3.3 INTERROGATE indication

The INTERROGATE indication primitive shall be offered from FE1 to application over TNSS-SAP as a response to a previously sent interrogation request to the served user. The primitive shall contain the SS-AL information parameters listed in table 3.

Interrogated individual TETRA identity parameter is a repeatable parameter that shall define one individual number, a list of individual numbers or a range of individual numbers. There shall be at least one defined group TETRA identity in a INTERROGATE request. SNA, if used, should refer to a SNA defined for served user.

Implementation of INTERROGATE indication is mandatory, if INTERROGATE request is supported.

Table 3: INTERROGATE indication primitive contents

Parameter	Indication	Remark
Interrogated TETRA identity	M	Repeatable
Interrogation result	M	Repeatable