



**Fixed Radio Systems;
Characteristics and requirements for
point-to-point equipment and antennas;
Part 1: Overview and system-independent
common characteristics**

STANDARDS PREVIEW
<https://standards.iteh.ai/catalog/standards/sist/1d-27ee-460c-8a1a-8fba0bbfcb57/etsi-en-302-217-1-v2-1-2013-07>

Reference

REN/ATTM-04016

Keywords

antenna, DFRS, digital, DRRS, FWA, point-to-point, radio, transmission

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2013.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and LTE™ are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

| | |
|---|-----------|
| Intellectual Property Rights | 4 |
| Foreword..... | 4 |
| Introduction | 5 |
| 1 Scope | 12 |
| 2 References | 12 |
| 2.1 Normative references | 12 |
| 2.2 Informative references | 15 |
| 3 Definitions, symbols and abbreviations | 17 |
| 3.1 Definitions | 17 |
| 3.2 Symbols | 22 |
| 3.3 Abbreviations | 23 |
| 4 General characteristics | 26 |
| 4.1 Performance and availability requirements | 26 |
| 4.2 Environmental profiles | 26 |
| 4.2.1 Environmental profile declared under the R&TTE Directive | 26 |
| 4.2.2 ETSI environmental profiles | 26 |
| 4.2.2.1 Equipment within weather-protected locations (indoor locations) | 27 |
| 4.2.2.2 Equipment for not-weather-protected locations (outdoor locations) | 27 |
| 4.2.3 Test environment profiles | 27 |
| 4.3 Power supply | 27 |
| 4.3.1 Power supply profile declared under the R&TTE Directive | 27 |
| 4.3.2 ETSI power supply profile | 28 |
| 4.4 System block diagram | 28 |
| 5 Baseband interfaces and parameters | 28 |
| 5.1 Plesiochronous interfaces | 29 |
| 5.2 ISDN interfaces | 29 |
| 5.3 Synchronous digital hierarchy interfaces | 29 |
| 5.4 Other baseband data interfaces | 29 |
| Annex A (informative): Miscellaneous characteristics..... | 30 |
| A.1 Telecommunications Management Network (TMN) interface | 30 |
| A.2 Mechanical characteristics | 30 |
| Annex B (informative): Notification of interfaces under article 4.1 of the R&TTE Directive | 31 |
| B.1 Applicability of TCAM-RIG format of radio interface specifications to Fixed Services | 31 |
| B.2 Proposed list of radio interface specifications for Fixed Services..... | 32 |
| Annex C (informative): Cross references to previously relevant ENs and TSs | 33 |
| History | 36 |

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Access, Terminals, Transmission and Multiplexing (ATTM).

The present document is part 1 of a multi-part deliverable covering the Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas, as identified below:

Part 1: "Overview and system-independent common characteristics";

Part 2-1: "System-dependent requirements for digital systems operating in frequency bands where frequency co-ordination is applied";

Part 2-2: "Digital systems operating in frequency bands where frequency co-ordination is applied; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive";

Part 3: "Equipment operating in frequency bands where both frequency coordinated or uncoordinated deployment might be applied; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE";

Part 4-1: "System-dependent requirements for antennas";

Part 4-2: "Antennas; Harmonized EN covering the essential requirements of article 3.2 of R&TTE Directive".

National transposition dates

| | |
|--|-------------------|
| Date of adoption of this EN: | 25 June 2013 |
| Date of latest announcement of this EN (doa): | 30 September 2013 |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 31 March 2014 |
| Date of withdrawal of any conflicting National Standard (dow): | 31 March 2014 |

Major variants with respect to previous published version

- System options identification has been changed, in line with corresponding changes in Parts 2-1 [i.33] and 2-2 [i.34] of EN 302 217. Old systems notations (A.1, ... B.1, ... C.1, ... D.1, ... E.1 ...) have been removed and the system capacity is defined in term of minimum Radio Interface Capacity (RIC) rather than previous hierarchic PDH/SDH interfaces. Each equipment in the scope of the present document refers to a coherent set of transmitter and receiver requirements uniquely defined on the basis of the following identifying parameters:
 - 1) operating frequency band;
 - 2) operating radio frequency channel separation;

- 3) spectral efficiency class, to which the minimum RIC density is associated.
- Cross reference to older "historical" source ENs, no longer of interest has been moved to an annex.
 - Required new and updated "definitions".
 - Alignment of frequency bands and equipment options introduced in other parts of EN 302 217 series.

Introduction

(i) Generality and historical background

Digital Fixed Radio Systems (DFRS), used in European countries, had been historically specified in a relatively large number of specific European Norms produced by ETSI.

Those previous documents, already superseded by first version of this EN 302 217 series, contained both essential requirements and other requirements that, even if not considered essential under the Directive 1999/5/EC [1] of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (hereafter mentioned as the R&TTE Directive) [1], may be applicable.

Standards for point-to-point systems, including antennas, cover a very large range of traffic capacities, channel separations (CS), modulation formats and applications over a very wide range of frequency bands that are summarized in table 1.

Table 1: Digital Fixed Radio Systems (DFRS) parameters

| Parameter | Range |
|----------------------|--|
| Frequency bands | from 1 GHz to 86 GHz |
| Traffic capacities | from 9,6 kbit/s to 622 Mbit/s and to Gigabit/s and above in the highest bands |
| Channel separations | from 25 kHz to 112 MHz and to Gigahertz and above in the highest bands |
| Modulation formats | from 2 to 2 048 states (amplitude and/or phase and/or frequency modulated states) |
| Typical applications | <p>POINT-TO-POINT (P-P) CONNECTIONS: rural and urban low/medium/high capacity links for mobile infrastructure, transport/trunk (long haul), FWA/BWA/MWA backhaul, access, governmental (non-military) links, private fixed networks, SAP/SAB P to P audio and video links</p> <p>STAND ALONE ANTENNAS: for all of the above applications when integral antennas are not employed</p> |

The regulatory framework for placing radio systems on the market, established by the R&TTE Directive [1] also requires the availability of Harmonized ENs covering the essential requirements under article 3.2 of the R&TTE Directive [1]. EN 302 217 series meet this demand by providing a rational subdivision of requirements into general, system dependent "not essential" and "essential" requirements from the perspective of the R&TTE Directive [1].

Part 1 includes system-independent common characteristics; these requirements are not essential under article 3.2 of the R&TTE Directive [1].

EN 302 217-2-2 [i.34], EN 302 217-3 [i.35] and EN 302 217-4-2 [i.37] are relevant to essential requirements under article 3.2 of the R&TTE Directive [1]. Additional system can be added for new available FS bands and for completing market available options.

In the present document, equipment is grouped into families of either similar frequency bands or applications. Five families are identified for frequency bands where frequency co-ordination is applied, corresponding, in both EN 302 217-2-1 [i.33] and EN 302 217-2-2 [i.34], to annexes referenced from A to E and one family associated with applications of packet data and combination of other signals mapped into proprietary transport modules, detailed in annex F.

- A frequency bands from 1,4 GHz to 2,7 GHz;
- B frequency bands from 3 GHz to 11 GHz (channel separation around 60 MHz and from 1,75 MHz up to around 30 MHz);
- C frequency bands from 3 GHz to 11 GHz (channel separation 40 MHz);
- D frequency bands 13 GHz, 15 GHz and 18 GHz;
- E frequency bands from 23 GHz to 55 GHz;
- Ea frequency bands from 71 GHz to 76 GHz and 81 GHz to 86 GHz (additional requirements when link-by-link coordination is applied);
- F definition of equivalent data rates for packet data, PDH/SDH and other signals on the traffic interface.

In the same way EN 302 217-3 [i.35] three families are identified for frequency bands where either co-ordinated or uncoordinated deployment might be applied (see note), corresponding to annexes referenced from UA to UC.

- UA frequency band from 57 GHz to 59 GHz;
- UB frequency band from 64 GHz to 66 GHz;
- UBa frequency band from 57 GHz to 66 GHz (alternative, in overlapping bands, to UA and UB);
- UC frequency bands from 71 GHz to 76 GHz and 81 GHz to 86 GHz.

NOTE: In these bands, CEPT administrations might have different views on the licensing and deployment requirements, ranging among uncoordinated, user self coordination (sometimes called "light licensing") or conventional link-by-link coordination. Therefore, from R&TTE Directive [1] point of view, the minimum of characteristics are considered among essential requirements, unless there is clear evidence that link-by-link coordination is the predominant method and additional requirements are consequently defined in EN 302 217-2-2 [i.34]; in this case, the supplier may chose between a "minimal" or a more complete assessment according the extension of the market addressed.

(ii) Cross references to previously relevant ENs and TSs

The EN 302 217 series replaced and superseded a number of older standards (frequency and/or capacity oriented), which remained, only as "historical" documents, in the ETSI data base. Provided that they may still be referenced in some documentation, annex C provides, for information, an overview of the correspondence between equipment considered in those standards and part/annexes in the present document.

Table 2: Void

(iii) Summary of system options provided

A number of options for equipment implementation are identified in EN 302 217 series; the set of characteristics applicable to each option is uniquely identified through three parameters:

- operating frequency band;
- operating radio frequency channel separation (CS);
- spectral efficiency class (as defined in EN 302 217-2-2 [i.34]).

Each option so identified has a "nominal" payload requirement in term of minimum RIC (Radio Interface Capacity) to be fulfilled when packet payloads are used (e.g. Ethernet, ATM, etc.); in case PDH/SDH traffic are alternatively provided, annex F of EN 302 217-2-2 [i.34] gives the translation from the minimum RIC to the minimum hierarchic interfaces.

Table 3 summarizes the relevant cross-reference between channel separation in various Fixed Service frequency bands and the available options of equipment provided in EN 302 217 series. They are shown in term of the minimum RIC payload, which, depending on the channel separation, correspond to a specific spectral efficiency class detailed in clause 1.2 of EN 302 217-2-2 [i.34] (identified, with increasing spectral efficiency, as classes 1, 2, 3, 4L, 4H, 5L, 5H, 6L, 6H 7 and 8). In classes from 5 to 8, two further sub-classes suffix (i.e. A and B) are provided for the same channel separation depending on whether ACAP or CCDP operation is, respectively, considered for the equipment use.

The minimum RIC payload in tables 3a and 3b are the minimum required for conformance to the present document and are based on the "minimum RIC density" defined, for each spectral efficiency class, in clause 1.2 of EN 302 217-2-2 [i.34]. Only some cases of systems in annex A, due to the smaller channel separation provided, are (exceptionally) labelled with typical *gross bit rate* rather than minimum RIC capacity rates.

However, equipment may offer a variety of base band interfaces, e.g. typical hierarchical rates PDH or SDH, ISDN, Ethernet as well as mixture of these or other standardised interfaces. Mapping/multiplexing of the various base-band interfaces into common frame(s) suitable for radio transmission may be done using standardised higher hierarchical frames or other proprietary methods.

Tables F.1a through F.1h in annex F of EN 302 217-2-2 [i.34] summarise the "minimum RIC" considered in the present document and, when only PDH or SDH interfaces are provided, give the equivalent capacity in term of number of 2 048 Mbit/s streams provided as multiple or single multiplexed PDH or SDH interfaces. These minimum capacities will be associated to the relevant channel separation and spectral efficiency classes defined.

The cells in tables 3a and 3b are filled only on the basis of available physical single equipment transmission capacity (up to a minimum RIC of 862 Mbit/s for class 8 systems), which is relevant for R&TTE Directive [1] Art. 3.2 assessment. Doubled capacity is, in principle, possible for any option using CCDP operation or, more in general, subdividing the payload over two channels; however, specific test procedures are provided in EN 302 217-2-2 [i.34] only for STM-4 interface or other high speed data interfaces when their payload is split over more than one equipment.

ETSI STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/1eb74723-2013-460c-8a1a-8fba0bbfdb57/etsi-en-302-217-1-v2.1.1-2013>

Table 3a: Cross reference of available equipment and antenna requirements in parts and annexes of EN 302 217 series:
Bands from 1,4 GHz to 18 GHz

| EN 302 217 series | | | | | | | | | | | | | | | | | |
|---|----------------------------|---|----------|---------------|----------|--|--------|-----|-------------|-----------------|-----------------------------|--------------------------|--------------|--------------|------------------|------------------|--|
| Common requirements → | | Part 1 (present document) (System independent common characteristics) | | | | | | | | | | | | | | | |
| Antenna requirements → | | Part 4-1 (Antenna general and complementary requirements) and Part 4-2 (HS for R&TTED Art. 3.2 Antenna characteristics) | | | | | | | | | | | | | | | |
| Equipment requirements → | | Part 2-1 (system-dependent complementary characteristics) and Part 2-2 (HS for R&TTED Art. 3.2 equipment characteristics) | | | | | | | | | | | | | | | |
| Relevant annex in Part 2-1 and Part 2-2 ⇒ | | A | | | | | B or D | | | | | | | | C | | |
| Frequency band (GHz)⇒ | | 1,4; 2,4 | 2,1; 2,6 | 1,4; 2,1; 2,6 | 2,1; 2,6 | Annex B : 3,5 ; 4 ; U4 ; L6 ; U6 ; 7 ; 8 ; 10,5 ; 11 Annex D : 13 ; 15 ; 18 | | | | | | | | Annex B : U6 | 4, U4, U6, 8, 11 | | |
| Minimum RIC (Mbit/s) provided with relevant equipment characteristics | Channel separation (MHz) ⇨ | CS < 1,75 and 2 | 1,75 | 3,5 | 7 | 14 | 1,75 | 3,5 | 7 | 13,75 / 14 / 15 | 27,5 / 28 / 29 / 29,65 / 30 | 55 / 56 / 58 / 59,3 / 60 | 110 (note 1) | 20 | 40 | | |
| | Spectral efficiency ↓ | | | | | | | | | | | | | | | | |
| | Reference index ↓ | Class ↓ | | | | | | | | | | | | | | | |
| | 1 | 1 | (note 2) | | 2 | | | | | | | | | | | | |
| | 2 | 2 | (note 2) | 2 | 4 | 8 | 16 | 2 | 4 | 8 | 16 | 32 | 64 | 128 | | | |
| | 3 | 3 | | | | | | 3 | 6 | 12 | 24 | 48 | 96 | 191 | | | |
| | 4 | 4L | (note 2) | 4 | 8 | 16 | 32 | 4 | 8 | 16 | 32 | 64 | 128 | 256 | 45 | | |
| | 5 | 4H | | | | | | | sSTM-14 (*) | 24 | 49 | 98 | 196 | 392 | | | |
| | 6 | 5L | | | | | | | | 29 | 58 | | | | | | |
| | 6 | 5LA, 5LB | | | | | | | | | | 117 | 235 | 470 | | 168 | |
| | 7 | 5H | | | | | | | sSTM-22 (*) | 34 | 68 | | | | | | |
| | 7 | 5HA, 5HB | | | | | | | | | | 137 | 274 (**) | 548 | | 137 (***) 196 | |
| | 8 | 6L | | | | | | | | 39 | 78 | | | | | | |
| | 8 | 6LA, 6LB | | | | | | | | | | 156 | 313 | 627 | | 224 | |
| 9 | 6H | | | | | | | | | 88 | | | | | | | |
| 9 | 6HA, 6HB | | | | | | | | | | 176 | 352 | 705 | | 252 (**) | | |
| 10 | 7 | | | | | | | | | 98 | | | | | | | |
| 10 | 7A, 7B | | | | | | | | | | 196 | 392 | 784 | | 280 | | |
| 11 | 8 | | | | | | | | | 107 | | | | | | | |
| | 8A, 8B | | | | | | | | | | 215 | 431 | 862 | | 308 | | |
| Equivalent capacity for hierarchic-only systems | | Annex F of parts 2-1 [i.33] and 2-2 [i.34] | | | | | | | | | | | | | | | |

NOTE 1: CS 110 MHz available only in 18 GHz band.
NOTE 2: For channel separations of 2 MHz and other various smaller than 1,75 MHz, only typical "gross bit rates" are defined.
(*): These systems are intended only for the transport of subSTM-0 capacities only in 18 GHz band.
(**): STM-4 capacity as combination of two 2 x STM-1 equipment operating on two channels in ACAP or CCDP or even non adjacent operation is also described.
(***) : Minimum RIC 137 Mbit/s option is special provision only for commonality of use of 5HB/28 MHz like equipment modulation also into 40 MHz channel arrangements.

**Table 3b: Cross reference of available equipment and antenna requirements in parts and annexes of EN 302 217 series:
Bands from 23 GHz to 80 GHz**

| EN 302 217 series | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|-----------------------|---|--------------------------|-----|-----|-----|-----------------------|------------|--------------------------|--------------------|--------------------|---------------------|----------------------|--------------------------------|----------------------|----------------------|----------------------|----------------------|-------|--|-------|--|----------|-------------------|----------|----------|
| Common requirements ⇨ | | Part 1 (present document) (System independent common characteristics) | | | | | | | | | | | | | | | | | | | | | | | | |
| Antenna requirements ⇨ | | Part 4-1 (Antenna general and complementary requirements) and Part 4-2 (HS for R&TTED Art. 3.2 Antenna characteristics) | | | | | | | | | | | | | | | | | | | | | | | | |
| Equipment requirements ⇨ | | Part 2-1 (system-dependent complementary characteristics) and Part 2-2 (HS for R&TTED Art. 3.2 equipment characteristics) | | | | | | | | | | | | | | | | | | Part 3 (R&TTED Art. 3.2 equipment characteristics) | | | | | | |
| Relevant annex Part 2-2 ⇨ | | E | | | | | | | | | | Ea (note 1) | | | | | | | | | | UA | UB | UBa | UC | |
| Frequency band (GHz) ⇨ | | 23, 26, 28, 31, 32, 38, 42 | | | | | | 50, 52, 55 | | | | | | 71 to 76 and 81 to 86 (note 1) | | | | | | | | 57 to 59 | 64 to 66 | 57 to 66 (note 2) | 71 to 76 | 81 to 86 |
| Minimum RIC (Mbit/s) provided with relevant equipment characteristics | Spectral efficiency ↓ | | Channel separation (MHz) | | | | | | Channel separation (MHz) | | | | | Channel separation (MHz) | | | | | | | | Channel size free or multiple of predefined slots | | | | |
| | Reference index ↓ | Class ↓ | 3,5 | 7 | 14 | 28 | 56 | 112 | 3,5 | 7 | 14 | 28 | 56 | 250 | 500 | 750 | 1 000 | 1 250 | 1 500 | 1 750 | 2 000 | | | | | |
| | 1 | 1 | | | | | | | 2 | 4 ^(***) | 8 ^(***) | 16 ^(***) | 32 ^(***) | 142 | 285 | 427 | 570 | 712 | 855 | 997 | 1 140 | See minimum spectral efficiency reported in the annexes. | | | | |
| | 2 | 2 | 4 ^(**) | 8 | 16 | 32 | 64 | 128 | 4 | 8 | 16 | 32 | 64 ^(***) | 285 | 570 | 855 | 1 140 ^(*) | 1 425 | 1 710 | 1 995 | 2 280 | | | | | |
| | 3 | 3 | 6 ^(**) | 12 | 24 | 48 | 96 | 191 | 6 | 12 | 24 | 48 | 96 ^(***) | 425 | 850 | 1 275 | 1 700 | 2 125 ^(*) | 2 550 | 2 975 | 3 400 | | | | | |
| | 4 | 4L | 8 ^(**) | 16 | 32 | 64 | 128 | 256 | | 16 | 32 | 64 | 128 ^(***) | 570 | 1 140 ^(*) | 1 710 | 2 280 ^(*) | 2 850 | | | | | | | | |
| | 5 | 4H | | 24 | 49 | 98 | 196 | 392 | | | | | | 875 | 1 750 | 2 625 | | | | | | | | | | |
| | 6 | 5L | | 29 | 58 | | | | | | | | | | | | | | | | | | | | | |
| | 6 | 5LA, 5LB | | | | 117 | 235 | 470 | | | | | | 1 050 ^(*) | 2 100 ^(*) | 3 150 ^(*) | | | | | | | | | | |
| | 7 | 5H | | 34 | 68 | | | | | | | | | | | | | | | | | | | | | |
| | 7 | 5HA, 5HB | | | | 137 | 274 ^(****) | 548 | | | | | | 1 225 | 2 450 | | | | | | | | | | | |
| | 8 | 6L | | 39 | 78 | | | | | | | | | | | | | | | | | | | | | |
| | 8 | 6LA, 6LB | | | | 156 | 313 | 627 | | | | | | 1 400 | 2 800 | | | | | | | | | | | |
| 9 | 6H | | | 88 | | | | | | | | | | | | | | | | | | | | | | |
| 9 | 6HA, 6HB | | | | 176 | 352 | 705 | | | | | | | | | | | | | | | | | | | |
| 10 | 7 | | | 98 | | | | | | | | | | | | | | | | | | | | | | |
| 10 | 7A, 7B | | | | 196 | 392 | 784 | | | | | | | | | | | | | | | | | | | |
| 11 | 8 | | | 107 | | | | | | | | | | | | | | | | | | | | | | |
| 11 | 8A, 8B | | | | 215 | 431 | 862 | | | | | | | | | | | | | | | | | | | |
| Equivalent capacity for hierarchic only systems | | Annexes F of parts 2-1 and 2-2 | | | | | | | | | | | | | | | | | | | | | | | | |

NOTE 1: Requirements for the bands 71 GHz to 76 GHz and 81 GHz to 86 GHz in annex Ea of Part 2-2 [i.34] are "additional" to those reported in annex UC of Part 3 [i.35].

NOTE 2: Alternative, in overlapping bands, to annexes UA and UB.

(*): RIC rounded down to closest $N \times 1$ Gbit/s rate shall also be considered valid.

(**): Not provided in 42 GHz band.

(***): Not provided in 50 GHz band.

(****): STM-4 capacity as combination of two 2 x STM-1 equipment operating on two channels in ACAP or CCDP or even non adjacent operation is also described.

(iv) User's guide

The requirements applicable to a specific point to point digital fixed radio systems (including its antenna) are summarised in figure 0 showing the major structure of the whole EN 302 217 series. The requirements are subdivided across the six parts of the EN series corresponding to their four major categories.

The first category (the present document) corresponds to "common" system independent characteristics which are either common to the whole family of equipment, i.e. performance and availability, environmental profiles, power supply, system block diagram, TMN interface, mechanical characteristics and baseband interfaces and parameters. The symbols and abbreviations, which apply to the EN 302 217 series, are listed in the present document. The present document defines those requirements and characteristics set out in the other parts of EN 302 217 series.

The second category (found in EN 302 217-2-1 [i.33] and EN 302 217-4-1 [i.36]) corresponds to "complementary" characteristics and requirements, which are not relevant to article 3.2 of the R&TTE Directive [1] but may guarantee better performance to the actual deployed links. Therefore, the supplier may wish to claim compliance to all or some of these requirements for showing enhanced characteristics of its product.

However, for completeness, EN 302 217-2-1 [i.33] and EN 302 217-4-1 [i.36] provide comprehensive description of the "main" and "complementary" requirements, for equipment operating in co-ordinated frequency bands and for "antennas".

Main requirements are requirements that are also related to the "essential requirements" under article 3.2 of the R&TTE Directive [1] and are further detailed in EN 302 217-2-2 [i.34], for equipment operating in co-ordinated frequency bands, and EN 302 217-4-2 [i.37], for antennas.

Complementary requirements are requirements that are not related to essential requirements under article 3.2 of the R&TTE Directive [1]. Nevertheless they are considered, having been commonly agreed for proper system operation and deployment when specific deployment conditions or compatibility requirements are present. Compliance to all or some of these requirements is made on a voluntary basis.

The limits for main and complementary requirements that are not common or parameterized for all of the equipment covered by one part, but specific to one frequency range, one RIC or PDH/SDH capacity, etc., are located in annexes.

The third category (EN 302 217-2-2 [i.34] and EN 302 217-4-2 [i.37]) is for equipment intended for frequency bands where link-by-link radio frequency coordination (either under administration control or required to the users in licensing procedure) over a specific radio frequency channels arrangement is generally used; it corresponds to essential phenomena, with respect to article 3.2 of the R&TTE Directive [1] and are consequently defined in harmonized standards. In this case a complete set of TX and RX parameters is retained essential and requirements are provided in the same format as in EN 302 217-2-1 [i.33] and EN 302 217-4-1 [i.36]. The limiting values associated with the essential requirements which are not common to all of the equipment covered by one part, but specific to one frequency range, one RIC or PDH/SDH capacity, etc, are located in annexes. Reference to each annex is the same for EN 302 217-2-1 [i.33] as in EN 302 217-2-2 [i.34]. An HS-RTT (requirements table) summarizes those requirements to be addressed in order to claim compliance.

The fourth category (EN 302 217-3 [i.35] and still EN 302 217-4-2 [i.37]) is for equipment intended for frequency bands where, for their propagation or regulatory nature, the conventional link-by-link radio frequency coordination is not generally used and a number of administrations may also apply less restrictive (and less protecting) regulatory measures. It still corresponds to essential phenomena, with respect to article 3.2 of the R&TTE Directive [1] and are consequently defined as harmonized standards. In this case a reduced set of TX and RX parameters is retained essential; however, when the coordinated deployment is considered predominant, additional set of requirements is further included in EN 302 217-2-2 [i.34] and the supplier may chose between the "minimal" or the more complete assessment according the extension of the market addressed.

To conclude, EN 302 217 series will be used as a decision tree, from the present document down to the relevant annexes/sub-annexes of parts EN 302 217-2-1 [i.33], EN 302 217-2-2 [i.34] and EN 302 217-3 [i.35].

At every level, a check of compliance is recommended to be performed.

| | |
|---|--|
| <p>EN 302 217-2-1 System dependent requirements for digital systems operating in frequency bands where frequency co-ordination is applied</p> <p>4 General characteristics 5 Main requirements 6 Complementary requirements</p> <p>Annex A Frequency bands 1,4 GHz to 2,7 GHz Annex B Frequency bands from 3 GHz to 11 GHz (CS up to 30 MHz) Annex C Frequency bands from 3 GHz to 11 GHz (CS 40 MHz) Annex D Frequency bands 13 GHz, 15 GHz and 18 GHz Annex E Frequency bands from 23 GHz to 55 GHz Annex Ea Frequency bands 71 GHz to 76 GHz and 81 GHz to 86 GHz Annex F Transmission of Packet Data Annex G (informative) Additional information</p> | <p>EN 302 217-2-2 (Harmonized Standard) Digital systems operating in frequency bands where frequency co-ordination is applied; Harmonized EN covering the essential requirements of Article 3.2 of the R&TTE Directive</p> <p>4 Technical requirements specifications 4.1 Environmental profile 4.2 Transmitter requirements 4.3 Receiver requirements 4.4 Antenna directional requirements 5 Testing for compliance with technical requirements</p> <p>Annex A (normative) Frequency bands 1,4 GHz to 2,7 GHz Annex B (normative) Frequency bands from 3 GHz to 11 GHz (CS up to 30 MHz and 56/60 MHz) Annex C (normative) Frequency bands from 3 GHz to 11 GHz (CS 40 MHz) Annex D (normative) Frequency bands 13 GHz, 15 GHz and 18 GHz Annex E (normative) Frequency bands from 23 GHz to 55 GHz Annex Ea (normative) Frequency bands 71 GHz to 76 GHz and 81 GHz to 86 GHz Annex F (normative) Definition of equivalent data rates for packet data, PDH/SDH and other signals on the traffic interface Annex G (normative) Test report in relation to flexible systems applications Annex H (normative) HS Requirement & conformance Test specifications (HS-RTT) Annex I (informative) Impact of power control (ATPC and/or RTPC), mixed mode and bandwidth adaptive operation on spectrum mask and link design requirements Annex J (informative) Typical interference sensitivity behaviour for frequency planning purpose</p> |
| <p>EN 302 217-3 (Harmonized Standard) Equipment operating in frequency bands where both frequency coordinated or uncoordinated deployment might be applied. Harmonized EN covering essential requirements of Article 3.2 of R&TTE Directive</p> <p>4.1 Environmental profile 4.2 RF channel selection 4.3 Transmitter requirements 4.4 Receiver requirements 5 Testing for compliance to technical requirements</p> <p>Annex A (normative) HS Requirement & conformance Test specifications (HS-RTT) Annex B (normative) Wide radio frequency band covering units and multirate equipment specification and tests Annex UA (normative) Frequency band around 58 GHz Annex UB (normative) Frequency band 64 GHz to 66 GHz Annex UBa (normative) Frequency band 57 GHz to 66 GHz Annex UC (normative) Frequency bands 71 GHz to 76 GHz and 81 GHz to 86 GHz Annex UD (informative) Rationale for the interference limit formula Annex UE (informative) Capacity and Receiver characteristics in the bands 64 GHz to 66 GHz, 71 GHz to 76 GHz and 81 GHz to 86 GHz</p> | <p>EN 302 217-4-1 System dependent requirements for antennas</p> <p>4 Frequency bands 5 Classification of antennas 6 Electrical characteristics</p> <p>Annex A (normative) Standardized RPE for Class 1 antennas in bands 3 GHz to 86 GHz Annex B (informative) Additional information Annex C (informative) Antenna gain and RPE information</p> |
| | <p>EN 302 217-4-2 (Harmonized Standard) Antennas; Harmonized EN covering the essential requirements of article 3.2 of R&TTE Directive</p> <p>4 Technical requirements specifications 4.1 Environmental profile 4.2 Radiation Pattern Envelope (RPE) 4.3 Cross-Polar Discrimination (XPD) 4.4 Antenna gain 5 Testing for compliance with technical requirements</p> <p>Annex A (normative) HS Requirement & conformance Test specifications (HS-RTT)</p> |

Figure 0: Structure of this EN 302 217 series