
Fiksni radijski sistemi - Karakteristike in zahteve za opremo in antene tipa točka-točka - 2-1. del: Sistemsko odvisne zahteve za digitalne sisteme, ki delujejo v frekvenčnih pasovih, kjer se uporablja frekvenčna koordinacija

Fixed Radio Systems - Characteristics and requirements for point-to-point equipment and antennas - Part 2-1: System-dependent requirements for digital systems operating in frequency bands where frequency co-ordination is applied

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 302 217-2-1 V2.1.1:2015](https://standards.iteh.ai/catalog/standards/sist/118ba55e-21b7-4704-87ab-53408c7dce31/sist-en-302-217-2-1-v2-1-1-2015)

<https://standards.iteh.ai/catalog/standards/sist/118ba55e-21b7-4704-87ab-53408c7dce31/sist-en-302-217-2-1-v2-1-1-2015>

Ta slovenski standard je istoveten z: EN 302 217-2-1 V2.1.1

ICS:

33.060.30	Radiorelejni in fiksni satelitski komunikacijski sistemi	Radio relay and fixed satellite communications systems
33.120.40	Antene	Aerials

SIST EN 302 217-2-1 V2.1.1:2015 **en**

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

SIST EN 302 217-2-1 V2.1.1:2015

<https://standards.iteh.ai/catalog/standards/sist/118ba55e-21b7-4704-87ab-53408c7dce31/sist-en-302-217-2-1-v2-1-1-2015>

ETSI EN 302 217-2-1 V2.1.1 (2014-12)



**Fixed Radio Systems;
Characteristics and requirements
for point-to-point equipment and antennas;
Part 2-1: System-dependent requirements
for digital systems operating in frequency bands
where frequency co-ordination is applied**

Reference

REN/ATTM-04017

Keywords

DFRS, digital, DRRS, FWA, point-to-point, radio,
regulation, transmission**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88**iTeh STANDARD PREVIEW**
(standards.iteh.ai)

SIST EN 302 217-2-1 V2.1.1:2015

<https://standards.iteh.ai/catalog/standards/sist/118ba55e-21b7-4704-87ab-53408c7dce37/etsi-en-302-217-2-1-v2-1-1-2015>**Important notice**

The present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
Introduction	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	8
3 Definitions, symbols and abbreviations	9
3.1 Definitions.....	9
3.2 Symbols.....	9
3.3 Abbreviations	9
4 General characteristics	9
4.1 Frequency bands and channel arrangements	9
4.2 Special compatibility requirements between systems	10
4.3 Transmission capacity and spectral efficiency	10
5 Main requirements.....	10
5.1 System nominal loading	11
5.2 Environmental profile.....	11
5.3 Transmitter characteristics.....	11
5.3.1 Transmitter power and power tolerance.....	11
5.3.1.1 Maximum power	11
5.3.1.2 Transmitter output power tolerance	11
5.3.2 Transmitter power and frequency control	12
5.3.2.1 Transmitter power control (ATPC and RTPC).....	12
5.3.2.1.1 Automatic Transmitter Power Control (ATPC).....	12
5.3.2.1.2 Remote Transmitter Power Control (RTPC)	13
5.3.2.2 Remote Frequency Control (RFC)	13
5.3.3 Radio Frequency (RF) spectrum mask.....	13
5.3.4 Discrete CW components exceeding the spectrum mask limit	13
5.3.4.1 Discrete CW components at the symbol rate	13
5.3.4.2 Other discrete CW components exceeding the spectrum mask limit	13
5.3.5 Spurious emissions - external	13
5.3.6 Radio frequency tolerance	13
5.4 Receiver characteristics	14
5.4.1 Spurious emissions-external	14
5.5 System performance without diversity.....	14
5.5.1 BER as a function of receiver signal level.....	14
5.5.2 Interference sensitivity.....	14
5.5.2.1 Co-channel "external" interference sensitivity	14
5.5.2.2 Adjacent channel interference sensitivity.....	14
5.5.2.3 CW spurious interference.....	14
6 Complementary requirements	15
6.1 Branching/feeder requirements	15
6.1.1 Waveguide flanges (or other connectors)	15
6.1.2 Return loss of feeder/antenna systems at equipment antenna port (C/C' reference point).....	16
6.2 Intermodulation products	16
6.3 Transmitter characteristics.....	17
6.3.1 Spurious emissions - internal.....	17
6.3.2 Radio Frequency (RF) spectrum mask when mixed supplier compatibility is required	17
6.4 Receiver characteristics	18
6.4.1 Maximum input level and input level range	18
6.4.2 Spurious emissions - internal	19

6.4.3	Image rejection	19
6.4.4	Innermost channel selectivity	20
6.5	System performance without diversity	20
6.5.1	Equipment Residual BER (RBER)	20
6.5.2	Distortion sensitivity	22
6.5.2.1	Introduction	22
6.5.2.2	Requirement	22
6.5.2.3	Assessment	23
6.5.3	Interference sensitivity for CCDP with XPIC operation	24
6.5.3.1	General	24
6.5.3.2	Co-channel "internal" interference sensitivity in flat fading conditions	24
6.6	System characteristics with diversity	24
6.6.1	Differential delay compensation	24
6.6.2	BER performance	24
Annex A (normative):	Spectrum masks and receiver selectivity when mixed supplier compatibility is required	25
A.0	Introduction	25
A.1	TX masks assessment	26
A.2	Normal channels - Emission mask floor	26
A.2.1	RBER impact	26
A.2.2	Local TX to RX compatibility	26
A.2.2.1	Spectrum mask	26
A.2.2.2	Receiver selectivity	27
A.3	Innermost channels for channel arrangements from about 4 GHz to about 8,5 GHz with channel separation of 28 MHz to 30 MHz	27
A.3.1	Innermost channels spectrum masks	27
A.3.2	Receiver innermost channel selectivity	29
A.4	Innermost channels for channel arrangements from about 4 GHz to 11 GHz with channel separation of 40 MHz	30
A.4.1	Innermost channels spectrum masks	30
A.4.2	Receiver innermost channels selectivity	31
A.5	Innermost channels for 18 GHz channel arrangements with channel separation of 55 MHz	32
A.5.1	Innermost channels spectrum masks	32
A.5.2	Receiver innermost channels selectivity	33
Annexes B to E:	Deleted and left void	35
Annex F (normative):	Definition of equivalent data rates for packet data, PDH/SDH and other signals on the traffic interface	36
Annex G (informative):	Additional information	37
G.1	Residual Bit Error Ratio (RBER) and Residual Frame Error Ratio (RFER)	37
G.2	Measurement test set for XPI characteristics	38
G.3	Differential delay compensation range	39
G.4	FER/BER equivalence and FER performance measurement equipment settings (example)	40
G.4.1	FER/BER equivalence	40
G.4.2	FER equipment settings and measurement techniques (example)	41
G.5	Automatic Transmitter Power Control (ATPC)	41
Annex H (informative):	Mitigation techniques referred in ERC/DEC(00)07 (18 GHz band)	43
Annex I (informative):	Change History	44
History		45

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Access, Terminals, Transmission and Multiplexing (ATTM).

The present document is part 2-1 of a multi-part deliverable covering the Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas. Full details of the entire series can be found in part 1 [15].

National transposition dates	
Date of adoption of this EN:	5 December 2014
Date of latest announcement of this EN (doa):	31 March 2015
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 September 2015
Date of withdrawal of any conflicting National Standard (dow):	30 September 2015

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**may not**", "**need**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The introduction of EN 302 217-1 [15] applies.

1 Scope

The present document summarizes all system-dependent requirements for Point-to-Point (P-P) equipment in applications deployed in bands where frequency co-ordination is generally applied. These requirements are introduced in two different clauses sub-sets:

- **Main requirements** are requirements that are also related to the "essential requirements" under article 3.2 of the R&TTE Directive [1] and further detailed in the Harmonized Standard EN 302 217-2-2 [16].
- **Complementary requirements** are requirements that are not related to essential requirements under article 3.2 of the R&TTE Directive [1]. Nevertheless they have been commonly agreed for proper system operation and deployment when specific deployment conditions or compatibility requirements are present. Compliance to all or some of these requirements is left to supplier decision.

Description and limits for parameters relevant to essential requirements under article 3.2 of R&TTE Directive [1] are given in the Harmonized Standard EN 302 217-2-2 [16].

For other system-dependent parameters where standardization is required but that do not affect the R&TTE Directive "essential requirements" mentioned above, description and limits are detailed in the present document in clause 6 and in the annex A, annex F and annex G.

The present document deals with Radio Frequency (RF) and base-band equipment characteristics; antenna system requirements are covered in EN 302 217-4-1 [i.9] and EN 302 217-4-2 [i.10].

The present document does not cover test procedures and test conditions which are set out in EN 301 126-1 [14].

As the maximum transmission rate in a given bandwidth depends on system spectral efficiency, equipment are subdivided in different spectral efficiency classes as defined in EN 302 217-2-2 [16].

The spectral efficiency classes are indicative only and do not imply any constraint to the actual modulation format, provided that all the requirements in the relevant parts of this Multi-part deliverable for the declared class are met.

Guidance on the definition of radio parameters relevant to the essential requirements under article 3.2 of R&TTE Directive [1] for DFRS may be found in TR 101 506 [i.6].

Technical background for most of the parameters and requirements referred to in this Multi-part deliverable may be found in TR 101 036-1 [i.5].

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- | | |
|-----|--|
| [1] | Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive). |
| [2] | CENELEC EN 122150: "Sectional Specification: Radio frequency coaxial connectors - Series EIA flange". |

- [3] CEPT/ERC/DEC(00)07: "ERC Decision of 19 October 2000 on the shared use of the band 17.7 - 19.7 GHz by the fixed service and Earth stations of the fixed-satellite service (space-to-Earth)".
- [4] ETSI EN 300 019-1-0: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-0: Classification of environmental conditions; Introduction".
- [5] ETSI EN 300 019-1-1: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-1: Classification of environmental conditions; Storage".
- [6] ETSI EN 300 019-1-2: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-2: Classification of environmental conditions; Transportation".
- [7] ETSI EN 300 019-1-3: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-3: Classification of environmental conditions; Stationary use at weatherprotected locations".
- [8] ETSI EN 300 019-1-4: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-4: Classification of environmental conditions; Stationary use at non-weatherprotected locations".
- [9] ETSI EN 300 019-2-0: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-0: Specification of environmental tests; Introduction".
- [10] ETSI EN 300 019-2-1: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-1: Specification of environmental tests; Storage".
- [11] ETSI EN 300 019-2-2: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-2: Specification of environmental tests; Transportation".
- [12] ETSI EN 300 019-2-3: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-3: Specification of environmental tests; Stationary use at weatherprotected locations".
- [13] ETSI EN 300 019-2-4: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-4: Specification of environmental tests; Stationary use at non-weatherprotected locations".
- [14] ETSI EN 301 126-1: "Fixed Radio Systems; Conformance testing; Part 1: Point-to-Point equipment - Definitions, general requirements and test procedures".
- [15] ETSI EN 302 217-1: "Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 1: Overview and system-independent common characteristics".
- [16] ETSI EN 302 217-2-2: "Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 2-2: Digital systems operating in frequency bands where frequency co-ordination is applied; Harmonized EN covering the essential requirements of Article 3.2 of the R&TTE Directive".
- [17] IEC 60153-2: "Hollow metallic waveguides. Part 2: Relevant specifications for ordinary rectangular waveguides".
- [18] IEC 60154-2: "Flanges for waveguides. Part 2: Relevant specifications for flanges for ordinary rectangular waveguides".
- [19] IEC 60169-1: "Radio-frequency connectors. Part 1: General requirements and measuring methods".
- [20] IEC 60339 (all parts): "General purpose rigid coaxial transmission lines and their associated flange connectors".

- [21] IEC 60835-2-4: "Methods of measurement for equipment used in digital microwave radio transmission systems - Part 2: Measurements on terrestrial radio-relay systems - Section 4: Transmitter/receiver including modulator/demodulator".
- [22] IEC 60835-2-8: "Methods of measurement for equipment used in digital microwave radio transmission systems - Part 2: Measurements on terrestrial radio-relay systems - Section 8: Adaptive equalizer".
- [23] IEEE 802.3-2005: "IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier Sense Multiple Access with Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications".
- [24] IEEE 1802.3-2001: "IEEE Conformance Test Methodology for IEEE Standards for Local and Metropolitan Area Networks - Specific Requirements - Part 3: Carrier Sense Multiple Access with Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications".
- [25] Void.
- [26] Recommendation ITU-R F.1093-2: "Effects of multipath propagation on the design and operation of line-of-sight digital fixed wireless systems".
- [27] Void.
- [28] Recommendation ITU-T O.151: "Error performance measuring equipment operating at the primary rate and above".
- [29] Recommendation ITU-T O.181: "Equipment to assess error performance on STM-N interfaces".
- [30] Recommendation ITU-T O.191: "Equipment to measure the cell transfer performance of ATM connections".

iTech STANDARD PREVIEW
(standards.iteh.ai)

2.2 Informative references

<https://standards.iteh.ai/catalog/standards/sist/118ba55e-21b7-4704-87ab-57d08c7c355c/etsi-en-302-217-2-1-v2-1-1-2015>

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ECC/REC(02)06: "Channel arrangements for digital Fixed Service Systems operating in the frequency range 7125-8500 MHz".
- [i.2] ERC/REC 12-03: "Harmonised radio frequency channel arrangements for digital terrestrial fixed systems operating in the band 17.7 GHz TO 19.7 GHz".
- [i.3] ERC/REC 14-01: "Radio-frequency channel arrangements for high capacity analogue and digital radio-relay systems operating in the band 5925 MHz - 6425 MHz".
- [i.4] ERC/REC 14-02: "Radio-frequency channel arrangements for high, medium and low capacity digital fixed service systems operating in the band 6425-7125 MHz".
- [i.5] ETSI TR 101 036-1: "Fixed Radio Systems; Generic wordings for standards on DFRS (Digital Fixed Radio Systems) characteristics; Part 1: General aspects and point-to-point equipment parameters".
- [i.6] ETSI TR 101 506: "Fixed Radio Systems; Generic definitions, terminology and applicability of essential requirements under the article 3.2 of 1999/05/EC Directive to Fixed Radio Systems".
- [i.7] ETSI TR 102 243-1: "Fixed Radio Systems; Representative values for transmitter power and antenna gain to support inter- and intra-compatibility and sharing analysis; Part 1: Digital point-to-point systems".
- [i.8] ETSI TR 103 103: "Fixed Radio Systems; Point-to-point systems; ATPC, RTPC, Adaptive Modulation (mixed-mode) and Bandwidth Adaptive functionalities; Technical background and impact on deployment, link design and coordination".

- [i.9] ETSI EN 302 217-4-1: "Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 4-1: System-dependent requirements for antennas".
- [i.10] ETSI EN 302 217-4-2: "Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 4-2: Antennas; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".
- [i.11] ETSI TR 101 854: "Fixed Radio Systems; Point-to-point equipment; Derivation of receiver interference parameters useful for planning fixed service point-to-point systems operating different equipment classes and/or capacities".
- [i.12] Recommendation ITU-R F.383-9: "Radio-frequency channel arrangements for high capacity fixed wireless systems operating in the lower 6 GHz (5 925 to 6 425 MHz) band".
- [i.13] Recommendation ITU-R F.384-11: "Radio -frequency channel arrangements for medium- and high-capacity digital fixed wireless systems operating in the 6 425-7 125 MHz band".
- [i.14] Recommendation ITU-R F.385-10: "Radio-frequency channel arrangements for fixed wireless systems operating in the 7 110-7 900 MHz band".
- [i.15] Recommendation ITU-R F.595-10: "Radio-frequency channel arrangements for fixed wireless systems operating in the 17.7-19.7 GHz frequency band".
- [i.16] Recommendation ITU-R P.530-15: "Propagation data and prediction methods required for the design of terrestrial line-of-sight systems".
- [i.17] J. Redd: "Calculating Statistical Confidence Levels for Error-Probability Estimates" Lightwave Magazine, pp. 110-114, April 2000.

NOTE: Available on the web at <http://www.lightwaveonline.com/>.

STANDARD PREVIEW
(standards.iteh.ai)

3 Definitions, symbols and abbreviations

<https://standards.iteh.ai/catalog/standards/sist/118ba55e-21b7-4704-87ab-53408c7dce31/sist-en-302-217-2-1-v2-1-1-2015>

3.1 Definitions

For the purposes of the present document, the terms and definitions given in EN 302 217-1 [15] apply.

3.2 Symbols

For the purposes of the present document, the symbols given in EN 302 217-1 [15] apply.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in EN 302 217-1 [15] apply.

4 General characteristics

4.1 Frequency bands and channel arrangements

Frequency bands and channel arrangements, which are relevant for equipment covered by the present document, are defined by Recommendation ITU-Rs and/or ECC (or CEPT/ERC) Recommendations and are referenced in the first table of each annex A through annex Ea (i.e. table A.1 through table Ea.1) of EN 302 217-2-2 [16].

Recommendation ITU-Rs and ECC (or CEPT/ERC Recommendation, see note) recommended frequency channel arrangements, known at the date of publication of this Multi-part deliverable, are set out for reference only. In general, the channel arrangement is relevant neither to article 3.2 of the R&TTE Directive [1] nor for other requirements in the present document; only the frequency band, actual channel separation and, in some cases innermost channels separation are relevant for defining the set of parameters and test suites relevant to each system.

NOTE: CEPT Recommendations were published until 2002 as CEPT/ERC Recommendations; consequently to the restructuring of ERC under new ECC organization, Recommendations developed after that date formally changed their reference as ECC Recommendations, without changing their applicability.

Other national or future Recommendation ITU-Rs or ECC Recommendations, set around the same or close to the frequency range of present Recommendation ITU-Rs or ECC Recommendations, are considered applicable to systems assessed against this Multi-part deliverable, provided that they use the same channel separation.

Specification and tests of wide radio-frequency band covering units and *multirate* or *mixed-mode* equipment are placed in normative annex G of EN 302 217-2-2 [16]. Whenever applicable, it is also valid for assessing parameters specified in the present document.

4.2 Special compatibility requirements between systems

There shall be no requirement to operate transmitting equipment from one supplier with receiving equipment from another and, depending on the deployment conditions, it shall be possible to operate the system in vertical and/or horizontal polarization, if required by the channel arrangement.

To be compatible with certain constraints given by existing installations and/or deployments already made with systems from other supplier or for different FS applications, new systems on the same path may be subject to additional requirements, other than those derived for a single supplier or same application environment.

NOTE: This does not imply that when a single supplier is involved there are no similar requirements; however, they do not need standardization because many other technical and cost-effective solutions might be flexibly adopted under suppliers' own responsibility only.

For the purposes of this Multi-part deliverable the following set of compatibility requirements between systems has been defined:

- a) There may be a requirement to multiplex different suppliers' equipment on the same polarization of the same antenna. This will not apply to systems with an integral antenna.
- b) There may be a requirement to multiplex different suppliers' equipment on different polarizations of the same antenna. This will not apply to systems with an integral antenna.

4.3 Transmission capacity and spectral efficiency

See clause 1.5 of EN 302 217-2-2 [16].

5 Main requirements

The following clauses summarize requirements related to the "essential requirements" under article 3.2 of the R&TTE Directive [1] that are further detailed in EN 302 217-2-2 [16]. However, for some requirements, besides the relevant essential limits set out in EN 302 217-2-2 [16] for the purpose of their separate publishing in the Official Journal of the European Communities (OJEU) under the R&TTE Directive [1], additional, non-essential, more stringent limits are here set out in response to specific compatibility requirements by network operators when deploying new systems on the same routes with existing systems from other suppliers.

5.1 System nominal loading

The specified transmitter and receiver characteristics shall be met with the appropriate baseband signals applied at reference point X' and received from reference point X of figure 1 of EN 302 217-1 [15].

Table 1: Baseband test signals

Type of baseband signal interface at X/X'	Test signal to be applied according to...
PDH	PRBS Recommendation ITU-T O.151 [28]
SDH	Recommendation ITU-T O.181 [29]
ATM	Recommendation ITU-T O.191 [30]
Ethernet interface (packet data)	IEEE 802.3 [23], IEEE 1802.3 [24]
Other than the above	Relevant standards which the interface refers to

5.2 Environmental profile

The required environmental profile for operation of the equipment shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the required operational environmental profile.

Preferably, the selected environmental profiles should be one of more ETSI profiles in EN 300 019 series (see [4] through [13]), standardized for various operating, transport and storage situations.

5.3 Transmitter characteristics

5.3.1 Transmitter power (and power tolerance)

5.3.1.1 Maximum power

The Maximum Output Power is an essential requirement under article 3.2 of R&TTE Directive [1] and is specified in EN 302 217-2-2 [16].

For guidance, in addition to the absolute maximum transmitter power, typical values of transmitter highest power for real equipment, of feeder loss and length, and of antenna diameter and gain are provided in TR 102 243-1 [i.7] in order to support inter-systems and intra-system compatibility and sharing analysis.

In some frequency bands, or parts of frequency bands, Recommendation ITU-Rs define specific limits in terms of output power and/or EIRP (or output power and/or EIRP density) in order to improve the compatibility with other Radio Services sharing these frequency bands with the FS.

An additional capability for output power level adjustment may be required, for regulatory purposes, in the interface regulations according to article 4.1 of the R&TTE Directive [1], in which case the range of adjustment, either by fixed or automatic attenuators, should be in increments of 5 dB or less.

In particular, for the band 18 GHz, the FS shall, where practical, implement the appropriate mitigation techniques as required in ERC/DEC(00)07 [3]. See annex H.

5.3.1.2 Transmitter output power tolerance

The power tolerance around the nominal output power together with the associated environmental profile, declared by the supplier, is considered essential under article 3.2 of R&TTE Directive [1]. For relevant limits see EN 302 217-2-2 [16].

Additionally, it should be taken into consideration that, in general, the declared profile for R&TTE Directive [1] assessment might not be coincident with the ETSI standardized ones in EN 300 019 series (see [4] through [13]), which have been specifically designed for telecommunication equipment in various deployment situations. Therefore, the supplier may decide to comply with equal or more stringent limits for operation of the system over some ETSI standardized environmental condition for which the system is designed to operate. Limits for this case are reported below.