
**Hexagon socket countersunk head
screws**

Vis à tête fraisée à six pans creux

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 10642:2004

<https://standards.iteh.ai/catalog/standards/sist/da3731b1-447c-4189-9d1d-f80fb4ef84/iso-10642-2004>



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 10642:2004

<https://standards.iteh.ai/catalog/standards/sist/da3731b1-447c-4189-9d1d-f680fb4ef84/iso-10642-2004>

© ISO 2004

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
1 Scope	1
2 Normative references	1
3 Dimensions and gauging of head	2
4 Requirements and reference International Standards	6
5 Designation	7

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 10642:2004

<https://standards.iteh.ai/catalog/standards/sist/da3731b1-447c-4189-9d1d-f680fb4ef84/iso-10642-2004>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 10642 was prepared by Technical Committee ISO/TC 2, *Fasteners*.

This second edition cancels and replaces the first edition (ISO 10642:1997), which has been technically revised.

ITEH STANDARD PREVIEW
(standards.iteh.ai)
<https://standards.iteh.ai/catalog/standards/sist/da3731b1-447c-4189-9d1d-f680fb4ef84/iso-10642-2004>

Hexagon socket countersunk head screws

1 Scope

This International Standard specifies the characteristics of hexagon socket countersunk head screws with threads from M3 up to and including M20, with product grade A and property classes 8.8, 10.9 and 12.9.

NOTE Particular attention is drawn to the note in Table 2 and to Table 3, concerning the limitation on ultimate tensile load.

If, in special cases, specifications other than those listed in this International Standard are required, they should be selected from existing International Standards, e.g. ISO 261, ISO 888, ISO 898-1, ISO 965-2 and ISO 4759-1.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 225, *Fasteners — Bolts, screws, studs and nuts — Symbols and designations of dimensions*

ISO 261, *ISO general-purpose metric screw threads — General plan*

ISO 888, *Bolts, screws and studs — Nominal lengths, and thread lengths for general purpose bolts*

ISO 898-1, *Mechanical properties of fasteners made of carbon steel and alloy steel — Part 1: Bolts, screws and studs*

ISO 965-2, *ISO general purpose metric screw threads — Tolerances — Part 2: Limits of sizes for general purpose external and internal screw threads — Medium quality*

ISO 965-3, *ISO general purpose metric screw threads — Tolerances — Part 3: Deviations for constructional screw threads*

ISO 3269, *Fasteners — Acceptance inspection*

ISO 4042, *Fasteners — Electroplated coatings*

ISO 4753, *Fasteners — Ends of parts with external ISO metric thread*

ISO 4759-1, *Tolerances for fasteners — Part 1: Bolts, screws, studs and nuts — Product grades A, B and C*

ISO 6157-1, *Fasteners — Surface discontinuities — Part 1: Bolts, screws and studs for general requirements*

ISO 6157-3, *Fasteners — Surface discontinuities — Part 3: Bolts, screws and studs for special requirements*

ISO 8992, *Fasteners — General requirements for bolts, screws, studs and nuts*

ISO 10683, *Fasteners — Non-electrolytically applied zinc flake coatings*


ISO 23429, *Gauging of hexagon sockets*

3 Dimensions and gauging of head

3.1 Dimensions

See Figure 1 and Table 1.

Symbols and designations of dimensions are defined in ISO 225.



STANDARD PREVIEW
(standards.iteh.ai)

ISO 10642:2004

Permissible alternative form of socket <https://standards.iteh.ai/catalog/standards/sist/da3731b1-447c-4189-9d1d-f680fb4ef84/iso-10642-2004>





Figure 1 — Hexagon socket countersunk head screws

For broached sockets which are at the maximum limit of size the overcut resulting from drilling shall not exceed 1/3 of the length of any flat of the socket which is $e/2$.



- a A slight rounding or countersink at the mouth of the socket is permissible.
- b Point to be chamfered or, for sizes M4 and below, "as rolled" in accordance with ISO 4753.
- c Edge of the head to be truncated or rounded.
- d $\alpha = 90^\circ \text{ à } 92^\circ$.
- e Incomplete thread $u \leq 2 P$.
- f d_s applies if values of $l_{s, \min}$ are specified.

Figure 1 — Hexagon socket countersunk head screws (continued)

3.2 Gauging of head

See Figure 2.


iTeh STANDARD PREVIEW

(standards.iteh.ai)

The top surface of the screw shall be located between the gauge surfaces A and B.

ISO 10642:2004
<https://standards.iteh.ai/catalog/standards/sist/da3731b1-447c-4189-9d1d-f680fb4ef84/iso-10642-2004>
 90° -0°30'

Tolerances in millimetres



- a $D = d_{k, \text{theor., max}}$ (see Table 1).
- b F is the Flushness tolerance of the head (see Table 1).

Figure 2 — Flushness gauge

Table 1 — Dimensions

Dimensions in millimetres

Thread (d)	M3	M4	M5	M6	M8	M10	M12	(M14) ⁹	M16	M20	
	<i>P</i> ^a	0,5	0,7	0,8	1	1,25	1,5	1,75	2	2	2,5
<i>b</i> ^b	18	20	22	24	28	32	36	40	44	52	
<i>d_a</i>	3,3	4,4	5,5	6,6	8,54	10,62	13,5	15,5	17,5	22	
<i>d_k</i>	6,72	8,96	11,20	13,44	17,92	22,40	26,88	30,8	33,60	40,32	
actual	5,54	7,53	9,43	11,34	15,24	19,22	23,12	26,52	29,01	36,05	
<i>d_s</i>	3,00	4,00	5,00	6,00	8,00	10,00	12,00	14,00	16,00	20,00	
min.	2,86	3,82	4,82	5,82	7,78	9,78	11,73	13,73	15,73	19,67	
<i>e^{c, d}</i>	2,303	2,873	3,443	4,583	5,723	6,863	9,149	11,429	11,429	13,716	
<i>k</i>	1,86	2,48	3,1	3,72	4,96	6,2	7,44	8,4	8,8	10,16	
<i>F^e</i>	0,25	0,25	0,3	0,35	0,4	0,4	0,45	0,5	0,6	0,75	
<i>r</i>	0,1	0,2	0,2	0,25	0,4	0,4	0,6	0,6	0,6	0,8	
nom.	2	2,5	3	4	5	6	8	10	10	12	
max.	2,08	2,58	3,08	4,095	5,14	6,140	8,175	10,175	10,175	12,212	
min.	2,02	2,52	3,02	4,020	5,02	6,020	8,025	10,025	10,025	12,032	
<i>t</i>	1,1	1,5	1,9	2,2	3	3,6	4,3	4,5	4,8	5,6	
<i>w</i>	0,25	0,45	0,66	0,7	1,16	1,62	1,8	1,62	2,2	2,2	
<i>z^f</i>	Shank length <i>l_s</i> and grip length <i>l_g</i>										
	nom.	min.	max.	<i>l_s</i>	<i>l_s</i>	<i>l_s</i>	<i>l_s</i>	<i>l_s</i>	<i>l_s</i>	<i>l_s</i>	<i>l_s</i>
	8	7,71	8,29	min.	max.	min.	max.	min.	max.	min.	max.
	10	9,71	10,29								
	12	11,65	12,35								
	16	15,65	16,35								
	20	19,58	20,42								
	25	24,58	25,42								
	30	29,58	30,42	9,5	12	6,5	10				
	35	34,5	35,5			11,5	15	9	13		
	40	39,5	40,5			16,5	20	14	18	11	16
	45	44,5	45,5					19	23	16	21
50	49,5	50,5					24	28	21	26	
55	54,4	55,6					26	31	26	31	
									15,75	22	
									20,75	27	
										23	

