

SLOVENSKI STANDARD
oSIST prEN 16704-1:2014
01-april-2014

Železniške naprave - Zgornji ustroj proge - Zagotavljanje varnosti med delom na progi - 1. del: Tveganje in splošna načela za varovanje stalnih in mobilnih delovnih mest

Railway applications - Track - Safety protection on the track during work - Part 1: Railway risks and common principles for protection of fixed and mobile work sites

Bahnanwendungen - Oberbau - Sicherungsmaßnahmen bei Gleisbauarbeiten - Teil 1: Eisenbahngefährdungen und allgemeine Prinzipien zum Schutz feststehender und ortsveränderlicher Baustellen

Applications ferroviaires - Voie - Protection et sécurité durant des travaux sur la voie - Partie 1: Risques ferroviaires et principes communs de protection des chantiers fixes et mobiles

Ta slovenski standard je istoveten z: prEN 16704-1

ICS:

13.100	Varnost pri delu. Industrijska higiena	Occupational safety. Industrial hygiene
93.100	Gradnja železnic	Construction of railways

oSIST prEN 16704-1:2014

en,fr,de

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

DRAFT
prEN 16704-1

February 2014

ICS 93.100

English Version

**Railway applications - Track - Safety protection on the track
during work - Part 1: Railway risks and common principles for
protection of fixed and mobile work sites**

Applications ferroviaires - Voie - Protection et sécurité
durant des travaux sur la voie - Partie 1: Risques
ferroviaires et principes communs de protection des
chantiers fixes et mobiles

Bahnanwendungen - Oberbau - Sicherungsmaßnahmen bei
Gleisbauarbeiten - Teil 1: Eisenbahngefährdungen und
allgemeine Prinzipien zum Schutz feststehender und
ortsveränderlicher Baustellen

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 256.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword	4
Introduction	5
1 Scope	5
2 Normative references	5
3 Terms and definitions	7
4 Common principles	14
4.1 General	14
4.2 Work done by 3 rd party	15
5 Principles of risk assessment	15
5.1 General	15
5.2 Decision about safety measures	16
5.3 Lines with more than one track	17
5.4 Supervision	17
5.5 Documentation	17
5.6 Consideration of human behaviour	17
5.7 Actualisation of risk assessment	17
5.8 Remote controlled equipment of the track	17
6 Hierarchy of Safety Measures and parameters for the 5 railway risks	18
6.1 General	18
6.2 Risk 1 – Personnel being struck by a train or injured due to wind drag on open working track (safety of the worker)	18
6.3 Risk 2 – Personnel being struck by a train or injured due to wind drag from a train on adjacent track (safety of the worker)	22
6.4 Risk 3 – Personnel being struck by machine or train on blocked track (safety of the worker in the worksite)	27
6.5 Risk 4 – Machines, material or equipment being struck by a train on the adjacent track (safety of the operation/safety of the worker)	28
6.6 Risk 5 – Personnel being electrified/electrocuted (safety of the worker)	30
7 Working in tunnels	35
7.1 General	35
7.2 Safety measures for staff working in tunnels	36
8 Designing infrastructure	37
8.1 General	37
8.2 Designing new infrastructure	38
8.3 Designing modifications of the infrastructure	38
9 Safety documentation and information	39
9.1 General	39
9.2 Safety document for planning	39
9.3 Safety information for briefing	41
9.4 Access to and from the work site	42
10 Use of personal protective equipment	42
Annex A (normative) Requirements and conditions to manage safety measures	43
A.1 Blocking	43
A.2 Separation	44
A.3 Warning	46
A.4 Additional measures	52

Annex B (normative) Parameters in risk assessment)	54
Annex C (informative) Matrix of main responsibilities	55
Annex D (informative) Noise level of machines	59
Annex E (informative) Warning and remembering devices	61
E.1 Collective warning device vs. individual warning device	61
E.2 Combination of acoustic warning and visual signalling devices	61
Annex F (informative) National speed limits for trains approaching work sites	62
Annex G (informative) Functions within the process "warning"	64
Annex H (informative) Format for safety plan on railway risks	66
H.1 General	66
H.2 Safety document for the railway risks 1 to 4	66
H.3 Decision about the safety measures	68
H.4 Planning of the safety measures	74
H.5 Handing out of the safety document and instructions on the site	75
Annex I (informative) Guideline for the decision of blocking the working track in relation to the use of hand-guided machines/tools/equipment	77
Annex J (informative) Process and documentation about disconnection of overhead line	78
J.1 Process of the decision about disconnection of overhead line	78
J.2 Minimum contents for the documentation of the decision about disconnection of overhead line	78
J.3 Documentation of disconnection of power for work near overhead line	80
Annex K (informative) Examples for the possibility to get into the vicinity zone of the overhead line system safety plan for railway risks	82
Annex L (informative) Job descriptions of personnel	83
L.1 Track worker	83
L.2 Look-out	84
L.3 Track Safety Assistant	84
L.4 Track safety Supervisor	85
L.5 Machine supervisor	85
L.6 Machine operator	86
L.7 Track safety planner	86
Annex M (informative) Principal EU directives	87
M.1 Directive 89/391/EEC:	87
M.2 Directive 2004/49/EEC:	87
M.3 Directive 92/57/EEC:	87
Bibliography	88

Foreword

This document (prEN 16704-1:2014) has been prepared by Technical Committee CEN/TC 256 "Railway applications", the secretariat of which is held by DIN.

This document is currently submitted to the CEN Enquiry.

For relationship with EU Directives, see Clause 6, which is an integral part of this document.

This European Standard is one of the series prEN 16704 "Railway applications - Track - Safety protection on the track during work" as listed below:

- *Part 1: Railway risks and common principles for protection of fixed and mobile work sites*
- *Part 2-1: Common solutions and technology — Technical requirements for Track Warning Systems (TWS)*
- *Part 2-2: Common solutions and technology — Technical requirements for barriers*
- *Part 3: Competences of personnel related to work on or near the railway track*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 16704-1:2017

<https://standards.iteh.ai/catalog/standards/sist/b0b21817-2efd-4cb3-bc74-4c3fc7b521da/sist-en-16704-1-2017>

Introduction

The purpose of this standard is to define a common approach to railway safety in relation to track work in the European Community.

National safety rules (for example national standards or company rules) should gradually be harmonized in line with this standard or be replaced by rules contained in this standard. The current situation, in which, national safety rules continue to play a role, should be regarded as a transitional stage, leading ultimately to a situation in which, European rules described here after, will apply.

1 Scope

This standard provides requirements and measures to deal with the significant and specific railway risks during track works and with common principles for the protection of fixed and mobile work sites with trains circulating on the working track and on the adjacent track. Railway risks and protection measures for access and egress to/from the worksite are considered in the same way as railway risks and protection measures for track work itself.

This standard is applicable to all operations related to track works activities on rail guided systems. Metro, tram and other light rail systems are excluded from the scope¹.

The following specific railway risks are taken into consideration:

- Risk 1: Personnel being struck by a train or injured due to wind drag from a train on open working track (safety of the worker);
- Risk 2: Personnel being struck by a train or injured due to wind drag from train on adjacent track (safety of the worker);
- Risk 3: Personnel being struck by machine or train on blocked track (safety of the worker);
- Risk 4: Machines, material or equipment being struck by a train on the adjacent track (safety of the operation/safety of the worker);
- Risk 5: Personnel being electrified by fixed electrical equipment (safety of the worker).

This standard also provides requirements to the process of installing basic preventive measures when planning new infrastructure or installing corrective measures when adapting existing infrastructure.

This standard may be extended to outside parties when it is considered appropriate and reasonable by the infrastructure manager, if one or more of the 5 significant risks described inside this standard, arise as a result of their activities in proximity of the track.

2 Normative references

prEN xxxxx-2-1:2013, *Railway applications – Track – Safety protection on the track during work – Part 2-1: Common solutions and technology – Technical requirements for Track Warning Systems (TWS)*

prEN xxxxx-2-2:2013, *Railway applications – Track – Safety protection on the track during work – Part 2-2: Common solutions and technology – Requirements for barriers*

¹ See directive 2008/57/EC.

prEN 16704-1:2014 (E)

prEN xxxxx-3:2013, *Railway applications – Track – Safety protection on the track during work – Part 3: Competences of personnel related to work on or near the railway track*

EN 471:2003, *Specification for high-visibility warning clothing*

EN ISO 7731, *Ergonomics – Danger signals for public and work areas, auditory danger signals*

EN 13977, *Railway applications – Track - Safety requirements for portable machines and trolleys for construction and maintenance*

EN 14033-1, *Railway applications – Track – Railbound construction and maintenance machines – Part 1: Technical requirements for running*

EN 14033-2, *Railway applications – Track – Railbound construction and maintenance machines – Part 2: Technical requirements for working*

EN 14033-3, *Railway applications – Track – Railbound construction and maintenance machines – Part 3: General safety requirements*

EN 14969:2006, *Railway applications – Track - Qualification system for railway trackwork contractors*

EN 15273-1, *Railway applications – Gauges – Part 1: General – Common rules for infrastructure and rolling stock*

EN 15273-2, *Railway applications – Gauges – Part 2: Rolling stock gauge*

EN 15273-3, *Railway applications – Gauges – Part 3: Structure gauges*

EN 15746-1, *Railway applications – Track – Road-rail machines and associated equipment – Part 1: Technical requirements for running and working*

EN 15746-2, *Railway applications – Track – Road-rail machines and associated equipment – Part 2: General safety requirements*

EN 15955-1, *Railway applications – Track – Demountable machines and associated equipment – Part 1: Technical requirements for running and working*

EN 15955-2, *Railway applications – Track – Demountable machines and associated equipment – Part 2: General safety requirements*

EN 50122-1:1997, *Railway applications – Fixed installations – Part 1: protective provisions relating to electrical safety and earthing*

EN 50126:1999, *Railway applications – The specification and demonstration of Reliability, Availability, Maintainability and Safety (RAMS)*

CLC/TR 50488, *Railway applications – Safety measures for the personnel working on or near overhead contact lines*

EN 61230:1996, *Live working – Portable equipment for earthing or earthing and short-circuiting*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

accident

unplanned, uncontrolled event giving rise to death, ill health, injury or other loss to persons (with focus on contractors and employees) or damage to material

3.2

adjacent track

track beside the working track or beside the working place where it is possible to get into the danger zone during work. The actual work takes place on the working track/worksites near an open track and is not planned to take place in the danger zone of the adjacent track or the presence of the person in the danger zone of the adjacent track is not intended

3.3

ALARP

means: as low as reasonably practicable

3.4

announcement time

period between the moment the warning starts and the moment a train passes the beginning of the work site

3.5

announcement distance

distance between the point of detection/observation of the train and the beginning of the work site

3.6

Automatic Track Warning System**ATWS**

TWS that detects approaching trains or rail vehicles by technical means (mobile technical measure)

3.7

barrier

common technical solution to realize preventive separation by a set of components to separate working zone and danger zone and to prevent workers from entering the danger zone unintentionally

3.8

blocked track

track where there is no (exploitative) traffic/circulation on the track. Engineering trains/rail bound machines may be allowed

3.9

clearing time

time needed to stop the work and clear the danger zone (in a normal manner/without hurrying; workers taking their tools with them) after warning, reach the safe area and assure that all workers have reached the safe area

3.10

danger

danger is defined as the potential for injury or fatality

prEN 16704-1:2014 (E)


3.11

Danger Zone**DZ**

area where a person, material or equipment can be struck by a railway vehicle or exposed to injury or fatality due to wind drag

The danger zone includes the working track and extends on both sides over a distance measured from the axis of the track or the outside edges of the rail. This distance is specified by national rules and is dependent on:

- the speed of the train circulation;
- the characteristics of the rolling stock (gauge and profile)



<https://standards.iteh.ai/catalog/standards/sist/b0b21817-2efd-4cb3-bc74-4c3fc7b521da/sist-en-16704-1-2017>

Key

- 1 danger zone
- 2 measurement of the danger zone of the track axis
- 3 measurement of the danger zone of the outside edge of the rail

Figure 1 — Definition of the danger zone

3.12

designated competent person

person identified by the lead organisation, being responsible for supervising the formal inquiry, formal investigation or local investigation

3.13

emergency

unforeseen or unplanned event which has life-threatening or extreme loss implications and requires immediate attention

3.14

exceptional circumstances

circumstances where, owing to adverse weather, equipment failure, accident, incident, extended working exceeding limits set in a working time pattern, it is necessary to take action in order to avoid or reduce risk to people or significant disruption to services

3.15**fixed electrical equipment**

electrical equipment for traction current as far as it is under the control of the infrastructure manager. This includes the overhead line system (see Figure 2, “safe distance”), third rail, landlines and base stations

3.16**GSM-R**

Global System for Mobile communications – Railway

3.17**incident**

unplanned, uncontrolled event which, under different circumstances, could have resulted in an accident. It includes events reported as “near miss”

3.18**infrastructure**

all systems, equipment, materials or structures, that, combined or alone, form part of the operational railway. Including but not limited to: the permanent way, land within the line side separation, the installations exclusively used for operational purposes, overhead electrified lines and all other systems equipment, materials or structures up to the boundaries of the railway site

3.19**Infrastructure Manager****IM**

organisation responsible for the safe and effective management of the infrastructure, including the management of safety and infrastructure change, asset management and the management of contractors

3.20**lookout**

person who gives warning to track workers (observing, signalling, warning)

3.21**maintenance**

work to preserve or improve the condition of a structure, including modification, repair and renewal

3.22**method statement**

statement in a required format of the methods, systems, tools, plant and equipment and competence of persons to be used in performing a particular task, for the purpose of demonstrating that safety is not compromised or violated. Developed following an assessment of the hazards/risk arising from undertaking the activity in the context of the operational railway and if appropriate the location at which the activity will be undertaken

3.23**portable tools/machines**

tools or machines which can be handled by one person (and with a weight less than 25 kg)

3.24**processing time**

period between detection of the train and giving the warning signal to the worksite. It is a parameter of the warning process

3.25**risk**

combination of the probable frequency of exposure to a hazard and the likely consequence (severity) of the exposure

3.26**risk assessment**


systematic process for identifying and evaluating risks to people and processes

prEN 16704-1:2014 (E)

3.27

safe distance

closest working limit where persons, tools or equipment can come near a live part of the fixed electrical equipment without danger arising. The safe distance is the border of the vicinity zone. For the overhead line system, see the following figure²⁾

**Key**

- 1 safe distance
- 2 feeder
- 3 pantograph

Figure 2 — Illustration of the safe distance for bare live parts of overhead line, feeder and pantograph

3.28

safety

avoidance of endangering, causing death, injury or poor health to railway customers, employees and contractors, and to the general public, caused by accidents, incidents or hazards, also avoidance of damage to property and the environment

3.29

safety margin

period of time which has to be taken into account because of possible hazards that may occur in reaching the safe area

²⁾ The outer “limit” of the vicinity zone as defined in CLC/TR 50488, is the demarcation line of “safe distance”.

3.30**separation**

method to keep apart the work process on the work site and the danger zone of the adjacent track/operational track. Separation prevents workers or machines/materials from entering unintended into the danger zone. Measures of separation are barriers, (steel) walls, work wagons, movement limiting devices e.g.

3.31**place of safety (risk by running vehicles)**

area where it is made sure that workers are protected from the railway risks 1 to 3. The stand area for a place of safety has a minimum size of 50 cm

Note 1 to entry: National conditions for the size of the place of safety apply.

3.32**safety plan for railway risks**

document issued as a part of a safe system of work and used to control the risk associated with working on or near the track. See Clause 6/Annex H/I. It contains details of arrangements for each work site to be taken to avoid or reduce the risks (1 to 5) identified at the risk assessment stage

3.33**safety risk**

probable rate or frequency of occurrence of a hazardous event multiplied by the safety consequences (fatalities, major injuries and minor injuries resulting from the occurrence of a particular hazardous event outcome) expressed in terms of injuries and/or fatalities

3.34**Signal Controlled Warning System****SCWS**

TWS which detect approaching trains or rail vehicles by data from the signalling system (permanent technical measure)

3.35**third party (3rd party)**

an entity and its personnel that does not belong to the organisation that controls the infrastructure or to the direct contractor or the subcontractor and which may impair the safe railway operation or the safety of the workers due to their activities

3.36**Track Warning Systems****TWS**

are used for the warning of workers on or nearby the danger zone. The used term ATWS (Track Warning System) in this standard for the protection of fixed and mobile work sites includes the technical systems ATWS (Automatic Track Warning System) and SCWS (Signal Controlled Warning System) and LOWS. See prEN xxxxx-2-1:2013.




Figure 3 — Overview to track warning systems

NOTE LOWS according to this standard also includes the chain of look outs.

3.37 vicinity zone

limited space outside the live working zone where an electrical hazard can exist

3.38 warning

signals for the timely perception of approaching railed vehicles (see A.3 steps 1 to 6)

3.38.1 collective warning

warning whereby the protective capacity is achieved for all persons working on the work site independently of how they individually behave. A "simple human misconduct" does not lead to the failure of the safeguarding system. The concept of "simple human misconduct" does not include the situation in which system security features or protective measures are avoided consciously or deliberately or used ineffectively

3.38.2 individual warning

warning whereby the protective capacity only is reached if all persons working on the work site behave correctly individually. The "simple human misconduct" ("this can happen sometimes") can lead to the failure of the safeguarding system for the person in question. Therefore the individual human behaviour of all people to be protected shall be taken into account

3.39 tunnel

confined area where railway risks 1 to 5 are more significant or where working poses specific hazards (i.e. wind drag, exhaust fumes, dust, noise, objects falling down from passing trains and being ricocheted by the tunnel walls etc..)

3.40 visual limitation/demarcation

measure by which the boundary between working zone and danger zone is indicated (i.e. line on the ground, flexible band, etc.). If risk 2 exists, visual limitation/demarcation shall not be used as a safety measure standing alone

3.41**worksite**

area which is protected by safety measures according to this standard in order to carry out engineering or maintenance activities. A worksite can be on or near³⁾ a railway line

3.42**working platform**

platform on a vehicle dedicated for working at heights

3.43**working track**

track where the track working activities are planned and performed

3.44**work wagon**

closed railway vehicle used for working on the infrastructure with work places in the closed unit only where people are protected against wind forces and drag and it is not possible to get into a danger zone unintended⁴⁾

Note 1 to entry: an open wagon does not mean a "work wagon".

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 16704-1:2017

<https://standards.iteh.ai/catalog/standards/sist/b0b21817-2efd-4cb3-bc74-4c3fc7b521da/sist-en-16704-1-2017>

³⁾ Possibility that personnel and equipment can come into the danger zone.

⁴⁾ e.g. access to the tracks is possible only by self-locking doors which can be opened by additional conscious action only.