

Designation: C1321 – 04

## Standard Practice for Installation and Use of Interior Radiation Control Coating Systems (IRCCS) in Building Construction<sup>1</sup>

This standard is issued under the fixed designation C1321; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\varepsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope

1.1 This practice has been prepared for use by the designer, specifier, and applicator of IRCCS (Interior Radiation Control Coating Systems) for use in building construction. The scope is limited to recommendations related to the use and installation of IRCCS, including a surface(s) having a far-infrared emittance of 0.25 or less that is sprayed or painted.<sup>2</sup> Some examples that this practice is intended to address include: (1) low emittance surfaces in vented building envelope cavities intended to retard radiant transfer across the vented airspace; (2) low emittance surfaces at interior building surfaces intended to retard radiant transfer to or from building surfaces intended to reduce radiant transfer to or from heating or cooling systems. See Fig. 1 and Fig. 2 for typical applications.

1.2 This practice covers the installation process from preinstallation inspection through post-installation. It does not cover the production of the Interior Radiation Control Coating Materials.

1.3 This practice is not intended to replace the manufacturer's installation instructions, but it shall be used in conjunction with such instructions. This practice is not intended to supersede local, state, or federal codes.

1.4 This practice assumes that the installer possesses a good working knowledge of the application codes and regulations, safety practices, tools, equipment, and methods necessary for the installation of Interior Coating Materials. It also assumes that the installer understands the fundamentals of building construction that affect the installation of an IRCCS.

1.5 When the installation or use of Interior Radiation Control Coating Materials, accessories, and systems may pose safety or health problems, the manufacturer shall provide the user appropriate current information regarding any known problems associated with the recommended use of the company's products and shall also recommend protective measures to be employed in their safe utilization. The user shall establish appropriate safety and health practices and determine the applicability of regulatory requirements prior to use.

1.6 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use. Specific precautionary statements are contained in Sections 5 and 7.

## 2. Referenced Documents

2.1 ASTM Standards:

- C168 Terminology Relating to Thermal Insulation
- C1371 Test Method for Determination of Emittance of Materials Near Room Temperature Using Portable Emissometers
- E84 Test Method for Surface Burning Characteristics of Building Materials
- E96/E96M Test Methods for Water Vapor Transmission of Materials
- 2.2 NFPA Standards:<sup>3</sup>
- NFPA 54 National Fuel Gas Code
- NFPA 211 Standard for Chimneys, Fireplaces and Vents 2.3 *Other Documents:*
- CPSC Product Safety Fact Sheet No. 18 "The Home Electrical System"<sup>4</sup>

## 3. Terminology

3.1 *Definitions*—For definitions of terms used in this practice, refer to Terminology C168.

3.2 Definitions of Terms Specific to This Standard:

3.2.1 *applicator*—the person or persons who apply interior reflective coating materials in buildings.

3.2.2 *conditioned space*—any space in a building that is served by a heating or cooling system.

3.2.3 Interior Radiation Control Coating Systems (IRCCS)—a building construction consisting of a low emittance (0.25 or less) surface bounded by an open air space. An

Copyright © ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States.

<sup>&</sup>lt;sup>1</sup> This practice is under the jurisdiction of ASTM Committee C16 on Thermal Insulation and is the direct responsibility of Subcommittee C16.21 on Reflective Insulation.

Current edition approved May 1, 2004. Published June 2004. Originally approved 1996. Last previous edition approved in 1998 as C1321–98. DOI: 10.1520/C1321-04.

<sup>&</sup>lt;sup>2</sup> The as-manufactured emittance of Interior Radiation Control Coating product, as determined on a typical substrate, should be stated on the label (see 7.2.1).

<sup>&</sup>lt;sup>3</sup> Available from National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.

<sup>&</sup>lt;sup>4</sup> Available from U.S. Consumer Product Safety Commission, Washington, DC 20207.