



**Technical characteristics and methods of measurement  
for equipment for generation, transmission  
and reception of Digital Selective Calling (DSC)  
in the maritime MF, MF/HF and/or VHF mobile service;  
Part 4: Class E DSC**

IT'S STANDARD PREVIEW  
<https://standards.iteh.ai/standards/etsi/EN-300-338-4-v1-2-1-2017-02-4118-a04f-f5b31209b70b/>

---

Reference

REN/ERM-TG26-087-4

---

Keywords

DSC, GMDSS, maritime, radio

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at  
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	6
Foreword.....	6
Modal verbs terminology.....	6
1 Scope .....	7
2 References .....	7
2.1 Normative references .....	7
2.2 Informative references.....	7
3 Definitions and abbreviations.....	8
3.1 Definitions.....	8
3.2 Abbreviations .....	9
4 Controls and Indicators in Class E DSC Equipment .....	10
4.1 Visual indication .....	10
4.1.0 General.....	10
4.1.1 DSC alphanumeric display .....	10
4.1.1.0 Primary display information.....	10
4.1.1.1 Additional display information .....	10
4.1.2 Display requirements for additional controllers.....	10
4.1.3 Handling visual information .....	11
5 Technical requirements .....	11
5.1 Facilities for DSC transmission and reception .....	11
5.1.1 Watch receiver capabilities .....	11
5.2 Facilities for coding and decoding of DSC .....	11
5.2.1 Call functions.....	11
5.2.2 INDIVIDUAL calls .....	11
5.2.3 GEOGRAPHIC area calls.....	12
5.2.4 DSC call functionality .....	12
6 Automated and Non-Automated Procedure Requirements in Class E DSC Equipment.....	13
6.1 Introduction .....	13
6.2 Non-automated features .....	13
6.2.0 Introduction.....	13
6.2.1 DSC Message Composition .....	13
6.2.2 Transmission of DSC messages and prioritized wait.....	14
6.2.3 Alarms .....	14
6.3 Standby.....	15
6.4 Sending distress automated procedure (need to be revised to HF multifrequency alert attempts) .....	16
6.4.1 Procedure .....	16
6.4.2 Tasks.....	18
6.4.3 Display .....	18
6.4.4 Dedicated distress button sub procedure.....	19
6.4.5 Transmission of the alert attempt.....	20
6.4.6 Updating position.....	20
6.4.7 Handling received DSC Messages.....	20
6.4.8 Alarms .....	20
6.4.9 Determining Subsequent communications.....	20
6.4.10 Automated tuning .....	20
6.4.11 Cancelling the Distress Alert .....	21
6.4.12 Acknowledgments .....	21
6.4.13 Termination.....	21
6.4.14 Warnings.....	21
6.5 Receiving distress automated procedure .....	22
6.5.1 Procedure .....	22
6.5.2 Tasks.....	23
6.5.3 Display.....	23

6.5.4	Handling received DSC Messages.....	24
6.5.5	Alarms .....	24
6.5.6	Determining Subsequent communications.....	24
6.5.7	Automated tuning .....	24
6.5.8	Acknowledgments .....	24
6.5.9	Termination.....	25
6.5.10	Warnings.....	25
6.6	Sending non distress automated procedure .....	25
6.6.1	Procedure .....	25
6.6.2	Tasks .....	26
6.6.3	Display .....	26
6.6.4	Handling received DSC Messages.....	27
6.6.5	Alarms .....	27
6.6.6	Automated tuning .....	27
6.6.7	Delayed Acknowledgements .....	28
6.6.8	Termination.....	28
6.6.9	Warnings.....	28
6.7	Receiving non distress automated procedure .....	28
6.7.1	Procedure .....	28
6.7.2	Tasks .....	29
6.7.3	Display .....	30
6.7.4	Handling received DSC messages .....	31
6.7.5	Alarms .....	31
6.7.6	Automated tuning .....	31
6.7.7	Acknowledgments .....	31
6.7.8	Termination.....	32
6.7.9	Warnings.....	32
6.8	Communications automated procedure .....	32
6.8.1	Procedure .....	32
6.8.2	Tasks .....	32
6.8.3	Display .....	33
6.8.4	Handling received DSC Messages.....	33
6.8.5	Tuning of the general receiver and transmitter .....	33
6.8.6	Termination.....	33
6.9	Handling incoming calls while the equipment is engaged .....	33
6.9.1	Procedure .....	33
6.9.2	Tasks .....	33
6.9.2.0	Introduction.....	33
6.9.2.1	Higher priority calls .....	33
6.9.2.1.0	Priority.....	33
6.9.2.1.1	Higher priority calls - acceptance .....	34
6.9.2.1.2	Higher priority calls - non acceptance .....	34
6.9.2.2	Other calls .....	34
6.9.2.3	Termination of automated procedures.....	35
6.9.2.4	Action after termination of an automated procedure.....	35
6.9.2.5	Putting automated procedures on hold (optional) .....	35
6.9.2.6	Controlling non-terminated automated procedures (optional) .....	35
<b>Annex A (normative):</b>	<b>DSC Message Composition .....</b>	<b>37</b>
A.1	Default values.....	37
<b>Annex B (normative):</b>	<b>Radius-centre point conversion and rounding algorithm .....</b>	<b>38</b>
B.1	Radius-centre point conversion.....	38
B.2	Rounding .....	39
B.3	Special cases for either form of area data entry .....	39
<b>Annex C (normative):</b>	<b>Automated non distress channel selection algorithm .....</b>	<b>40</b>
<b>Annex D (normative):</b>	<b>Alarms.....</b>	<b>41</b>

D.1 Alarm specifications.....	41
D.2 Alarming with critical errors .....	42
D.3 Default alarm sounds.....	42
D.4 Other alarm sounds.....	43
History .....	44

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/3f6b24a6-4e20-4118-a04f-f5b3f209b70b/etsi-en-300-338-4-v1.2.1-2017-02>

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document is part 4 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.2].

The present document covers the operator interfaces and operating system for Class E DSC equipment.

National transposition dates	
Date of adoption of this EN:	8 February 2017
Date of latest announcement of this EN (doa):	31 May 2017
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 November 2017
Date of withdrawal of any conflicting National Standard (dow):	30 November 2018

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# 1 Scope

The present document states the minimum requirements for general communication for shipborne fixed installations using DSC - class E.

Class E DSC is intended to be used in the Medium Frequency (MF) and/or High Frequency (HF) bands of the Maritime Mobile Service (MMS), for distress, urgency and safety communication and general communications and uses telephony for subsequent communications.

The present document is part 4 of a multi-part deliverable that covers the requirements to be fulfilled by equipment that is either integrated with a transmitter and/or a receiver or equipment that is a stand-alone DSC terminal.

These requirements include the relevant provisions and the guidelines of the IMO as detailed in MSC/Circ.803 [i.1] for non-SOLAS vessels participating in the GMDSS as well as Commission Decision of 4 September 2003 (2004/71/EC [i.3]).

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ITU Radio Regulations (2016).
- [2] Recommendation ITU-R M.493-14 (09/2015): "Digital selective-calling system for use in the maritime mobile service"

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] IMO Circular MSC/Circ-803: "Participation of non-SOLAS ships in the Global Maritime Distress and Safety System (GMDSS)".
- [i.2] ETSI EN 300 338-1: "Technical characteristics and methods of measurement for equipment for generation, transmission and reception of Digital Selective Calling (DSC) in the maritime MF, MF/HF and/or VHF mobile service; Part 1: Common requirements".
- [i.3] Commission Decision 2004/71/EC of 4 September 2003 on essential requirements relating to marine radio communication equipment which is intended to be used on non-SOLAS vessels and to participate in the Global Maritime Distress and Safety System (GMDSS).

- [i.4] Maritime Safety Committee MSC 302(87): "Adoption of performance standards for bridge alert management".
- [i.5] IEC 61924-2 Edition 1 (including IEC 61924-2 Corrigendum 1 November 2013): "Maritime navigation and radiocommunication equipment and systems - integrated navigation systems - Part 2: Modular structure for INS - operational and performance requirements, methods of testing and required test results".

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI EN 300 338-1 [i.2] and the following apply:

**acknowledged:** automated procedure that indicates the objective of the initial DSC message has been achieved

**active:** automated procedure which has control of the general receiver and transmitter and is thus able to engage in subsequent communications and receive DSC messages on both the watch receiver and general receiver

**automated procedure:** set of actions necessary to complete the objective of an initiating DSC message or non DSC communication event

NOTE 1: Four DSC automated procedures are designed to process these. They are the receiving of distress DSC messages, the receiving of non distress DSC messages, the sending of distress DSC alert attempts and the sending of non distress DSC messages. In addition a fifth procedure is designed to handle non DSC communication events.

NOTE 2: These automated procedures are called:

- Received distress automated procedure.
- Sending distress automated procedure.
- Received non-distress automated procedure.
- Sending non-distress automated procedure.
- Communications automated procedure.

**block:** inhibit a function by making it inaccessible from the user interface

**class E:** DSC class intended to provide minimum facilities for MF/HF DSC distress, urgency and safety as well as routine calling and reception, not necessarily in full accordance with IMO GMDSS carriage requirements for MF installations

**default:** value selected or an action taken by the equipment software in the absence of any operator input

**distress DSC message:** DSC message or acknowledgement containing the distress information

**distress event:** unique distress situation identified by two parameters of the distress information; the MMSI of the vessel in distress and the nature of distress

**engaged:** equipment that is busy handling an automated procedure

**factory default:** default value that is set by the manufacturer such that the field or behaviour is defined prior to any operator intervention

**general receiver:** transceiver used for the reception of all subsequent communications

NOTE: It is important to distinguish this unit from the watch receiver.



**information characters:** set of symbols in a DSC message that contains the items of interest for the recipient and is used to compute the ECC symbol that terminates the message

NOTE: These symbols are repeated in the DX/RX time diversity pattern.

**initial DSC message:** DSC message that starts an automated procedure

**non distress DSC message:** DSC messages or acknowledgments that do not have the format specifier or category of "distress"

**objective:** intent of the DSC message either to establish subsequent communications or request information

**operator options:** any choices the operator can make while the automated procedure is engaged

**pertinent to the automated procedure:** DSC messages that have something to do with the procedure and are therefore 'handled' by the procedure

NOTE: A DSC message is pertinent to an automated procedure if the set of information characters in the DSC message has the correct values.

**pertinent to the station:** any DSC message that would start an automated procedure if the radio were in standby

**self-terminating alarm:** short alarm that stops by itself without operator intervention

NOTE: The purpose of this alarm is to inform the operator that a DSC message is received but it does not require his immediate attention.

**symbol (as part of the DSC sentence):** 7 binary bits of a 10 bit DSC word that have the information content

**top level:** items, buttons, or functions are present and visible without requiring any action by the operator (such as scrolling, opening up menus, or removing any obscuring covers, etc.)

**two-tone alarm:** alarm consisting of a repetition of the 2 200 Hz frequency for 250 ms followed by a 1 300 Hz frequency for 250 ms

NOTE: This alarm is used for the initiation of the received distress DSC automated procedure.

**urgency alarm:** alarm consisting of a repetition of the 2 200 Hz frequency for 250 ms followed by 250 ms period of silence

NOTE: This alarm is used for the initiation of the received non distress DSC automated procedure when the category of the initiating DSC message is "urgency".

**watch receiver:** separate receiver in DSC radios that continuously monitors the appropriate MF, HF or MF and HF DSC distress frequencies

**word (as part of the DSC sentence):** 10 binary bits that make up the coded entities of a transmitted DSC message

NOTE: The 10 bits consist of a 7 bit "symbol" that gives the information content and 3 bit error check that gives the number of 0 binary bits in the 7 bit symbol.

## 3.2 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI EN 300 338-1 [i.2] apply.

## 4 Controls and Indicators in Class E DSC Equipment

### 4.1 Visual indication

#### 4.1.0 General

Any visual display of the information content shall be clearly legible under all ambient light conditions.

#### 4.1.1 DSC alphanumeric display

##### 4.1.1.0 Primary display information

The display characters shall have a minimum height of 3,5 mm, and a nominal character width/height ratio of 0,7.

The display shall have a minimum of 12 characters per line and a minimum of 32 characters total.

Any displayed information shall be static. Horizontal scrolling techniques are not permitted (see clause 4.1.3).

The display shall be capable of:

- prompting the operator if an incorrect operation is attempted;
- displaying error messages;
- displaying incoming and logged calls in plain language;
- displaying all the user programmable information content of a DSC call.

##### 4.1.1.1 Additional display information

Additional display characters or symbols shall be capable of:

- showing the functions and options currently available;
- displaying that unread received DSC calls are present in memory;
- displaying other visual alarms;
- displaying whether the position and time information is automatically entered or manually entered.

For integrated equipment there shall be additional display characters and symbols as required for displaying operating frequency, channel number and other radio parameters.

Where logic flows and procedural guidance, expressed by graphical symbols, have an advantage over text, this shall be allowed. Any graphical symbols shall be clearly defined in the operation manual.

#### 4.1.2 Display requirements for additional controllers

Where the additional controller is a fixed installation, it shall have exactly the same characteristics as the primary controller, including the display.

Where the additional controller is a handheld device, it shall have exactly the same characteristics as the primary controller, except for the display, which may be scaled down for a minimum character height of 2 mm.

### 4.1.3 Handling visual information

In case all information, or user options, required for the active automated procedure, cannot be contained on a single screen, means shall be available to inform the user:

- a) that more information is available;
- b) how to select the relevant information not yet displayed, e.g. by means of a next button or info key.

---

## 5 Technical requirements

### 5.1 Facilities for DSC transmission and reception

#### 5.1.1 Watch receiver capabilities

The watchkeeping receiver part of the DSC equipment shall be designed for continuous operation on:

- MF equipment: 2 187,5 kHz;
- HF equipment: 8 414,5 kHz; 4 207,5 kHz, 6 312 kHz, 12 577 kHz and 16 804,5 kHz.

The watchkeeping receiver need not operate when the transmitter is in use.

The user may be permitted to deselect up to three of the following frequencies as appropriate for propagation reasons:

- 4 207,5 kHz;
- 6 312 kHz;
- 12 577 kHz; and
- 16 804,5 kHz.

### 5.2 Facilities for coding and decoding of DSC

#### 5.2.1 Call functions

The facilities for coding and composition of calls shall be so arranged that it is possible for the operator quickly and precisely to enter a call. The types of DSC calls provided in this equipment are specified in clause 5.2.4.

The CALL functions shall permit selection of the following functions:

- INDIVIDUAL: for making a call to a specific MMSI;
- GROUP: for making a call to a specific Group MMSI;
- GEOGRAPHIC: for making geographic area calls;
- RECEIVED CALLS: for retrieving stored incoming DSC calls;
- OTHER: for equipment housekeeping functions.

#### 5.2.2 INDIVIDUAL calls

The INDIVIDUAL call facility shall permit either the MANUAL entry of a MMSI or the selection of a station from the DIRECTORY list. The DIRECTORY list shall have a facility for at least 10 entries. Their MMSIs shall be programmable. If the called station is a coast station (i.e. MMSI commencing 00) no further information shall be requested from the operator. If the called station is a ship station the equipment shall request input of a channel number.

The equipment shall assist the operator by suggesting a suitable inter-ship channel as defined in appendix 17 of the ITU Radio Regulations [1].

### 5.2.3 GEOGRAPHIC area calls

It shall be possible to transmit GEOGRAPHIC calls by means of deliberate actions, such as two levels of menu instructions.

The operator shall be able to select either Urgency or Safety category and the equipment shall propose the default working frequency of 2 182 kHz for MF equipment or 8 291 kHz for HF equipment (the operator shall have the option to change the frequency).

After the transmission of the GEOGRAPHIC call, the equipment shall automatically tune to selected working frequency and select the maximum transmitter power.

### 5.2.4 DSC call functionality

The following DSC calls shall be available in the equipment.

Table 1

CALL TYPE	Tx	Rx	Format specifier	Notes
Distress alert (RT)	Y	Y	112	
Distress alert (FEC)	N	Y	112	Subsequent comms 113
Distress acknowledgement (RT)	#	Y	116	
Distress acknowledgement (FEC)	#	Y	116	Subsequent comms 113
Distress relay individual (RT)	#	Y	120	This includes DROBOSE
Distress relay Individual (FEC)	#	Y	120	Subsequent comms 113
Distress relay Geographic area (RT)	#	Y	102	
Distress relay Geographic area (FEC)	#	Y	102	Subsequent comms 113
Distress relay All Ships (RT)	#	O	116	
Distress relay All Ships (FEC)	#	O	116	Subsequent comms 113
Distress relay ACK Individual (RT)	#	Y	120	
Distress relay ACK All Ships (RT)	#	O	116	
Distress relay ACK Individual (FEC)	#	Y	120	
Distress relay ACK All Ships (FEC)	#	O	116	
Geographic area RT call	Y	Y	102	Urgency (110) and Safety (108) only
Individual RT call	N	Y	120	Urgency (110) and Safety (108) only
Individual RT call acknowledgement	Y	N	120	Urgency (110) and Safety (108) only
Individual RT call acknowledgement "unable to comply"	Y	Y	120	Urgency (110) and Safety (108) only
Individual test call	Y	Y	120	Safety (108) only
Individual test call acknowledgement	Y	Y	120	Safety (108) only
Routine group call RT	Y	Y	114	
Routine individual RT call	Y	Y	120	
Routine individual RT call with position	Y	N	120	
Routine individual RT ACK	Y	Y	120	
Position request	N	Y	120	Safety (108) only
Position request ACK	Y	N	120	Safety (108) only
Distress Alert Cancel	Y	Y	112	This is the 'self addressed' distress ACK

If any other calls, not listed in table 1, are implemented in the device, they shall comply with tables A1-4.1 to A1-4.9 of Recommendation ITU-R M.493-14 [2]. Individual routine category polling and position calls from previous versions of Recommendation ITU-R M.493 may be implemented for the sake of reverse compatibility.

Call types marked # shall not be available in the equipment.

Call types marked Y shall be available in the equipment.

Call types marked N are not required to be available in the equipment.

Call types marked O are for reverse compatibility with older equipment.