



SLOVENSKI STANDARD
SIST EN 301 908-7 V5.2.1:2011
01-september-2011

**Celična omrežja IMT - Harmonizirani EN, ki zajema bistvene zahteve člena 3.2
direktive R&TTE - 7. del: CDMA TDD (UTRA TDD) bazne postaje (BS)**

IMT cellular networks - Harmonized EN covering the essential requirements of article 3.2
of the R&TTE Directive - Part 7: CDMA TDD (UTRA TDD) Base Stations (BS)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **EN 301 908-7 Version 5.2.1**

SIST EN 301 908-7 V5.2.1:2011
<https://standards.iteh.ai/catalog/standards/sist/2868a5b7-c1c5-4c00-96c6-140576a2a698/sist-en-301-908-7-v5-2-1-2011>

ICS:

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
-----------	---------------------------------------	---

SIST EN 301 908-7 V5.2.1:2011	en
--------------------------------------	-----------

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 908-7 V5.2.1:2011

<https://standards.iteh.ai/catalog/standards/sist/2868a3b7-c1c3-4c60-96e6-140576a2a698/sist-en-301-908-7-v5-2-1-2011>

ETSI EN 301 908-7 V5.2.1 (2011-07)

Harmonized European Standard

**IMT cellular networks;
Harmonized EN covering the essential requirements
of article 3.2 of the R&TTE Directive;
Part 7: CDMA TDD (UTRA TDD) Base Stations (BS)**

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST EN 301 908-7 V5.2.1:2011](https://standards.iteh.ai/catalog/standards/sist/2868a3b7-c1c3-4c60-96c6-140576a2a698/sist-en-301-908-7-v5-2-1-2011)

<https://standards.iteh.ai/catalog/standards/sist/2868a3b7-c1c3-4c60-96c6-140576a2a698/sist-en-301-908-7-v5-2-1-2011>



Reference

REN/MSG-TFES-006-7

Keywords

3G, 3GPP, cellular, digital, IMB, IMT, IMT-2000,
MBSFN, mobile, radio, regulation, TD-CDMA,
TDD, UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 908-7 V5.2.1:2011

<https://standards.iteh.ai/catalog/standards/sist/2868a3b7-c1c3-4c60-96c6-140576a2a07a/etsi-en-301-908-7-v5-2-1-2011>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	6
Foreword.....	6
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	9
2.2 Informative references.....	9
3 Definitions, symbols and abbreviations	9
3.1 Definitions	9
3.2 Symbols.....	10
3.3 Abbreviations	10
4 Technical requirements specifications	11
4.1 Environmental profile.....	11
4.2 Conformance requirements	12
4.2.1 Introduction.....	12
4.2.2 Spectrum emission mask	12
4.2.2.1 Definition	12
4.2.2.1.1 3,84 Mcps TDD option.....	12
4.2.2.1.2 1,28 Mcps TDD option.....	12
4.2.2.1.3 7,68 Mcps TDD option.....	12
4.2.2.2 Limits	13
4.2.2.2.1 3,84 Mcps TDD option.....	13
4.2.2.2.2 1,28 Mcps TDD option.....	14
4.2.2.2.3 7,68 Mcps TDD option.....	15
4.2.2.3 Conformance	16
4.2.3 Transmitter adjacent channel leakage power ratio.....	16
4.2.3.1 Definition	16
4.2.3.2 Limits	16
4.2.3.2.1 General requirements.....	16
4.2.3.2.2 Co-existence with UTRA-FDD	17
4.2.3.2.3 Co-existence with unsynchronized UTRA TDD on adjacent channels	18
4.2.3.3 Conformance.....	20
4.2.4 Transmitter spurious emissions.....	20
4.2.4.1 Definition	20
4.2.4.2 Limits	20
4.2.4.2.1 General requirements.....	20
4.2.4.2.2 Co-existence with GSM900.....	21
4.2.4.2.3 Co-existence with DCS1800	22
4.2.4.2.4 Co-existence with UTRA FDD	22
4.2.4.2.5 Co-existence with unsynchronized TDD.....	23
4.2.4.3 Conformance.....	23
4.2.5 Base station maximum output power.....	23
4.2.5.1 Definition	23
4.2.5.2 Limits	23
4.2.5.3 Conformance.....	23
4.2.6 Transmit intermodulation	23
4.2.6.1 Definition	23
4.2.6.2 Limits	23
4.2.6.2.1 3,84 Mcps TDD option.....	23
4.2.6.2.2 1,28 Mcps TDD option.....	24
4.2.6.2.3 7,68 Mcps TDD option.....	24
4.2.6.3 Conformance.....	24
4.2.7 Receiver spurious emissions	24

4.2.7.1	Definition	24
4.2.7.2	Limits	24
4.2.7.2.1	3,84 Mcps TDD option	25
4.2.7.2.2	1,28 Mcps TDD option	25
4.2.7.2.3	7,68 Mcps TDD option	25
4.2.7.3	Conformance	25
4.2.8	Receiver blocking characteristics	26
4.2.8.1	Definition	26
4.2.8.2	Limits	26
4.2.8.2.1	3,84 Mcps TDD option	26
4.2.8.2.2	1,28 Mcps TDD option	27
4.2.8.2.3	7,68 Mcps TDD option	28
4.2.8.3	Conformance	29
4.2.9	Receiver intermodulation characteristics	30
4.2.9.1	Definition	30
4.2.9.2	Limits	30
4.2.9.2.1	3,84 Mcps TDD option	30
4.2.9.2.2	1,28 Mcps TDD option	30
4.2.9.2.3	7,68 Mcps TDD option	31
4.2.9.3	Conformance	31
4.2.10	Receiver adjacent channel selectivity	31
4.2.10.1	Definition	31
4.2.10.2	Limits	31
4.2.10.2.1	3,84 Mcps TDD option	31
4.2.10.2.2	1,28 Mcps TDD option	32
4.2.10.2.3	7,68 Mcps TDD option	32
4.2.10.3	Conformance	33
5	Testing for compliance with technical requirements	33
5.1	Environmental conditions for testing	33
5.2	Interpretation of the measurement results	33
5.3	Essential radio test suites	35
5.3.1	Spectrum emission mask	35
5.3.1.1	Method of test	35
5.3.1.1.1	Initial conditions	35
5.3.1.1.2	Procedure	38
5.3.1.2	Test requirements	38
5.3.1.2.1	3,84 Mcps TDD option	38
5.3.1.2.2	1,28 Mcps TDD option	39
5.3.1.2.3	7,68 Mcps TDD option	39
5.3.2	Transmitter adjacent channel leakage power ratio	39
5.3.2.1	Method of test	39
5.3.2.1.1	Initial conditions	39
5.3.2.1.2	Procedure	42
5.3.2.2	Test requirements	44
5.3.2.2.1	3,84 Mcps TDD option	44
5.3.2.2.2	1,28 Mcps TDD option	44
5.3.2.2.3	7,68 Mcps TDD option	44
5.3.3	Transmitter spurious emissions	44
5.3.3.1	Method of test	44
5.3.3.1.1	Initial conditions	44
5.3.3.1.2	Procedure	47
5.3.3.2	Test requirements	47
5.3.4	Base station maximum output power	47
5.3.4.1	Method of test	47
5.3.4.1.1	Initial conditions	47
5.3.4.1.2	Procedure	49
5.3.4.2	Test requirements	49
5.3.5	Transmit intermodulation	49
5.3.5.1	Method of test	49
5.3.5.1.1	Initial conditions	49
5.3.5.1.2	Procedure	55

STANDARD PREVIEW
(standards.iteh.ai)

5.3.5.2	Test requirements	55
5.3.6	Receiver spurious emissions	55
5.3.6.1	Method of test	55
5.3.6.1.1	Initial conditions	55
5.3.6.1.2	Procedure	56
5.3.6.2	Test requirements	58
5.3.7	Receiver blocking characteristics	58
5.3.7.1	Method of test	58
5.3.7.1.1	Initial conditions	58
5.3.7.1.2	Procedure	59
5.3.7.2	Test requirements	60
5.3.8	Receiver intermodulation characteristics	60
5.3.8.1	Method of test	60
5.3.8.1.1	Initial conditions	60
5.3.8.1.2	Procedure	61
5.3.8.2	Test requirements	61
5.3.9	Receiver adjacent channel selectivity	61
5.3.9.1	Method of test	61
5.3.9.1.1	Initial conditions	61
5.3.9.1.2	Procedure	63
5.3.9.1.3	Test requirements	63
Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT)	64
Annex B (normative):	BS configurations	66
B.1	Receiver Diversity	66
B.2	Power Supply options	66
B.3	Ancillary RF amplifiers	66
B.4	BS using antenna arrays	66
B.4.1	Receiver tests	67
B.4.2	Transmitter tests	67
Annex C (informative):	Environmental profile specification	68
Annex D (informative):	The EN title in the official languages	69
Annex E (informative):	Bibliography	70
History		71

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (EN) has been produced by ETSI Technical Committee Mobile Standards Group (MSG).

The present document has been produced by ETSI in response to mandate M/284 from the European Commission issued under Council Directive 98/34/EC [i.1] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.2].

See article 5.1 of Directive 1999/5/EC [i.2] for information on presumption of conformity and Harmonised Standards or parts thereof the references of which have been published in the Official Journal of the European Union.

The requirements relevant to Directive 1999/5/EC [i.2] are summarised in annex A.

The present document is part 7 of a multi-part deliverable covering the essential requirements under article 3.2 of Directive 1999/5/EC [i.2] (R&TTE Directive) for Base Stations (BS), Repeaters and User Equipment (UE) for IMT cellular networks, as identified below:

- Part 1: "Introduction and common requirements";
- Part 2: "CDMA Direct Spread (UTRA FDD) User Equipment (UE)";
- Part 3: "CDMA Direct Spread (UTRA FDD) Base Stations (BS)";
- Part 4: "CDMA Multi-Carrier (cdma2000) User Equipment (UE)";
- Part 5: "CDMA Multi-Carrier (cdma2000) Base Stations (BS)";
- Part 6: "CDMA TDD (UTRA TDD) User Equipment (UE)";
- Part 7: "CDMA TDD (UTRA TDD) Base Stations (BS)";**
- Part 8: "Harmonized EN for IMT-2000, TDMA Single-Carrier (UWC 136) (UE) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 9: "Harmonized EN for IMT-2000, TDMA Single-Carrier (UWC 136) (BS) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 10: "Harmonized EN for IMT-2000, FDMA/TDMA (DECT) covering essential requirements of article 3.2 of the R&TTE Directive";
- Part 11: "CDMA Direct Spread (UTRA FDD) (Repeaters)";
- Part 12: "Harmonized EN for IMT-2000, CDMA Multi-Carrier (cdma2000) (Repeaters) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 13: "Evolved Universal Terrestrial Radio Access (E-UTRA) User Equipment (UE)";

- Part 14: "Evolved Universal Terrestrial Radio Access (E-UTRA) Base Stations (BS)";
- Part 15: "Evolved Universal Terrestrial Radio Access (E-UTRA FDD) (Repeaters)";
- Part 16: "Harmonized EN for IMT-2000, Evolved CDMA Multi-Carrier Ultra Mobile Broadband (UMB) (UE) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 17: "Harmonized EN for IMT-2000, Evolved CDMA Multi-Carrier Ultra Mobile Broadband (UMB) (BS) covering the essential requirements of article 3.2 of the R&TTE Directive";
- Part 18: "E-UTRA, UTRA and GSM/EDGE Multi-Standard Radio (MSR) Base Station (BS)";
- Part 19: "OFDMA TDD WMAN (Mobile WiMAX) TDD User Equipment (UE)";
- Part 20: "OFDMA TDD WMAN (Mobile WiMAX) TDD Base Stations (BS)";
- Part 21: "OFDMA TDD WMAN (Mobile WiMAX) FDD User Equipment (UE)";
- Part 22: "OFDMA TDD WMAN (Mobile WiMAX) FDD Base Stations (BS)".

National transposition dates	
Date of adoption of this EN:	4 July 2011
Date of latest announcement of this EN (doa):	31 October 2011
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 April 2012
Date of withdrawal of any conflicting National Standard (dow):	30 April 2013

SIST EN 301 908-7 V5.2.1:2011

Introduction

<https://standards.iteh.ai/catalog/standards/sist/2868a3b7-c1c3-4c60-96e6-140576a2a698/sist-en-301-908-7-v5-2-1-2011>

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.2]. The modular structure is shown in EG 201 399 [i.3].

1 Scope

The present document applies to the following radio equipment type:

- Base stations for IMT-2000 CDMA TDD (UTRA TDD).

This radio equipment type is capable of operating in all or any part of the frequency bands given in table 1-1.

Table 1-1: CDMA TDD Base Station frequency bands

UTRA TDD Band	Direction of transmission	IMT-2000 CDMA TDD service operating bands
a	Transmit and Receive	1 900 MHz to 1 920 MHz
	Transmit and Receive	2 010 MHz to 2 025 MHz
d	Transmit and Receive	2 570 MHz to 2 620 MHz

The requirements in the present document apply to both Wide Area Base Stations and Local Area Base Stations unless otherwise stated.

The UTRA TDD component of IMT-2000 CDMA TDD supports three options of the TDD mode with the chip rates of 3,84 Mchip/s, 1,28 Mchip/s and 7,68 Mchip/s. These three options are called the 3,84 Mcps TDD option, the 1,28 Mchip/s TDD option and the 7,68 Mcps TDD option respectively. The requirements are listed in different clauses only if the parameters deviate.

The present document covers requirements for:

- 3,84 Mcps TDD option Base Station for Releases 99, 4, 5, 6, 7, 8 and 9;
- 1,28 Mcps TDD option Base Stations for Releases 4, 5, 6, 7, 8 and 9;
- 7,68 Mcps TDD option Base Stations for Releases 7, 8 and 9.

For the case of IMB, only the 3,84 Mcps UTRA TDD option applies.

For general purpose Base Stations of Releases 99 and 4 only the requirements for Wide Area Base Stations apply.

The present document is intended to cover the provisions of Directive 1999/5/EC [i.2] (R&TTE Directive) article 3.2, which states that "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive [i.2] may apply to equipment within the scope of the present document.

NOTE: A list of such ENs is included on the web site: <http://www.newapproach.org/>.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] Void.
- [2] ETSI TS 125 105 (V9.2.0): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) radio transmission and reception (TDD) (3GPP TS 25.105 version 9.2.0 Release 9)".
- [3] ETSI TS 125 142 (V9.4.0): "Universal Mobile Telecommunications System (UMTS); Base Station (BS) conformance testing (TDD) (3GPP TS 25.142 version 9.4.0 Release 9)".
- [4] ITU-R Recommendation SM.329-11 (2011): "Unwanted emissions in the spurious domain".
- [5] ETSI EN 301 908-1 (V5.2.1): "IMT cellular networks; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive Part 1: Introduction and common requirements".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations.
- [i.2] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- [i.3] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the R&TTE Directive".
- [i.4] ETSI TR 100 028 (V1.4.1) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

ancillary RF amplifier: piece of equipment, which when connected by RF coaxial cables to the BS, has the primary function to provide amplification between the transmit and/or receive antenna connector of a BS and an antenna without requiring any control signal to fulfil its amplifying function

B: appropriate frequency in the Bottom of the operating frequency band of the BS: "RF channel"

Base Station class: wide area Base Station or local area Base Station, as declared by the manufacturer

chip rate: rate of "chips" (modulated symbols after spreading) per second

DPCHo: mechanism used to simulate an individual intracell interferer in the cell with one code and a spreading factor of 16

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

F_{uw}: frequency offset of the unwanted interfering signal from the assigned channel frequency of the wanted signal

local area Base Station: Base Station, characterized by requirements derived from Pico Cell scenarios with a BS to UE coupling loss equals to 45 dB

M: appropriate frequency in the Middle of the operating frequency band of the BS: "RF channel"

maximum output power (P_{max}): mean power level per carrier of the Base Station measured at the antenna connector in a specific reference condition, where the period of measurement is a transmit timeslot excluding the guard period

MBSFN-only UE: UE operable in receive mode only (for the purpose of MBSFN reception)

mean power: when applied to a CDMA modulated signal this is the power (transmitted or received) in a bandwidth of at least $(1 + \alpha)$ times the chip rate of the radio access mode, where the period of measurement is a transmit timeslot excluding the guard period unless otherwise stated

operating band: frequency range that is defined with a specific set of technical requirements, in which UTRA TDD operates

NOTE: The operating band(s) for a UTRA TDD BS is declared by the manufacturer according to the designations in table 1-1. Operating bands for UTRA are designated with Roman numerals, while the corresponding operating bands for E-UTRA are designated with Arabic numerals.

output power: mean power of one carrier of the Base Station, delivered to a load with resistance equal to the nominal load impedance of the transmitter

RATed output Power (PRAT): mean power level per carrier that the manufacturer has declared to be available at the antenna connector

RRC filtered mean power: mean power as measured through a root raised cosine filter with roll-off factor α and a bandwidth equal to the chip rate of the radio access mode

T: appropriate frequency in the Top of the operating frequency band of the BS: "RF channel"

wide area Base Stations: Base Station, characterized by requirements derived from macrocell and microcell scenarios with BS to UE coupling losses equal to 70 dB and 53 dB

<https://standards.iteh.ai/catalog/standards/sist/2868a3b7-c1c3-4c60-96c6-140576a2a698/sist-en-301-908-7-v5-2-1-2011>

3.2 Symbols

For the purposes of the present document, the following symbols apply:

α	roll-off factor, $\alpha = 0,22$
Ω	electrical impedance
$\frac{DPCH_o - E_c}{I_{or}}$	ratio of the average transmits energy per PN chip for the DPCH _o to the total transmit power
	spectral density in one time slot
F	Frequency (of the assigned channel frequency of the wanted signal)
F _{uw}	the frequency offset of the unwanted interfering signal from the assigned channel frequency of the wanted signal
P _i	power of the signal at antenna connector <i>i</i>
P _s	sum of the power for all antenna connectors

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

16QAM	16 - Quadrature Amplitude Modulation
3GPP	3 rd Generation Partnership Project
ACLR	Adjacent Channel Leakage power Ratio
ACS	Adjacent Channel Selectivity
BER	Bit Error Ratio

BS	Base Station
BTS	Base Transceiver Station
CDMA	Code Division Multiple Access
CW	Continuous Wave

NOTE: Unmodulated signal.

dB	deciBel
dBm	deciBel relative to 1 milliwatt
DC	Direct Current
DCS	Digital Cellular System
DL	Down Link (forward link)
DPCH	Dedicated Physical CHannel
DUT	Device Under Test
ERM	Electromagnetic compatibility and Radio spectrum Matters
EUT	Equipment Under Test
E-UTRA	Evolved Universal Terrestrial Radio Access
FDD	Frequency Division Duplexing
GSM	Global System for Mobile
HS-PDSCH	High Speed Physical Downlink Shared Channel
IMB	Integrated Mobile Broadcast
IMT-2000	International Mobile Telecommunications 2000
MBMS	Multimedia Broadcast and Multicast Service
MBSFN	MBMS over a Single Frequency Network
MS	Mobile Station
MSG	Mobile Standards Group
P	output Power
Pmax	Maximum output power of the Base Station
PRAT	RATed output Power of the Base Station
R&TTE	Radio and Telecommunications Terminal Equipment
RF	Radio Frequency
RMS	Root-Mean Square
RRC	Root-Raised Cosine
Rx	Receiver
SCH	Synchronization CHannel
TDD	Time Division Duplexing
TFES	Task Force for European Standards for IMT
TRX	Transmitter-Receiver
TS	Time Slot
Tx	Transmitter
UARFCN	UTRA Absolute Radio Frequency Channel Number
UE	User Equipment
UL	Up Link (reverse link)
UMTS	Universal Mobile Telecommunications System
UTRA	Universal Terrestrial Radio Access
WCDMA	Wideband Code Division Multiple Access

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the required operational environmental profile.

For guidance on how a supplier can declare the environmental profile see annex C.

4.2 Conformance requirements

This clause describes the conformance requirements for UTRA TDD.

4.2.1 Introduction

To meet the essential requirement under article 3.2 of the R&TTE Directive [i.2] for IMT Base Stations (BS) seven essential parameters in addition to those in EN 301 908-1 [5] have been identified. Table 4.2.1-1 provides a cross reference between these seven essential parameters and the corresponding nine technical requirements for equipment within the scope of the present document.

To fulfil an essential parameter the compliance with all the corresponding technical requirements in table 4.2.1-1 must be verified. For the case of an MBSFN-only BS the technical requirements in clauses 4.2.2, 4.2.3, 4.2.4, 4.2.5 and 4.2.6 shall apply.

Table 4.2.1-1: Cross references

Essential parameter	Corresponding technical requirements
Spectrum emissions mask	4.2.2 Spectrum emission mask
	4.2.3 Transmitter Adjacent Channel Leakage power Ratio (ACLR)
Conducted spurious emissions from the transmitter antenna connector	4.2.4 Transmitter spurious emissions
Accuracy of maximum output power	4.2.5 Base station maximum output power
Intermodulation attenuation of the transmitter	4.2.6 Transmit intermodulation
Conducted spurious emissions from the receiver antenna connector	4.2.7 Receiver spurious emissions
Impact of interference on receiver performance	4.2.8 Receiver blocking characteristics
	4.2.9 Receiver intermodulation characteristics
Receiver adjacent channel selectivity	4.2.10 Receiver Adjacent Channel Selectivity (ACS)

The technical requirements in the present document apply for Base Stations supporting UTRA TDD. The technical requirements also apply to the BS configurations described in annex B.

4.2.2 Spectrum emission mask

4.2.2.1 Definition

Spectrum emission mask defines an out of band emission requirement for the Base Station transmitter. These out of band emissions are emissions immediately outside the channel bandwidth resulting from the modulation process and non-linearity in the transmitter but excluding spurious emissions.

4.2.2.1.1 3,84 Mcps TDD option

The spectrum emission mask specifies the limit of the transmitter out of band emissions at frequency offsets from the assigned channel frequency of the wanted signal between 2,5 MHz and 12,5 MHz.

4.2.2.1.2 1,28 Mcps TDD option

The spectrum emission mask specifies the limit of the transmitter out of band emissions at frequency offsets from the assigned channel frequency of the wanted signal between 0,8 MHz and 4 MHz.

4.2.2.1.3 7,68 Mcps TDD option

The spectrum emission mask specifies the limit of the transmitter out of band emissions at frequency offsets from the assigned channel frequency of the wanted signal between 5 MHz and 25 MHz.

4.2.2.2 Limits

4.2.2.2.1 3,84 Mcps TDD option

The requirement shall apply to both Wide Area BS and Local Area BS. The requirement shall be met by a Base Station transmitting on a single RF carrier configured in accordance with the manufacturer's specification. Emissions shall not exceed the maximum level specified in tables 4.2.2.2.1-1 to 4.2.2.2.1-4 in the frequency range of f_{offset} from 2 515 MHz to f_{offset} from the carrier frequency, where:

- f_{offset} is the separation between the carrier frequency and the centre frequency of the measuring filter;
- $f_{\text{offset}_{\text{max}}}$ is either 12,5 MHz or the offset to the UMTS Tx band edge (DL transmission in the following bands: 1 900 MHz to 1 920 MHz, 2 010 MHz to 2 025 MHz and 2 570 MHz to 2 620 MHz), whichever is the greater.

The spectrum emissions measured according to clause 5.3.1.1.2 shall not exceed the maximum level specified in tables 4.2.2.2.1-1 to 4.2.2.2.1-4 for the appropriate BS maximum output power.

Table 4.2.2.2.1-1: Test requirements for spectrum emission mask values, BS maximum output power $P \geq 43$ dBm (3,84 Mcps TDD option)

Frequency offset of measurement filter centre frequency, f_{offset}	Maximum level	Measurement bandwidth
$2,515 \text{ MHz} \leq f_{\text{offset}} < 2,715 \text{ MHz}$	-12,5 dBm	30 kHz
$2,715 \text{ MHz} \leq f_{\text{offset}} < 3,515 \text{ MHz}$	$-12,5 \text{ dBm} - 15 \left(\frac{f_{\text{offset}}}{\text{MHz}} - 2,715 \right) \text{ dB}$	30 kHz
$3,515 \text{ MHz} \leq f_{\text{offset}} < 4,0 \text{ MHz}$	-24,5 dBm	30 kHz
$4,0 \text{ MHz} \leq f_{\text{offset}} < 8,0 \text{ MHz}$	-11,5 dBm	1 MHz
$8,0 \text{ MHz} \leq f_{\text{offset}} < f_{\text{offset}_{\text{max}}}$	-11,5 dBm	1 MHz

SIST EN 301 908-7 V5.2.1:2011

Table 4.2.2.2.1-2: Test requirements for spectrum emission mask values, BS maximum output power $39 \text{ dBm} \leq P < 43 \text{ dBm}$ (3,84 Mcps TDD option)

Frequency offset of measurement filter centre frequency, f_{offset}	Maximum level	Measurement bandwidth
$2,515 \text{ MHz} \leq f_{\text{offset}} < 2,715 \text{ MHz}$	-12,5 dBm	30 kHz
$2,715 \text{ MHz} \leq f_{\text{offset}} < 3,515 \text{ MHz}$	$-12,5 \text{ dBm} - 15 \left(\frac{f_{\text{offset}}}{\text{MHz}} - 2,715 \right) \text{ dB}$	30 kHz
$3,515 \text{ MHz} \leq f_{\text{offset}} < 4,0 \text{ MHz}$	-24,5 dBm	30 kHz
$4,0 \text{ MHz} \leq f_{\text{offset}} < 8,0 \text{ MHz}$	-11,5 dBm	1 MHz
$8,0 \text{ MHz} \leq f_{\text{offset}} < f_{\text{offset}_{\text{max}}}$	$P - 54,5 \text{ dB}$	1 MHz

Table 4.2.2.2.1-3: Test requirements for spectrum emission mask values, BS maximum output power $31 \text{ dBm} \leq P < 39 \text{ dBm}$ (3,84 Mcps TDD option)

Frequency offset of measurement filter centre frequency, f_{offset}	Maximum level	Measurement bandwidth
$2,515 \text{ MHz} \leq f_{\text{offset}} < 2,715 \text{ MHz}$	$P - 51,5 \text{ dB}$	30 kHz
$2,715 \text{ MHz} \leq f_{\text{offset}} < 3,515 \text{ MHz}$	$P - 51,5 \text{ dB} - 15 \left(\frac{f_{\text{offset}}}{\text{MHz}} - 2,715 \right) \text{ dB}$	30 kHz
$3,515 \text{ MHz} \leq f_{\text{offset}} < 4,0 \text{ MHz}$	$P - 63,5 \text{ dB}$	30 kHz
$4,0 \text{ MHz} \leq f_{\text{offset}} < 8,0 \text{ MHz}$	$P - 50,5 \text{ dB}$	1 MHz
$8,0 \text{ MHz} \leq f_{\text{offset}} < f_{\text{offset}_{\text{max}}}$	$P - 54,5 \text{ dB}$	1 MHz