
Digitalne povezave VHF zrak-tla (VDL), 2. način - Tehnične karakteristike in merilne metode za talno opremo - 3. del: Harmonizirani EN, ki zajema bistvene zahteve člena 3.2 direktive R&TTE

VHF air-ground Digital Link (VDL) Mode 2 - Technical characteristics and methods of measurement for ground-based equipment - Part 3: Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 841-3 V1.1.1:2011](https://standards.iteh.ai/catalog/standards/sist/f6a841c2-49e7-4c24-ac08-f594f5e53dad/sist-en-301-841-3-v1-1-1-2011)

[https://standards.iteh.ai/catalog/standards/sist/f6a841c2-49e7-4c24-ac08-](https://standards.iteh.ai/catalog/standards/sist/f6a841c2-49e7-4c24-ac08-f594f5e53dad/sist-en-301-841-3-v1-1-1-2011)

[f594f5e53dad/sist-en-301-841-3-v1-1-1-2011](https://standards.iteh.ai/catalog/standards/sist/f6a841c2-49e7-4c24-ac08-f594f5e53dad/sist-en-301-841-3-v1-1-1-2011)

Ta slovenski standard je istoveten z: EN 301 841-3 Version 1.1.1

ICS:

33.060.99

Druga oprema za radijske
komunikacije

Other equipment for
radiocommunications

SIST EN 301 841-3 V1.1.1:2011

en

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 841-3 V1.1.1:2011

<https://standards.iteh.ai/catalog/standards/sist/f6a841c2-49e7-4c24-ac08-f594f5e53dad/sist-en-301-841-3-v1-1-1-2011>

ETSI EN 301 841-3 V1.1.1 (2011-11)



**VHF air-ground Digital Link (VDL) Mode 2;
Technical characteristics and methods of measurement
for ground-based equipment;
Part 3: Harmonized EN covering the essential requirements
of article 3.2 of the R&TTE Directive**

SIST EN 301 841-3 V1.1.1:2011
http://standards.globalspec.com/stds/49600000/et
f594f5e53dad/sist-en-301-841-3-v1-1-1-2011

Reference

DEN/ERM-JTFEA-006

Keywords

aeronautical, AM, DSB, radio, testing, VHF

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 841-3 V1.1.1:2011

<https://standards.iteh.ai/catalog/standards/sist/f6a841c2-49e7-4c24-ac08-f594f5e53da1/sist-en-301-841-3-v1-1-1-2011>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Introduction	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references	6
3 Definitions and abbreviations	7
3.1 Definitions	7
3.2 Abbreviations	8
4 Technical requirements specifications	8
4.1 Environmental profile.....	8
4.2 Conformance requirements	8
4.2.1 Transmitter requirements	8
4.2.1.1 Frequency error	8
4.2.1.1.1 Requirement	8
4.2.1.1.2 Conformance	9
4.2.1.2 Manufacturer's declared output power	9
4.2.1.2.1 Requirement	9
4.2.1.2.2 Conformance	9
4.2.1.3 Adjacent channel power	9
4.2.1.3.1 Requirement	9
4.2.1.3.2 Conformance	9
4.2.1.4 Conducted spurious emissions	9
4.2.1.4.1 Requirement	9
4.2.1.4.2 Conformance	9
4.2.1.5 Cabinet radiation	9
4.2.1.5.1 Requirement	9
4.2.1.5.2 Conformance	9
4.2.1.6 Void.....	9
4.2.1.7 Intermodulation attenuation	9
4.2.1.7.1 Requirements	9
4.2.1.7.2 Conformance	10
4.2.1.8 RF power release time.....	10
4.2.1.8.1 Requirement	10
4.2.1.8.2 Conformance	10
4.2.1.9 Void.....	10
4.2.1.10 Transient behaviour of the transmitter	10
4.2.1.10.1 Receiver to transmitter turn-around time.....	10
4.2.1.10.2 Transmitter to receiver turn-around time.....	10
4.2.1.11 Modulation Accuracy - Symbol constellation error	10
4.2.1.11.1 Requirement	10
4.2.1.11.2 Conformance	10
4.2.2 Receiver requirements	10
4.2.2.1 Sensitivity	10
4.2.2.1.1 Requirement	10
4.2.2.1.2 Conformance	11
4.2.2.2 Co-channel interference	11
4.2.2.2.1 Requirement	11
4.2.2.2.2 Conformance	11
4.2.2.3 First adjacent channel rejection.....	11
4.2.2.3.1 Requirement	11
4.2.2.3.2 Conformance	11

4.2.2.4	Spurious response rejection of signals within the VHF aeronautical band	11
4.2.2.4.1	Requirement	11
4.2.2.4.2	Conformance	11
4.2.2.5	Spurious response rejection of signals outside the VHF aeronautical band	11
4.2.2.5.1	Requirement	11
4.2.2.5.2	Conformance	11
4.2.2.6	In-band Intermodulation response rejection	11
4.2.2.6.1	Requirement	11
4.2.2.6.2	Conformance	11
4.2.2.7	Blocking or desensitization	12
4.2.2.7.1	Requirement	12
4.2.2.7.2	Conformance	12
4.2.2.8	Conducted spurious emission	12
4.2.2.8.1	Requirement	12
4.2.2.8.2	Conformance	12
4.2.2.9	Cabinet radiation	12
4.2.2.9.1	Requirement	12
4.2.2.9.2	Conformance	12
5	Testing for compliance with technical requirements	12
5.1	Environmental conditions for testing	12
5.1.1	Normal and extreme test conditions	12
5.1.2	Test power source	12
5.2	Interpretation of the measurement results	13
5.3	Essential radio test suites	14
5.3.1	Transmitter test specifications	14
5.3.1.1	Frequency error	14
5.3.1.2	Manufacturer's declared output power	14
5.3.1.3	Adjacent channel power	14
5.3.1.4	Conducted Spurious emissions	14
5.3.1.5	Cabinet Radiation	14
5.3.1.6	Void	14
5.3.1.7	Inter-modulation attenuation	14
5.3.1.8	RF power release time	14
5.3.1.9	Void	14
5.3.1.10	Transient behaviour of the transmitter	14
5.3.1.10.1	Receiver to transmitter turn-around time	14
5.3.1.10.2	Transmitter to receiver turn-around time	14
5.3.1.11	Modulation accuracy - Symbol constellation error	14
5.3.2	Receiver test specifications	15
5.3.2.1	Sensitivity	15
5.3.2.2	Co-channel interference	15
5.3.2.3	Adjacent channel rejection	15
5.3.2.4	Spurious response rejection of signals within the VHF aeronautical band	15
5.3.2.5	Spurious response rejection of signals outside the VHF aeronautical band	15
5.3.2.6	In-band Intermodulation rejection	15
5.3.2.7	Blocking or desensitization	15
5.3.2.8	Conducted spurious emission	15
5.3.2.9	Cabinet Radiation	15
Annex A (normative):	HS Requirements and conformance Test specifications Table (HS-RTT)	16
Annex B (informative):	The EN title in the official languages	18
Annex C (informative):	Bibliography	19
History		20

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonized European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been produced by ETSI in response to a mandate from the European Commission issued under Council Directive 98/34/EC [i.5] (as amended) laying down a procedure for the provision of information in the field of technical standards and regulations.

The title and reference to the present document are intended to be included in the publication in the Official Journal of the European Union of titles and references of Harmonized Standard under the Directive 1999/5/EC [i.2].

See article 5.1 of Directive 1999/5/EC [i.2] for information on presumption of conformity and Harmonized Standards or parts thereof the references of which have been published in the Official Journal of the European Union.

The requirements relevant to Directive 1999/5/EC [i.2] are summarized in annex A.

The present document is part 3 of a multi-part deliverable covering VHF air-ground Digital Link (VDL) Mode 2; Technical characteristics and methods of measurement for ground-based equipment, as identified below:

Part 1: "Physical layer and MAC sub-layer";

Part 2: "Upper layers";

Part 3: "Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive".

National transposition dates

Date of adoption of this EN:	7 November 2011
Date of latest announcement of this EN (doa):	29 February 2012
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 August 2012
Date of withdrawal of any conflicting National Standard (dow):	31 August 2012

Introduction

The present document is part of a set of standards developed by ETSI and is designed to fit in a modular structure to cover all radio and telecommunications terminal equipment within the scope of the R&TTE Directive [i.2]. The modular structure is shown in EG 201 399 [i.4].

1 Scope

The present document applies to VDL Mode 2 ground-air digital communications using Differential Eight Phase Shift Keying (D8PSK), intended for channel increments of 25 kHz. The VDL Mode 2 system provides data communication exchanges between aircraft and ground-based systems, operating in the VHF band (117,975 MHz to 137,000 MHz). The scope of the present document is limited to ground based stations.

NOTE 1: The VDL Mode 2 can be used as an Air/Ground sub-network of the Aeronautical Telecommunication Network (ATN) using a band with AM(R)S spectrum allocation.

The present document is intended to cover the provisions of Directive 1999/5/EC [i.2] (R&TTE Directive), article 3.2, which states that "... radio equipment shall be so constructed that it effectively uses the spectrum allocated to terrestrial/space radio communications and orbital resources so as to avoid harmful interference".

In addition to the present document, other ENs that specify technical requirements in respect of essential requirements under other parts of article 3 of the R&TTE Directive as well as essential requirements under the Single European Sky Interoperability Regulation [i.3] (as amended) and related implementing rules may apply to equipment within the scope of the present document.

NOTE 2: A list of such ENs is included on the web site <http://www.newapproach.org>.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 301 841-1 (V1.3.1): "VHF air-ground Digital Link (VDL) Mode 2; Technical characteristics and methods of measurement for ground-based equipment; Part 1: Physical layer and MAC sub-layer".
- [2] ETSI EN 300 113-1 (V1.6.2): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector; Part 1: Technical characteristics and methods of measurement".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 100 028 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".

- [i.2] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).
- NOTE: As amended by Regulation (EC) 1882/2003 of the European Parliament and of the Council of 29 March 2003.
- [i.3] Regulation (EC) 552/2004 of the European Parliament and Council of 10 March 2004 on the interoperability of the European Air Traffic Management network (the interoperability Regulation).
- NOTE: OJEU L96, 31.03.2004, p. 26-42 as amended by Regulation (EC) 1070/2009 of the European Parliament and of the Council of 21 October 2009, OJEU L300/34, 14/11/2009.
- [i.4] ETSI EG 201 399: "Electromagnetic compatibility and Radio spectrum Matters (ERM); A guide to the production of Harmonized Standards for application under the R&TTE Directive".
- [i.5] Directive 98/34/EC of the European Parliament and of the Council of 22 June 1998 laying down a procedure for the provision of information in the field of technical standards and regulations and of rules on Information Society services as amended by Directive 98/48/EC of the European Parliament and of the Council of 20 July 1998 and by Council Directive 2006/96/EC of 20 November 2006.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in the R&TTE Directive [i.2] and the following apply:

adjacent channel power: amount of the modulated RF signal power transmitted outside of the assigned channel

NOTE: Adjacent channel power includes discrete spurious, signal sidebands, and noise density (including phase noise) at the transmitter output.

adjacent channel rejection: receiver's ability to demodulate the desired signal and meet the uncorrected BER requirement in the presence of an interfering signal in an adjacent channel

NOTE: The ratio (in dB) between the adjacent interfering signal level and the desired signal level necessary to achieve the specified minimum uncorrected BER, is the Adjacent Channel Rejection (ACR) ratio.

Aeronautical Mobile Service (AMS): mobile service between ground based stations and airborne stations, or between aircraft stations, in which survival craft stations may participate

average transmitter output power: average power supplied to the antenna transmission line by a transmitter during an interval of time sufficiently long, compared with the lowest frequency encountered in the modulation, taken under normal operating conditions

Bit Error Rate (BER): ratio between the number of erroneous bits received and the total number of bits received

NOTE: The uncorrected BER represents the BER without the benefit of Forward Error Correction (FEC).

Co-Channel Interference (CCI): capability of a receiver to demodulate the desired signal and achieve the minimum specified BER performance in the presence of an unwanted signal at the same assigned channel

NOTE: The ratio (in dB) between the wanted signal level and the unwanted signal level is the co-channel interference ratio.

conducted measurements: measurements which are made using a direct RF connection to the equipment under test

data rate: with a nominal data rate of 31 500 bits/s, the VDL Mode 2 symbol rate is expected to be 10 500 symbols/s

environmental profile: range of environmental conditions under which equipment within the scope of the present document is required to comply with the provisions of the present document

ground based station: aeronautical station equipment, in the Aeronautical Mobile Service (AMS), for use with an external antenna and intended for use at a fixed location

radiated measurements: measurements which involve the measurement of a radiated field

spurious emissions: conducted RF emissions on a frequency or frequencies which are outside the necessary bandwidth and the level of which may be reduced without affecting the corresponding transmission of information

NOTE: Spurious emissions include parasitic emissions, intermodulation products and frequency conversion products.

X 25: ITU-T standard for the protocols and message formats that define the interface between a terminal and a packet switching network

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACR	Adjacent Channel Rejection
AM	Amplitude Modulation
AM(R)S	Aeronautical Mobile (Route) Service
AMS	Aeronautical Mobile Service
ATN	Aeronautical Telecommunication Network
BER	Bit Error Rate
CCI	Co-Channel Interference
D8PSK	Differential Eight Phase Shift Keying
DSB	Double Side Band
FEC	Forward Error Correction
R&TTE	Radio and Telecommunications Terminal Equipment (Directive 1999/5/EC [i.2])
RF	Radio Frequency
VDL	VHF Data Link
VHF	Very High Frequency

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be declared by the supplier. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the declared operational environmental profile.

4.2 Conformance requirements

4.2.1 Transmitter requirements

4.2.1.1 Frequency error

4.2.1.1.1 Requirement

Requirement for frequency tolerance is specified in EN 301 841-1 [1], clause 6.2.10.

4.2.1.1.2 Conformance

Conformance tests as defined in clause 5.3.1.1 shall be carried out with the limits defined by clause 4.2.1.1.1.

4.2.1.2 Manufacturer's declared output power

4.2.1.2.1 Requirement

Requirement for manufacturer's declared output power is specified in EN 301 841-1 [1], clause 6.2.2.

4.2.1.2.2 Conformance

Conformance tests as defined in clause 5.3.1.2 shall be carried out with the limits defined by clause 4.2.1.2.1.

4.2.1.3 Adjacent channel power

4.2.1.3.1 Requirement

Requirement for adjacent channel power is specified in EN 301 841-1 [1], clause 6.2.8.

4.2.1.3.2 Conformance

Conformance tests as defined in clause 5.3.1.3 shall be carried out with the limits defined by clause 4.2.1.3.1.

4.2.1.4 Conducted spurious emissions

4.2.1.4.1 Requirement

Requirement for conducted spurious emissions is specified in EN 301 841-1 [1], clause 6.2.7.

4.2.1.4.2

Conformance

Conformance tests as defined in clause 5.3.1.4 shall be carried out with the limits defined by clause 4.2.1.4.1.

4.2.1.5 Cabinet radiation

4.2.1.5.1 Requirement

Requirement for cabinet radiation is specified in EN 300 113-1 [2], clause 7.5.4, table 5.

4.2.1.5.2 Conformance

Conformance tests as defined in clause 5.3.1.5 shall be carried out with the limits defined by clause 4.2.1.5.1.

4.2.1.6 Void

4.2.1.7 Intermodulation attenuation

4.2.1.7.1 Requirements

Requirement for Inter-modulation attenuation is specified in EN 300 113-1 [2], clause 7.6.3.

If the intended use of the base station equipment is not in the special service conditions class as described in that clause, this has to be stated clearly in the user manual and/or in the installation manual.

NOTE: The required class (general - or special service conditions) depends on the local situation and regulatory frequency assignment.