

SLOVENSKI STANDARD oSIST ISO 1830:2011

01-marec-2011

Papir, karton in lepenka - Določevanje manganov, topnih v kisli	² apir. k	arton in le	penka - Do	ločevanie	manganov.	topnih	v kisli
---	----------------------	-------------	------------	-----------	-----------	--------	---------

Paper, board and pulps -- Determination of acid-soluble manganese

Papiers, cartons et pâtes -- Détermination du manganèse soluble dans l'acide

Ta slovenski standard je istoveten z: ISO 1830:2005

ICS:

85.040 Vlaknine Pulps

85.060 Papir, karton in lepenka Paper and board

oSIST ISO 1830:2011 en

oSIST ISO 1830:2011

oSIST ISO 1830:2011

INTERNATIONAL STANDARD

ISO 1830

Second edition 2005-04-15

Paper, board and pulps — Determination of acid-soluble manganese

Papiers, cartons et pâtes — Détermination du manganèse soluble dans l'acide



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Page

Contents

Forew	ordi	V
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Principle	2
5	Reagents and materials	2
6	Apparatus and equipment	2
7	Sampling and preparation of sample	3
8 8.1 8.2	Procedurelgnition and dissolution of the residue	3
9	Preparation of calibration solutions	4
10	Determination	4
11	Calculation	4
12 12.1 12.2	Precision	5
13	Test report	5
Biblio	graphy	6

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 1830 was prepared by Technical Committee ISO/TC 6, Paper, board and pulps.

This second edition cancels and replaces the first edition (ISO 1830:1982), which included the photometric procedure as well as the procedure based on atomic absorption spectroscopy. The photometric procedure has been deleted, as it is now seldom used. The scope has been enlarged to include paper and board, in addition to pulp.

ISO 1830 has been harmonized with ISO 777 ^[1], ISO 778 ^[2] and ISO 779 ^[3], in order to make it possible to perform the final measurement of all four elements on the same solution.

Paper, board and pulps — Determination of acid-soluble manganese

WARNING — The method specified in this International Standard involves the use of some hazardous chemicals and of gases that can form explosive mixtures with air. Care should be taken to ensure that the relevant precautions are observed.

1 Scope

This International Standard specifies the procedure for the determination of acid-soluble manganese by flame atomic absorption spectrometry or by plasma emission spectroscopy.

It is applicable to all kinds of paper, board and pulps.

This International Standard specifies a method to determine manganese in the acid-soluble part of the ignition residue, i.e. that part of the ignition residue remaining after ignition which is soluble in hydrochloric acid. In the case where the residue is completely soluble, the result obtained by the procedure specified in this International Standard is a measure of the total amount of manganese in the sample.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 186, Paper and board — Sampling to determine average quality

ISO 287, Paper and board — Determination of moisture content — Oven-drying method

ISO 638, Pulps — Determination of dry matter content

ISO 1762, Paper, board and pulps — Determination of residue (ash) on ignition at 525 °C

ISO 3696, Water for analytical laboratory use — Specification and test methods

ISO 7213, Pulps — Sampling for testing

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

mass fraction of manganese

amount of the element manganese, expressed as milligrams per kilogram of oven-dry sample, in the solution obtained after ignition of the specimen at 525 °C and treating the residue with 6 mol/l hydrochloric acid

4 Principle

A test portion is ignited at 525 °C and the residue is treated with 6 mol/l hydrochloric acid. The test solution is aspirated into an acetylene/dinitrogen monoxide or acetylene/air flame and the mass fraction of manganese is determined by one of the following procedures:

- measurement of the absorption of the 279,5 nm line emitted by a manganese hollow-cathode lamp; or
- measurement of the absorption of the 257,6 nm line emitted by plasma emission spectrometry.

5 Reagents and materials

Use only chemicals of recognized analytical grade.

- **5.1 Water**: distilled or deionised water shall be used throughout the test. The conductivity of the water shall not exceed 0,1 mS/m after boiling for 1 h and cooling to between 20 °C and 25 °C. Instructions for the determination of conductivity are given in ISO 3696.
- **5.2** Hydrochloric acid, about 6 mol/l.

Dilute 500 ml of concentrated hydrochloric acid (density 1,19 g/ml) in 500 ml of water.

5.3 Manganese stock solution, 100 mg/l of Mn.

Weigh 0,308 g \pm 0,001 g of manganese sulfate monohydrate (MnSO₄·H₂O), dried to constant mass at a temperature of 400 °C to 450 °C prior to use, into a 1 000 ml volumetric flask. Add 0,5 ml of hydrochloric acid (5.2), dilute with water to the mark and mix.

1 ml of this stock solution contains 0,10 mg of Mn.

5.4 Manganese standard solution, 10 mg/l of Mn.

Transfer 100 ml of the manganese stock solution (5.3) to a 1 000 ml volumetric flask. Add 200 ml of hydrochloric acid (5.2), dilute with water (5.1) to the mark and mix.

1 ml of this standard solution contains 0,01 mg of Mn.

Commercially available certified standard manganese solutions may be used.

5.5 Acetylene gas and/or dinitrogen monoxide gas, of a grade suitable for atomic absorption spectrometry.

WARNING — Acetylene gas forms explosive mixtures with air.

5.6 Appropriate gas, for the plasma spectrometer (6.4). Argon is usually recommended as a carrier gas.

6 Apparatus and equipment

Ordinary laboratory equipment. Clean all equipment in 0,1 mol/l hydrochloric acid.

- **6.1 Filter paper**, ash free, particle retention 20 μm to 25 μm.
- **6.2 Dishes**, of platinum or quartz.