

Designation: D 5372 – 04

# Standard Guide for Evaluation of Hydrocarbon Heat Transfer Fluids<sup>1</sup>

This standard is issued under the fixed designation D 5372; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

# 1. Scope<sup>2</sup>

1.1 This guide provides information, without specific limits, for selecting standard test methods for testing heat transfer fluids for quality and aging. These test methods are considered particularly useful in characterizing hydrocarbon heat transfer fluids in closed systems.

# 2. Referenced Documents

#### 2.1 ASTM Standards: <sup>3</sup>

- D 86 Test Method for Distillation of Petroleum Products
- D 91 Test Method for Precipitation Number of Lubricating Oils
- D 92 Test Method for Flash and Fire Points by Cleveland Open Cup Tester
- D 93 Test Methods for Flash Point by Pensky-Martens Closed Cup Tester
- D 95 Test Method for Water in Petroleum Products and Bituminous Materials by Distillation
- D 97 Test Methods for Pour Point of Petroleum Oils
- D 189 Test Method for Conradson Carbon Residue of Petroleum Products
- D 445 Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (and the Calculation of Dynamic Viscosity)
- D 471 Test Method for Rubber Property-Effect of Liquids
- D 524 Test Method for Ramsbottom Carbon Residue of Petroleum Products
- D 664 Test Method for Acid Number of Petroleum Products by Potentiometric Titration
- D 893 Test Method for Insolubles in Used Lubricating Oils
- D 1160 Test Method for Distillation of Petroleum Products at Reduced Pressure
- D 1298 Test Method for Density, Relative Density (Specific

Gravity), or API Gravity of Crude Petroleum and Liquid Petroleum Products by Hydrometer Method

- D 1500 Test Method for ASTM Color of Petroleum Products (ASTM Color Scale)
- D 2160 Test Method for Thermal Stability of Hydraulic  ${\rm Fluids}^4$
- D 2270 Practice for Calculating Viscosity Index from Kinematic Viscosity at 40 and 100°C
- D 2717 Test Method for Thermal Conductivity of Liquids
- D 2766 Test Method for Specific Heat of Liquids and Solids
- D 2887 Test Method for Boiling Range Distribution of Petroleum Fractions by Gas Chromatography
- D 3241 Test Method for Thermal Oxidation Stability of Aviation Turbine Fuels (JFTOT Procedure)
- D 4530 Test Method for Carbon Residue (Micro Method)
- D 6743 Test Method for Thermal Stability of Organic Heat Transfer Fluids
- E 659 Test Method for Autoignition Temperature of Liquid Chemicals
- G 4 Guide for Conducting Corrosion Tests in Field Applications

# 3. Terminology

### 3.1 Description of Term Specific to This Standard:

3.1.1 *heat transfer fluid*—a petroleum oil or related hydrocarbon material which remains essentially a liquid while transferring heat to or from an apparatus or process. Small percentages of nonhydrocarbon components such as antioxidants and dispersants can be present.

#### 4. Significance and Use

4.1 The significance of each test method will depend upon the system in use and the purpose of the test method as listed under Section 5. Use the most recent editions of ASTM test methods.

#### 5. Recommended Test Procedures

5.1 Pumpability of the Fluid:

5.1.1 *Flash Point*, closed cup (Test Method D 93)—This test method will detect low flash ends which are one cause of cavitation during pumping. In closed systems, especially when fluids are exposed to temperatures of 225°C (approximately

<sup>&</sup>lt;sup>1</sup> This guide is under the jurisdiction of ASTM Committee D02 on Petroleum Products and Lubricants and is the direct responsibility of Subcommittee D02.L0 on Industrial Lubricants.

Current edition approved May 1, 2004. Published June 2004. Originally approved in 1993. Last previous edition approved in 1998 as D 5372–93 (1998).

<sup>&</sup>lt;sup>2</sup> The background for this standard was developed by a questionnaire circulated by ASTM-ASLE technical division L-VI-2 and reported in *Lubrication Engineering*, Vol 32, No. 8, August 1976, pp. 411–416.

<sup>&</sup>lt;sup>3</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

<sup>&</sup>lt;sup>4</sup> Withdrawn.

Copyright © ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States.