

Designation: D 6687 – 04

Standard Guide for Testing Printing Ink Vehicles and Components Thereof¹

This standard is issued under the fixed designation D 6687; the number immediately following the designation indicates the vear of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This guide covers a list of test methods, practices, guides, and specifications that can be used for the testing and evaluation of printing ink vehicles and components thereof (see Table 1).

1.2 This guide includes methods that were developed to test impact and non-impact inks and vehicles associated with letterpress, lithography, flexography and gravure. Tests on raw materials and analytical tests in general have been included.

1.3 Other ASTM standards not specified here may also be applicable.

1.4 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory requirements prior to use.

2. Terminology

2.1 Definitions:

2.1.1 *printing ink*, *n*—a colored or pigmented liquid or paste composition that is applied by printing machinery.

2.1.1.1 Discussion-Printing inks may contain vehicles, colorants, waxes, solvents, and other additives. Bulk inks are tested for dispersion, tinting strength, density, heat and storage stability, rheology, and printing properties.

2.1.2 *vehicle*, *n*—the portion of a printing ink that excludes the colorant.

2.1.2.1 Discussion-Ink vehicles typically include the resin/ solvent portion of the printing ink. Other printing ink additives, generally not included in the vehicle, are waxes, antioxidants and driers.

3. Test Categories

3.1 For convenience in selection, the test methods, practices, guides, and specifications listed in this guide are listed numerically (see Table 1) and by property of interest (see Table 2).

4. Precision and Bias

4.1 If available, precision for each test method listed can be found in the latest revision of that test method.

¹ This guide is under the jurisdiction of ASTM Committee D01 on Paint and

5. Keywords adad-6ba93e69a097/astm-d6687-04

5.1 printing inks; printing ink vehicles; test methods and practices (tabulation of); vehicles

Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.37 on Ink Vehicles.

Copyright © ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States.

Current edition approved June 1, 2004. Published July 2004. Originally approved in 2001. Last previous edition approved in 2002 as D 6687 - 02.

↓ D 6687 – 04

TABLE 1 Numerical Listing of Ink Vehicle Related Standards

| ASTM Desig | gnation Volume | Title |
|------------------|---------------------------|--|
| D 16 | 06.01 | Terminology for Paint, Related Coatings, Materials and Applications |
| D 56 | 05.01 | Test Method for Flash Point by Tag Closed Tester |
| D 86 | 05.01 | Test Method for Distillation of Petroleum Products at Atmospheric Pressure |
| D 93 | 05.01 | Test Method for Flash Point by Pensky-Martens Closed Cup Tester |
| D 154 | 06.03 | Guide for Testing Varnishes |
| D 445 | 05.01 | Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (the Calculation of Dynamic Viscosity) |
| D 562 | 06.01 | Test Method for Consistency of Paints Measuring Krebs Unit (KU) Viscosity Using the Stormer Viscometer |
| D 611 | 05.01 | Test Methods for Aniline Point and Mixed Aniline Point of Petroleum Products and Hydrocarbon Solvents |
| D 971 | 10.03 | Test Method for Interfacial Tension of Oil Against Water by the Ring Method |
| D 1200 | 06.01 | Test Method for Viscosity by Ford Viscosity Cup |
| D 1259 | 06.01 | Test Method for Nonvolatile Content of Resin Solutions |
| D 1310 | 06.01 | Test Method for Flash Point and Fire Point of Liquids by Tag Open-Cup Apparatus |
| D 1331 | 15.04 | Test Methods for Surface and Interfacial Tension of Solutions of Surface-Active Agents |
| D 1353 | 06.04 | Test Method for Nonvolatile Matter in Volatile Solvents for Use in Paint, Varnish, Lacquer, and Related Products |
| D 1475 | 06.01 | Test Method for Density of Liquid Coatings, Inks, and Related Products |
| D 1544 | 06.01 | Test Method for Color of Transparent Liquids (Gardner Color Scale) |
| D 1545 | 06.03 | Test Method for Viscosity of Transparent Liquids by Bubble Time Method |
| D 1639 | 06.03 | Test Method for Acid Value of Organic Coating Materials |
| D 1725 D 1963 | 06.03 | Test Method for Viscosity of Resin Solutions Test Method for Specific Gravity of Drying Oils, Varnishes, Resins, and Related Materials at 25/25°C |
| D 1963 D 2074 | 06.03 | |
| D 2074 D 2196 | 06.03 06.01 | Test Methods for Total, Primary, Secondary, and Tertiary Amine Values of Fatty Amines by Alternative Indicator Method Test Methods for Rheological Properties of Non-Newtonian Materials by Rotational (Brookfield Type) Viscometer |
| D 2369 | 06.01 | Test Method for Volatile Content of Coatings |
| D 2309 D 3278 | 06.01 | Test Method for Flash Point of Liquids by Small Scale Closed-Cup Apparatus |
| D 3792 | 06.01 | Test Method for Water Content of Coatings by Direct Injection Into a Gas Chromatograph |
| D 3825 | 05.02 | Test Method for Dynamic Surface Tension by the Fast-Bubble Technique |
| D 3828 | 05.02 | Test Method for Flash Point by Small Scale Closed Tester |
| D 3934 | 06.01 | Test Method for Flash/No Flash Test- Equilibrium Method by a Closed-Cup Apparatus |
| D 3960 | 06.01 | Practice For Determining Volatile Organic Compound (VOC) Content of Paints and Related Coatings |
| D 4017 | 06.01 | Test Method for Water in Paints and Paint Materials by Karl Fischer Method |
| D 4040 | 06.02 | Test Method for Viscosity of Printing Inks and Vehicles by the Falling-Rod Viscometer |
| D 4212 | 06.01 | Test Method for Viscosity by Dip-Type Viscosity Cups |
| D 4287 | 06.01 | Test Method for High-Shear Viscosity Using a Cone/Plate Viscometer |
| D 4302 | 06.02 | Specification For Artists' Oil, Resin-Oil, and Alkyd Paints |
| D 4359 | 06.01 | Test Method for Determining Whether a Material is a Liquid or a Solid |
| D 4361 | 06.02 | Test Method for Apparent Tack of Printing Inks and Vehicles by a Three-Roller Tackmeter |
| D 4713 | 06.02 | Test Methods for Nonvolatile Content of Heatset and Liquid Printing Ink Systems |
| D 4758 | 06.03 | Test Method for Nonvolatile Content of Latexes |
| D 4942 | 06.02 | Test Methods for Water Pickup of Lithographic Printing Inks and Vehicles in a Laboratory Mixer |
| D 5010 | 06.02 | Guide for Testing Printing Inks and Related Materials |
| D 5062 | 06.03 | Test Method for Resin Solution Dilutability by Volumetric/Gravimetric Determination |
| D 5165 | 06.03 | Practice for Laboratory Preparation of Gelled Vehicles Using a Resin Kettle |
| D 5166 | 06.03 | Practice for Laboratory Preparation of Gelled Vehicle Samples Using a Microwave Oven |
| D 5661 | os://sta/06.03 ds.iten.a/ | CTest Method for Relative Solvency of Petroleum Oils by the PKP Method Da93669a097/astm-d6687-04 |
| D 5958 | 06.03 | Practices for Preparation of Oil-Based Ink Resin Solutions |
| D 6038 | 06.03 | Test Method for Determining the Compatibility of Resin/Solvent Mixtures by Precipitation Temperature |
| D 6336 | 06.03 | Practice for Evaluation of Vehicles for Pigment Wetting Using a Vacuum Modified Sigma Blade Mixer |
| D 6419 | 06.02 | Test Method for Volatile Content of Sheet-Fed and Coldset Web Offset Printing Inks |
| D 6579 | 06.03 | Practice for Molecular Weight Averages and Molecular Weight Distribution of Hydrocarbon and Terpene Resins by Size- Exclusion Chromatography |
| D 6606 | 06.03 | Test Method for Viscosity and Yield of Vehicles and Varnishes by the Duke Viscometer |
| D 6887 | 06.03 | Test Method for Testing Alkyd Compatibility with Resin or Resin Solutions |
| D 6989 | 06.03 | Practices for Preparation of Solvent and Water Based Ink Resin Solutions |
| E 1 | 14.03 | Specification for ASTM Thermometers |
| E 28 | 06.03 | Test Method for Softening Point of Resins Derived from Naval Stores by Ring-and-Ball Apparatus |
| E 70 | 15.05 | Test Method for pH of Aqueous Solutions With the Glass Electrode |
| E 222 | 15.05 | Test Methods for Hydroxyl Groups Using Acetic Anhydride Acetylation |
| E 230 | 14.03 | Specification and Temperature-Electromotive Force (EMF) Tables for Standardized Thermocouples |
| E 691 | 14.02 | Practice for Conducting an Interlaboratory Study to Determine the Precision of a Test Method |