



SLOVENSKI STANDARD

SIST-TS ETSI/TS 102 657 V1.7.1:2012

01-marec-2012

Zakonito prestrezanje (LI) - Ravnanje z zadržanimi podatki - Izročilni vmesnik za zahtevo in izročanje zadržanih podatkov

Lawful Interception (LI) - Retained data handling - Handover interface for the request and delivery of retained data

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **TS 102 657 Version 1.7.1**

SIST-TS ETSI/TS 102 657 V1.7.1:2012
<https://standards.iteh.ai/catalog/standards/sist/68213da1-4e64-413e-b9cc-46cd0c03d119/sist-ts-etsi-ts-102-657-v1-7-1-2012>

ICS:

33.040.40	Podatkovna komunikacijska omrežja	Data communication networks
35.200	Vmesniška in povezovalna oprema	Interface and interconnection equipment

SIST-TS ETSI/TS 102 657 V1.7.1:2012 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST-TS ETSI/TS 102 657 V1.7.1:2012](https://standards.iteh.ai/catalog/standards/sist/682f3da1-4e64-413e-b9ce-46cd0c03d119/sist-ts-etsi-ts-102-657-v1-7-1-2012)

<https://standards.iteh.ai/catalog/standards/sist/682f3da1-4e64-413e-b9ce-46cd0c03d119/sist-ts-etsi-ts-102-657-v1-7-1-2012>

ETSI TS 102 657 V1.7.1 (2010-10)

Technical Specification

**Lawful Interception (LI);
Retained data handling;
Handover interface for the request and
delivery of retained data**

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST-TS ETSI/TS 102 657 V1.7.1:2012](https://standards.iteh.ai/catalog/standards/sist/682f3da1-4e64-413e-b9ce-46cd0c03d119/sist-ts-etsi-ts-102-657-v1-7-1-2012)

<https://standards.iteh.ai/catalog/standards/sist/682f3da1-4e64-413e-b9ce-46cd0c03d119/sist-ts-etsi-ts-102-657-v1-7-1-2012>



Reference

RTS/LI-00077

Keywords

handover, retention

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST-TS ETSI/TS 102 657 V1.7.1:2012](https://standards.iteh.ai/catalog/standards/sist/682f3da1-4e64-413e-b9ce-46cd0c03d119/etsi-ts-102-657-v1-7-1-2012)

<https://standards.iteh.ai/catalog/standards/sist/682f3da1-4e64-413e-b9ce-46cd0c03d119/etsi-ts-102-657-v1-7-1-2012>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	8
Foreword.....	8
1 Scope	9
2 References	9
2.1 Normative references	9
2.2 Informative references.....	10
3 Definitions and abbreviations.....	10
3.1 Definitions.....	10
3.2 Abbreviations	11
4 Overview of handover interface	12
4.1 Reference model.....	12
4.2 Structure of document and applicable communication domains	14
4.3 Categories of retained data	15
4.4 Handover Interface port 1 (HI-A) and Handover Interface port 2 (HI-B).....	15
4.5 Model used for the RDHI.....	16
5 Handover interface message flows.....	16
5.1 Introduction	16
5.1.1 Summary of this clause.....	16
5.1.2 Message flow modes.....	16
5.1.3 Delivery cases.....	17
5.1.4 "Active" requests and "closed" requests	17
5.1.5 Errors and failure situations.....	17
5.1.5.1 Error and failure types.....	17
5.1.5.2 Request process failure feedback.....	17
5.1.5.3 Other errors.....	18
5.1.6 Cancelling a request.....	18
5.1.7 Delivery of results.....	18
5.1.8 State diagram	19
5.2 Message flows for general situation	20
5.2.1 Delivery of a response	20
5.2.2 Cancellation of request	21
5.2.3 Multi-part delivery.....	22
5.3 Message flows for Authorized-Organization-initiated scenario.....	22
5.3.1 Delivery of results or a failure response	22
5.3.2 Cancellation of request	24
5.3.3 Multi-part delivery.....	24
5.4 HI-A and HI-B addressing.....	25
6 Definition of the elements for retained data messages	26
6.1 Header information.....	26
6.1.1 Use of header information	26
6.1.2 RequestID field specification.....	26
6.1.3 CSP Identifiers.....	26
6.1.3.1 Use of CSP identifiers (CSPID)	26
6.1.3.2 Third Party CSP Identifier (thirdPartyCSPID).....	26
6.1.4 Timestamp (timeStamp)	27
6.2 Retained Data response	27
6.2.1 General.....	27
6.2.2 Additional information in response messages.....	27
6.2.2.1 Record number (recordNumber)	27
6.2.2.2 Response status (ResponseStatus).....	27
6.2.3 Volatile information.....	27
6.2.4 Unavailable parameters.....	28
6.3 Retained Data requests	28

6.3.1	Information contained within a request	28
6.3.2	Format of a request	28
6.3.3	Additional information in requests	29
6.3.3.1	Priority of a request	29
6.3.3.2	Maximum hits	29
6.4	Error messages	29
7	Data exchange techniques	29
7.1	General	29
7.2	HTTP data exchange	30
7.2.1	Basic configuration	30
7.2.2	Single client/server	30
7.2.3	Mutual client/server	30
7.2.4	Details common to both single and mutual cases	30
7.3	Direct TCP data exchange	31
7.3.1	Transport layer	31
7.3.1.1	Introduction	31
7.3.1.2	TCP settings	31
7.3.2	Network layer	31
7.3.3	Delivery networks	31
8	Security Measures	31
8.1	General	31
8.2	Connection Level Security	31
8.3	Application Level Security	32
8.4	Technical Security Measures	32
8.4.1	General	32
8.4.2	Connection Level	33
8.4.3	Application Level	33
8.4.3.1	Hashes	33
8.4.3.2	Digital Signatures	33
8.4.3.3	HI-B Non-Repudiation	33
8.4.3.4	Digital Signatures and Message Structure	33
Annex A (normative): Data fields		34
A.1	Summary	34
A.1.1	Introduction to data fields	34
A.1.2	Choice of data modelling language	34
A.1.3	Overview	34
A.2	Parameter definition for common fields	35
A.2.1	RetainedDataHeader	35
A.2.1.1	Parameters	35
A.2.1.2	RequestID parameters	35
A.2.2	RetainedDataPayload	35
A.2.2.1	RequestMessage parameters	35
A.2.2.2	RequestAcknowledgement parameters	35
A.2.2.3	ResponseMessage parameters	36
A.2.2.4	GetStatusMessage parameters	36
A.2.2.5	StatusMessage parameters	36
A.2.2.6	ErrorMessage parameters	37
A.2.3	GenericSubscriberInfo	37
A.2.3.1	Parameters	37
A.2.3.2	OrganizationInfo parameters	37
A.2.3.3	IndividualInfo parameters	37
A.3	ASN.1 definitions	38
A.3.1	General	38
A.3.1.1	ASN.1 syntax tree	38
A.3.1.2	General remarks on ASN.1	38
A.3.2	ASN.1 Definitions for message headers	39
A.3.2.1	Message wrappers	39
A.3.2.2	Message headers	39

A.3.3	ASN.1 definitions for common fields.....	43
A.3.4	Schematic representation of top level ASN.1	45
Annex B (normative): Service-specific details for telephony services		47
B.1	Scope	47
B.2	Telephony fields	47
B.2.1	General	47
B.2.2	Telephony Subscriber	47
B.2.2.1	subscriber ID	47
B.2.2.2	genericSubscriberInfo	47
B.2.2.3	telephonySubscriberInfo	48
B.2.2.4	subscribedTelephonyServices	48
B.2.2.4.1	Description	48
B.2.3	Telephony Billing Details	48
B.2.3.1	BillingRecords	49
B.2.4	Telephony ServiceUsage	49
B.2.4.1	Parameters.....	49
B.2.4.2	PartyInformation.....	50
B.2.4.3	SMSInformation	50
B.2.4.4	MmsInformation	51
B.2.5	TelephonyDevice.....	51
B.2.5.1	General.....	51
B.2.6	TelephonyNetworkElement.....	51
B.2.6.1	General.....	51
B.2.6.2	Location parameters.....	52
B.2.6.2.1	General	52
B.2.6.2.2	GSM Location Information	52
B.2.6.2.3	UMTS Location Information	52
B.2.6.2.4	Extended Location	53
B.3	ASN.1 definitions for telephony.....	53
B.4	Schematic view of ASN.1 definitions	66
Annex C (normative): Service-specific details for asynchronous message services		67
C.1	Scope	67
C.2	Descriptions.....	67
C.2.1	General	67
C.2.2	MsgSubscriber	68
C.2.3	MsgSubscriberID	68
C.2.4	MsgStore	68
C.2.5	MsgStoreID	68
C.2.6	MsgAddress.....	68
C.2.7	MsgProviderID	68
C.2.8	MsgServiceUsage.....	69
C.2.9	MsgTransmission	69
C.2.10	MsgStoreOperation	69
C.3	ASN.1 definitions for asynchronous message services	70
C.4	Schematic view of ASN.1 definitions	73
Annex D (normative): Service-specific details for synchronous multi-media services		74
D.1	Scope	74
D.2	Multimedia fields	74
D.2.1	General	74
D.2.2	Multimedia Subscriber	74
D.2.2.1	subscriberID.....	74
D.2.2.2	genericSubscriberInfo	75
D.2.2.3	multimediaSubscriberInfo	75

D.2.2.4	subscribedMultimediaServices	75
D.2.2.4.1	Description	75
D.2.3	MultimediaBillingDetails	75
D.2.3.1	MultimediaBillingDetails	75
D.2.3.2	MultimediaBillingRecords.....	76
D.2.4	Multimedia ServiceUsage	76
D.2.4.1	Parameters.....	76
D.2.4.2	PartyInformation.....	77
D.2.4.3	IMSInformation	77
D.2.4.4	MediaComponents.....	77
D.3	ASN.1 definitions for Multimedia.....	78
D.4	Schematic view of ASN.1 definitions	83
Annex E (normative): Service-specific details for network access services		84
E.1	Scope	84
E.2	Descriptions.....	84
E.2.1	General	84
E.2.2	NASubscriber	84
E.2.3	NAServiceSubscription	85
E.2.4	NAServiceUsage	85
E.2.5	NADevice.....	86
E.2.6	NANwElement	86
E.2.7	NABillingDetails.....	87
E.3	ASN.1 definitions for network access services	87
E.4	Schematic view of ASN.1 definitions	92
Annex F (informative): Basic set of search routines for Retained Data.....		93
F.1	Example set of search routines SIST-TS ETSI/TS 102 657 V1.7.1:2012	93
F.1.1	Introduction	93
F.1.2	Summary of search case https://standards.iteh.ai/catalog/standards/sist/682f3da1-4e64-413e-b9ce-46cd0c03d119/sist-ts-etsi-ts-102-657-v1-7-1-2012	93
F.1.3	Subscriber records	93
F.2	Telephony data	94
F.2.1	Telephony subscriber	94
F.2.2	Telephony billing details	94
F.2.3	Telephony service usage	94
F.2.4	Telephony network element	94
F.3	Messaging data.....	95
F.3.1	Message subscriber.....	95
F.3.2	Message service usage.....	95
F.4	Network Access data.....	95
F.4.1	NA subscriber.....	95
F.4.2	NA service usage.....	96
Annex G (informative): Examples of search routines		97
G.1	Introduction	97
G.2	Example for telephony subscriber query in clause F.2.1.....	97
G.3	Example for telephony service usage query in clause F.2.3.....	98
Annex H (informative): Further information on data categories.....		99
H.1	General	99
H.2	Further information on subscriber data	99
H.2.1	Subscriber data requests	99
H.2.2	Generic subscriber data records.....	99

H.2.3	Service Specific Subscriber Reply Data	100
H.3	Further information on usage data.....	101
H.3.1	Usage requests.....	101
H.3.2	Usage data categories	101
H.3.3	Usage: Traffic Data (Reply)	101
H.3.4	Usage: Traffic Data related information (Reply).....	101
H.3.5	Usage: communication independent user activities (Reply).....	102
H.3.6	Usage: network Activity Data (Reply)	102
H.4	Further information on network element data	102
H.4.1	Network element requests	102
H.4.2	Network Configuration Data Reply Data	102
Annex I (informative):	Manual techniques.....	103
Annex J (informative):	Informative mapping of data fields to the EU Data Retention Directive.....	104
Annex K (informative):	Single versus multi part deliveries	105
K.1	General	105
K.2	Criteria for multi part delivery	105
K.3	Subscriptions into the future.....	106
Annex L (informative):	Change Request History.....	107
History		109

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST-TS ETSI/TS 102 657 V1.7.1:2012](https://standards.iteh.ai/catalog/standards/sist/682f3da1-4e64-413e-b9ce-46cd0c03d119/sist-ts-etsi-ts-102-657-v1-7-1-2012)

<https://standards.iteh.ai/catalog/standards/sist/682f3da1-4e64-413e-b9ce-46cd0c03d119/sist-ts-etsi-ts-102-657-v1-7-1-2012>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Lawful Interception (LI).

The ASN.1 module and XML schema are also available as an electronic attachment to the original document from the ETSI site (see details in clause A.3.1.2).

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST-TS ETSI/TS 102 657 V1.7.1:2012](https://standards.iteh.ai/catalog/standards/sist/682f3da1-4e64-413e-b9ce-46cd0c03d119/sist-ts-etsi-ts-102-657-v1-7-1-2012)

<https://standards.iteh.ai/catalog/standards/sist/682f3da1-4e64-413e-b9ce-46cd0c03d119/sist-ts-etsi-ts-102-657-v1-7-1-2012>

1 Scope

The present document contains handover requirements and a handover specification for the data that is identified in EU Directive 2006/24/EC on Data Retention [1]. The handover requirements from TS 102 656 [2] are derived from the requirements contained in and implied by the EU Directive [1] and by other national legislations. The present document considers both the requesting of retained data and the delivery of the results.

The present document defines an electronic interface. An informative annex describes how this interface may be adapted for manual techniques. Apart from in annex I, the present document does not consider manual techniques.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] Directive 2006/24/EC of the European Parliament and of the Council of 15 March 2006 on the retention of data generated or processed in connection with the provision of publicly available electronic communications services or of public communications networks and amending Directive 2002/58/EC
 - [2] ETSI TS 102 656: "Lawful Interception (LI); Retained Data; Requirements of Law Enforcement Agencies for handling Retained Data".
 - [3] ETSI TS 102 232-1: "Lawful Interception (LI); Handover Interface and Service-Specific Details (SSD) for IP delivery; Part 1: Handover specification for IP delivery".
 - [4] ISO 3166-1: "Codes for the representation of names of countries and their subdivisions - Part 1: Country codes".
 - [5] ISO 4217: "Codes for the representation of currencies and funds".
 - [6] ETSI TS 101 671: "Lawful Interception (LI); Handover interface for the lawful interception of telecommunications traffic".
- NOTE: Periodically TS 101 671 is published as ES 201 671. A reference to the latest version of the TS as above reflects the latest stable content from ETSI/TC LI.
- [7] ETSI EN 300 356 (all parts): "Integrated Services Digital Network (ISDN); Signalling System No.7 (SS7); ISDN User Part (ISUP) version 4 for the international interface".
 - [8] ETSI TS 100 974: "Digital cellular telecommunications system (Phase 2+); Mobile Application Part (MAP) Specification (3GPP TS 09.02)".
 - [9] ETSI TS 124 008: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; Mobile radio interface Layer 3 specification; Core network protocols; Stage 3 (3GPP TS 24.008)".
 - [10] ETSI TS 125 431: "Universal Mobile Telecommunications System (UMTS); UTRAN Iub interface Layer 1 (3GPP TS 25.431)".

- [11] ETSI TS 133 108: "Universal Mobile Telecommunications System (UMTS); LTE; 3G security; Handover interface for Lawful Interception (LI) (3GPP TS 33.108)".
- [12] ETSI TS 101 109: "Digital cellular telecommunications system (Phase 2+); Universal Geographical Area Description (GAD) (3GPP TS 03.32 version 7.2.0)".
- [13] FIPS PUB 186-2: "Digital Signature Standard (DSS)".
- [14] IETF RFC 2616: "Hypertext Transfer Protocol - HTTP/1.1".
- [15] IETF RFC 2818: "HTTP Over TLS".
- [16] ETSI TS 123 040: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); Technical realization of Short Message Service (SMS) (3GPP TS 23.040)".
- [17] IETF RFC 0793: "Transmission Control Protocol".
- [18] IETF RFC 2581: "TCP Congestion Control".
- [19] IETF RFC 2988: "Computing TCP's Retransmission Timer".
- [20] IETF RFC 1122: "Requirements for Internet Hosts - Communication Layers".
- [21] IETF RFC 0791: "Internet Protocol".
- [22] ETSI ES 282 002: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); PSTN/ISDN Emulation Sub-system (PES); Functional architecture".
- [23] IETF RFC 0822: "Standard for the format of ARPA internet text messages".
- [24] IETF RFC 2822: "Internet Message Format".
- [25] ETSI TS 123 228: "Digital cellular telecommunications system (Phase 2+); Universal Mobile Telecommunications System (UMTS); LTE; IP Multimedia Subsystem (IMS); Stage 2 (3GPP TS 23.228)".
- [26] IETF RFC 3261: "SIP: Session Initiation Protocol".

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

Not applicable.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

authorized organization: any authority legally authorized to request or receive retained data e.g. a Law Enforcement Agency

Handover Interface A (HI-A): administrative handover interface comprising requests for information and their responses

Handover Interface B (HI-B): data handover interface comprising the retained data transmission of information

lawful authorization: permission granted to an Authorized Organization under certain conditions to request specified telecommunications retained data and requiring co-operation from a network operator/service provider/access provider

NOTE: Typically, this refers to a warrant or order issued by a lawfully authorized body.

location information: information relating to the geographic, physical or logical location of an identity relating to an interception subject

number: any address (E.164, IP, email, URI) used for routing in a network or in a service on a user level or network/service level

request: legal requirement for a Communications Service Provider (CSP) to disclose retained data in accordance with relevant national law

requesting authority: any entity possessing the necessary jurisdiction and authority pursuant to law to compel a service provider to deliver retained subscriber information or traffic data specified in a query

response to request of information: response from the CSP to the requesting authority acknowledging or rejecting a request for information

retained data record: set of data elements for a specific subscriber/user related to a specific service transaction

service transaction: instance of a service given by a CSP to a subscriber/user

service transaction record: set of data elements describing a service transaction (details to be determined)

transmission of information: transmission of retained data from the CSP to the requesting authority

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ADSL	Asymmetric Digital Subscriber Line
APN	Access Point Name
ASN	Abstract Syntax Notation
BER	Basic Encoding Rules
CPE	Customer Premises Equipment
CS	Circuit Switched
CSP	Communications Service Provider
CSPID	CSP Identifier
DNS	Domain Name System
DSA	Digital Signature Algorithm
DSL	Digital Subscriber Line
DSS	Digital Signature Standard
DVD	Digital Versatile Disc or Digital Video Disc
EMS	Enhanced Messaging Service
GGSN	Gateway GPRS Support Node
GPRS	General Packet Radio Service
GSM	Global System for Mobile communications
HI	Handover Interface
HTTP	HyperText Transfer Protocol
HTTPS	HyperText Transfer Protocol over Secure Socket Layer
ICCID	Integrated Circuit Card ID
ID	IDentifier
IEI	Information Element Identifier
IMAP	Internet Message Access Protocol
IMEI	International Mobile Equipment Identity
IMS	IP Multimedia Subsystem
IMSI	International Mobile Subscriber Identity
IP	Internet Protocol
IPSec	Internet Protocol Security
IRI	Intercept Related Information
ISDN	Integrated Services Digital Network

ISUP	ISDN User Part
LAN	Local Area Network
LI	Lawful Interception
MAC	Media Access Control
MMS	Multimedia Messaging Service
MSC	Mobile Switching Centre
MSISDN	Mobile Subscriber ISDN number
MSN	Multiple Subscriber Number
NA	Network Access
NAS	Network Access Server
PDP	Packet Data Protocol
PDU	Protocol Data Unit
PS	Packet Switched
PSTN	Public Switched Telephone Network
PUK	Personal Unblocking Key
RAI	Routing Area Identifier
RD	Retained Data
RDHI	Retained Data Handover Interface
SAI	Service Area Identifier
SGSN	Serving GPRS Support Node
SHA	Secure Hash Algorithm
SIM	Subscriber Identity Module
SIP	Session Initiation Protocol
SMS	Short Message Service
SMTP	Simple Mail Transfer Protocol
TCP	Transmission Control Protocol
TLS	Transport Layer Security
UMTS	Universal Mobile Telecommunication System
URI	Uniform Resource Identifier
UTF	Unicode Transformation Format
UTM	Universal Transverse Mercator
WGS	World Geodetic System
XML	eXtensible Markup Language

THIS STANDARD PREVIEW
(standards.iteh.ai)

SIST-TS ETSI/TS 102 657 V1.7.1:2012


<https://standards.iteh.ai/catalog/standards/sist/682f3da1-4e64-413e-b9ce-46cd0c03d119/sist-ts-etsi-ts-102-657-v1-7-1-2012>

4 Overview of handover interface

4.1 Reference model

The generic Handover Interface adopts a two-port structure such that administrative request/response information (HI-A) and Retained Data Information (HI-B) are logically separated.

Figure 1 is the reference model for the request and transmission of retained telecommunications data.



NOTE 1: The term Authorized Organization covers any agency legally authorized to make RDHI requests (see clause 3.1).

NOTE 2: HI-B delivers data from CSP to the Authorized Organization. There may be related supporting lower level messages from the Authorized Organization to CSP on HI-B.

Figure 1: Functional diagram showing handover interface HI

Each of these two parties can be expanded to show some of their internal functions. This is not to proscribe how implementations of the present document must be organized, and is purely informational.

Within the CSP block, three internal CSP functions can be identified: an *administrative function* to manage the RD requests and responses; a *data collection function* to collect data from the various internal network elements and prepare the data for retention; a *data store management function* to index and store the data, execute queries, and manage the maximum retention period for RD.

Within the Authorized Organization block, two functions can be identified: an *issuing authority* responsible for initiating new RDHI requests; a *receiving authority* to accept the RDHI responses. In many situations, the authority issuing a request will also be the authority to receive the responses. However, the issuing authority may indicate a different delivery point for HI-B responses, in which case the issuing authority and receiving authority will be different.

These internal functions, and the interfaces between them, do not form a normative part of the present document.




Figure 2: Functional model (informative)

A CSP or Authorized Organization may outsource some of its internal functions to a third party. It is a national option whether or not outsourcing is allowed, or whether conditions apply.