



SLOVENSKI STANDARD

DSIST ETS 300 494-2:1999

01-1999

8 [[]HJbY]nVc`ýUbYVfYnj fj] bYhY_ca i b]_UWY'fB 97 HL!'DfcZ` [YbYf] bY[U
XcghcdUf] 5 DL!'&"XY.'CX'dfcZ`UcXj]gbUdfYg_i ýUbUgdYWZ`_UWY'fDGHGZ!
dfYbcgbUfUX]g_UnU_`f]hYj

Digital Enhanced Cordless Telecommunications (DECT); Generic Access Profile (GAP);
Profile Test Specification (PTS); Part 2: Profile Specific Test Specification (PSTS) -
Portable radio Termination (PT)

Ta slovenski standard je istoveten z: ETS 300 494-2 E1.% - *!\$,

ICS:

33.070.30 Öä äæ) ^Á à[|za) ^
à!^: ç!çã } ^Á ^\ [{ ~ } ä æä
ÖÖÖVD Digital Enhanced Cordless
Telecommunications (DECT)

DSIST ETS 300 494-2:1999

en



EUROPEAN
TELECOMMUNICATION
STANDARD

ETS 300 494-2

August 1996

Source: ETSI TC-RES

Reference: DE/RES-03040-2

ICS: 33.020, 33.060.50

Key words: DECT, GAP, testing

**Radio Equipment and Systems (RES);
Digital Enhanced Cordless Telecommunications (DECT);
Generic Access Profile (GAP);
Profile Test Specification (PTS);
Part 2: Profile Specific Test Specification (PSTS)
- Portable radio Termination (PT)**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1996. All rights reserved.

Contents

Foreword		7
1	Scope	9
2	Normative references	9
3	Definitions and abbreviations	11
3.1	Definitions	11
3.2	Abbreviations	12
4	Relevant test cases list	12
4.1	Network (NWK) layer	12
4.1.1	Test Suite Structure (TSS)	13
4.1.2	Test case index	15
4.2	Data Link Control (DLC) layer	19
4.2.1	Test suite structure	19
4.2.2	Test case index	20
4.3	Medium Access Control (MAC) layer	21
4.3.1	Test suite structure	22
4.3.2	Test case index	23
4.4	PHysical (PH) layer	24
4.4.1	Manufacturer declarations	24
4.4.2	Normal Transmitted Power (NTP)	24
4.4.2.1	Verdict criteria for IUTs with an integral antenna	24
4.4.2.2	Verdict criteria for IUTs with external antenna connection(s)	24
4.4.3	PP radio receiver sensitivity	24
4.4.4	Radio receiver interference performance	25
4.4.5	Receiver intermodulation performance	25
4.4.6	User controlled volume control	25
5	Additional test cases list	25
5.1	Test purposes	25
5.1.1	NWK layer	25
5.1.2	DLC layer	25
5.1.3	MAC layer	25
5.1.4	PH layer	25
5.2	Test cases	26
5.2.1	NWK layer	26
5.2.2	DLC layer	26
5.2.3	MAC layer	26
5.2.4	PH layer	26
5.2.4.1	Receiver sensitivity tolerance of transmitter deviation variations	26
5.2.4.1.1	Definition	26
5.2.4.1.2	Test environment	26
5.2.4.1.3	Method of measurement	26
5.2.4.1.4	Verdict criteria	27
5.2.4.2	Receiver timing tolerance of a PT	27
5.2.4.2.1	Definition	27
5.2.4.2.2	Test environment	27
5.2.4.2.3	Method of measurement, Part 1	27
5.2.4.2.4	Method of measurement, Part 2	28
5.2.4.2.5	Verdict criteria for part 1	28
5.2.4.2.6	Verdict criteria for part 2	28
5.2.4.3	Transmission of Z-field	28
5.2.4.3.1	Definition	28
5.2.4.3.2	Test environment	28

	5.2.4.3.3	Method of measurement	29
	5.2.4.3.4	Verdict criteria	29
Annex A (normative):	Profile Implementation eXtra Information for Testing (IXIT) proforma		30
A.1	General		30
A.2	Profile XRL		30
A.2.1	WK layer protocol		30
	A.2.1.1	Addresses	30
	A.2.1.2	Parameter values	30
	A.2.1.3	Timer values	30
	A.2.1.4	Counters values	30
	A.2.1.5	Protocol constants values	31
	A.2.1.6	Control of Protocol Data Units (PDU) sending	31
A.2.2	DLC layer protocol		31
	A.2.2.1	Addresses	31
	A.2.2.2	Parameter values	31
	A.2.2.3	Timer values	31
	A.2.2.4	Counters values	31
	A.2.2.5	Protocol constants values	32
	A.2.2.6	Control of PDU sending	32
A.2.3	MAC layer protocol		32
	A.2.3.1	Addresses	32
	A.2.3.2	Parameter values	32
	A.2.3.3	Timer values	32
	A.2.3.4	Counters values	32
	A.2.3.5	Protocol constants values	33
	A.2.3.6	Control of PDU sending	33
A.2.4	PH layer protocol		33
	A.2.4.1	Addresses	33
	A.2.4.2	Parameter values	33
	A.2.4.3	Timer values	33
	A.2.4.4	Counters values	33
	A.2.4.5	Protocol constants values	33
	A.2.4.6	Control of PDU sending	33
A.3	Profile specific IXIT		34
	A.3.1	NWK layer	34
	A.3.2	DLC layer	34
	A.3.3	MAC layer	34
	A.3.4	PH layer	34
	A.3.5	Configuration constraints	34
Annex B (normative):	Profile Conformance Test Report (PCTR) proforma		35
B.1	Identification summary		35
	B.1.1	Profile CTR	35
	B.1.2	Implementation Under Test (IUT)	35
	B.1.3	Testing environment	36
	B.1.4	Limits and reservations	36
	B.1.5	Comments	36
B.2	IUT conformance status		36
B.3	Static conformance summary		37
B.4	Dynamic conformance summary		37
B.5	Static conformance review report		37
B.6	Test campaign report		38
	B.6.1	NWK layer	38

B.6.2	DLC layer	40
B.6.3	MAC layer	41
B.6.4	PH layer	42
B.7	Observations	42
Annex C (normative): System Conformance Test Report proforma (SCTR)		43
C.1	Identification summary	43
C.1.1	System Conformance Test Report (SCTR)	43
C.1.2	Test Laboratory	43
C.1.3	Client	44
C.1.4	System Under Test (SUT)	44
C.1.5	Profile	44
C.1.6	Nature of conformance testing	45
C.1.7	Limits and reservations	45
C.1.8	Record of agreement	45
C.1.9	Comments	46
C.2	System report summary	46
C.2.1	Profile testing summary for GAP NWK layer PT	46
C.2.2	Profile testing summary for GAP DLC layer PT	47
C.2.3	Profile testing summary for GAP MAC layer PT	48
C.2.4	Profile testing summary for GAP PH layer PT	49
Annex D (normative): System Conformance Statement (SCS) proforma		50
D.1	Identification summary	50
D.1.1	SCS identification	50
D.1.2	IUT identification	50
D.1.3	Client identification	50
D.1.4	Supplier identification	51
D.1.5	Manufacturer identification	51
D.1.6	Protocols identification	52
D.1.7	Profile identification	52
D.2	Miscellaneous system information	52
D.2.1	Configuration	52
D.2.2	Other information	52
History		53

Blank page