



Technical Report

Powerline Telecommunications (PLT); Powerline communication recommendations for smart metering and home automation

PREVIEW
iTech Standards (standards.iteh.ai)
Full standard available at: <https://standards.iteh.ai/catalog/standards/sist/69ad94c1-c569-41af-9c85-7dab38c808a1/etsi-tr-103-240-v1.1.1-2014-01>

Reference

DTR/PLT-00031

Keywords

powerline, smart meter

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2014.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and LTE™ are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	4
Foreword.....	4
1 Scope	5
2 References	5
2.1 Normative references	5
2.2 Informative references.....	5
3 Definitions and abbreviations.....	6
3.1 Definitions.....	6
3.2 Abbreviations	7
4 Recommendations for functionalities.....	8
4.1 List of functionalities.....	8
4.2 List of additional functionalities.....	8
4.3 Home automation	8
4.4 M2M gateway	9
5 General Recommendations on PLT Communication.....	9
5.1 Frequency Bands	9
5.2 Coexistence with existing technologies.....	10
5.3 Power Consumption	10
5.4 Transmission Robustness	10
5.5 Security	10
5.6 Adaptive Communication.....	10
6 Recommendations on PHY layer for Smart Meters.....	10
7 Recommendations on MAC layer for Smart Meters.....	11
8 Recommendations on Transport layer for Smart Meters	11
9 Recommendations on Application layer for Smart Meters	11
9.1 Metering Application	11
10 Home Automation Recommendations	12
10.1 Scope of requirement.....	12
10.2 Overview	12
10.3 General requirements	12
10.3.1 Openness and availability.....	13
10.3.2 Range.....	13
10.3.3 Power consumption.....	13
10.3.4 Data rate.....	13
10.3.5 Robustness	13
10.3.6 EMC Regulatory compliance.....	14
10.3.7 Coexistence.....	14
10.3.8 Security	14
10.3.9 Latency	14
History	15

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Report (TR) has been produced by ETSI Technical Committee Powerline Telecommunications (PLT).

ITeH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/69ad94c1-c569-41af-9c85-7dab38c808af/etsi-tr-103-240-v1.1.1-2014-01>

1 Scope

The present document concentrates on recommendations for power line communication for smart meters and home automation using IP based transports along with DLMS/COSEM data models.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are necessary for the application of the present document.

Not applicable.

2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] CENELEC EN 50065-1: "Signalling on low-voltage electrical installations in the frequency range 3 kHz to 148,5 kHz - Part 1: General requirements, frequency bands and electromagnetic disturbances".
- [i.2] Recommendation ITU-T G.9972: "Coexistence mechanism for wireline home networking transceivers".
- [i.3] IEC 62056-47: "Electricity metering - Data exchange for meter reading, tariff and load control - Part 47: COSEM transport layers for IPv4 networks".
- [i.4] IEEE 802.15.4TM: "IEEE Standard for Information technology-- Local and metropolitan area networks-- Specific requirements-- Part 15.4: Wireless Medium Access Control (MAC) and Physical Layer (PHY) Specifications for Low Rate Wireless Personal Area Networks (WPANs)".
- [i.5] Recommendation ITU-T G.993.2: "VDSL2 :Very High Speed Digital Subscriber Line transceivers 2".
- [i.6] Recommendation ITU-T G.9903: "Narrowband Orthogonal Frequency Division Multiplexing Power Line Communication Transceivers for G3-PLC Networks".
- [i.7] Recommendation ITU-T G.9904: "Narrowband orthogonal frequency division multiplexing power line communication transceivers for PRIME networks".
- [i.8] IEEE 1901.2TM - 2013: "IEEE Standard for Low-Frequency (less than 500kHz) Narrowband Power Line Communications for Smart grid Applications".
- [i.9] IEEE 1901TM - 2010: "IEEE Standard for Broadband over Power Line Networks: Medium Access Control and Physical Layer Specifications".

[i.10] HomePlug Green PHY™ Specification.

NOTE: See http://www.homeplug.org/tech/homeplug_gp.

[i.11] ETSI TS 102 578: "PowerLine Telecommunications (PLT); Coexistence between PLT Modems and Short Wave Radio broadcasting services".

[i.12] IETF RFC 4919: "IPv6 over Low-Power Wireless Personal Area Networks (6LoWPANs): Overview, Assumptions, Problem Statement, and Goals".

[i.13] IETF RFC 4944: "Transmission of IPv6 Packets over IEEE 802.15.4 Networks".

[i.14] ISO/IEC 14908-3: "Information technology -- Control network protocol -- Part 3: Power line channel specification".

[i.15] Recommendation ITU-T G.9901: "Narrowband Orthogonal Frequency Division Multiplexing Power Line Communication Transceivers - Power Spectral Density Specification".

[i.16] Directive 2005/32/EC of the European Parliament and of the Council of 6 July 2005 establishing a framework for the setting of ecodesign requirements for energy-using products and amending Council Directive 92/42/EEC and Directives 96/57/EC and 2000/55/EC of the European Parliament and of the Council.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

Data Link Layer (DLL): (e.g. media access control or MAC) is where the exchange of frames (many bits) is performed

NOTE: The network layer is the level where paths are determined and logical addressing is applied for packets (many frames). End-to-end connections are formed at the transport layer and segments (many packets) are exchanged. The session layer deals with interhost communication. The presentation layer deals with data representation and encryption. Finally, the application layer is the level at which interaction with a user is attained. Sometimes technologies will use a different model from the seven layers of the OSI stack. These models may only reference three or four layers: however the functionality of all seven OSI layers is typically bundled in to the model regardless. The OSI model is generally accepted as the most detailed practical representation of communication functionality.

Home Area Networks (HAN): sometimes referred to as a Premise Area Network (PAN) or a Building Area Network (BAN), is an application specific LAN, which includes devices within a single premise (industrial site, commercial business or home) communicating over one or more networks.

NOTE: Electric utilities are looking to leverage these networks to provide relief during high demand periods (demand response) by communicating through some type of home gateway bridging utility and home networks. Internet service providers are looking to provide revenue generating services using home automation networks.

Home System (HS): is an interconnection of functional devices as:

- Energy Meter;
- Local Display;
- Demand Response device and
- Local application server.

Local Area Networks (LAN): this zone identifies a "close" set of devices in communication, as the name implies, in a local configuration

NOTE: Often each floor of a building may be on its own LAN, or a single server room may be a LAN.

RPL: IPv6 Routing Protocol for Low-Power and Lossy Networks

smart energy meter: is a device to measure the energy consumption data and make these data available for Smart service provider and the local application server, mostly operating in two way communications device in reliable manner with a set of management functions

NOTE: All communications are generally encrypted and provide real time or near real time measurements to the local application server.

Smart Grid (SG): smart grid is achieved by overlaying the power systems infrastructure with communications infrastructure

NOTE: Benefits are derived by delineating the communications infrastructure along functions that are not quite tied on a one-to-one basis with the power system infrastructure.

The Physical layer (or PHY layer): physical layer is the transmission of data at the bits levels from the signal processing extracted from electrical lines media

use case: description of a specific configuration/deployment scenario of a system from the user point of view

NOTE: The user consider the system as a blackbox and he perceive from the outside the system from the interactions and responses.

Wide Area Networks (WAN): this zone is the bridge between FANs and SANs and the utility LAN and back office

NOTE: This includes communications from control centres to the substations. This is commonly referred to as 'backhaul' communications.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

6LowPAN	IPv6 Low Power Wireless Personal Area Network
CE	Consumer Electronics
CFL	Compact Fluorescent Lights
COSEM	Companion Specification for Energy Metering
DLL	Data Link Layer
DLMS	Device Language Message Specification
DRM	Digital Radio Mondiale
EC	European Commission
EMC	Electro Magnetic Compatibility
EN	European Norm
ESNA	Energy Services Network Association
FAN	Field Area Network
FFT	Fast Fourier Transform
GFCI	Ground Fault Circuit Interrupter
HAN	Home Area network
IEC	International Electrotechnical Commission
IHD	In Home Displays
IP	Internet Protocol
IPTV	Internet Protocol based Television
ISP	Internet Service Provider
LAN	Local Area Network
M2M	Machine to Machine
MAC	Media Access Control
MDU	Multi Dwelling Units
MTBF	Mean Time Between Failures
OFDM	Orthogonal Frequency Division Multiplex

OSI	Open System Interconnection
PHY	Physical layer
PLC	Power Line Communications
RCCB	Residual-Current Circuit Breaker
SAN	Sensor Area Network
TCP	Transmission Control Protocol
UDP	User Datagram Protocol

4 Recommendations for functionalities

4.1 List of functionalities

Smart Meters are designed for utilities (electricity, gas, water and heating) which are able to base their bills and meter readings on accurate consumption provided by the meter's interface.

Smart Metering provides also information to:

- the customer on request for energy saving and the home gateway propose decisions on their energy usage;
- energy suppliers to understand their customer energy usage and services;
- distributors for monitoring the energy usage and network management; and
- monitoring the customer generating their own electricity for the financial reward on the final billing.

4.2 List of additional functionalities

The proposed list of 6 main additional functionalities is set out below. The functionalities have been expressed in broad terms Identifying functionalities at high level will permit flexibility, innovation and competition.

- F1. Remote reading of metrological register(s) and provision to designated market organisation(s).
- F2. Two-way communication between the metering system and designated market organisation(s).
- F3. Meter supporting advanced tariffing and payment systems.
- F4. Meter allowing remote disablement and enablement of supply.
- F5. Two way communication data passive interface with (and where appropriate directly controlling) individual devices within the home/building.
- F6. Meter providing information via portal/gateway to an in-home/building display or auxiliary equipment.
- F7. Monitoring for electricity theft.
- F8. Meter providing power quality data and alarms.

4.3 Home automation

Home automation and energy management systems need to get information on consumption data from smart meters. In Home Displays (IHD) (including smart phones and laptops) are designed to show actual load demand to customers. To enable open application support to these use cases, a passive data interface is defined to the smart energy meter and the M2M gateway where home automation gateways can connect and get data. This method enables different kinds of home automation systems and energy management technologies to connect to smart meters using a standardized interface. Home automation and energy management gateways can have communication to M2M gateways or smart energy meters.

"Passive" means here that it is not be possible to inadmissibly affect the operation and the metrology of the smart energy meter/M2M gateway, in particular any legally relevant function.

The main issues are:

- interface to smart home architecture;
- open communication protocol;
- home displays;
- TCP/IP or UDP/IP enabled machines;
- "one-to-many" remote communication towards M2M gateway or smart energy meter.

4.4 M2M gateway

The M2M gateway should ensure mass data transportation from many distributed energy meters in the field to one or several concentrated data collection hubs using public networks. The functions of this gateway need to support all possible data items from all connected meters, home automation and energy management systems.

The main issues of this M2M gateway are:

- remote communication;
- gateway between private and public networks;
- open for applicable data protocol, architecture and physical layers;
- remote reprogramming;
- security access;
- possible alliance with electricity meter.

Metering systems are the central data backbone of any smart metering infrastructure. As these systems may be connected to public networks and may operate in security related utility environments, a proper support of state-of-the-art security obligations and guidelines is mandatory. To enable open access to metering systems of several suppliers and technology vendors, head end systems need to support a common communication and data exchange standard. Central communication systems may be the communication gateway to public smart meter data portals and need to support open interfaces to such portals.

The main issues of this metering system are:

- data collector for M2M gateways and direct communications meters;
- data warehouse for billing systems;
- data and system access security;
- installation management;
- remote control of smart meters.

5 General Recommendations on PLT Communication

5.1 Frequency Bands

PLT for Smart Meters and Home Automation should operate in following Frequency Bands:

- CENELEC A, B and C frequency bands for Europe as specified in [i.2]; or
- Broadband PLT band 2 MHz to 30 MHz.