



SLOVENSKI STANDARD SIST EN 301 003-2:2000

01-december-2000

ü]fc_cdUgcj bc`X][]HJbc`ca fYy`Y`n`]bhY[f]fUb]a]`g]fcf]hj Ua]`f6 !=G8 BŁ!`Dfc]c_c`
X][]HJbY`bUfc b]y`Y`g][bU]nUWY`Y`y`h`&`fB GG&Ł!`? UfU_hyf]gh_Y`nj YnY!`A cX]Z]Wf]Ub`Y`
j f\ b`Y`WY`] bY\]]fcgh`df]`Ugfb_]_i`nj YnY!`&`XY.`:n`Uj Uc`g`UXbcgh`]nj YXVY
dfc]c_c`UfD=7 GŁ!`DfcZfa UgdYWZ]_UWY`

Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; Peak cell rate modification by the connection owner; Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification

(standards.iteh.ai)

[SIST EN 301 003-2:2000](https://standards.iteh.ai/catalog/standards/sist/fb02d193-3c52-4fff-a1ec-d317de6cc308/sist-en-301-003-2-2000)

<https://standards.iteh.ai/catalog/standards/sist/fb02d193-3c52-4fff-a1ec-d317de6cc308/sist-en-301-003-2-2000>

Ta slovenski standard je istoveten z: EN 301 003-2 Version 1.1.3

ICS:

33.080	Digitalno omrežje z integriranimi storitvami (ISDN)	Integrated Services Digital Network (ISDN)
--------	---	--

SIST EN 301 003-2:2000 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 003-2:2000](#)

<https://standards.iteh.ai/catalog/standards/sist/fb02d193-3c52-4fff-a1ec-d317de6cc308/sist-en-301-003-2-2000>

EN 301 003-2 V1.1.3 (1999-05)

European Standard (Telecommunications series)

**Broadband Integrated Services Digital Network (B-ISDN);
Digital Subscriber Signalling System No. two (DSS2) protocol;
Connection characteristics;
Peak cell rate modification by the connection owner;
Part 2: Protocol Implementation Conformance
Statement (PICS) proforma specification**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 003-2:2000](#)

<https://standards.iteh.ai/catalog/standards/sist/fb02d193-3c52-4ff-a1ec-d317de6cc308/sist-en-301-003-2-2000>



Reference

DEN/SPS-05083-2 (9aci0ie0.PDF)

Keywords

ATM, B-ISDN, broadband, DSS2, ISDN, layer 3,
PICS, UNI

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C

Association à but non lucratif enregistrée à la

Sous-Prefecture de Grasse (06) N° 7803/88

<https://standards.etsi.org/catalog/standards/sist/en-301-003-2-2000>

Internet

secretariat@etsi.fr

Individual copies of this ETSI deliverable
can be downloaded from

<http://www.etsi.org>

If you find errors in the present document, send your
comment to: editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1999.
All rights reserved.

Contents

Intellectual Property Rights	4
Foreword	4
1 Scope	5
2 References	5
3 Definitions, symbols and abbreviations	5
3.1 Definitions	5
3.2 Symbols	6
3.3 Abbreviations	6
4 Conformance	6
Annex A (normative): PICS proforma for EN 301 003-1	7
A.1 Guidance for completing the PICS proforma	7
A.1.1 Purpose and structure	7
A.1.2 Abbreviations and conventions	7
A.1.3 Instructions for completing the PICS proforma	8
A.1.4 The PICS proforma tables	9
A.1.4.1 Correspondence to physical interface	9
A.1.4.2 Structure of the tables	9
A.1.4.3 Support for received PDU parameters	9
A.2 Identification of the implementation	10
A.2.1 Date of the statement	10
A.2.2 Implementation Under Test (IUT) identification	10
A.2.3 System Under Test (SUT) identification	10
A.2.4 Product supplier	11
A.2.5 Client	11
A.2.6 PICS contact person	12
A.3 Identification of the protocol to which this PICS proforma applies	12
A.4 Global statement of conformance	12
A.5 Roles	13
A.6 Major capabilities	13
A.7 Requesting entity	14
A.7.1 Messages received	14
A.7.2 Messages transmitted	14
A.7.3 Requesting entity protocol data unit parameters	15
A.7.3.1 Requesting entity protocol data unit parameters received	15
A.7.3.2 Requesting entity protocol data unit parameters transmitted	15
A.8 Responding entity	16
A.8.1 Messages received	16
A.8.2 Messages transmitted	16
A.8.3 Responding entity protocol data unit parameters	17
A.8.3.1 Responding entity protocol data unit parameters received	17
A.8.3.2 Responding entity protocol data unit parameters transmitted	17
A.9 Timers	18
History	19

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Signalling Protocols and Switching (SPS).

The present document is part 2 of a multi-part standard covering the Digital Subscriber Signalling System No. two (DSS2) protocol specification for the Broadband Integrated Services Digital Network (B-ISDN) peak cell rate modification by the connection owner, as described below:

- Part 1: "Protocol specification [ITU-T Recommendation Q.2963.1 (1996), modified]";
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";**
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";
- Part 5: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network";
- Part 6: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network".

To evaluate conformance of a particular implementation, it is necessary to have a statement of which capabilities and options have been implemented for a given Open Systems Interconnection (OSI) protocol. Such a statement is called a Protocol Implementation Conformance Statement (PICS).

National transposition dates	
Date of adoption of this EN:	2 April 1999
Date of latest announcement of this EN (doa):	31 July 1999
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2000
Date of withdrawal of any conflicting National Standard (dow):	31 January 2000

1 Scope

This second part of EN 301 003 provides the Protocol Interface Conformance Statement (PICS) proforma for the for peak cell rate modification for the Broadband-Integrated Services Digital Network (B-ISDN) by means of the Digital Subscriber Signalling System No. two (DSS2) protocol as specified in EN 301 003-1 [2] in compliance with the relevant requirements and in accordance with the relevant guidance given in ISO/IEC 9646-7 [4].

The supplier of a protocol implementation which is claimed to conform to EN 301 003-1 [2] is required to complete a copy of the PICS proforma provided in annex A of the present document and is required to provide the information necessary to identify the supplier and the implementation.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- iTeh STANDARD PREVIEW
(standards.iteh.ai)
- [1] EN 300 443-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; B-ISDN user-network interface layer 3 specification for basic call/bearer control; Part 1: Protocol specification [ITU-T Recommendation Q.2931 (1995), modified]". [https://standards.iteh.ai/catalog/standards/sist/fb02d193-3c52-4ff1-a1ec-1031-broadband-integrated-services-digital-network-\(b-isdn\);-digital-subscriber-signalling-system-no.-two-\(dss2\)-protocol;-connection-characteristics;-peak-cell-rate-modification-by-the-connection-owner;-part-1:-protocol-specification](https://standards.iteh.ai/catalog/standards/sist/fb02d193-3c52-4ff1-a1ec-1031-broadband-integrated-services-digital-network-(b-isdn);-digital-subscriber-signalling-system-no.-two-(dss2)-protocol;-connection-characteristics;-peak-cell-rate-modification-by-the-connection-owner;-part-1:-protocol-specification)
- [2] EN 301 003-1 (V1.1.3) "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; Peak cell rate modification by the connection owner; Part 1: Protocol specification [ITU-T Recommendation Q.2963.1 (1996), modified]".
- [3] ISO/IEC 9646-1: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- [4] ISO/IEC 9646-7: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply, in addition to those given in EN 301 003-1 [2]:

Protocol Implementation Conformance Statement (PICS): a statement made by the supplier of an Open Systems Interconnection (OSI) implementation or system, stating which capabilities have been implemented for a given OSI protocol (see ISO/IEC 9646-1 [3])

PICS proforma: a document, in the form of a questionnaire, designed by the protocol specifier or conformance test suite specifier, which, when completed for an OSI implementation or system becomes the PICS (see ISO/IEC 9646-1 [3])

static conformance review: a review of the extent to which the static conformance requirements are met by the IUT, accomplished by comparing the PICS with the static conformance requirements expressed in the relevant standard(s) (see ISO/IEC 9646-1 [3])

3.2 Symbols

For the purposes of the present document, the following symbols apply:

AND	Boolean "and"
C	Conditional requirement (to be observed if the relevant conditions apply)
M	Mandatory requirement (to be observed in all cases)
N/A	Not applicable, not supported or the conditions for status are not meet
No	not supported
NOT	Boolean "not"
O	Option (may be selected to suit the implementation, provided that any requirements applicable to the option are observed)
O.n	Options, but support required for either at least one or only one of the options in the group labelled with the same numeral "n"
OR	Boolean "or"
Yes	supported

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

B-ISDN	Broadband Integrated Services Digital Network
DSS2	Digital Subscriber Signalling System No. two
IER	Information Elements Received
IET	Information Elements Transmitted
IUT	Implementation Under Test
MC	Major Capabilities
MR	Messages Received
MT	Messages Transmitted
OSI	Open Systems Interconnection
PCR	Peak Cell Rate
PICS	Protocol Implementation Conformance Statement
R	Role
SCS	System Conformance Statement
SUT	System Under Test
TM	Timer

4 Conformance

A PICS proforma that conforms to this PICS proforma specification shall be technically equivalent to annex A, and shall preserve the numbering and ordering of the items in annex A.

A PICS proforma that conforms to this PICS proforma specification shall:

- describe an implementation which conforms to EN 301 003-1 [2];
- be a conforming PICS proforma, which has been completed in accordance with the instructions for completion given in clause A.1; and
- include the information necessary to uniquely identify both the supplier and the implementation.

Annex A (normative): PICS proforma for EN 301 003-1

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the PICS proforma in this annex so that it can be used for its intended purposes and may further publish the completed PICS.

A.1 Guidance for completing the PICS proforma

A.1.1 Purpose and structure

The purpose of this PICS proforma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in EN 301 003-1 [2] may provide information in a standardized manner.

The PICS proforma is subdivided into clauses as follows:

- guidance for completing the various parts of the PICS proforma;
 - identification of the implementation;
 - identification of the protocol to which this PICS proforma applies;
 - global statement of conformance;
 - questions to determine roles;
 - questions for the user role; and
 - questions for the network role.
- ITC STANDARD PREVIEW
 (standards.iteh.ai)
 SIST EN 301 003-2:2000
<https://standards.iteh.ai/catalog/standards/sist/fb02d193-3c52-4fff-a1ec-d317de6cc308/sist-en-301-003-2-2000>

A.1.2 Abbreviations and conventions

The PICS proforma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [4].

Item column

The item column contains a unique reference (a mnemonic plus a number) for each item within the PICS proforma. Items are not always numbered sequentially.

Item description column

The item description contains a brief summary of the static requirement for which a support answer is required.

Conditions for status column

The conditions for status column contains a specification, if appropriate, of the predicate upon which a conditional status is based.

Status column

The following notations, defined in ISO/IEC 9646-7 [4], are used for the status column:

I	Irrelevant or out-of-scope - this capability is outside the scope of the EN to which this PICS proforma applies and is not subject to conformance testing in this context.
M	Mandatory - the capability is required to be supported.
N/A	Not Applicable - in the given context, it is impossible to use the capability. No answer in the support column is required.
O	Optional - the capability may be supported or not.
O.i	qualified optional - for mutually exclusive or selectable options from a set. "i" is an integer that identifies a unique group of related optional items and the logic of their selection, defined below the table.
X	eXcluded or prohibited - there is a requirement not to use this capability in a given context.

NOTE: To support a capability means that the capability is implemented in conformance to EN 300 443-1 [1].

Reference column

Except where explicitly stated, the reference column refers to the appropriate text of ITU-T Recommendation Q.2931 as modified by EN 300 443-1 [1] describing the particular item. Note, however, that a reference indicates only the location of the most essential information about an item. All additional requirements contained in EN 300 443-1 [1] have also to be taken into account when making a statement about the conformance of that particular item.

ITeH STANDARD PREVIEW

Support column

(standards.iteh.ai)

The following notation, defined in ISO/IEC 9646-7 [4], is used for the support column:

<input type="checkbox"/> Yes <input type="checkbox"/> No	Tick "Yes" if item is supported, tick "No" if item is not supported.
<input type="checkbox"/> N/A	Tick "N/A" if the item is "not applicable".

Prerequisite line

A prerequisite line takes the form: Prerequisite: <predicate>.

A prerequisite line after a subclause heading or table title indicates that the whole subclause or the whole table is not required to be completed if the predicate is FALSE.

A.1.3 Instructions for completing the PICS proforma

The supplier of the implementation shall complete the PICS proforma. For each row in each PICS proforma table the supplier shall enter an explicit answer (i.e., by ticking the appropriate "Yes", "No", or "N/A" in each of the support column boxes provided. Where a support column box is left blank, or where it is marked "N/A" without any tickbox, no answer is required.

If necessary, the supplier may enter additional comments at the end of each table, or separately.

More detailed instructions may be found at the beginning of each subclause of the proforma.

A.1.4 The PICS proforma tables

A.1.4.1 Correspondence to physical interface

The "implementation" (IUT) about which the PICS proforma asks questions corresponds to a layer 3 implementation on top of ONE physical interface. If the SUT implements more than one configuration, then a layer 3 PICS shall be created for each type of interface (and for each configuration of each interface) provided by the SUT.

A.1.4.2 Structure of the tables

The supplier shall provide answers to the questions concerning the major roles of the IUT (table A.1). The supplier shall then provide answers to the questions relating to the capabilities of the IUT in one of the major roles as appropriate. Apart from the initial questions to determine roles, the major roles of the IUT; the user role (R 2.1) and the network role (R 2.2), are treated completely separately in the PICS proforma. It is only necessary to complete the questions for the supported role.

A.1.4.3 Support for received PDU parameters

In the PDU parameter tables, the PICS proforma asks questions about the information elements (parameters) supported in messages (PDUs) received by the IUT. This subclause explains, in the context of EN 301 003-1 [2], what "to support a received PDU parameter" means.

The requirement that an IUT is able to parse an information element in a received message is already implied by claiming support for the receipt of that received message. This means that "to support a received PDU parameter" implies more.

iTeh STANDARD PREVIEW

Information elements in a received message are regarded as either transparent or non-transparent.

A non-transparent information element is one that causes the protocol control entity to vary its behaviour in accordance with the content of the information element. To support a non-transparent information element means an IUT can process the received parameter and behave according to the procedures described in EN 301 003-1 [2].

An information element is transparent if the actions taken according to its contents are not detectable in the subsequent behaviour of the protocol (i.e. EN 301 003-1 [2] does not specify the behaviour). To support a transparent information element means an IUT can receive the information element concerned and pass it to an appropriate processing entity; the information element is not discarded by the protocol control entity. Non-support of a transparent information element means the IUT discards it.

Transparent parameters are marked by a "(T)" in the PDU parameter tables.