
**Information technology — Abstract
Syntax Notation One (ASN.1): Constraint
specification**

*Technologies de l'information — Notation de syntaxe abstraite
numéro un (ASN.1): Spécification des contraintes*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 8824-3:2002](https://standards.iteh.ai/catalog/standards/sist/9ad8720b-92c1-4b9b-9d95-64c523a28d2c/iso-iec-8824-3-2002)

<https://standards.iteh.ai/catalog/standards/sist/9ad8720b-92c1-4b9b-9d95-64c523a28d2c/iso-iec-8824-3-2002>

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 8824-3:2002](https://standards.iteh.ai/catalog/standards/sist/9ad8720b-92c1-4b9b-9d95-64c523a28d2c/iso-iec-8824-3-2002)

<https://standards.iteh.ai/catalog/standards/sist/9ad8720b-92c1-4b9b-9d95-64c523a28d2c/iso-iec-8824-3-2002>

© ISO/IEC 2002

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published by ISO in 2003

Published in Switzerland

CONTENTS

	<i>Page</i>
Introduction	v
1 Scope	1
2 Normative references	1
2.1 Identical Recommendations International Standards	1
3 Definitions	1
3.1 Specification of basic notation	1
3.2 Information object specification	1
3.3 Parameterization of ASN.1 specification	1
3.4 Additional definitions	1
4 Abbreviations	2
5 Convention	2
6 Notation	2
6.1 Constraint	2
7 ASN.1 lexical items	2
7.1 Additional keyword items	2
8 General constraint specification	3
9 User-defined constraints	3
10 Table constraints, including component relation constraints	4
11 Contents Constraints	7
Annex A – Constraining instance-of types	8
Annex B – Summary of the notation	9

[ISO/IEC 8824-3:2002](https://standards.iteh.ai/catalog/standards/sist/9ad8720b-92c1-4b9b-9d95-64c523a28d2c/iso-iec-8824-3-2002)

<https://standards.iteh.ai/catalog/standards/sist/9ad8720b-92c1-4b9b-9d95-64c523a28d2c/iso-iec-8824-3-2002>

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 8824-3 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*, in collaboration with ITU-T. The identical text is published as ITU-T Rec. X.682.

This third edition cancels and replaces the second edition (ISO/IEC 8824-3:1998), which has been technically revised. It also incorporates the Technical Corrigenda ISO/IEC 8824-3:1998/Cor.1:2001, ISO/IEC 8824-3:1998/Cor.2:2002 and ISO/IEC 8824-3:1998/Cor.3:2002.

ISO/IEC 8824 consists of the following parts, under the general title *Information technology — Abstract Syntax Notation One (ASN.1)*:

- *Part 1: Specification of basic notation*
- *Part 2: Information object specification*
- *Part 3: Constraint specification*
- *Part 4: Parameterization of ASN.1 specifications*

Introduction

Application designers require a notation to define a structured data type to convey their semantics. This is provided in ITU-T Rec. X.680 | ISO/IEC 8824-1 and ITU-T Rec. X.681 | ISO/IEC 8824-2. A notation is also required to further constrain the values that can appear. Examples of such constraints are restricting the range of some component(s), or using a specified information object set to constrain an "ObjectClassFieldType" component, or using the "AtNotation" to specify a relation between components.

This Recommendation | International Standard provides the notation for the general case of constraint specification.

NOTE 1 – For historical reasons the special case of a "subtype constraint" is specified in ITU-T Rec. X.680 | ISO/IEC 8824-1.

Constraint notation can appear (in round brackets) after any use of the syntactic construct "Type", and the purpose of this Recommendation | International Standard is to specify the general case of what goes in the round brackets.

NOTE 2 – Multiple constraints (each inside its own round brackets) can be applied to the same "Type", as the result of constraining a "Type" is itself formally a "Type" construct.

When a constraint is applied to the textually outermost use of a "Type" construct, it results in the creation of a new type which is a subtype of the original (parent) type.

A subtype of a parent type can itself be used in defining other subtypes of the same parent type in other uses of the constraint notation. Thus the subset of values constituting a subtype can be defined either by limiting the range of the parent type, or by specifying the subtype as a union of sets of values.

NOTE 3 – The "ValueSet" notation specified in ITU-T Rec. X.680 | ISO/IEC 8824-1, 15.7, provides a further means of specifying a subtype.

Constraints may also be used to produce a subtype of a parent type (as described above) when the notation is embedded within another type. However, some "component relation" constraints are textually included following a "Type" (within a set or sequence type definition), but are not used to restrict the set of possible values of the "Type" which they follow (the referencing component). Rather, they specify a relation between the value of the referencing component and the value of one or more other "Type"s in the same set or sequence type (called the referenced components).

Component relation constraints can be seen as subtyping the sequence type within which they are embedded, but not necessarily the referencing type.

A constraint on an "ObjectClassFieldType" component can be applied by restricting the type or values in the component by using an information object set. Such constraints are called table constraints, since they are specified in terms of the "associated table" of the object set. The component relation constraints defined in this Recommendation | International Standard are a special case of table constraints.

Finally, a "Type" may be subtyped by specifying the set of values in the subtype by human-readable text. Such a constraint is called a user-defined constraint. For example, a user-defined constraint can be specified to constrain a **BIT STRING** to the set of values produced by the encryption of a value of a specified ASN.1 type.

It is the purpose of this Recommendation | International Standard to provide the notation to be used for specifying table constraints (including component relation constraints), and user-defined constraints.

NOTE 4 – In general, full support for the specification of constraints in a flexible way (particularly component relation constraints, subtyping constraints, and user-defined constraints with a formally defined body) would require notation with a power comparable to that of programming languages. Such power can only be sensibly provided by the establishment of links from the ASN.1 notation into some other defined computer language. This version of this Recommendation | International Standard does not provide such links, and hence supports only a small number of constraining mechanisms.

While the embedding of notation defining constraints (subtypes and relationships) will frequently be the most convenient form of specification (particularly for the simple subtyping of primitive components of structures), separate (external) specification will sometimes be preferred, particularly where the constraints are being imposed by a separate group from that which defined the basic protocol.

NOTE 5 – The parameterization defined in ITU-T Rec. X.683 | ISO/IEC 8824-4 is specifically designed to enable a piece of ASN.1 specification (and in particular, a constraint) to be parameterized, allowing the actual constraint to be imposed by some other group that provides actual parameters for the parameterized construct.

The notations for constraint specification supported here are:

- user-defined constraints (see clause 9);
- table constraints, including component relation constraints between two components which are carrying values related to an information object, defined using the notation of ITU-T Rec. X.681 | ISO/IEC 8824-2 (see clause 10);
- contents constraints (see clause 11).

The application of table constraints to the "InstanceOfType" construct of ITU-T Rec. X.681 | ISO/IEC 8824-2, Annex C, is specified in Annex A.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/IEC 8824-3:2002](https://standards.iteh.ai/catalog/standards/sist/9ad8720b-92c1-4b9b-9d95-64c523a28d2c/iso-iec-8824-3-2002)

<https://standards.iteh.ai/catalog/standards/sist/9ad8720b-92c1-4b9b-9d95-64c523a28d2c/iso-iec-8824-3-2002>

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

Information technology – Abstract Syntax Notation One (ASN.1): Constraint specification

1 Scope

This Recommendation | International Standard is part of Abstract Syntax Notation One (ASN.1) and provides notation for specifying user-defined constraints, table constraints, and contents constraints.

2 Normative references

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

(standards.iteh.ai)

2.1 Identical Recommendations | International Standards

- ITU-T Recommendation X.680 (2002) | ISO/IEC 8824-1:2002, *Information technology – Abstract Syntax Notation One (ASN.1): Specification of basic notation.*
- ITU-T Recommendation X.681 (2002) | ISO/IEC 8824-2:2002, *Information technology – Abstract Syntax Notation One (ASN.1): Information object specification.*
- ITU-T Recommendation X.683 (2002) | ISO/IEC 8824-4:2002, *Information technology – Abstract Syntax Notation One (ASN.1): Parameterization of ASN.1 specifications.*

3 Definitions

For the purposes of this Recommendation | International Standard, the following definitions apply.

3.1 Specification of basic notation

This Recommendation | International Standard uses the terms defined in ITU-T Rec. X.680 | ISO/IEC 8824-1.

3.2 Information object specification

This Recommendation | International Standard uses the terms defined in ITU-T Rec. X.681 | ISO/IEC 8824-2.

3.3 Parameterization of ASN.1 specification

This Recommendation | International Standard uses the following term defined in ITU-T Rec. X.683 | ISO/IEC 8824-4:

- parameterized type.

3.4 Additional definitions

3.4.1 component relation constraint: A constraint on the values of a set type or sequence type which is textually associated with one of the component types (the referencing component) of the set type or sequence type, and which

ISO/IEC 8824-3:2002 (E)

specifies the relationship between the value of that component and the values of one or more other components (the referenced components).

3.4.2 constrained type: The innermost "Type" which contains the referencing component and all of the referenced components of some component relation constraint.

3.4.3 constraining set: The information object set referenced in some component relation constraint.

3.4.4 constraining table: The associated table (see ITU-T Rec. X.681 | ISO/IEC 8824-2, clause 13) corresponding to a constraining set.

3.4.5 referenced component: A component of a set type or sequence type identified in a component relation constraint.

3.4.6 referencing component: A component of a set type or sequence type which has an associated component relation constraint.

3.4.7 selected rows: Those rows of a constraining table which contain, in the appropriate columns, the values of all of the referenced components.

3.4.8 table constraint: A constraint applied to an object class field type which demands that its values conform to the contents of the appropriate column of some table.

3.4.9 user-defined constraint: A constraint which requires a more complicated statement than can be accommodated by the other forms of constraint, and which must therefore involve specification by some means outside of ASN.1.

4 Abbreviations

For the purposes of this Recommendation | International Standard, the following abbreviation applies:

ASN.1 Abstract Syntax Notation One

5 Convention

This Recommendation | International Standard employs the notational convention defined in ITU-T Rec. X.680 | ISO/IEC 8824-1, clause 5.

6 Notation

This clause summarizes the notation defined in this Recommendation | International Standard.

6.1 Constraint

The following notation which can be used as an alternative for "ConstraintSpec" (see ITU-T Rec. X.680 | ISO/IEC 8824-1, 45.6) is defined in this Recommendation | International Standard:

– GeneralConstraint (see 8.1).

7 ASN.1 lexical items

In addition to the lexical items specified in ITU-T Rec. X.680 | ISO/IEC 8824-1, clause 11, this Recommendation | International Standard makes use of the lexical items specified in the following subclauses. The general rules applicable to these lexical items are as defined in ITU-T Rec. X.680 | ISO/IEC 8824-1, 11.1. These new lexical items make use of the ASN.1 character set, as specified in ITU-T Rec. X.680 | ISO/IEC 8824-1, clause 10.

7.1 Additional keywords

The names **CONSTRAINED**, **CONTAINING**, **ENCODED** and **BY** are listed in ITU-T Rec. X.680 | ISO/IEC 8824-1, 11.27, as reserved words.

8 General constraint specification

8.1 The notation for a "GeneralConstraint" is as follows:

```
GeneralConstraint ::=
    UserDefinedConstraint
  | TableConstraint
  | ContentsConstraint
```

8.2 The various possibilities for specification of the constraint are defined as follows:

- a) "UserDefinedConstraint", in clause 9;
- b) "TableConstraint", in clause 10;
- c) "ContentsConstraint", in clause 11.

9 User-defined constraints

NOTE 1 – This form of constraint specification can be regarded as a special form of ASN.1 comment, since it is not fully machine-processable. However, it would be possible for an automatic tool to use the presence of a particular user-defined constraint to invoke user-supplied constraint checking.

NOTE 2 – Protocol designers should be aware that since the definition of a constraint in this way is not fully machine-processable, a specification which employs this capability may be less easy to handle with automatic tools.

9.1 A user-defined constraint is specified by the syntax:

```
UserDefinedConstraint ::=
    CONSTRAINED BY "{" UserDefinedConstraintParameter "," * "}"
```

9.2 It is recommended that the actual constraint be referenced by a comment anywhere inside the braces ("{" and "}"). This comment should clearly state what constraint is imposed by the "UserDefinedConstraint".

NOTE – If there are any "UserDefinedConstraintParameter"s within the braces (see 9.3), the comments may precede, follow, or be interspersed among them, at the definer's convenience.

9.3 The actual constraint to be applied may depend on some parameters. For each such parameter, a "UserDefinedConstraintParameter" shall be included in the "UserDefinedConstraint". Each "UserDefinedConstraintParameter" shall be any "Value", "ValueSet", "Object", "ObjectSet", "Type" or "DefinedObjectClass" which is defined inline or is a reference name.

NOTE – The reference name may be a dummy parameter if the "UserDefinedConstraint" is used within a "ParameterizedAssignment".

```
UserDefinedConstraintParameter ::=
    Governor ":" Value
  | Governor ":" ValueSet
  | Governor ":" Object
  | Governor ":" ObjectSet
  | Type
  | DefinedObjectClass
```

The notation "Governor" is defined in ITU-T Rec. X.683 | ISO/IEC 8824-4, 8.3. When the first or second alternatives are used, the "Governor" shall be a "Type". When the third or fourth alternatives are used, the "Governor" shall be a "DefinedObjectClass".

9.4 Example

If an application designer wishes to specify that certain components are to be bit strings carrying an encryption of the value of some ASN.1 type (different for each component), then (using the parameterization of ITU-T Rec. X.683 | ISO/IEC 8824-4) the parameterized **ENCRYPTED** type can be defined as follows:

```
ENCRYPTED {ToBeEnciphered} ::= BIT STRING
(CONSTRAINED BY
  {-- must be the result of the encipherment of some BER-encoded
   -- value of -- ToBeEnciphered}
  ! Error : securityViolation)
```