

**SLOVENSKI STANDARD**  
**SIST EN 300 676-1 V1.5.2:2011**  
**01-april-2011**

---

**Talni VHF ročni, mobilni in fiksni radijski oddajniki, sprejemniki in sprejemniki-oddajniki za VHF aeronavtično mobilno storitev, ki uporablja amplitudno modulacijo - 1. del: Tehnične karakteristike in merilne metode**

Ground-based VHF hand-held, mobile and fixed radio transmitters, receivers and transceivers for the VHF aeronautical mobile service using amplitude modulation - Part 1: Technical characteristics and methods of measurement

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 300 676-1 V1.5.2:2011](#)

<https://standards.iteh.ai/catalog/standards/sist/44152fc2-9ae8-4a7b-9ef1-521c8584beda/sist-en-300-676-1-v1-5-2-2011>

**Ta slovenski standard je istoveten z: EN 300 676-1 Version 1.5.2**

---

**ICS:**

33.060.20	Sprejemna in oddajna oprema	Receiving and transmitting equipment
49.090	Oprema in instrumenti v zračnih in vesoljskih plovilih	On-board equipment and instruments

**SIST EN 300 676-1 V1.5.2:2011**

**en**

**iTeh STANDARD PREVIEW  
(standards.iteh.ai)**

SIST EN 300 676-1 V1.5.2:2011

<https://standards.iteh.ai/catalog/standards/sist/44152fc2-9ae8-4a7b-9ef1-521c8584beda/sist-en-300-676-1-v1-5-2-2011>

# ETSI EN 300 676-1

V1.5.2 (2011-03)

European Standard

## Ground-based VHF hand-held, mobile and fixed radio transmitters, receivers and transceivers for the VHF aeronautical mobile service using amplitude modulation; Part 1:Technical characteristics and methods of measurement

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

SIST EN 300 676-1 V1.5.2:2011

<https://standards.iteh.ai/catalog/standards/sist/44152fc2-9ae8-4a7b-9ef1-521c8584beda/sist-en-300-676-1-v1-5-2-2011>



---

Reference

REN/ERM-JTFAA-008

---

Keywords

aeronautical, AM, DSB, radio, testing, VHF

***ETSI***

650 Route des Lucioles  
 F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
 Association à but non lucratif enregistrée à la  
 Sous-Préfecture de Grasse 06 N° 7303/88

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 676-1 V1.5.2:2011](#)

<https://standards.iteh.ai/catalog/standards/sist/44152fc2-9ae8-4a7b-9ef1-521c8584bc0d?version=0.0.1&language=en>  
**Important notice**

---

Individual copies of the present document can be downloaded from:  
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaircor/ETSI\\_support.asp](http://portal.etsi.org/chaircor/ETSI_support.asp)

---

***Copyright Notification***

No part may be reproduced except as authorized by written permission.  
 The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2011.  
 All rights reserved.

**DECT™, PLUGTESTS™, UMTS™, TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**LTE™** is a Trade Mark of ETSI currently being registered  
 for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

## Contents

Intellectual Property Rights .....	7
Foreword.....	7
Introduction .....	7
1 Scope .....	9
2 References .....	9
2.1 Normative references .....	9
2.2 Informative references.....	9
3 Definitions and abbreviations.....	10
3.1 Definitions .....	10
3.2 Abbreviations .....	10
4 General requirements .....	11
4.1 Controls and indicators.....	11
4.2 Class of emission and modulation characteristics .....	11
4.3 Warm up.....	11
5 Test conditions, power sources and ambient temperatures .....	11
5.1 Normal and extreme test conditions .....	11
5.2 Test power source.....	12
5.3 Normal test conditions.....	12
5.3.1 Normal temperature and humidity .....	12
5.3.2 Normal power sources .....	12
5.3.2.1 Mains voltage and frequency .....	12
5.3.2.2 Regulated lead-acid battery power sources used on vehicles .....	12
5.3.2.3 Other power sources.....	12
5.4 Extreme test conditions.....	12
5.4.1 Extreme temperatures .....	12
5.4.2 Extreme values of test power sources .....	13
5.4.2.1 Mains voltage .....	13
5.4.2.2 Other power sources.....	13
5.4.3 Extended temperatures.....	13
5.5 Performance test.....	13
5.6 Environmental tests .....	13
5.6.1 General.....	13
5.6.2 Procedure for tests at extreme temperatures .....	14
5.6.3 Temperature tests.....	14
5.6.3.1 High temperature.....	14
5.6.3.2 Low temperature .....	14
6 General conditions of measurement.....	14
6.1 Receiver test signal arrangement.....	14
6.1.1 Test signal sources .....	14
6.1.2 Nominal frequency .....	14
6.1.3 Normal test signal .....	15
6.1.4 Squelch .....	15
6.1.5 Normal audio output power .....	15
6.1.6 Audio AGC .....	15
6.2 Transmitter test signal arrangement .....	15
6.2.1 Coaxial termination.....	15
6.2.2 Signal sources .....	15
6.2.3 Normal test signal .....	15
6.3 Test channels .....	15
7 Transmitter .....	15
7.1 Protection of the transmitter .....	16

7.1.1	Definition.....	16
7.1.2	Method of measurement .....	16
7.1.3	Requirement.....	16
7.2	Frequency error .....	16
7.2.1	Definition.....	16
7.2.2	Method of measurement .....	16
7.2.3	Limits.....	16
7.3	Carrier power.....	17
7.3.1	Definitions .....	17
7.3.2	Method of measurement .....	17
7.3.3	Tolerances.....	17
7.3.3.1	Normal test conditions .....	17
7.3.3.2	Extreme test conditions .....	17
7.4	Amplitude modulation characteristic.....	17
7.4.1	Modulation depth (speech) .....	17
7.4.1.1	Definitions.....	17
7.4.1.2	Method of measurement.....	17
7.4.1.3	Limits .....	18
7.4.1.4	Modulation depth (analogue data mode).....	18
7.4.1.5	Method of measurement.....	18
7.4.1.6	Limits .....	18
7.4.2	Modulation compression (speech mode) .....	18
7.4.2.1	Definition .....	18
7.4.2.2	Method of measurement.....	18
7.4.2.3	Limits .....	18
7.4.3	Amplitude modulation distortion.....	19
7.4.3.1	Definition .....	19
7.4.3.2	Method of measurement.....	19
7.4.3.3	Limits .....	19
7.4.4	Audio frequency response .....	19
7.4.4.1	Definition .....	19
7.4.4.2	Method of measurement.....	19
7.4.4.3	Limits 8,33 kHz/channel spacing <a href="#">SIST EN 300 676-1 V1.5.2:2011</a> .....	19
7.4.4.4	Limits 25 kHz channel spacing <a href="#">data/sist-en-300-676-1-v1-5-2-2011</a> .....	19
7.4.4.5	Limits 25 kHz channel spacing (Data) .....	20
7.4.5	Group delay variation (data mode only) .....	20
7.4.5.1	Definition .....	20
7.4.5.2	Transmitter method of measurement.....	20
7.4.5.3	Limits .....	20
7.5	Adjacent channel power .....	20
7.5.1	Definition.....	20
7.5.2	Measurement.....	21
7.5.3	Limits.....	21
7.6	Broadband noise measurement.....	21
7.6.1	Definition.....	21
7.6.2	Method of measurement .....	22
7.6.3	Limit .....	22
7.7	Conducted spurious emissions .....	22
7.7.1	Definition.....	22
7.7.2	Method of measurement .....	23
7.7.3	Limits.....	23
7.8	Intermodulation attenuation.....	23
7.8.1	Definition.....	23
7.8.2	Method of measurement .....	24
7.8.3	Limits.....	24
7.9	RF power attack time and release time.....	24
7.9.1	Definitions .....	24
7.9.2	Method of measurement .....	25
7.9.2.1	Attack time.....	25
7.9.2.2	Release time .....	25
7.9.3	Limits.....	26
7.10	Keying Transient frequency behaviour of the transmitter .....	26

7.10.1	Definitions .....	26
7.10.2	Method of measurement .....	26
7.10.3	Limits .....	26
7.11	Sidetone .....	27
7.11.1	Limits .....	27
7.12	Cabinet Radiation .....	27
8	Receiver .....	27
8.1	Sensitivity .....	27
8.1.1	Definition .....	27
8.1.2	Method of measurement .....	27
8.1.3	Limits .....	27
8.2	Harmonic distortion .....	28
8.2.1	Definition .....	28
8.2.2	Method of measurement .....	28
8.2.3	Limits .....	28
8.3	Audio frequency response .....	28
8.3.1	Definition .....	28
8.3.2	Method of measurement .....	28
8.3.3	Limits .....	28
8.3.4	Limit for DATA operation .....	28
8.4	Audio noise .....	29
8.4.1	Definition .....	29
8.4.2	Method of measurement .....	29
8.4.3	Limits .....	29
8.5	Effective acceptance bandwidth .....	29
8.5.1	Definition .....	29
8.5.2	Method of measurement .....	29
8.5.3	Limits .....	29
8.6	Adjacent channel rejection <i>(standards.iteh.ai)</i> .....	30
8.6.1	Definition .....	30
8.6.2	Method of measurement .....	30
8.6.3	Limits .....	30
8.7	Spurious response rejection <i>521c8584beda/sist-en-300-676-1-V1-5-2-2011</i> .....	30
8.7.1	Definition .....	31
8.7.2	Introduction to the method of measurement .....	31
8.7.3	Method of search of the limited frequency range .....	31
8.7.4	Method of measurement .....	31
8.7.5	Limit .....	32
8.8	Intermodulation response rejection .....	32
8.8.1	Definition .....	32
8.8.2	Method of measurement .....	32
8.8.3	Limit .....	32
8.9	Blocking or desensitization .....	33
8.9.1	Definition .....	33
8.9.2	Method of measurement .....	33
8.9.3	Limit .....	33
8.10	Conducted spurious emissions .....	33
8.10.1	Definition .....	33
8.10.2	Method of measuring the power level .....	33
8.10.3	Limits .....	34
8.11	Squelch operation .....	34
8.11.1	Definition .....	34
8.11.2	Method of measurement .....	34
8.11.3	Limits .....	34
8.12	Cross modulation rejection .....	35
8.12.1	Definition .....	35
8.12.2	Method of measurement .....	35
8.12.3	Limits .....	35
8.13	Receiver dynamic range .....	35
8.13.1	Definition .....	35
8.13.2	Method of measurement .....	35

8.13.3	Limit .....	36
8.14	AGC attack time and release time (data mode only) .....	36
8.14.1	Definitions .....	36
8.14.2	Method of measurement .....	36
8.14.2.1	Attack time .....	36
8.14.2.2	AGC Decay time .....	36
8.14.3	Limits .....	36
8.15	AF AGC .....	37
8.15.1	Definition .....	37
8.15.2	Method of measurement .....	37
8.15.3	Limit .....	37
8.16	Group delay variation (data mode only) .....	37
8.16.1	Definition .....	37
8.16.2	Receiver method of measurement .....	37
8.16.3	Limits .....	38
8.17	Cabinet Radiation .....	38
9	Measurement uncertainty and interpretation of the measured results .....	38
9.1	Maximum measurement uncertainties .....	38
9.2	Interpretation of the measurement results .....	39
<b>Annex A (normative):</b>	<b>Auxiliary cables.....</b>	<b>40</b>
<b>Annex B (normative):</b>	<b>Specification for adjacent channel power measurement arrangements.....</b>	<b>41</b>
B.1	Power measuring receiver specification .....	41
B.1.1	IF filter .....	41
B.1.2	Attenuation indicator .....	42
B.1.3	RMS value indicator .....	42
B.1.4	Oscillator and amplifier .....	42
<b>Annex C (informative):</b>	<b>Bibliography SIST EN 300 676-1 V1.5.2:2011.....</b>	<b>43</b>
History .....	<a href="https://standards.iteh.ai/catalog/standards/sist/44152fc2-9ae8-4a7b-9ef1-521c8584beda/sist-en-300-676-1-v1-5-2-2011">https://standards.iteh.ai/catalog/standards/sist/44152fc2-9ae8-4a7b-9ef1-521c8584beda/sist-en-300-676-1-v1-5-2-2011</a>	44

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document is part 1 of a multi-part deliverable covering the Ground-based VHF hand-held, mobile and fixed radio transmitters, receivers and transceivers for the VHF aeronautical mobile service using amplitude modulation, as identified below:

**Part 1: "Technical characteristics and methods of measurement";**

Part 2: "Harmonized EN covering essential requirements of article 3.2 of the R&TTE Directive".

## (standards.iteh.ai) National transposition dates

Date of latest announcement of this EN (doa):	<a href="https://standards.iteh.ai/catalog/standards/sist/44152fc2-9ae8-4a7b-9ef1-521c8584beda/sist-en-300-676-1-v1-5-2-2011">SIST EN 300 676-1 V1.5.2:2011 <a href="https://standards.iteh.ai/catalog/standards/sist/44152fc2-9ae8-4a7b-9ef1-521c8584beda/sist-en-300-676-1-v1-5-2-2011">https://standards.iteh.ai/catalog/standards/sist/44152fc2-9ae8-4a7b-9ef1-521c8584beda/sist-en-300-676-1-v1-5-2-2011</a></a>	30 June 2011
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	<a href="https://standards.iteh.ai/catalog/standards/sist/44152fc2-9ae8-4a7b-9ef1-521c8584beda/sist-en-300-676-1-v1-5-2-2011">521c8584beda/sist-en-300-676-1-v1-5-2-2011</a>	31 December 2011
Date of withdrawal of any conflicting National Standard (dow):		31 December 2011

## Introduction

The present document states the minimum performance requirements for ground based radio transmitters, transceivers and receivers for the aeronautical mobile service operating in the VHF band (118 MHz to 136,975 MHz), using Double Sideband Amplitude Modulation with 8,33 kHz or 25 kHz channel spacing.

NOTE: For equipment designed to cover the extended VHF frequency bands 108 MHz to 117,975 MHz and 137 MHz to 155,975 MHz the same test methods and procedures may be applied to show technical acceptance of the product in the band 108 MHz to 155,975 MHz.

Additional requirements, outside the scope of the present document, may be required to ensure operation in the 108 MHz to 117,975 MHz band does not cause interference to the FM broadcast band.

The present document may be used by accredited test laboratories for the assessment of the performance of the equipment. The performance of the equipment submitted for type testing should be representative for the performance of the corresponding production model.

The present document has been written on the assumption that:

- the type test measurements will be performed only once, in an accredited test laboratory and the measurements accepted by the various authorities in order to grant type approval;
- if equipment available on the market is required to be checked it will be tested in accordance with the methods of measurement specified in the present document.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 676-1 V1.5.2:2011](#)

<https://standards.iteh.ai/catalog/standards/sist/44152fc2-9ae8-4a7b-9ef1-521c8584beda/sist-en-300-676-1-v1-5-2-2011>

## 1 Scope

The present document states the minimum performance requirements for radio transmitters, receivers and transceivers at ground-based aeronautical stations operating in the VHF band (118 MHz to 136,975 MHz) allocated to the aeronautical mobile service.

In situations where transmitters and receivers are located in close proximity there is the possibility of interference. In such cases, external filters and isolators may be necessary as part of the installation to achieve an isolation performance in excess of the minima defined in the present document to overcome the interference.

The present document applies to DSB AM systems, with channel separations of 8,33 kHz or 25 kHz intended for analogue speech and ground base stations with a channel spacing of 25 kHz intended for ACARS data communication.

**NOTE:** The test methods and procedures in the present document may also be used to show technical acceptance for radio transmitters, receivers and transceivers at ground based aeronautical stations operating with 25 kHz channel spacing in the extended VHF bands (108 MHz to 117,975 MHz and 137 MHz to 155,975 MHz).

The scope of the present document is limited to ground base stations, ground mobile and hand held radios for ground use.

## 2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>. [SIST EN 300 676-1 V1.5.2:2011](#)

**NOTE:** While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

### 2.1 Normative references

The following referenced documents are necessary for the application of the present document.

- [1] ITU-T Recommendation O.41: "Psophometer for use on telephone-type circuits".
- [2] ICAO Annex 10 Volume V (July 2001, including amendments up to amendment 84): "Aeronautical Radio Frequency Spectrum Utilization".
- [3] ETSI EN 300 113-1: "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Radio equipment intended for the transmission of data (and/or speech) using constant or non-constant envelope modulation and having an antenna connector; Part 1: Technical characteristics and methods of measurement".

### 2.2 Informative references

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 100 028 (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics".
- [i.2] ISO 7637 (parts 1 and 2): "Road vehicles - Electrical disturbances from conduction and coupling".

- [i.3] Directive 1999/5/EC of the European Parliament and of the Council of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity (R&TTE Directive).

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**aeronautical mobile service:** mobile service between aeronautical stations and aircraft stations, or between aircraft stations, in which survival craft stations may participate

**conducted measurements:** measurements which are made using a direct RF connection to the equipment under test

**ground base station:** aeronautical station equipment, in the aeronautical mobile service, for use with an external antenna and intended for use at a fixed location

**hand held:** radio equipment with integral batteries, designed to be hand portable and operated hand held

**integral antenna equipment:** radio communications equipment with an antenna integrated into the equipment without the use of an external connector and considered to be part of the equipment

NOTE: An integral antenna may be internal or external to the equipment. In equipment of this type, a  $50\ \Omega$  RF connection point should be provided for test purposes. A connection point for an AF modulating input and for AF output measurements should also be provided.

**mobile station:** radio equipment designed for permanent or temporary vehicle installation and operation, including provision for vehicle DC power supply, and connections for external antenna, PTT key, microphone, speaker and/or headphone

SIST EN 300 676-1 V1.5.2:2011

**non-integral antenna equipment:** radio communications equipment with a connector intended for connection to an antenna  
<https://standards.iteh.ai/catalog/standards/sist/44152fc2-9ae8-4a7b-9ef1-521c8584beda/sist-en-300-676-1-v1-5-2-2011>

**portable station:** radio equipment with integral battery for independent hand-carried use

NOTE: Provisions may be made for connections of an external antenna, PTT key, microphone, headphone and charger, but principally to be operated as a self contained unit.

**radiated measurements:** measurements which involve the measurement of a radiated field

### 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACARS	Aircraft Communications Addressing and Reporting System
AF	Audio Frequency
AGC	Automatic Gain Control
AM	Amplitude Modulation
dBc	dB relative to the carrier power
DSB	Double Side Band
ICAO	International Civil Aviation Organization
IF	Intermediate Frequency
ppm	parts per million
RF	Radio Frequency
rms	root mean square
SINAD	(Signal + Noise + Distortion)/(Noise + Distortion)
VSWR	Voltage Standing Wave Ratio

## 4 General requirements

8,33 kHz equipment shall be able to operate on all channels in the List of Assignable Frequencies defined in Appendix 2, chapter 4, Group F (see clause 4.1.8.1.2) of the ICAO Annex 10 Volume V [2].

The channel labelling used for 8,33 kHz channel spacing is based on a frequency-channel pairing in accordance with table 4.1 (bis) of ICAO Annex 10 Volume V [2] clause 4.1.2.4.

25 kHz equipment shall be able to operate on the frequencies 118,0 MHz to 136,975 MHz in accordance with ICAO Annex 10 Volume V [2], Appendix to Chapter 4.

It shall not be possible to transmit while any frequency synthesizer used within the transmitter is out of lock.

It shall not be possible to transmit during channel switching operations.

### 4.1 Controls and indicators

The equipment shall have the following controls and indicators as a minimum:

- a visual indication that the device is switched on;
- a facility to disable the squelch for test purposes;
- a visual indication that the carrier is being produced.

The equipment shall also meet the following requirements:

- iTeh STANDARD PREVIEW  
(standards.iteh.ai)
- the user shall not have access to any control which, if wrongly set, might impair the technical characteristics of the equipment.

### 4.2 Class of emission and modulation characteristics

The equipment shall use Double Side Band (DSB) Amplitude Modulation (AM) full carrier, (6K80A3EJN for 25 kHz, 5K00A3EJN for 8,33 kHz), for speech and 13k0A2D for data. The equipment shall be designed to operate satisfactorily with a channel separation of 8,33 kHz or 25 kHz.

### 4.3 Warm up

After being switched on the equipment shall meet the requirements of the present document within one minute under normal test conditions (see clause 5.3).

If the equipment includes parts which require to be heated in order to operate correctly (e.g. crystal ovens) a warming up period of 10 minutes of those parts shall be allowed.

## 5 Test conditions, power sources and ambient temperatures

### 5.1 Normal and extreme test conditions

Measurements shall be made under normal test conditions (see clause 5.3) and also, where stated, under extreme test conditions (see clauses 5.4.1 and 5.4.2).