# TECHNICAL SPECIFICATION



First edition 2003-11-15

# Acceptance tests for CO<sub>2</sub>-laser beam machines for welding and cutting using 2D moving optics type

Essais de réception des machines de soudage et de coupage par faisceau laser  $CO_2$ , à l'aide d'optiques mobiles 2D

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/TS 17477:2003</u> https://standards.iteh.ai/catalog/standards/sist/3b5ca9b4-73fl-4b4b-b362-25fa158e2172/iso-ts-17477-2003



Reference number ISO/TS 17477:2003(E)

#### PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/TS 17477:2003</u> https://standards.iteh.ai/catalog/standards/sist/3b5ca9b4-73f1-4b4b-b362-25fa158e2172/iso-ts-17477-2003

© ISO 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org Published in Switzerland

#### Contents

Forew	/ord	iv
Introd	Terms and definitions Classification of machine type Acceptance test conditions	v
1	Scope	1
2	Terms and definitions	1
3	Classification of machine type	1
4	Acceptance test conditions	1
5	Acceptance test items	2
6	Records of test results	5
Annex	A (informative) Class A test report on acceptance test of CO <sub>2</sub> -laser beam machines	6
Annex	<b>B</b> (informative) Class B test report on acceptance test of CO <sub>2</sub> -laser beam machines	7
Biblio	graphy	8

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/TS 17477:2003</u> https://standards.iteh.ai/catalog/standards/sist/3b5ca9b4-73f1-4b4b-b362-25fa158e2172/iso-ts-17477-2003

#### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In other circumstances, particularly when there is an urgent market requirement for such documents, a technical committee may decide to publish other types of normative document:

- an ISO Publicly Available Specification (ISO/PAS) represents an agreement between technical experts in an ISO working group and is accepted for publication if it is approved by more than 50 % of the members of the parent committee casting avote; TANDARD PREVIEW
- an ISO Technical Specification (ISO/TS) represents an agreement between the members of a technical committee and is accepted for publication if it is approved by 2/3 of the members of the committee casting a vote.

#### ISO/TS 17477:2003

An ISO/PAS or ISO/TS is reviewed after three years in order to decide whether it will be confirmed for a further three years, revised to become an International Standard, or withdrawn. If the ISO/PAS or ISO/TS is confirmed, it is reviewed again after a further three years, at which time it must either be transformed into an International Standard or be withdrawn.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/TS 17477 was prepared by Technical Committee ISO/TC 44, *Welding and allied processes*, Subcommittee SC 10, *Unification of requirements in the field of metal welding*.

#### Introduction

Requests for official interpretations of any aspect of this Technical Specification should be directed to the Secretariat of ISO/TC 44/SC 10, *Unification of requirements in the field of metal welding* via your national standards body, a complete listing of which can be found at www.iso.org.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/TS 17477:2003</u> https://standards.iteh.ai/catalog/standards/sist/3b5ca9b4-73fl-4b4b-b362-25fa158e2172/iso-ts-17477-2003

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/TS 17477:2003</u> https://standards.iteh.ai/catalog/standards/sist/3b5ca9b4-73f1-4b4b-b362-25fa158e2172/iso-ts-17477-2003

# Acceptance tests for CO<sub>2</sub>-laser beam machines for welding and cutting using 2D moving optics type

#### 1 Scope

The purpose of this Technical Specification is to provide a guideline on minimum requirements for acceptance tests by using practical test methods for the two-dimensional  $CO_2$ -laser beam machines for welding and cutting, fixing a workpiece on the platen, by using moving optics. This Technical Specification is not applicable to machines that use an articulated robot.

This Technical Specification does not cover hazard protection devices that shall be used with laser machining equipment such as the devices for discharging chips and particles that are generated during welding and cutting.

#### 2 Terms and definitions

iTeh STANDARD PREVIEW

For the purposes of this document, the following terms and definitions apply. (standards.iteh.ai)

#### 2.1

#### deviation from intersection

longest distance between any two points that is made by three or more straight intersects

25fa158e2172/iso-ts-17477-2003

#### 2.2

#### marking

tracing the trajectory of the machining head and marking it on the paper with a ballpoint pen, an equivalent marking pen installed on the tip of the machining head, or scribe the trajectory with a low-power laser beam, or an equivalent instrument agreed between the parties concerned, when the laser machine is being operated

#### 3 Classification of machine type

Judgement criteria/allowance value are classified into two machine types as follows:

- Class A: laser beam source is built into moving machine;
- Class B: laser beam source is not built into moving machine.

#### 4 Acceptance test conditions

#### 4.1 Installation environment

The laser machine to be subjected to the acceptance test shall be installed in such a way that the welding and cutting operation will not significantly be disturbed by vibrations and temperature variations.

#### 4.2 Power supply

The power source for the laser machine and its cooling system shall conform to the manufacturer's specifications for the equipment. Output voltage fluctuations shall be within  $\pm$  10 % of the nominal voltage.

#### Cooling system 4.3

If the cooling system is not supplied with the welding and cutting equipment, it shall conform to the welding and cutting equipment manufacturer's specifications (for the water flow, temperature control range, cooling capacity, etc.).

The quality of the cooling water (purity, conductivity, pH, etc.) shall be as specified by the welding and cutting equipment manufacturer.

#### 4.4 Gas supply and gas supply system

The flow rate and quality of the laser gases, assist gases or shield gas (plasma removing, cutting and welding gases), and purging gases shall be as specified by the welding and cutting equipment manufacturer.

#### Operating instruction for users 4.5

Technical information necessary for operation, maintenance and control of the equipment and at least the minimum information related to the safety of welding and cutting processing equipment, shall be provided by the supplier.

### iTeh STANDARD PREVIEW (standards.iteh.ai)

#### Acceptance test items 5

#### ISO/TS 17477:2003

Check of parts https://standards.iteh.ai/catalog/standards/sist/3b5ca9b4-73f1-4b4b-b362-

A check shall be made that all specified parts of the equipment are available and properly installed.

#### Machine accuracy verification testing 5.2

#### 5.2.1 Accuracy test variables

The following variables shall be checked for accuracy in accordance with 5.2.3 and 5.2.4:

trajectory accuracy; a)

5.1

- straightness of the motion in X-axis direction; b)
- straightness of the motion in Y-axis direction; C)
- squareness between X and Y axes; d)
- positioning accuracy of the motion in X-axis direction; e)
- positioning accuracy of the motion in Y-axis direction; f)
- g) machining speed accuracy.
- NOTE See also Table 1.

#### 5.2.2 Measuring instruments

Measurements for the accuracy tests shall be carried out with calibrated measuring instruments, such as standard scale, tape measure, dial gauge and/or steel wire, or other measuring instruments as agreed between the parties concerned.

#### 5.2.3 Test methods

#### 5.2.3.1 General

The accuracy of the variables listed in 5.2.1 shall be verified using the following methods.

#### 5.2.3.2 Trajectory accuracy

The laser machine shall be used to draw the diagram, shown in Figure 1 with external dimensions 800 mm  $\times$  800 mm. The starting position shall be A and follow the sequence as listed under Figure 1, i.e. A, B, C, D, A, C, H, etc. For laser machines with an effective machining range less than 800 mm  $\times$  800 mm, the largest square covering the effective machining range shall be drawn. The pattern shall be drawn at 1 000 mm/min using the machine's numerical control system. Deviations from the intersections, meandering of trajectories and deviations of arc trajectories shall be monitored in accordance with the following procedures. For laser machines with a single-sided drive, the test shall be carried out on the driving side. The pattern shown in Figure 1 shall be drawn as follows:

- 1) one side of the external square shall be drawn parallel to the X-axis;
- iTeh STANDARD PREVIEW
- 2) all straight lines shall be drawn continuously; (standards.iteh.ai)
- 3) the circle shall be drawn continuously;
- 4) the circle shall be overwritten once in both the clockwise and anti-clockwise directions;
- 5) dwell time shall be determined by the parties concerned.

The deviation of any line at an intersection where three or more straight lines come together (A to H) or intersect (J to R) shall be measured.

Meandering of the trajectory shall be checked by measuring the maximum deviation of the actual trajectory from each straight ruled line shown in Figure 1.

Deviation of the arc trajectory shall be checked by measuring the maximum deviation of the circle that has been overwritten in both the clockwise and anti-clockwise directions.

#### 5.2.3.3 Straightness of the motion in X-axis direction

Draw a straight line on the paper placed on a flat plate, such as a steel plate, fitting a ballpoint pen on to the machining head, or scribe the straight line using the low-power laser beam, moving the laser machine in the X-axis direction.

Stretch a steel wire between both ends of this straight line, and measure the maximum deviation of the straight line from the steel wire by measurement scope, at every 1 000 mm in the X-axis direction.

This test should be performed over the whole range of the effective machining length of the laser machine.