

Designation: D 1858 - 63 (Reapproved 2000)

# Standard Specification for Creosote-Petroleum Solution<sup>1</sup>

This standard is issued under the fixed designation D 1858; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon  $(\epsilon)$  indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

### 1. Scope

1.1 This specification covers creosote-petroleum solution for use in the preservative treatment of timber.

#### 2. Referenced Documents

- 2.1 ASTM Standards:
- D 390 Specification for Coal-Tar Creosote for the Preservative Treatment of Piles, Poles, and Timbers for Marine, Land, and Fresh Water Use<sup>2</sup>
- D 1859 Specification for Petroleum for Blending with Creosote<sup>2</sup>
- 2.2 Other Standard:

AWPA P3 Standard for Creosote-Petroleum Oil Solution<sup>3</sup>

## 3. Composition

3.1 Creosote-petroleum solution shall consist of specified proportions of coal-tar creosote conforming to Specification D 390, and petroleum conforming to Specification D 1859. The creosote-petroleum solution shall contain not less than 50 volume percent of the creosote.

#### 4. Test Methods

4.1 Once these materials have been blended, there is no existing standard method to determine the relative amounts of the components. Therefore, each of the components shall be analyzed separately before blending for conformance to the respective specifications.

## 5. Keywords

5.1 creosote-petroleum solution

Current edition effective Sept. 30, 1963. Originally issued 1961. Replaces D 1858 – 61 T.

https://standards.iteh.ai/catalog/standards/sist/004b23cb-554d-45b7-b2dd-99b076ffa2f9/astm-d1858-632000

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).

<sup>&</sup>lt;sup>1</sup> This specification is under the jurisdiction of ASTM Committee D-7 on Wood and is the direct responsibility of Subcommittee D07.06 on Treatments for Wood Products.

<sup>&</sup>lt;sup>2</sup> Annual Book of ASTM Standards, Vol 04.10.

<sup>&</sup>lt;sup>3</sup> Available from American Wood-Preservers' Association, P.O. Box 286, Woodstock, MD 21163-0286.