

---

---

**Building construction machinery and  
equipment — Concrete pumps —**

**Part 1:  
Terminology and commercial  
specifications**

**iTeh STANDARD PREVIEW**  
*Machines et matériels pour la construction des bâtiments — Pompes à  
béton —  
(standards.iteh.ai)*  
*Partie 1. Terminologie et spécifications commerciales*

[ISO 21573-1:2006](https://standards.iteh.ai/catalog/standards/sist/f0730f56-e76e-4698-8de0-18594fa851ba/iso-21573-1-2006)

<https://standards.iteh.ai/catalog/standards/sist/f0730f56-e76e-4698-8de0-18594fa851ba/iso-21573-1-2006>



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 21573-1:2006](https://standards.iteh.ai/catalog/standards/sist/f0730f56-e76e-4698-8de0-18594fa851ba/iso-21573-1-2006)

<https://standards.iteh.ai/catalog/standards/sist/f0730f56-e76e-4698-8de0-18594fa851ba/iso-21573-1-2006>

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

Foreword.....	iv
Introduction .....	v
1 Scope .....	1
2 Normative references .....	1
3 Terms and definitions.....	1
4 Classification of the concrete pumps.....	3
5 Commercial specifications .....	4
5.1 General characteristics .....	4
5.2 Applicable concrete.....	4
5.3 Drive .....	5
5.4 Dimensional characteristics .....	5
5.5 Conveying-pipe cleaning device.....	5
5.6 Chassis cleaning device .....	5
5.7 Distributing boom .....	6
5.8 Outrigger component.....	6
5.9 Hydraulic system .....	6
5.10 Truck chassis .....	7
5.11 Trailer chassis.....	7
5.12 Attachments and tools .....	7
Annex A (informative) Examples of concrete pump designs and their assemblies .....	8

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 21573-1 was prepared by Technical Committee ISO/TC 195, *Building construction machinery and equipment*, Subcommittee SC 1, *Machinery and equipment for concrete work*.

ISO 21573 consists of the following parts, under the general title *Building construction machinery and equipment — Concrete pumps*:

— *Part 1: Terminology and commercial specifications*

— *Part 2: Procedure for examination of technical parameters*

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO 21573-1:2006

<https://standards.iteh.ai/catalog/standards/sist/f0730f56-e76e-4698-8de0-18594fa851ba/iso-21573-1-2006>

## Introduction

This part of ISO 21573 deals with concrete pumps used on building sites for concrete-mix delivery. It provides definitions and technical characteristics of the relevant machines. The figures in Annex A give examples of current structures of concrete pumps and their principles of operation.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 21573-1:2006](https://standards.iteh.ai/catalog/standards/sist/f0730f56-e76e-4698-8de0-18594fa851ba/iso-21573-1-2006)

<https://standards.iteh.ai/catalog/standards/sist/f0730f56-e76e-4698-8de0-18594fa851ba/iso-21573-1-2006>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 21573-1:2006

<https://standards.iteh.ai/catalog/standards/sist/f0730f56-e76e-4698-8de0-18594fa851ba/iso-21573-1-2006>

# Building construction machinery and equipment — Concrete pumps —

## Part 1: Terminology and commercial specifications

### 1 Scope

This part of ISO 21573 establishes terminology and commercial-literature specifications for concrete pumps which are used on building sites for concrete-mix delivery.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 11375:1998, *Building construction machinery and equipment — Terms and definitions*

[ISO 21573-1:2006](https://standards.iteh.ai/catalog/standards/sist/f0730f56-e76e-4698-8de0-18594fa851ba/iso-21573-1-2006)

[https://standards.iteh.ai/catalog/standards/sist/f0730f56-e76e-4698-8de0-](https://standards.iteh.ai/catalog/standards/sist/f0730f56-e76e-4698-8de0-18594fa851ba/iso-21573-1-2006)

[18594fa851ba/iso-21573-1-2006](https://standards.iteh.ai/catalog/standards/sist/f0730f56-e76e-4698-8de0-18594fa851ba/iso-21573-1-2006)

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 11375 and the following apply.

#### 3.1

##### **piston-type concrete pump**

pump in which a piston is used to impart energy to the concrete mix, with the intent of transporting the mix to and through the conveying pipe and/or hose

See Figure A.1.

#### 3.2

##### **rotary-type concrete pump**

pump in which a peristaltic action is used to impart energy to the concrete mix with the intent of transporting the mix to and through the conveying pipe and/or hose

See Figures A.6, A.7, A.8 and A.9.

#### 3.3

##### **stationary-type concrete pump**

skid, rail or wheeled-chassis mounted concrete pump intended for long-term operation on one building site

See Figure A.13.

**3.4 piston-type concrete-pump's valve system**  
system composed of cut-off valves successively locking and opening concrete-mix flow from the hopper to the concrete cylinder and from the latter to the conveying pipe

See Figures A.2, A.3, A.4 and A.5.

NOTE The operation of the valves is synchronised so that, when the concrete-mix flow from the hopper to the concrete cylinder is opened, the flow to the conveying pipe is closed. Various types of valve systems (see Table 1) are identified.

**3.5 distributing boom**  
folded boom with fixed concrete-mix conveying pipe of which the role is to deliver concrete mix to work areas within its reach

See Figure A.14.

NOTE The boom has the possibility of folding in the vertical plane and slewing around the vertical axis. Typically, a rubber hose is fixed to the end of the conveying pipe, to facilitate concrete-mix distribution.

**3.6 maximum applicable aggregate size**  
largest size of aggregate that can be consistently delivered through the concrete pump without blockage, including through any conveying pipe that is normally supplied on the finished product

**3.7 minimum applicable slump**  
minimum value of slump applicable for conveying by concrete pump

**3.8 maximum theoretical pumping capacity**  
theoretical delivery volume which is obtained at the maximum strokes/revolutions per minute of concrete pump

NOTE The actual delivery volume is obtained by calculating the product of the volumetric efficiency and the theoretical delivery volume of the concrete pump. Using concrete of slump value 18 cm to 21 cm, the volumetric efficiency is about 90 %.

$$Q_{th} = \left( \pi \times d^2 / 4 \right) \times s \times n \times 10^{-9}$$

$$Q_a = Q_{th} \times \eta_v$$

where

- $Q_{th}$  is the theoretical delivery volume (m<sup>3</sup>/h);
- $Q_a$  is the actual delivery volume (m<sup>3</sup>/h);
- $d$  is the diameter of the concrete cylinder piston (mm);
- $s$  is the stroke (mm);
- $n$  is the number of strokes per hour;
- $\eta_v$  is the volumetric efficiency, equal to 0,8 to 0,9.



#### 4 Classification of the concrete pumps

In general terms, concrete pumps are typically classified by the following four main characteristics (see Table 1):

- type of pumping unit;
- mode or frequency of transportation;
- form of conveying;
- concrete-mix delivery with assistance.

**Table 1 — Classification of the concrete pumps**

Classification	Type	Current examples	Reference Figures
Type of pumping unit	Piston	Hydraulic driven	Figure A.1
		Mechanical driven	—
		Single piston	—
		Multi piston	Figure A.1
	Rotary	Vacuum Elastic	Figure A.6, A.7 Figure A.8, A.9
Mode or frequency of transportation	Self-propelled mobile	Truck mounted	ISO 11375, Figure 41
	Non self-propelled mobile	Trailer mounted (with tires on highway)	ISO 11375, Figure 42
		Trailer mounted, steel wheels (rides on rails)	—
		Trailer mounted, track	—
	Stationary	Skid mounted/Fixed in place Trailer mounted (with tires off-road)	Figure A.11 ISO 11375, Figure 42
Form of conveying	With integral distribution boom	Truck mounted	ISO 11375, Figure 41
		Trailer mounted	ISO 11375, Figure 43
	With separate distribution boom	Tower mounted boom	ISO 11375, Figure 44
		Articulating distribution arm (with support legs)	—
With connected conveying line	Pipe and/or hose run from pump to placement	—	
Concrete-mix delivery with assistance	With pressurized air	Concrete spraying	—

## 5 Commercial specifications

### 5.1 General characteristics

The following characteristics shall be specified:

- model and type;
- manufacturer's name;
- maximum theoretical pumping capacity (m<sup>3</sup>/h);
- maximum theoretical pressure in concrete (MPa);
- diameter of concrete pumping cylinder (mm);
- stroke of concrete pumping cylinder (mm);
- number of strokes per minute (min<sup>-1</sup>);
- outlet diameter of concrete valve device (mm);
- capacity of hopper (m<sup>3</sup>);
- engine power (kW);
- acceptable leaning angle of the machine during pumping operation (degrees);
- operating mass<sup>1)</sup> (kg).

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO 21573-1:2006

<https://standards.iteh.ai/catalog/standards/sist/f0730f56-e76e-4698-8de0-18594a0310/iso-21573-1-2006>

The manufacturer shall provide means for correlating the machine's theoretical maximum concrete line pressure to the theoretical pumping distance capability.

### 5.2 Applicable concrete

Specify the following:

- maximum applicable size of aggregate (mm);
- minimum applicable slump value (cm).

---

1) Specify the mass of the concrete pump under the following conditions:

- ready to run;
- with or without cab (to be stated);
- including standard equipment;
- with a driver of mass 75 kg;
- with fuel tank full;
- with cleaning water, cooling, lubrication and hydraulic systems full.

### 5.3 Drive

Specify the type of the concrete pump's drive:

- by the vehicle engine and additional gear box for hydraulic pump's driving;
- by a separate engine and gear box driving the hydraulic system.

### 5.4 Dimensional characteristics

Specify the following:

- overall dimensions:
  - length,  $L$  (mm);
  - width,  $W$  (mm);
  - height,  $H$  (mm);
- wheel base,  $L1$  (mm);
- hopper height from the ground,  $H1$  mm;
- reach of distributing boom (m).

For maximum out-reach of the distributing boom, see Figure A.14.

### 5.5 Conveying-pipe cleaning device

Specify the following:

- model;
- operation method (water or pneumatic system);
- performance:
  - delivery volume (l/min);
  - delivery pressure (MPa).

### 5.6 Chassis cleaning device

Specify the following:

- model;
- cleaning-water tank capacity (l).