



**SLOVENSKI STANDARD
PSIST I-ETS 300 176:1998**

01-december-1998

8 [[]HJbY]nVc`yUbYyj fcdg_YVfYnj fj] bYhY_Y_ca i b]_UWYfB 97 Hk!`GdYWZ_UWYU
cXcVf]hj YbY[UdfYg_i gU

Digital Enhanced Cordless Telecommunications (DECT); Approval test specification

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: I-ETS 300 176 Edition 1

<https://standards.iteh.ai/catalog/standards/sist/963e2db4-e865-4f9f-80b1-0355d259801b/psist-i-ets-300-176-1998>

ICS:

33.060 Radijske komunikacije Radiocommunications


PSIST I-ETS 300 176:1998

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[PSIST I-ETS 300 176:1998](#)

<https://standards.iteh.ai/catalog/standards/sist/963e2db4-e865-49f-80b1-0355d259801b/psist-i-ets-300-176-1998>



I
E
T
S

**INTERIM
EUROPEAN
TELECOMMUNICATION
STANDARD**

I-ETS 300 176

October 1992

Source: ETSI TC-RES

Reference: DI/RES 3002

ICS: 33.060

Key words: DECT

iTeh STANDARD PREVIEW
Radio Equipment and Systems (RES);
Digital European Cordless Telecommunications (DECT)
Approval test specification

(standards.iteh.ai)
PSIST I-ETS 300 176:1998
<https://standards.iteh.ai/en/standards/PSIST-I-ETS-300-176-1998/0355d259801b/psist-i-ets-300-176-1998>

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1992. All rights reserved.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[PSIST I-ETS 300 176:1998](https://standards.iteh.ai/catalog/standards/sist/963e2db4-e865-49f-80b1-0355d259801b/psist-i-ets-300-176-1998)

<https://standards.iteh.ai/catalog/standards/sist/963e2db4-e865-49f-80b1-0355d259801b/psist-i-ets-300-176-1998>

Contents

Foreword	11
1 Scope	13
2 Normative references	13
3 Definitions, symbols and abbreviations	15
3.1 Manufacturer's declaration	15
3.2 Definitions	15
3.3 Abbreviations	18
4 General	19
4.1 Document layout	19
4.1.1 Test suites	19
4.1.2 Test groups	20
4.1.3 Test cases	21
4.2 Presentation of equipment for testing purposes	22
4.2.1 Choice of model for approval testing	22
4.2.2 Description of equipment	22
4.2.2.1 Protocol Implementation Conformance Specification (PICS)	22
4.2.2.2 Protocol Implementation eXtra Information for Testing (PIXIT)	22
4.2.2.3 Environmental test conditions	22
4.3 Mechanical and electrical design	22
4.3.1 General	22
4.3.2 Controls	22
4.4 Applicability of approval tests	22
4.4.1 All equipment	23
4.4.2 Equipment that includes a radio transmitter	23
4.4.3 Equipment that is to transmit and receive speech	23
4.4.4 Equipment that is to be declared as complying with the Public Access Profile (PAP)	23
4.4.5 Equipment declared as having implemented bearer handover	23
4.4.6 Equipment with a synchronisation port	23
4.5 Interpretation of the measurement results	23
5 General test requirements	23
5.1 Test philosophy	23
5.2 Test site	25
5.2.1 Open air test site	25
5.2.1.1 Description	25
5.2.1.2 Calibration	25
5.2.1.2.1 For emissions radiated by the IUT	25
5.2.1.2.2 For emissions radiated into the IUT	26
5.2.2 Anechoic chamber	27
5.2.2.1 General	27
5.2.2.2 Description	27
5.2.2.3 Influence of parasitic reflections	30
5.2.2.4 Calibration and mode of use	30
5.2.3 Low noise room	30
5.2.4 Stripline coupler	30
5.2.4.1 Description	30
5.2.4.2 Calibration	31

	5.2.4.3	Mode of use	31
5.3		Standard position	31
5.4		Acoustic coupler	32
	5.4.1	General	32
	5.4.2	Description	32
	5.4.3	Calibration	32
	5.4.3.1	Measuring arrangement for calibration	33
5.5		Test antenna of the LT	33
5.6		Substitution antenna	33
5.7		Test fixture	33
	5.7.1	Description	33
	5.7.1.1	Calibration of the test fixture for the measurement of transmitter characteristics	34
	5.7.1.2	Calibration of the test fixture for the measurement of receiver characteristics	35
	5.7.1.3	Mode of use	35
	5.7.2	Equipment with a temporary or internal permanent antenna connector	35
	5.7.2.1	Equipment with a temporary antenna connector	35
5.8		Indoor test site	36
	5.8.1	Description	36
	5.8.2	Test for parasitic reflections	37
	5.8.3	Calibration and mode of use	37
5.9		Lower Tester (LT)	37
	5.9.1	Description	37
	5.9.2	Connections between the IUT and the LT	37
	5.9.3	Functions and abilities	38
	5.9.4	Signal generation uncertainty	38
	5.9.4.1	Interfering DECT-like RF signals	38
	5.9.4.2	CW interferers	38
	5.9.4.3	Test modulation signals	38
	5.9.5	Measurement uncertainty	39
	5.9.5.1	RF measurements	39
	5.9.5.2	Speech and telephony tests	39
5.10		Upper Tester (UT)	40
	5.10.1	Description of the UT	40
	5.10.2	The test standby mode	40
	5.10.3	Test messages	40
5.11		Description of a reference FT and PT	41
5.12		General test methods	41
	5.12.1	Sampling the RF signal	41
	5.12.1.1	Introduction	41
	5.12.1.2	Sampling method	41
	5.12.2	Test arrangement for interference testing	41
	5.12.2.1	PT to PT arrangement	41
	5.12.2.2	FT to FT arrangement	42
	5.12.2.3	FT to PT arrangement	42
	5.12.3	Determining the reference position	43
	5.12.3.1	Case 1: IUTs that cannot transmit	43
	5.12.3.2	Case 2: IUTs that can transmit	43
5.13		Test set-up	43
	5.13.1	Test set-up 1	43
	5.13.2	Test set-up 2	44
	5.13.3	Test set-up 3	44
	5.13.4	Test set-up 4	45
	5.13.5	Test set-up 5	45
6		Test conditions, power sources and ambient temperatures	46
	6.1	General	46
	6.2	Nominal test conditions	46
	6.3	Extreme test conditions	47

6.4	Test power source - general requirements	48
6.5	Nominal test power source.....	48
6.5.1	Mains voltage.....	48
6.5.2	Regulated lead acid battery power sources.....	48
6.5.3	Nickel cadmium battery.....	48
6.5.4	Other power sources.....	48
6.6	Extreme test power source.....	48
6.6.1	Mains voltage.....	48
6.6.2	Regulated lead acid battery power sources.....	48
6.6.3	Nickel cadmium battery.....	48
6.6.4	Other power sources.....	49
7	Accuracy and stability of RF carriers.....	49
7.1	Definition	49
7.2	Test environment.....	49
7.3	Method of measurement.....	49
7.4	Verdict criteria when the IUT is a RFP	50
7.5	Verdict criteria when the IUT is a PP	50
7.5.1	Case 1: when the measurement is made during the first 1 s of the IUT going into a transmit mode from a non-transmitting mode	50
7.5.2	Case 2: When the measurement is made at any other time	50
8	Accuracy and stability of timing parameters.....	50
8.1	Slot structure definitions.....	50
8.2	Definition of the position of b0	51
8.3	Measurement of packet timing jitter	51
8.3.1	Test environment.....	51
8.3.2	Method of measurement.....	51
8.3.3	Verdict criteria	52
8.4	Measurement of timing jitter from bit-to-bit in the same slot on the same channel	52
8.4.1	Test environment.....	52
8.4.2	Method of measurement.....	53
8.4.3	Verdict criteria	53
8.5	Measurement of the reference timing accuracy of a RFP	53
8.5.1	Test environment.....	53
8.5.2	Method of measurement.....	53
8.5.3	Verdict criteria	54
9	Transmission burst	54
9.1	Definitions.....	54
9.1.1	Physical packets	54
9.1.2	Transmitted power	54
9.1.3	Normal Transmitted Power (NTP).....	54
9.1.4	Transmitter attack time.....	54
9.1.5	Transmitter release time	54
9.1.6	Minimum power.....	55
9.1.7	Maximum power.....	55
9.1.8	Maintenance of transmission after packet end	55
9.1.9	Transmitter idle power output.....	55
9.2	Test environment.....	55
9.3	Method of measurement.....	55
9.4	Verdict criteria	55
10	Transmitted power	56
10.1	Definitions.....	56
10.1.1	PP and RFP with an integral antenna	56
10.1.2	PP and RFP with external connections for all antennas.....	56
10.1.3	PP and RFP with both integral and external antennas.....	56
10.2	PP and RFP with an integral antenna.....	57
10.2.1	Test environment.....	57

10.2.2	Method of measurement	57
10.2.3	Verdict criteria for all IUTs.....	57
10.2.4	Verdict criteria for IUTs with the Public Access Profile (PAP).....	58
10.2.5	Declaration for IUTs with the public access profile.....	58
10.3	PP and RFP with external antenna connection(s)	58
10.3.1	Test environment.....	58
10.3.2	Method of measurement	58
10.3.3	Verdict criteria for all IUTs.....	58
10.3.4	Verdict criteria for IUTs with the public access profile.....	58
11	RF carrier modulation	59
11.1	Test environment.....	59
11.2	Method of measurement, parts 1 and 2.....	59
11.2.1	Part 1.....	59
11.2.2	Part 2.....	59
11.3	Method of measurement, parts 3 and 4.....	60
11.3.1	Part 3.....	60
11.3.2	Part 4.....	60
11.4	Verdict criteria for part 1.....	60
11.5	Verdict criteria for part 2.....	60
11.6	Verdict criteria for part 3.....	60
11.7	Verdict criteria for part 4.....	60
12	Unwanted RF power radiation	61
12.1	General test conditions	61
12.2	Emissions due to modulation	61
12.2.1	Definition.....	61
12.2.2	Test environment.....	62
12.2.3	Method of measurement.....	62
12.2.4	Verdict criteria.....	63
12.3	Emissions due to transmitter transients.....	63
12.3.1	Definition.....	63
12.3.2	Test environment.....	63
12.3.3	Method of measurement.....	63
12.3.4	Verdict criteria.....	64
12.4	Emissions due to intermodulation.....	64
12.4.1	Definition.....	64
12.4.2	Test environment.....	64
12.4.3	Method of measurement	65
12.4.4	Verdict criteria.....	66
12.5	Spurious emissions when allocated a transmit channel	66
12.5.1	Definition.....	66
12.5.2	Radiated emissions	66
12.5.2.1	Test environment	66
12.5.2.2	Method of measurement.....	66
12.5.2.3	Verdict criteria	67
12.5.3	Conducted spurious emissions.....	67
12.5.3.1	Test environment	67
12.5.3.2	Method of measurement.....	67
12.5.3.3	Verdict criteria.....	67
13	Radio receiver testing.....	68
13.1	Radio receiver sensitivity.....	68
13.1.1	Definition.....	68
13.1.2	Test environment.....	68
13.1.3	Method of measurement	68
13.1.4	Verdict criteria.....	68
13.2	Radio receiver reference bit error rate	68
13.2.1	Definition.....	68
13.2.2	Test environment.....	69

	13.2.3	Method of measurement	69
	13.2.4	Verdict criteria	69
13.3		Radio receiver interference performance.....	69
	13.3.1	Definition	69
	13.3.2	Test environment.....	69
	13.3.3	Method of measurement	69
	13.3.4	Verdict criteria	70
13.4		Radio receiver blocking case 1: other asynchronous DECT channels.....	70
	13.4.1	Definition	70
	13.4.2	Test environment.....	70
	13.4.3	Method of measurement	71
	13.4.4	Verdict criteria	71
13.5		Radio receiver blocking case 2: in-channel interference.....	71
	13.5.1	Definition	71
	13.5.2	Test environment.....	71
	13.5.3	Method of measurement	72
	13.5.4	Verdict criteria	72
13.6		Receiver intermodulation performance	72
	13.6.1	Definition	72
	13.6.2	Test environment.....	72
	13.6.3	Method of measurement	73
	13.6.4	Verdict criteria	73
13.7		Spurious emissions when the radio endpoint has no allocated transmit channel	73
	13.7.1	Definition	73
	13.7.2	Test environment.....	73
	13.7.3	Method of measurement	74
	13.7.4	Verdict criteria (outside the DECT band)	74
	13.7.5	Verdict criteria (inside the DECT band)	74
14		Synchronisation port (FT only).....	74
	14.1	Description	74
	14.2	Test environment.....	74
	14.3	FT as the master.....	75
	14.3.1	Method of measurement	75
	14.3.2	Verdict criteria	75
	14.4	FT as the slave	75
	14.4.1	Method of measurement	75
	14.4.2	Verdict criteria: Class 1 FTs.....	76
	14.4.3	Verdict criteria: Class 2 FTs.....	76
15		Speech and telephony tests	76
	15.1	Test configurations.....	76
	15.1.1	General	76
	15.1.2	Testing a DECT system.....	76
	15.1.3	Testing a separate PP or FP.....	76
	15.1.4	Reference FP (ReFP) and Reference PP (RePP)	77
	15.1.5	Applicability of tests.....	78
	15.2	Digital signal level.....	78
	15.3	General conditions of test	79
	15.4	Ideal codec.....	79
	15.5	Electro-acoustical equipment.....	79
	15.6	Speech coding scheme.....	79
	15.7	PP sending frequency response	80
	15.8	PP receiving frequency response.....	80
	15.9	PP loudness rating	80
	15.9.1	SLR _H	80
	15.9.2	RLR _H	80
	15.10	User controlled volume control in PP.....	81
	15.10.1	SLR _H	81
	15.10.2	RLR _H	81

15.11	PP adaptive volume control	81
15.12	FP adaptive volume control	81
15.13	PP talker sidetone masking rating.....	81
15.14	Listener sidetone.....	82
15.15	Terminal Coupling Loss of a PP.....	82
15.16	Artificial echo loss of a FP with a 4-wire interface	83
15.17	Echo control device of a FP with a 4-wire interface	83
15.18	Stability loss - fixed geometry.....	83
15.19	Stability loss variable geometry	84
15.20	Sending distortion.....	84
15.21	Receiving distortion	85
15.22	Side tone distortion.....	85
15.23	Out of band (sending).....	85
15.24	Out of band (receiving)	85
15.25	Sending noise	85
15.26	Sending noise (narrow band).....	86
15.27	Receiving noise	86
15.28	Sampling frequency level (receiving)	86
15.29	Acoustic shock.....	86
15.29.1	Continuous signal.....	86
15.29.2	Peak signal	87
15.30	DECT network delay	87
15.30.1	FP connected to a network with a digital 4-wire interface	87
15.30.2	Network with an FP with an analogue 4-wire interface.....	88
15.30.3	Network with an FP with an analogue 2-wire interface.....	88
15.31	PP delay.....	88
15.32	FP delay.....	89
15.32.1	Digital 4-wire interface.....	90
15.32.2	Analogue 4-wire interface.....	91
15.32.3	Analogue 2-wire interface.....	91
15.32.3.1	If a 4-wire interface point is accessible.....	91
15.32.3.2	If only a 2-wire interface point is accessible.....	91
15.33	Network echo control.....	91
15.33.1	4-wire interface.....	91
15.33.2	Analogue 2-wire interface.....	92
15.33.2.1	Requirement 1.....	92
15.33.2.2	Requirement 2.....	93
15.34	PP ambient noise rejection.....	93
15.35	Loudspeaker and hands-free facilities	93
16	Requirements for public access	94
16.1	Description of the features	94
16.1.1	Speech.....	94
16.1.2	Bell on	94
16.1.3	Bell off.....	94
16.1.4	Off-hook	94
16.1.5	On-hook (full release)	94
16.1.6	Partial release.....	94
16.1.7	Dialled digits (basic)	94
16.1.8	Dialled digits (additional)	94
16.1.9	Dialling delimiter	94
16.1.10	Dialling delimiter request	94
16.1.11	Register recall.....	95
16.1.12	Go to Dual Tone Multi-Frequency	95
16.1.13	Go to pulse.....	95
16.1.14	Pause (interdigit pause)	95
16.1.15	Specific trunk carrier selection.....	95
16.1.16	Incoming call	95
16.1.17	Hold call.....	95
16.1.18	Re-connection of a held call.....	95

16.1.19	Forced re-connection.....	95
16.1.20	Authentication of portable part.....	95
16.1.21	Authentication of user	95
16.1.22	Authentication of fixed part.....	95
16.1.23	Silent polling.....	96
16.1.24	Class of service field indication.....	96
16.1.25	Inter-operator roaming registration	96
16.1.26	Control of supervisory tones.....	96
16.1.27	Regular security handshake	96
16.1.28	Signalling of display characters.....	96
16.1.29	Display control characters.....	96
16.1.30	ZAP suspend	96
16.1.31	ZAP terminate.....	97
16.1.32	Alphanumeric text messaging and radiopaging service.....	97
16.1.33	Voice and user data traffic encryption activation/deactivation	97
16.1.34	Signalling traffic encryption activation/de-activation.....	97
16.1.35	Debit public access service	97
16.1.36	Credit public access service	97
16.1.37	Credit agency public access service	97
16.1.38	On-demand (hot-bill) public access service.....	97
16.1.39	Advice of tariff request.....	98
16.1.40	Advice of charge request	98
16.1.41	Location registration for incoming calls, paging or messages	98
16.1.42	Location de-registration for incoming calls, paging or messages	98
16.1.43	Queue management	98
16.1.44	Queue entry request.....	98
16.1.45	Queue exit request	98
16.1.46	"Portable part inaccessible" indication	98
16.1.47	"In-range" indication.....	98
16.1.48	Emergency service access request.....	98
16.1.49	Indication of teleservices available request	98
16.1.50	Indication of teleservices available	98
16.1.51	Selection of service provider/network operator	99
16.1.52	Selection of required teleservice	99
16.1.53	Selection of bearer service.....	99
16.1.54	Validation of portable part user.....	99
16.1.55	Validation of portable part	99
16.1.56	Validation of identity module	99
16.1.57	User identification	99
16.1.58	Group address.....	99
16.1.59	Selection of additional character sets.....	99
16.1.60	Data capability	99
16.1.61	Keypad protocol for supplementary services	99
16.1.62	Feature key management protocol for supplementary services	99
16.1.63	Functional protocol for supplementary services.....	100
16.1.64	Dial tone detection indication	100
16.1.65	Request for indication of (temporary) subscriber number.....	100
16.1.66	Portable part capability/fixed part capability data exchange	100
16.1.67	Subscription registration user procedure (on-air).....	100
16.1.68	Subscription registration user procedure (keypad)	100
16.1.69	Subscription registration user procedure (DECT authentication module)....	100
16.1.70	Subscription data exchange (on-air).....	100
16.1.71	Multicell fixed part coverage	100
16.1.72	Handover	100
16.1.72.1	Description.....	100
16.1.72.2	Bearer handover test procedure (portable parts only).....	101
16.1.72.3	Test environment	101
16.1.72.4	Method of verification.....	101
16.1.72.5	Verdict criteria.....	101
16.1.73	Multiple subscription registration.....	101

16.1.74	All-physical-channel capability.....	101
16.2	Summary of DECT public access service facilities.....	102
Annex A (informative):	Report references.....	104
Annex B (normative):	Procedures for test fixture calibration and for measurement of radiated spurious emissions	105
B.1	Calibration of test fixture for receiver measurements	105
B.1.1	Method of measurement	105
B.2	Radiated measurements	106
B.2.1	General	106
B.2.2	Radiated spurious emissions	107
B.2.2.1	Definition.....	107
B.2.2.2	Method of measurement	107
B.2.3	Cabinet radiation	109
B.2.3.1	Definition.....	109
B.2.3.2	Method of measurement	109
Annex C (normative):	Procedure for measurement of conducted spurious emissions	110
C.1	Conducted spurious emissions.....	110
C.1.1	Definition	110
C.1.2	Method of measurement	110
History		111

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[PSIST I-ETS 300 176:1998](https://standards.iteh.ai/catalog/standards/sist/963e2db4-e865-49f-80b1-0355d259801b/psist-i-ets-300-176-1998)

<https://standards.iteh.ai/catalog/standards/sist/963e2db4-e865-49f-80b1-0355d259801b/psist-i-ets-300-176-1998>

Foreword

This Interim European Telecommunication Standard (I-ETS) has been produced by the Radio Equipment and Systems (RES) Technical Committee of the European Telecommunications Standards Institute (ETSI).

This I-ETS contains text pertaining to approval testing of the Digital European Cordless Telecommunications (DECT) Common Interface.

Such text should be considered as guidance to approval (or licensing) authorities.

The Public Access Profile (PAP) Clause contains an Applicant's Declaration. Extensive tests for the PAP are currently under development. It is intended to add these to the TBR 11 when available.

Network attachment requirements will be referred from TBRs.

Details of the DECT Common Interface may be found in ETS 300 175.

Further details of the DECT system may be found in the ETSI Technical Reports, ETR 015 [11], and ETR 043 [10], and also in the draft ETSI Technical Report, "Digital European Cordless Telecommunications System Description Document" [12].

iTeh STANDARD PREVIEW (standards.iteh.ai)

[PSIST I-ETS 300 176:1998](https://standards.iteh.ai/catalog/standards/sist/963e2db4-e865-49f-80b1-0355d259801b/psist-i-ets-300-176-1998)

<https://standards.iteh.ai/catalog/standards/sist/963e2db4-e865-49f-80b1-0355d259801b/psist-i-ets-300-176-1998>

Blank page

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[PSIST I-ETS 300 176:1998](https://standards.iteh.ai/catalog/standards/sist/963e2db4-e865-49f-80b1-0355d259801b/psist-i-ets-300-176-1998)

<https://standards.iteh.ai/catalog/standards/sist/963e2db4-e865-49f-80b1-0355d259801b/psist-i-ets-300-176-1998>

1 Scope

This Interim European Telecommunication Standard (I-ETS) specifies the approval tests applicable to all Digital European Cordless Telecommunications (DECT) equipment.

Its aims are to ensure the following:

- efficient use of the radio frequency spectrum;
- no harm is done to any connected network and its services as well as to other radio networks and services;
- no harm is done to other DECT equipment and its services;
- inter-operability between DECT equipment intended for public access.

2 Normative references

This Interim European Telecommunication Standard (I-ETS) incorporates, by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to, or revisions of, any of these publications apply to this I-ETS only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

- [1] ETS 300 175-1: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT) Common Interface Part 1: Overview".
- [2] ETS 300 175-2: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT) Common Interface Part 2: Physical layer".
- [3] ETS 300 175-3: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT) Common Interface Part 3: Medium access control layer".
- [4] ETS 300 175-4: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT) Common Interface Part 4: Data link control layer".
- [5] ETS 300 175-5: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT) Common Interface Part 5: Network layer".
- [6] ETS 300 175-6: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT) Common Interface Part 6: Identities and addressing".
- [7] ETS 300 175-7: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT) Common Interface Part 7: Security features".
- [8] ETS 300 175-8: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT) Common Interface Part 8: Speech coding and transmission".
- [9] ETS 300 175-9: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT) Common Interface Part 9: Public access profile".