

---

---

**Information technology — Streaming  
Lossless Data Compression algorithm  
(SLDC)**

*Technologies de l'information — Algorithme de compression sans perte de  
données en mode continu (SDLC)*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 22091:2002](https://standards.iteh.ai/catalog/standards/sist/ba18c004-aa97-495f-b85d-99af0924e742/iso-iec-22091-2002)

[https://standards.iteh.ai/catalog/standards/sist/ba18c004-aa97-495f-b85d-  
99af0924e742/iso-iec-22091-2002](https://standards.iteh.ai/catalog/standards/sist/ba18c004-aa97-495f-b85d-99af0924e742/iso-iec-22091-2002)



**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 22091:2002](https://standards.iteh.ai/catalog/standards/sist/ba18c004-aa97-495f-b85d-99af0924e742/iso-iec-22091-2002)

<https://standards.iteh.ai/catalog/standards/sist/ba18c004-aa97-495f-b85d-99af0924e742/iso-iec-22091-2002>

© ISO/IEC 2002

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.ch](mailto:copyright@iso.ch)  
Web [www.iso.ch](http://www.iso.ch)

Printed in Switzerland

## Contents

1	Scope	1
2	Conformance	1
3	Normative reference	1
4	Terms and definitions	1
4.1	Access Point	1
4.2	Control Symbol	1
4.3	Copy Pointer	1
4.4	data byte	1
4.5	Data Symbol	1
4.6	Displacement Field	1
4.7	Encoded Data Stream	1
4.8	Encoded Record	1
4.9	End Marker	2
4.10	End Of Record Symbol (EOR Symbol)	2
4.11	File Mark	2
4.12	File Mark Symbol	2
4.13	Flush Symbol	2
4.14	History Buffer	2
4.15	Literal 1	2
4.16	Literal 2	2
4.17	Matching String	2
4.18	Match Count	2
4.19	Match Count Field	2
4.20	Pad	2
4.21	Record	2
4.22	Record Segment	2
4.23	Reset X Symbol	2
4.24	Reset 1 Symbol	2
4.25	Reset 2 Symbol	2
4.26	scheme 1	2
4.27	Scheme 1 Symbol	2
4.28	scheme 2	3
4.29	Scheme 2 Symbol	3
4.30	user data	3
5	Conventions and Notations	3
5.1	Representation of numbers	3
5.2	Names	3
6	Acronyms	3
7	Algorithm Overview	3
7.1	Scheme 1 Encoding	3
7.2	Scheme 2 Encoding	3
7.3	History Buffer	4
8	Encoding Specification	4
8.1	User Data	4
8.2	History Buffer	4
8.3	Encoded Data Stream	4

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

[ISO/IEC 22091:2002](https://standards.iteh.ai/catalog/standards/sist/ba18c004-aa97-495f-b85d-99af0924e742/iso-iec-22091-2002)

<https://standards.iteh.ai/catalog/standards/sist/ba18c004-aa97-495f-b85d-99af0924e742/iso-iec-22091-2002>

<b>8.3.1</b>	Access Point	<b>5</b>
<b>8.4</b>	Data Symbols	<b>5</b>
<b>8.4.1</b>	Literal 1 Data Symbols	<b>5</b>
<b>8.4.2</b>	Copy Pointer Data Symbols	<b>5</b>
<b>8.4.3</b>	Literal 2 Data Symbols	<b>6</b>
<b>8.5</b>	Control Symbols	<b>7</b>
<b>8.6</b>	Pad	<b>8</b>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 22091:2002](https://standards.iteh.ai/catalog/standards/sist/ba18c004-aa97-495f-b85d-99af0924e742/iso-iec-22091-2002)

<https://standards.iteh.ai/catalog/standards/sist/ba18c004-aa97-495f-b85d-99af0924e742/iso-iec-22091-2002>

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC 22091 was prepared by ECMA (as ECMA-321) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information Technology*, in parallel with its approval by national bodies of ISO and IEC.

<https://standards.iteh.ai/catalog/standards/sist/ba18c004-aa97-495f-b85d-99af0924e742/iso-iec-22091-2002>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 22091:2002](#)

<https://standards.iteh.ai/catalog/standards/sist/ba18c004-aa97-495f-b85d-99af0924e742/iso-iec-22091-2002>

# Information technology — Streaming Lossless Data Compression algorithm (SLDC)

## 1 Scope

This International Standard specifies a lossless compression algorithm to reduce the number of 8-bit bytes required to represent data records and File Marks. The algorithm is known as Streaming Lossless Data Compression algorithm (SLDC).

One buffer size (1 024 bytes) is specified.

The numerical identifier according to ISO/IEC 11576 allocated to this algorithm is 6.

## 2 Conformance

A compression algorithm shall be in conformance with this International Standard if its Encoded Data Stream satisfies the requirements of this International Standard.

## 3 Normative reference

The following normative document contains provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative document indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO/IEC 11576:1994 *Information technology — Procedure for the registration of algorithms for the lossless compression of data*

## 4 Terms and definitions

For the purpose of this International Standard the following terms and definitions apply.

### 4.1 Access Point

A location in the Encoded Data Stream at which data may be decoded.

### 4.2 Control Symbol

A Control Symbol may change the compression scheme, reset the History Buffer, mark the end of a Record, indicate a File Mark, or indicate the termination of an Encoded Data Stream.

### 4.3 Copy Pointer

A part of the Encoded Data Stream output in scheme 1 that replaces a string of data bytes with a specification of a Matching String.

### 4.4 data byte

An element of user data that is to be encoded.

### 4.5 Data Symbol

An element of an Encoded Record that represents one or more data bytes.

### 4.6 Displacement Field

A field in the Copy Pointer that specifies the location within the History Buffer of the first byte of a Matching String.

### 4.7 Encoded Data Stream

The output stream after encoding User Data.

### 4.8 Encoded Record

The output stream after encoding one Record of user data.

#### 4.9 End Marker

A Control Symbol that denotes termination of an Encoded Data Stream.

#### 4.10 End Of Record Symbol (EOR Symbol)

A Control Symbol that denotes the end of a Record in the Encoded Data Stream.

#### 4.11 File Mark

A recorded element used to mark organisational boundaries (e.g. directory boundaries) in user data.

#### 4.12 File Mark Symbol

A Control Symbol in Encoded Data Stream that denotes a File Mark in user data.

#### 4.13 Flush Symbol

A Control Symbol that, if required, is followed by Pad to make the size of the Encoded Data Stream an integer multiple of 32 bits.

#### 4.14 History Buffer

A data structure where incoming data bytes are stored for use by scheme 1 compression and decompression.

#### 4.15 Literal 1

A part of the Encoded Data Stream, output in scheme 1, that represents a single data byte not encoded into any Copy Pointer.

#### 4.16 Literal 2

A part of the Encoded Data Stream, output in scheme 2, that represents a single data byte.

#### 4.17 Matching String

A sequence of two or more bytes in the History Buffer that is identical with a sequence of bytes in the user data.

#### 4.18 Match Count

The length, in bytes, of a Matching String.

#### 4.19 Match Count Field

That part of a Copy Pointer that specifies the Match Count.

#### 4.20 Pad

A number of bits inserted into the Encoded Data Stream so that the size of Encoded Data Stream is an integer multiple of 32 bits.

#### 4.21 Record

An element of user data that contains at least one data byte.

#### 4.22 Record Segment

A section of a Record encoded in a given scheme.

#### 4.23 Reset X Symbol

A generic reference to either the Reset 1 Symbol or the Reset 2 Symbol.

#### 4.24 Reset 1 Symbol

A Control Symbol that indicates History Buffer reset, and that subsequent symbols are encoded in scheme 1.

#### 4.25 Reset 2 Symbol

A Control Symbol that indicates History Buffer reset, and that subsequent symbols are encoded in scheme 2.

#### 4.26 scheme 1

A compression scheme that uses a History Buffer to achieve data compression.

#### 4.27 Scheme 1 Symbol

A Control Symbol that indicates subsequent Data Symbols are either Copy Pointers or Literal 1s.

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

[ISO/IEC 22091:2002](https://standards.iteh.ai/catalog/standards/sist/ba18c004-aa97-495f-b85d-99af0924e742/iso-iec-22091-2002)

<https://standards.iteh.ai/catalog/standards/sist/ba18c004-aa97-495f-b85d-99af0924e742/iso-iec-22091-2002>



#### 4.28 scheme 2

A packing scheme designed to encode uncompressible data with minimal expansion.

#### 4.29 Scheme 2 Symbol

A Control Symbol that indicates subsequent Data Symbols are encoded in scheme 2.

#### 4.30 user data

Information that is to be encoded, according to this compression algorithm.

### 5 Conventions and Notations

#### 5.1 Representation of numbers

The following conventions and notations apply in this document unless otherwise stated.

- The setting of bits is denoted by ZERO or ONE.
- Numbers in binary notation and bit combinations are strings of digits represented by ZEROs and ONES with the most significant bit to the left.
- Letters and digits in parentheses represent numbers in hexadecimal notation.
- All other numbers are in decimal form.

#### 5.2 Names

The names of basic elements, e.g. specific fields, are written with a capital initial letter.

### 6 Acronyms

EOR End Of Record

lsb least significant bit

msb most significant bit

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/IEC 22091:2002](https://standards.iteh.ai/catalog/standards/sist/ba18c004-aa97-495f-b85d-99af0924e742/iso-iec-22091-2002)

<https://standards.iteh.ai/catalog/standards/sist/ba18c004-aa97-495f-b85d-99af0924e742/iso-iec-22091-2002>

### 7 Algorithm Overview

User data that is to be compressed according to this International Standard consists of Records and File Marks. Records consist of 8-bit data bytes, and may be of any non-zero length.

Data bytes may be encoded in either scheme 1 or scheme 2.

#### 7.1 Scheme 1 Encoding

There may exist within Records repeating strings of two or more data bytes such that information about the length and position of one string may be substituted in place of a subsequent copy or copies of that same string. This information is known as a Copy Pointer. This International Standard allows Copy Pointer substitution when corresponding bytes of the two strings are offset by 1 to 1 023 data bytes within user data. Where string matches occur, data compression is possible, and the number of bits of encoded data can be less than the number of bits of user data, and data compression is possible. Any data bytes that are part of a repeated string may be encoded as a Copy Pointer. Any data byte that is not encoded as a Copy Pointer is encoded as a Literal 1, in which a leading bit set to ZERO is added to the data byte, thereby indicating that this is a Literal 1. Regions over which Copy Pointers and literal values are encoded are defined as being encoded according to scheme 1. Scheme 1 encoding is identical with that of ISO/IEC 15200, except for the addition of Control Symbols. These are both implementations of the Lempel-Ziv 1 (LZ1) class of data compression algorithms. Following a Reset 1 Symbol or a Scheme 1 Symbol, all bytes of user data shall be encoded according to scheme 1.

#### 7.2 Scheme 2 Encoding

There may also exist within user data, regions in which few such repeating strings exist. Where there are no repeating strings, scheme1 encoding requires a 9-bit Literal 1 value in the Encoded Data Stream for every data byte. This results in an Encoded Data Stream that has 12,5 % more bits than the user data. In order to avoid this data expansion, scheme 2 encoding may be used. In scheme 2 encoding, data bytes are copied to the output bit stream. In order for a decoder to distinguish a data byte set to (FF) from a Control Symbol, a trailing bit set to ZERO is encoded following every data byte of (FF). For random data, this tends to produce an Encoded Data Stream that has about 0,05 % more bits than the user data. Following a Reset 2 Symbol or a Scheme 2 Symbol, all bytes of user data shall be encoded according to scheme 2.