

SLOVENSKI STANDARD SIST EN 13683:2004+A2:2011

01-maj-2011

Oprema za nego vrta - Motorni drobilniki/sekalniki - Varnost					
Garden equipment - Integrally powered shredders/chippers - Safety					
Gartengeräte - Motorgetriebene Schredder/Zerkleinerer - Sicherheit					
Matériel de jardinage - Broyeurs/déchiqueteurs à moteur intégré - Sécurité					
Ta slovenski standard je istoveten z: EN 13683:2003+A2:2011					
https://standards.iteh.ai/catalog/standards/sist/d5455601-6d0d-4c21-					
9542-b65d9325be1c/sist-en-13683-2004a2-2011					
<u>ICS:</u>					
65.060.70 Vrtnarska oprema	Horticultural equipment				
SIST EN 13683:2004+A2:2011	en,fr				

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 13683:2004+A2:2011</u> https://standards.iteh.ai/catalog/standards/sist/d5455601-6d0d-4c21-9542-b65d9325be1c/sist-en-13683-2004a2-2011

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 13683:2003+A2

March 2011

ICS 65.060.70

Supersedes EN 13683:2003+A1:2009

English Version

Garden equipment - Integrally powered shredders/chippers -Safety

Matériel de jardinage - Broyeurs/déchiqueteurs à moteur intégré - Sécurité Gartengeräte - Motorgetriebene Schredder/Zerkleinerer -Sicherheit

This European Standard was approved by CEN on 8 September 2003 and includes Amendment 1 approved by CEN on 14 March 2009 and Amendment 2 approved by CEN on 3 December 2010.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom. SIST EN 13683:2004+A2:2011

> https://standards.iteh.ai/catalog/standards/sist/d5455601-6d0d-4c21-9542-b65d9325be1c/sist-en-13683-2004a2-2011



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Forewo	Foreword4				
0	Introduction	.5			
1	Scope	.6			
2	Normative references	.6			
3	Terms and definitions	.7			
4	List of significant hazards	11			
5	Safety requirements and/or measures	13			
5.1	General	13			
5.2	Access to power driven components	13			
5.2.1 5.2.2	Peed Safety openings	13			
5.2.3	Guards	26			
5.2.4	Power driven components except cutting means	26			
5.3	Hot exhaust surfaces	27			
5.3.1	General	27			
5.3.2	Test equipment and method of test	27			
5.3.3	Test acceptance	27			
5.4	Controls	29			
5.4.1	Location	29			
5.4.Z	Identification of controls	29 20			
5.4.5	Protection from exhaust filmes catalog/standards/sist/d5455601-6d0d-4c21-	29			
5.6	Flectrical requirements	29			
5.6.1	General	29			
5.0.0					
5.6.2	Low voltage battery circuits (not including magneto grounding circuits)	29			
5.6.2 5.6.3	Low voltage battery circuits (not including magneto grounding circuits) Overload protection	29 30			
5.6.2 5.6.3 5.6.4	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts	29 30 30			
5.6.2 5.6.3 5.6.4 5.7	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage	29 30 30 30			
5.6.2 5.6.3 5.6.4 5.7 5.8	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport	29 30 30 30 30 30			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport Verification of safety requirements	29 30 30 30 30 30 30			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9 5.9.1	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport Verification of safety requirements Test conditions	29 30 30 30 30 30 30 30			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9 5.9.1 5.9.2	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport Verification of safety requirements Test conditions Thrown object test (see 5.2.3.1)	29 30 30 30 30 30 30 30 31			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9 5.9.1 5.9.2 5.9.3 5.9.4	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport Verification of safety requirements Test conditions Thrown object test (see 5.2.3.1) Stability	29 30 30 30 30 30 30 31 34			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9 5.9.1 5.9.2 5.9.3 5.9.4 5.9.4 5.10	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport Verification of safety requirements Test conditions Thrown object test (see 5.2.3.1) Stability Dynamic stability test	29 30 30 30 30 30 30 31 34 34 35			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9 5.9.1 5.9.2 5.9.3 5.9.3 5.9.4 5.10 5.10	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport Verification of safety requirements Test conditions Thrown object test (see 5.2.3.1) Stability Dynamic stability test Noise Noise	29 30 30 30 30 30 30 31 34 34 35 35			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9 5.9.1 5.9.2 5.9.3 5.9.4 5.10 5.10.1 5.10.2	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport Verification of safety requirements Test conditions Thrown object test (see 5.2.3.1) Stability Dynamic stability test Noise Noise reduction as a safety requirement Verification of requirements on noise – Noise measurement	29 30 30 30 30 30 30 31 34 35 35 35			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9 5.9.1 5.9.2 5.9.3 5.9.4 5.10 5.10.1 5.10.2	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport Verification of safety requirements Test conditions Thrown object test (see 5.2.3.1) Stability Dynamic stability test Noise Noise reduction as a safety requirement. Verification of requirements on noise – Noise measurement	29 30 30 30 30 30 30 31 34 35 35 35			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9 5.9.1 5.9.2 5.9.3 5.9.4 5.10 5.10.1 5.10.2 6 6	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport Verification of safety requirements Test conditions Thrown object test (see 5.2.3.1) Stability Dynamic stability test Noise Noise reduction as a safety requirement Verification of requirements on noise – Noise measurement Information for use	29 30 30 30 30 30 30 31 34 35 35 35 36 26			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9 5.9.1 5.9.2 5.9.3 5.9.4 5.10 5.10.1 5.10.2 6 6.1 6.2	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport Verification of safety requirements Test conditions Thrown object test (see 5.2.3.1) Stability Dynamic stability test Noise Noise reduction as a safety requirement Verification of requirements on noise – Noise measurement Information for use Instruction for use	29 30 30 30 30 30 30 31 34 35 35 36 37			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9 5.9.1 5.9.2 5.9.3 5.9.4 5.10 5.10.2 6 6.1 6.2 6.2 6.2.1	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport Verification of safety requirements Test conditions Thrown object test (see 5.2.3.1) Stability Dynamic stability test Noise Noise reduction as a safety requirement Verification of requirements on noise – Noise measurement Information for use Instruction for use Marking Minimum marking	29 30 30 30 30 30 31 34 35 35 36 37 37			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9 5.9.1 5.9.2 5.9.3 5.9.4 5.10 5.10.1 5.10.2 6 6.1 6.2 6.2 6.2.1 6.2.2	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport Verification of safety requirements Test conditions Thrown object test (see 5.2.3.1). Stability Dynamic stability test Noise Noise reduction as a safety requirement. Verification of requirements on noise – Noise measurement Information for use Instruction for use Marking Minimum marking Warning marking	29 30 30 30 30 30 31 34 35 35 36 37 38			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9 5.9.1 5.9.2 5.9.3 5.9.4 5.10 5.10.1 5.10.2 6 6.1 6.2 6.2.1 6.2.2 6.2.3	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport Verification of safety requirements Test conditions Thrown object test (see 5.2.3.1) Stability Dynamic stability test Noise Noise reduction as a safety requirement Verification of requirements on noise – Noise measurement Information for use Instruction for use Marking Warning marking Marking durability	29 30 30 30 30 30 30 30 31 34 35 35 36 37 38 38			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9 5.9.1 5.9.2 5.9.3 5.9.4 5.10 5.10.1 5.10.2 6 6.1 6.2 6.2.1 6.2.2 6.2.3 6.2.4	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport	29 30 30 30 30 30 30 30 31 34 35 35 36 37 38 33 38 38			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9 5.9.1 5.9.2 5.9.3 5.9.4 5.10 5.10.1 5.10.2 6 6.1 6.2 6.2.1 6.2.2 6.2.3 6.2.4 A	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport Verification of safety requirements Test conditions Thrown object test (see 5.2.3.1) Stability Dynamic stability test Noise Noise reduction as a safety requirement. Verification of requirements on noise – Noise measurement Information for use Instruction for use Marking Marking durability A (informative) Imp Examples of inlet openings where the safety distance is	29 30 30 30 30 30 31 34 35 35 36 37 38 33 33 33 33 33 33 33 33 33 33 33 33			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9 5.9.1 5.9.2 5.9.3 5.9.4 5.10 5.10.1 5.10.2 6 6.1 6.2 6.2 6.2.1 6.2.3 6.2.4 Annex	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport	29 30 30 30 31 34 35 36 37 388 39			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9 5.9.1 5.9.2 5.9.3 5.9.4 5.10 5.10.1 5.10.2 6 6.1 6.2 6.2.1 6.2.2 6.2.1 6.2.2 6.2.3 6.2.4 Annex	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport Verification of safety requirements. Test conditions. Thrown object test (see 5.2.3.1). Stability Dynamic stability test Noise Noise reduction as a safety requirement. Verification of requirements on noise – Noise measurement Information for use Instruction for use Marking Marking Marking durability Test A (informative) P Examples of inlet openings where the safety distance is ≥ 200 mm (see 5.2.1.3) @	29 30 300 310			
5.6.2 5.6.3 5.6.4 5.7 5.8 5.9 5.9.1 5.9.2 5.9.3 5.9.4 5.10 5.10.1 5.10.2 6 6.1 6.2 6.2.1 6.2.2 6.2.3 6.2.4 Annex	Low voltage battery circuits (not including magneto grounding circuits) Overload protection Terminals and uninsulated electrical parts Liquid spillage Transport Verification of safety requirements Test conditions Thrown object test (see 5.2.3.1) Stability Dynamic stability test Noise Noise reduction as a safety requirement. Verification of requirements on noise – Noise measurement Information for use Instruction for use Marking Minimum marking Warning marking Marking durability Test A (informative) © Examples of inlet openings where the safety distance is ≥ 200 mm (see 5.2.1.3) B (normative)	29 30 300 300 301 31 32 330 330 330 330 330 331 34 35 36 377 38 39 42			

C.1	Corrugated fibreboard target panel composition	44
C.2	Corrugated fibreboard penetration test	44
0.2.1	General	44
C 2 3	Corrugated fibrohoard samples	44 11
C 2 4	Procedure	44
C.2.5	Acceptance criteria	45
Annex	D (informative) Safety instructions	47
D.1	General	47
D.2 D 2 1	Training	41 17
D.2.1	Preparation	47
D.2.3	Operation	48
D.2.4	Maintenance and storage	49
D.2.5	Additional safety instructions for units with bagging attachments	49
Annov	E (normative) Symbols and/or nictograms	50
E.1	General	50
E.2	Pictograms	50
Annov	\mathbf{E} (permetive) Noise test code - Engineering method (grade 2)	52
F 1	Scope	52
F.2	A-weighted sound power level determination	52
F.3	A-weighted emission sound pressure level measurement	53
F.4	Requirements for test floor	57
F.4.1	Artificial surface	57
F.4.2	Natural grass I.I.e.h. S.I.A.N.D.A.R.D. P.R.E.V.I.E.W	57
F.5	Installation, mounting and operating conditions	57
F.6	Measurement uncertainties and declaration of noise emission values	58
F.7	Information to be recorded and reported	58
Annex	G (informative) Example of a material and construction fulfilling the requirements	
	for an artificial surface and site hai/catalog/standards/sist/d5455601-6d0d-4c21-	59
G.1	Material	59
G.2	Construction	59
Annex	ZA (informative) \Lambda Relationship between this European Standard and the	
	Essential Requirements of EU Directive 2006/42/EC (A2)	61
Diblies	ronhy	62
BIDIIOO		UZ

Foreword

This document (EN 13683:2003+A2:2011) has been prepared by Technical Committee CEN/TC 144 "Tractors and machinery for agriculture and forestry", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2011, and conflicting national standards shall be withdrawn at the latest by September 2011.

This document includes Amendment 1, approved by CEN on 2009-03-14 and Amendment 2, approved by CEN on 2010-12-13.

This document supersedes A2 EN 13683:2003+A1:2009 (A2).

The start and finish of text introduced or altered by amendment is indicated in the text by tags $\boxed{\mathbb{A}}$ $\boxed{\mathbb{A}}$ and $\boxed{\mathbb{A}}$ $\boxed{\mathbb{A}}$.

 $|A_2\rangle$ deleted text $\langle A_2 \rangle$

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

A) For relationship with EU Directive(s), see informative A) Annex ZA (A), which A) is an integral part (A) of this document. (A)

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or/CENELEC] shall not be held responsible for didentifying any or all such patent rights. 9542-b65d9325be1c/sist-en-13683-2004a2-2011

Annexes A, D and G are informative. Annexes B, C, E and F are normative.

This document includes a Bibliography.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

0 Introduction

This document is a type C standard as stated in EN 1070:1998.

The machinery concerned and the extent to which hazards, hazardous situations and events are covered are indicated in the scope of this document.

When provisions of this type C standard are different from those which are stated in type A or B standards, the provisions of this type C standard take precedence over the provisions of the other standards, for machines that have been designed and built according to the provisions of this type C standard.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 13683:2004+A2:2011</u> https://standards.iteh.ai/catalog/standards/sist/d5455601-6d0d-4c21-9542-b65d9325be1c/sist-en-13683-2004a2-2011

1 Scope

This European Standard specifies safety requirements and their verification for the design and construction of hand fed, shredders/chippers with integral power source and with or without vacuum assisted collection which are designed primarily to reduce organic material to smaller pieces. It is only applicable to shredders/chippers that are designed for use outdoors in a stationary position by an operator standing on the ground. A This standard applies to shredders/chippers with feed intake openings or segments, in this standard referred to as feed safety openings and being of any shape complying with the safety distance requirements of this standard with regard to contact with the cutting means, that in total will fit into a square of 250 mm \times 250 mm measured at the plane of the opening(s).

A2 deleted text (A2

This standard describes methods of elimination or reduction of hazards arising from the use of shredders/chippers. In addition it specifies the type of information to be provided by the manufacturer on safe working practices.

This standard does not cover requirements for:

- units driven by an external power source;
- mobile use of units which can be used in both stationary and mobile modes;
- units with powered discharge intended to broadcast material or load vehicles;

(standards.iteh.ai)

- units with separate mechanically powered feed intake or attachments; (A) https://standards.iteh.ai/catalog/standards/sist/d5455601-6d0d-4c21-
- units with cutting means of either one or more non-metallic filaments, or one or more non-metallic cutting elements pivotally mounted on a generally circular central drive unit, where these cutting elements rely on centrifugal force to achieve cutting, and have a kinetic energy for each single cutting means of less than 10 J;

 A_2

 A_2

— electrical powered and battery-powered shredders/chippers.

Environmental hazards and EMC have not been considered in this standard.

This standard deals with all significant hazards, hazardous situations and events relevant to shredders/chippers, when they are used as intended (see clause 4).

This document is not applicable to shredders/chippers which are manufactured before the date of publication of this document by CEN.

2 Normative references

This European Standard incorporates, by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies (including amendments).

 $|A_2\rangle$ deleted text $\langle A_2 \rangle$

▶ EN 953:1997+A1:2009, Safety of machinery — Guards — General requirements for the design and construction of fixed and movable guards ♣

EN 954-1:1996, Safety of machinery — Safety-related parts of control systems — Part 1: General principles for design.

EN 1070:1998, Safety of machinery — Terminology.

A EN 61032:1998, Protection of persons and equipment by enclosures — Probes for verification (IEC 61032:1997) A

EN ISO 354:2003, Acoustics — Measurement of sound absorption in a reverberation room (ISO 354:2003).

EN ISO 3744:1995, Acoustics — Determination of sound power levels of noise sources using sound pressure — Engineering method in an essentially free field over a reflecting plane (ISO 3744:1994).

EN ISO 11201:1995, Acoustics — Noise emitted by machinery and equipment — Measurement of emission sound pressure levels at a work station and at other specified positions — Engineering method in an essentially free field over a reflecting plane (ISO 11201:1995).

EN ISO 11688-1:1998, Acoustics — Recommended practice for the design of low-noise machinery and equipment — Part 1: Planning (ISO/TR 11688-1:1995).

EN ISO 12100-1:2003, Safety of machinery — Basic concepts, general principles for design — Part 1: Basic terminology, methodology (ISO 12100-1:2003) DPREVIEW

EN ISO 12100-2:2003, Safety of machinery - Basic concepts, general principles for design — Part 2: Technical principles (ISO 12100-2:2003)

EN ISO 13849-1:2008, Safety of machinery Safety-related parts of control systems — Part 1: General principles for design (ISO 13849-1:2006) and add sist d5455601-6d0d-4c21-9542-b65d9325be1c/sist-en-13683-2004a2-2011

EN ISO 13857:2008, Safety of machinery — Safety distances to prevent hazard zones being reached by upper and lower limbs (ISO 13857:2008) (A)

ISO 3767-1:1998, Tractors, machinery for agriculture and forestry, powered lawn and garden equipment — Symbols for operator controls and other displays — Part 1: Common symbols.

ISO 3767-3:1995, Tractors, machinery for agriculture and forestry, powered lawn and garden equipment — Symbols for operator controls and other displays — Part 3: Symbols for powered lawn and garden equipment.

ISO 3767-4:1993, Tractors, machinery for agriculture and forestry, powered lawn and garden equipment — Symbols for operator controls and other displays — Part 4: Symbols for forestry machinery.

ISO 3864-1:2002, Graphical symbols — Safety colours and safety signs — Part 1: Design principles for safety signs in workplaces and public areas.

ISO 11684:1995, Tractors, machinery for agriculture and forestry, powered lawn and garden equipment — Safety signs and hazard pictorials — General principles.

3 Terms and definitions

For the purposes of this European Standard, the terms and definitions given in EN 1070:1998 and the following apply.

3.1

discharge chute

extension of the opening through which the shredded or chipped material is discharged

3.2

discharge zone

any space wherein material is intended to be ejected from the machine

3.3

exhaust system

means of conveying exhaust gases from the power source to the atmosphere

3.4

feed safety opening

opening through which material is passed located at the relevant safety distance from the cutting means. This may be the same as the feed intake opening (3.5) or at some point between the feed intake opening and the cutting means. It is W in Table 1

3.5

feed intake opening

opening through which material is inserted to be fed to the cutting mechanism. A feed intake opening can become feed safety opening(s) if the relevant safety distance from the cutting means is met

3.6

normal operation

any use of the machine which is specified by the manufacturer, and which is consistent with such activities as reducing organic material, starting, stopping, and fuelling

(standards.iteh.ai)

3.7

normal use

normal operation, plus routine maintenance, servicing, cleaning, transporting, attaching or removing accessories, and making adjustments as determined by the manufacturer's instructions 9542-b65d9325be1c/sist-en-13683-2004a2-2011

3.8

material discharge deflector

fixed or movable component used to direct the flow of processed material discharging from the machine

3.9

maximum operating speed

highest power source speed obtainable when adjusted in accordance with manufacturer's specifications and/or instructions with the cutting means engaged

A2 3.10

operator presence control

device that automatically interrupts power to the cutting means when the operator's actuating force is removed $\langle\!\!\!A_2\!\!\!$

3.11

power source

engine or motor which provides energy for linear or rotational movement

3.12

screen (grid)

perforated metal piece or bar(s) located between the cutting means and discharge chute or opening of the machine to assist in reducing bulk organic materials to smaller pieces

3.13 shredder/chipper

Key

1

2

machine designed for use in a stationary position having one or more cutting means for the purpose of reducing organic materials to smaller pieces. See Figures 1, 2 and 3





Key

- 1 Feed intake opening
- 2 Discharge chute

iTeh STANDARD PREVIEW (standrigde2iteh.ai)



Key

- 1 Feed intake opening
- 2 Discharge chute

Figure 3

Figures 1, 2 and 3 — Examples of typical shredders/chippers

4 List of significant hazards

This clause contains for defined danger zones all the significant hazards, hazardous situations and events, as far as they are dealt with in this standard, identified by risk assessment as significant for these types of machines and which require specific action by the designer or manufacturer to eliminate or to reduce the risk (see Table 1). It is the responsibility of the manufacturer to check whether or not the safety requirements recommended by the standard apply to each significant hazard presented by its specific machine and to validate that the risk assessment is complete with particular attention to:

- intended use of the machine including maintenance, setting and cleaning and its reasonably foreseeable misuse;
- identification of all significant hazards associated with the machine.

Ref. No.	Hazard	Location or event	Reference of this standard			
Hazards	Hazards, hazardous situations and hazardous events					
	Mechanical hazards due to:					
	- machine parts or workpieces, e.g.:					
	a) relative location;	Safe positioning of the machine	76.1; annex D			
	b) mass and velocity (kinetic energy of elements in controlled or uncontrolled motion);	Dynamic stability of machine	5.9.4			
	c) inadequacy of mechanical strength;	Guard failure/strength	5.2.3.2			
1.3	Cutting or severing hazard SIST EN 136 https://standards.iteh.ai/catalog/s	8 Feeding Amaterial into the tr machine sist/d5455601-6d0d-4c2	5.2.1; 6.1; annex D 1-			
	9542-b65d9325be1c/s	Clearing processed material from discharge chute	5.2.2; 6.1; annex D			
1.4	Entanglement hazard	Feeding material into the cutting means	6.1; 6.2; annex D			
1.5	Drawing-in or trapping hazard	Feeding material into the cutting means	5.2.1; 6.1; annex D			
1.6	Impact hazard	Thrown objects	5.2.3.1; 5.9.2; 6.1; annex D			
2	Electrical hazards due to:					
2.1	Contact of persons with live parts (direct contact)	High voltage and ignition parts	5.6.4			
2.2	Contact of persons with parts which have become live under faulty conditions (indirect contact)	Damage caused by oil, fuel, abrasion etc	5.6.2.1			
3	Thermal hazards, resulting in:					
3.1	Burns, scalds and other injuries by a possible contact of persons with objects or materials with an extreme high or low temperature, by flames or explosions and also by the radiation of heat sources	Contact with hot parts	5.3			
4	Hazards generated by noise, resulting in:					
4.1	Hearing loss (deafness), other physiological disorders (e.g. loss of balance, loss of awareness)	Hearing damage due to machine and/or processing of material	5.10; 6.1; 6.2; annexes D, F and G			

Table 1 — List of significant hazards associated with shredders/chippers

Table 1 (continued) — List of significant hazards associated with shredders/chippers

nd annex D						
nd annex D						
nnex D						
nnex D						
annex D						
< D						
nnex D						
6.2; annex D						
1; annex D						
annex D						
¢D						
Additional hazards, hazardous situations and hazardous events due to mobility						
7						
annex D						
< D						

5 Safety requirements and/or measures

5.1 General

The machine shall comply with the safety requirements and/or protective measures of this clause. In addition, the machine shall be designed according to the principles of EN ISO 12100 for hazards relevant but not significant, which are not dealt with by this document (e.g. sharp edges on the outside of the machine).

5.2 Access to power driven components

5.2.1 Feed safety openings

5.2.1.1 General

To safeguard against contact with the cutting means through the feed safety opening(s) the machine shall either:

- be constructed to meet the dimensional requirements given in 5.2.1.2 or 5.2.1.3 and Table 2, or
- if a straight rod of 1 m length and 12 mm diameter will not pass through the opening to contact the cutting means the tortuous path test of 5.2.1.4 shall apply.

Where a feed intake opening is divided into two or more feed safety openings, the device that creates the division shall be rigid and permanently attached to the feed intake opening.

5.2.1.2 Dimensional requirements - Single feed safety openings

Where a safety opening is a slot, square or round the safety opening shall, as a minimum be in accordance with Table 2.

Where a feed safety opening is of an irregular shape, the size of opening shall be established by:

- a) determining:
 - the diameter of the smallest round opening and
 - the side of the smallest square opening and
 - the width of the narrowest slot opening

into which the irregular opening can be completely inserted (see EN ISO 13857:2008, Figure 3);

b) selecting the corresponding three minimum safety distances according to Table 2.

The shortest safety distance of the three values selected according to b) may be used.

Verification

The measured dimensions of the safety openings, as defined in this clause, and safety distances shall comply with Table 2.