

## SLOVENSKI STANDARD SIST EN 14276-1:2007+A1:2011

01-maj-2011

#### Tlačna oprema za hladilne sisteme in toplotne črpalke - 1. del: Posode - Splošne zahteve

Pressure equipment for refrigerating systems and heat pumps - Part 1: Vessels -General requirements

Druckgeräte für Kälteanlagen und Wärmepumpen - Teil 1: Behälter - Allgemeine Anforderungen iTeh STANDARD PREVIEW

(standards.iteh.ai)
Equipements sous pression pour systèmes de réfrigération et pompes à chaleur - Partie 1: Récipients - Exigences générales : Récipients - Récipients

https://standards.iteh.ai/catalog/standards/sist/a44460f0-e5e1-4441-8c58-

Ta slovenski standard je istoveten z: EN 14276-1-2007a1-2011

ICS:

23.020.30 Tlačne posode, plinske Pressure vessels, gas

> jeklenke cylinders

27.080 Toplotne črpalke Heat pumps

27.200 Hladilna tehnologija Refrigerating technology

SIST EN 14276-1:2007+A1:2011 en,fr,de SIST EN 14276-1:2007+A1:2011

# iTeh STANDARD PREVIEW (standards.iteh.ai)

1f079b681028/sist-en-14276-1-2007a1-2011

<u>SIST EN 14276-1:2007+A1:2011</u> https://standards.iteh.ai/catalog/standards/sist/a44460f0-e5e1-4441-8c58EUROPEAN STANDARD NORME EUROPÉENNE

**EUROPÄISCHE NORM** 

EN 14276-1:2006+A1

February 2011

ICS 23.020.30; 27.080; 27.200

Supersedes EN 14276-1:2006

#### **English Version**

## Pressure equipment for refrigerating systems and heat pumps -Part 1: Vessels - General requirements

Equipements sous pression pour systèmes de réfrigération et pompes à chaleur - Partie 1: Récipients - Exigences générales

Druckgeräte für Kälteanlagen und Wärmepumpen - Teil 1: Behälter - Allgemeine Anforderungen

This European Standard was approved by CEN on 24 May 2006 and includes Amendment 1 approved by CEN on 13 December 2010.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

SIST EN 14276-1:2007+A1:2011

https://standards.iteh.ai/catalog/standards/sist/a44460f0-e5e1-4441-8c58-1f079b681028/sist-en-14276-1-2007a1-2011



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

## **Contents**

Forew	vord	4
Introd	luction	5
1	Scope	6
2	Normative references	6
3	Terms and definitions	8
3.1	Definitions	8
3.2	Symbols, quantities and units	11
4	Materials	13
4.1	General	13
4.2	Requirements for materials to be used for pressurised parts	14
4.3	Requirements for materials	14
4.4	Requirements for prevention of brittle fracture	15
4.5	Material documentation	16
4.6	Materials for non-pressure retaining parts	16
5	Pressure Vessel classification	16
5.1	Category of vessel TEN STANDARD PREVIEW	16
5.2	Fluid classification (standards.iteh.ai)	17
6	Design	17
6.1	SIST EN 14276-1:2007+A1:2011  Generalhttps://standards.itch.ui/catalog/standards/sist/u44460f0-e5e1-4441-8c58	17
6.2	Corrosion and corrosion protection 81028/sist-en-14276-1-2007a1-2011	17
6.3	Stress corrosion cracking	18
6.4	Loading	18
6.5	Maximum allowable pressure PS	18
6.6	Design pressure $P_{ m d}$	18
6.7	Calculation pressure P or P <sub>c</sub>	19
6.8	Design temperature $t_{\rm d}$	19
6.9	Minimum material temperature	19
6.10	Calculation temperature tc	19
6.11	Joint coefficient	20
6.12	Design stress	21
6.13	Access and inspection openings, venting and draining provisions, filling and discharge provisions and handling devices	22
6.14	Methods for design	23
7	Manufacturing	28
7.1	General	28
7.2	Material traceability	28
7.3	Manufacturing tolerances	28
7.4	Permanent joints	28
7.5	Forming of pressure parts	33
^		

7.6	Post weld heat treatment	34
7.7	Internal cleanness	34
7.8	Repairs/Reworks	34
7.9	Finishing operations	34
8	Testing and inspection	35
8.1	Performance of inspection and testing	35
8.2	Design documentation, review and approval	35
8.3	Type approval	37
8.4	Calibration	37
8.5	Material	37
8.6	Manufacturing	38
8.7	Non destructive testing	38
8.8	Subcontracted elements	38
8.9	Final inspection	38
8.10	Marking	39
8.11	Documentation	40
Annex	A (normative) Alternative requirements for prevention of brittle fracture: Method according to temperature stress cases	42
Annex	B (normative) Specification and approval of brazing procedures, brazers and brazing operators	46
	C (normative) Pressure testing	
<b>Annex</b>	D (informative) Relations between the different pressures of a set -4441-8658-	64
Annex	E (normative) Experimental methods 1/079b681028/sist-en-14276-1-2007a1-2011	65
Annex	F (normative) Material characteristics for design	70
Annex	G (informative) Component classification in the sense of the Pressure Equipment Directive (PED)	72
Annex	H (informative) Selection of module of conformity	73
Annex	I (normative) Grouping system for materials	75
Annex	J (informative) DN System	77
Annex	K (normative) Specification and approval of expansion procedures and operators	78
Annex	ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 97/23/EC	84
Bibliog	graphy	86

#### **Foreword**

This document (EN 14276-1:2006+A1:2011) has been prepared by Technical Committee CEN/TC 182 "Refrigerating systems, safety and environmental requirements", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by August 2011, and conflicting national standards shall be withdrawn at the latest by August 2011.

This document includes Amendment 1, approved by CEN on 2010-12-13.

This document supersedes EN 14276-1:2006.

The start and finish of text introduced or altered by amendment is indicated in the text by tags [A]

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association to support Essential Requirements of EU Directive 97/23/EC concerning Pressure Equipment.

For relationship with EU Directive 97/23/EC see informative Annex ZA, which is an integral part of this document.

This document consists of the following parts under the general title "Pressure equipment for refrigerating systems and heat pumps": https://standards.iteh.ai/catalog/standards/sist/a44460f0-e5e1-4441-8c58
1f079b681028/sist-en-14276-1-2007a1-2011

- Part 1: Vessels General requirements
- Part 2: Piping General requirements

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

## Introduction

This standard recognises the unique nature of vessels for refrigerating systems or heat pumps and is intended to address the specific needs of the refrigeration and heat pump industry. This standard should be read in conjunction with the various parts of EN 13445.

When the text of this standard modifies or supplements a clause within EN 13445, then this standard should prevail. Where this standard does not modify or supplement the requirements of a clause, the requirements of EN 13445 should prevail.

The unique nature of a refrigerating system is defined as follows:

- a) the purpose of the refrigerating system is to extract and reject heat (this involves both cooling and heating);
- b) to operate the refrigerating system a pressure-imposing element (e.g. a compressor or an energy source) is necessary;
- c) the refrigerating system has a defined refrigerant charge in a closed circuit;
- d) the refrigerant has a chemical composition and purity defined in the relevant standards;
- e) the pressure of the refrigerant decreases when the temperature decreases (see typical curve in Annex A of this standard);
- f) due to the maximum temperature limit of 200 °C and the maximum pressure limit of 64 bar, the time dependant creep and fatigue due to pressure variation or vibrations are not significant design factors except for some materials such as aluminium, copper and titanium where the fatigue shall be taken into account;
- g) the risk of overpressure is due to:

SIST EN 14276-1:2007+A1:2011

- the pressure imposing element; iteh.ai/catalog/standards/sist/a44460f0-e5e1-4441-8c58-
- an external heat source (e.g. life or hot water);1-14276-1-2007a1-2011
- improper operation.
- h) the refrigerating system is designed to minimise refrigerant emissions and the ingress of contaminants.

Only hermetic compressors are covered by this standard.

#### Scope

This European Standard specifies the requirements for material, design, manufacturing, testing and documentation for stationary pressure vessels intended for use in refrigerating systems and heat pumps. These systems are referenced in this standard as refrigerating systems as defined in EN 378-1.

This European Standard applies to vessels including welded or brazed attachments up to and including the nozzle flanges, screwed, welded or brazed connectors or to the edge to be welded or brazed at the first circumferential joint connecting piping or other elements.

This European Standard applies to pressure vessels with an internal pressure down to - 1 bar, to account for the evacuation of the vessel prior to charging with refrigerant.

This European Standard applies to both the mechanical loading conditions and thermal conditions as defined in EN 13445-3 associated with refrigerating systems. It applies to pressure vessels subject to the maximum allowable temperatures for which nominal design stresses for materials are derived using EN 13445-2 and EN 13445-3 or as specified in this standard. In addition vessels designed to this standard should have a maximum design temperature not exceeding 200 °C and a maximum design pressure not exceeding 64 bars. Outside of these limits, it is important that EN 13445 be used for the design, construction and inspection of the vessel. Under these circumstances it is important that the unique nature of refrigerating plant, as indicated in the introduction to this standard, also be taken into account.

It is important that pressure vessels used in refrigerating systems and heat pumps of category less than II as defined in Annex H comply with other relevant clauses of EN 378-2 for vessels.

This European Standard applies to pressure vessels where the main pressure bearing parts are manufactured from metallic ductile materials as defined in Clause 4 and Annex I of this standard.

standards.iteh.ail This European Standard does not apply to vessels of the following types:

- SIST EN 14276-1:2007+A1:2011
- vessels of riveted construction:
   vessels o
  - 1f079b681028/sist-en-14276-1-2007a1-2011
- multilayered, autofrettaged or prestressed vessels;
- vessels directly heated by a flame;
- « roll bond » heat exchangers.

#### Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 287-1:2004, Qualification test of welders — Fusion welding — Part 1: Steels

A EN 378-1:2008+A1:2010, Refrigerating systems and heat pumps — Safety and environmental requirements — Part 1: Basic requirements, definitions, classification and selection criteria

EN 378-2:2008+A1:2009, Refrigerating systems and heat pumps — Safety and environmental requirements — Part 2: Design, construction, testing, marking and documentation

EN 378-4:2008, Refrigerating systems and heat pumps — Safety and environmental requirements — Part 4: Operation, maintenance, repair and recovery (41)

EN 764-1:2004, Pressure equipment — Part 1: Terminology — Pressure, temperature, volume, nominal size

EN 764-2:2002, Pressure equipment — Part 2: Quantities, symbols and units

EN 764-3:2002, Pressure equipment — Part 3: Definition of parties involved

EN 764-4:2002, Pressure equipment — Part 4: Establishment of technical delivery conditions for metallic materials

EN 764-5:2002, Pressure equipment — Part 5: Compliance and inspection documentation of materials

EN 837-1:1996, Pressure gauges — Part 1: Bourdon tube pressure gauges — Dimensions, metrology, requirements and testing

EN 910:1996, Destructive tests on welds in metallic materials — Bend tests

EN 1005-2:2003+A1:2008, Safety of machinery — Human physical performance — Part 2: Manual handling of machinery and component parts of machinery [A]

A1) deleted text (A1)

EN 1045:1997, Brazing — Fluxes for brazing — Classification and technical delivery conditions

A EN 1173:2008, Copper and copper alloys — Material condition designation

EN 1418:1997, Welding personnel — Approval testing of welding operators for fusion welding and resistance weld setters for fully mechanized and automatic welding of metallic materials

A<sub>1</sub>) deleted text (A<sub>1</sub>

EN 10111:2008, Continuously not-rolled low carbon steel sheet and strip for cold forming — Technical delivery conditions
 (standards.iteh.ai)

EN 10130:2006, Cold-rolled low carbon steel flat products for cold forming — Technical delivery conditions &

EN 10160:1999, Ultrasonic testing of steel flat product of thickness equal or greater than 6 mm (reflection method)

EN 10164:2004, Steel products with improved deformation properties perpendicular to the surface of the product — Technical delivery conditions

EN 10204:2004, Metallic products — Types of inspection documents

(A) EN 12517-1:2006, Non-destructive testing of welds — Part 1: Evaluation of welded joints in steel, nickel, titanium and their alloys by radiography — Acceptance levels (A)

EN 12797:2000 + A1:2003, Brazing — Destructive tests of brazed joints

EN 12799:2000 + A1:2003, Brazing — Non-destructive examination of brazed joints

(A) EN 13445-2:2009, Unfired pressure vessels — Part 2: Materials

EN 13445-3:2009, Unfired pressure vessels — Part 3: Design

EN 13445-4:2009, Unfired pressure vessels — Part 4: Fabrication

EN 13445-5:2009, Unfired pressure vessels — Part 5: Inspection and testing

EN 13445-6:2009, Unfired pressure vessels — Part 6: Requirements for the design and fabrication of pressure vessels and pressure vessel parts constructed from spheroidal graphite cast iron

EN 13445-8:2009, Unfired pressure vessels — Part 8: Additional requirements for pressure vessels of aluminium and aluminium alloys (A)

EN 22553:1994, Welded, brazed and soldered joints — Symbolic representation on drawings (ISO 2553:1992)

EN ISO 3677:1995, Filler metal for soft soldering, brazing and braze welding — Designation (ISO 3677:1992)

♠ EN ISO 4063:2009, Welding and allied processes — Nomenclature of processes and reference numbers (ISO 4063:2009) ♠

EN ISO 5817:2007, Welding — Fusion-welded joints in steel, nickel, titanium and their alloys (beam welding excluded) — Quality levels for imperfections (ISO 5817:2003, corrected version:2005, including Technical Corrigendum 1:2006) [4]

EN ISO 6892-1:2009, Metallic materials — Tensile testing — Part 1: Method of test at room temperature (ISO 6892-1:2009) (ISO 6892-1:2009)

EN ISO 7438:2005, Metallic materials — Bend test (ISO 7438:2005)

EN ISO 10012:2003, Measurement management systems — Requirements for measurement processes and measuring equipment (ISO 10012:2003)

EN ISO 15607:2003, Specification and qualification of welding procedures for metallic materials — General rules (ISO 15607:2003)

EN ISO 15609-1:2004, Specification and qualification of welding procedures for metallic materials — Welding procedure specification — Part 1: Arc welding (ISO 15609-1:2004)

EN ISO 15611:2003, Specification and qualification of welding procedures for metallic materials — Qualification based on previous welding experience (ISO 15611:2003)

Teh STANDARD PREVIEW

EN ISO 15612:2004, Specification and qualification of welding procedures for metallic materials — Qualification by adoption of a standard welding procedure (ISO 15612:2004) S. Iteh. a)

EN ISO 15614-1:2004, Specification and qualification of welding procedures for metallic materials — Welding procedure test — Part 1: Arc and gas welding of steels and arc welding of nickel and nickel alloys (ISO 15614-1:2004)

EN ISO 15614-8:2002, Specification and qualification of welding procedures for metallic materials — Welding procedure test — Part 8: Welding of tubes to tube-plate joints (ISO 15614-8:2002)

(ISO 17672:2010, Brazing — Filler metals (ISO 17672:2010)

ISO 817:2005, Refrigerants — Designation system

ISO 857-1:1998, Welding and allied processes — Vocabulary — Part 1: Metal welding processes

ISO 5187:1985, Welding and allied processes — Assemblies made with soft solders and brazing filler metals — Mechanical test methods

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 378-1:2008+A1:2010, EN 764-1:2004, EN 764-2:2002, EN 764-3:2002, EN 764-4:2002, EN 764-5:2002, ISO 857-1:1998 and the following apply.

#### 3.1 Definitions

#### 3.1.1 Temperatures stress cases

#### 3.1.1.1

min  $t_{0.100}$ 

lowest temperature at which pressurised parts are allowed to be used at a stress of up to 100 % of the design stress at 20 °C (standard design stress)

#### 3.1.1.2

#### $min t_0 75$

lowest temperature at which pressurised parts are allowed to be used when their stress is a maximum of 75 % of the design stress at 20 °C (reduced stress)

#### 3.1.1.3

#### $\min t_{0.50}$

lowest temperature at which pressurised parts are allowed to be used when their stress is a maximum of 50 % of the design stress at 20 °C (medium stress)

#### 3.1.1.4

#### $\min t_{0.25}$

lowest temperature at which pressurised parts are allowed to be used when their stress is a maximum of 25 % of the design stress at 20 °C (low stress)

#### 3.1.2

#### corrosion

all forms of material wastage (e.g. oxidation, erosion, wear and abrasion)

#### A<sub>1</sub> 3.1.3

#### safety data sheet

document which gives all necessary information for prevention, safety, storage, transportation, labelling, use and disposal of substances and preparations which have a risk for health, safety or environment (A)

#### 3.1.4

## maximum design temperature eh STANDARD PREVIEW

highest temperature that can occur during operation or standstill of the refrigerating system or during testing under test conditions (standards.iteh.ai)

NOTE This temperature is equivalent to the maximum allowable temperature as defined in article 1.2.4 of the PED.

SISTEN 14276-1:2007+A1:2011

### 3.1.5 https://standards.iteh.ai/catalog/standards/sist/a44460f0-e5e1-4441-8c58-

### minimum design temperature 1f079b681028/sist-en-14276-1-2007a1-2011

lowest temperature that can occur during operation or standstill of the refrigerating system or during testing under test conditions

NOTE This temperature is equivalent to the minimum allowable temperature as defined in article 1.2.4 of the PED.

#### 3.1.6

#### main pressure bearing part

components of the vessel retaining the pressure and contributing to the vessel strength such as shell, tubesheet, end plate, dished ends, connection or fitting

#### 3.1.7

#### volume

internal volume of a compartment ready for operation, including the volume of nozzles to the first connection (flange, coupling, weld, braze) and excluding the volume of permanent internal part

#### 3.1.8

#### « roll bond » heat exchanger

heat exchanger consisting of two plates which are weld-bonded together with the exception of the printed circuit forming the refrigerant passage which is obtained by inflation under pressure

#### 3.1.9

#### maximum operating pressure

maximum pressure which the vessel can withstand without the operation of any safety accessory with a continuous operation of the pressure generator (compressor, heat source...)

NOTE This pressure determines the maximum operating conditions for equipment users.

#### 3.1.10


#### maximum standstill pressure

maximum pressure which the vessel can withstand without operation of any safety accessory when the pressure generator is not in operation. This pressure occurs during transportation, storage or shut down of the pressure generator

#### 3.1.11

#### deep drawing

process of forming by stamping when the ratio of depth (H) by diameter (D) is greater than or equal to 0,45, see Figure 1



#### Key

H depth D diameter

## iTeh STigure 1D Deep drawing EVIEW

#### 3.1.12

## (standards.iteh.ai)

#### manual brazing

brazing operation performed and controlled by hand 14276-1:2007+A1:2011

#### 3.1.13

semi-automatic brazing

https://standards.iteh.ai/catalog/standards/sist/a44460f0-e5e1-4441-8c58-1f079b681028/sist-en-14276-1-2007a1-2011

brazing with equipment which controls only the brazing filler metal feed.

NOTE The advance of the brazing is manually controlled

#### 3.1.14

#### machine brazing

brazing with equipment which performs the brazing operation under the constant control of a brazing operator

#### 3.1.15

#### automatic brazing

brazing with equipment which performs the brazing operation without constant observation and adjustment by a brazing operator

#### 3.1.16

#### brazer

person who performs a manual or semiautomatic brazing operation

#### 3.1.17

#### brazing operator

person who operates a machine or automatic brazing equipment

#### 3.1.18

#### semiautomatic expansion

expansion with equipment which controls the operation and where the operator manually introduces the equipment to the inside of the tube

#### 3.1.19

#### machine expansion

expansion with equipment which performs the expansion operation under the constant control of operator

#### 3.1.20

#### automatic expansion

expansion with equipment which performs the expansion operation without constant observation and adjustment by an expansion operator

#### 3.1.21

#### expansion operator

person who makes an expansion joint

#### 3.1.22

#### rolling

plastic cold forming of tubes by means of a tool which have several rolls turning during the operation

#### 3.2 Symbols, quantities and units

Symbols, quantities and units used in this standard are listed in Table 1.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 14276-1:2007+A1:2011 https://standards.iteh.ai/catalog/standards/sist/a44460f0-e5e1-4441-8c58-1f079b681028/sist-en-14276-1-2007a1-2011

Table 1 — Symbols, quantities and units

Symbol	Quantity	Unit
A	elongation after fracture	%
$A_{t}$	strengthened area tube side	mm²
$A_{ m V}$	strengthened	mm²
$A_{ m W}$	effective area of expanded joint	mm²
С	corrosion allowance	mm
$d_{tube}$	nominal outside diameter of tubes	mm
$d_{e}$	external diameter of tube	mm
$d_{\mathrm{i}}$	internal diameter of tube	mm
$D_{\mathrm{s}}$	internal shell diameter	mm
DN	Nominal diameter	_
e	thickness	mm
$e_{act}$	actual thickness	mm
$e_{\mathrm{b}}$	brazing joint size of tube in the tubesheet	mm
$e_{ m W}$	welding joint size of tube in the tubesheet	mm
$e_{\rm n}$	nominal thickness ANDARD PREVIEW	mm
$E_{tube}$	Elasticity modulus for tube material at design temperature	MPa
f	nominal design stress at design temperature	MPa
$f_{tube}$	nominal design stress of tube material at design temperature 1°Cc58-	MPa
$f_{ttest}$	nominal design stress at test temperature to c 2007a1-2011	MPa
$F_{ m s}$	tube force generated by shell side	N
$F_{tube}$	tube force generated by tube side	N
$l_{\mathrm{tx}}$	expanded length on tube inside tubesheet	mm
$l_{ m k}$	unsupported tube length	mm
$L_0$	gauge length for tensile test	mm
$N_{tube}$	Number of tube for a tubular heat exchanger	_
p	tube pitch for tubesheet	mm
$P_{\rm c}$	calculation pressure (in formula, $P_c$ can be replaced by $P$ )	MPa or bar <sup>a</sup>
$P_{d}$	design pressure	MPa or bar <sup>a</sup>
$P_{(max)}$	maximum design pressure	MPa or bar <sup>a</sup>
PS	maximum allowable pressure	MPa or bar <sup>a</sup>
$P_{test}$	test pressure	MPa or bar <sup>a</sup>
$P_{\rm v}$	shell side calculation pressure	MPa or bar <sup>a</sup>
$P_{tube}$	tube side calculation pressure	MPa or bara
PED	Pressure Equipment Directive n° 97/23/EC	_
$Q_{tube}$	tube force due to tube side	N
$Q_{ m V}$	tube force due to tubesheet	N

Table 1 (continued)

Symbol	Quantity	Unit			
$R_{ m eH}$	upper yield strength	MPa			
R <sub>m</sub>	tensile strength	MPa			
$R_{ m mmin}$	minimum tensile strength	MPa			
$R_{ m m \ avg}$	average value of tensile strength of several test specimens	MPa			
$R_{ m mmax}$	maximum tensile strength specified in the standard	MPa			
$R_{\mathrm{m/t}}$	tensile strength at temperature t °C	MPa			
R <sub>m/ttest</sub>	tensile strength at test temperature t °C	MPa			
$R_{ m p \ avg}$	average value of proof strength of several test specimens	MPa			
$R_{\rm p0,2}$	0,2 % proof strength	MPa			
R <sub>p0,2/t</sub>	0,2 % proof strength at temperature t °C	MPa			
R <sub>p0,2/ttest</sub>	0,2 % proof strength at test temperature t °C	MPa			
R <sub>p1,0</sub>	1,0 % proof strength	MPa			
R <sub>p1,0/t</sub>	1,0 % proof strength at temperature t °C	MPa			
R <sub>p1,0/ttest</sub>	1,0 % proof strength at test temperature t °C	MPa			
$S_0$	original cross section area NDARD PREVIEW	mm <sup>2</sup>			
$S_{ m F}$	safety factor (standards.iteh.ai)	_			
$t_{ m c}$	calculation temperature	°C			
$t_{ m d}$	design temperature SIST EN 14276-12007+A1:2011	°C			
$t_{ m ha}$	temperature of heat absorbing fluid 14276-1-2007a1-2011	°C			
$t_{ m he}$	temperature of heat emitting fluid	°C			
z	joint coefficient	_			
α	thermal expansion	_			
$\delta_{ m e}$	negative wall thickness tolerance	mm			
ν	Poisson's ratio	_			
μ	basic ligament efficiency of the tubesheet	_			
<sup>a</sup> 1 bar = 100 000	a 1 bar = 100 000 Pa = 0,1 MPa = 0,1 N/mm <sup>2</sup>				

#### 4 Materials

#### 4.1 General

The requirements for materials referenced in this standard shall conform to EN 13445-2, unless modified by the clauses of this section. This standard or reference to other relevant standards shall cover materials not included in EN 13445-2.

It is permitted to use non-metallic materials (e.g. gaskets, coatings, insulating materials, sightglasses) provided they are compatible with the other materials, refrigerants and lubricants present.