



# SLOVENSKI STANDARD

## SIST ISO 2859-4:2010

01-julij-2010

---

**Postopki vzorčenja za kontrolo po opisnih spremenljivkah - 4. del: Postopki za ugotavljanje deklariranih ravni kakovosti**

Sampling procedures for inspection by attributes -- Part 4: Procedures for assessment of declared quality levels

### iTeh STANDARD PREVIEW

Règles d'échantillonnage pour les contrôles par attributs -- Partie 4: Procédures pour l'évaluation des niveaux déclarés de qualité

[SIST ISO 2859-4:2010](https://standards.itih.ai/catalog/standards/sist/d281961e-bad2-4b9a-a946-51c5cb60353c/sist-iso-2859-4-2010)

**Ta slovenski standard je istoveten z: ISO 2859-4:2002**

---

**ICS:**

03.120.30	Uporaba statističnih metod	Application of statistical methods
-----------	----------------------------	------------------------------------

**SIST ISO 2859-4:2010**

**en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST ISO 2859-4:2010

<https://standards.iteh.ai/catalog/standards/sist/d281961e-bad2-4b9a-a946-5fe3eb60353c/sist-iso-2859-4-2010>

# INTERNATIONAL STANDARD

**ISO**  
**2859-4**

Second edition  
2002-08-01

---

---

## Sampling procedures for inspection by attributes —

### Part 4: Procedures for assessment of declared quality levels

iTeh **STANDARD PREVIEW**

*Règles d'échantillonnage pour les contrôles par attributs —*

**(standards.iteh.ai)**

*Partie 4: Procédures pour l'évaluation des niveaux déclarés de qualité*

[SIST ISO 2859-4:2010](https://standards.iteh.ai/catalog/standards/sist/d281961e-bad2-4b9a-a946-5fe3eb60353c/sist-iso-2859-4-2010)

<https://standards.iteh.ai/catalog/standards/sist/d281961e-bad2-4b9a-a946-5fe3eb60353c/sist-iso-2859-4-2010>



Reference number  
ISO 2859-4:2002(E)

© ISO 2002

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 2859-4:2010](https://standards.iteh.ai/catalog/standards/sist/d281961e-bad2-4b9a-a946-5fe3eb60353c/sist-iso-2859-4-2010)

<https://standards.iteh.ai/catalog/standards/sist/d281961e-bad2-4b9a-a946-5fe3eb60353c/sist-iso-2859-4-2010>

© ISO 2002

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.ch](mailto:copyright@iso.ch)  
Web [www.iso.ch](http://www.iso.ch)

Printed in Switzerland

**Contents**

	Page
1 Scope .....	1
2 Normative references .....	2
3 Terms, definitions, symbols and abbreviations .....	2
4 Principles .....	3
5 Declared quality level (DQL) .....	4
6 Sampling plans .....	4
7 Operating a sampling plan .....	6
8 Further information .....	7

**Annex**

A Examples of use of the procedures .....	11
A.1 Example 1 .....	11
A.2 Example 2 .....	11
A.3 Example 3 .....	11

**ITeH STANDARD PREVIEW**  
(standards.iteh.ai)

[SIST ISO 2859-4:2010](https://standards.iteh.ai/catalog/standards/sist/d281961e-bad2-4b9a-a946-5fe3eb60353c/sist-iso-2859-4-2010)

<https://standards.iteh.ai/catalog/standards/sist/d281961e-bad2-4b9a-a946-5fe3eb60353c/sist-iso-2859-4-2010>

## ISO 2859-4:2002(E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO 2859 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 2859-4 was prepared by Technical Committee ISO/TC 69, *Applications of statistical methods*, Subcommittee SC 5, *Acceptance sampling*.

This second edition cancels and replaces the first edition (ISO 2859-4:1999), which has been technically revised.

ISO 2859 consists of the following parts, under the general title *Sampling procedures for inspection by attributes*:

- *Part 0: Introduction to the ISO 2859 attribute sampling system*
- *Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection*
- *Part 2: Sampling plans indexed by limiting quality (LQ) for isolated lot inspection*
- *Part 3: Skip-lot sampling procedures*
- *Part 4: Procedures for assessment of declared quality levels*

Annex A of this part of ISO 2859 is for information only.

## Introduction

The procedures in this part of ISO 2859 differ in their scope from the procedures in ISO 2859 Parts 1 to 3. The system of acceptance sampling procedures that are specified in ISO 2859 Parts 1 to 3 are intended to be used in bilateral agreements between two parties. The acceptance sampling procedures are intended to be used as simple, pragmatic rules for releasing product after inspection of only a limited sample of a consignment, and therefore the procedures do not make reference (either explicitly or implicitly) to any formally declared quality level.

Under acceptance sampling there is no sharp borderline between quality levels that should be considered acceptable and qualities that should be rejected by the procedure. For the procedures in ISO 2859-1 the two parties agree upon some acceptance quality limit (AQL) which is the worst tolerable process average when a continuing series of lots is submitted. The switching rules and the sampling schemes in ISO 2859-1 are designed to encourage the suppliers to have process averages consistently better than the AQL selected. In order to keep sample sizes moderate, the protection against accepting individual lots of inferior quality may be less than that provided by sampling plans targeted for sentencing individual lots. The procedures in ISO 2859-2, on the contrary, are designed to provide good protection against accepting individual lots of inferior quality (LQ), but at the expense of a possible high risk of not accepting lots of qualities that both parties actually would consider to be acceptable.

Procedures in ISO 2859 Parts 1 to 3 are well suited for acceptance sampling purposes, but they should not be used in reviews, audits, etc. to verify a quality that has been declared for some entity. The main reason is that the procedures have been indexed in terms of quality levels that are relevant solely for the pragmatic purposes of acceptance sampling, and the various risks have been balanced accordingly.

The procedures in this part of ISO 2859 have been developed as a response to the growing need for sampling procedures suitable for formal, systematic inspections such as reviews or audits. When performing such a formal inspection, it is necessary for the authority to consider the risk of reaching an incorrect conclusion, and to take this risk into account in planning and executing the review/audit/testing, etc.

This part of ISO 2859 provides guidance and rules to assist the user in taking this risk into account in an informed manner.

The rules in this part of ISO 2859 have been devised such that there is only a small, limited risk of contradicting the declared quality level when in fact the actual level conforms to the declared level.

If it were also desired that there should be a similarly small risk of not contradicting the declared quality level when in fact the actual quality level does not conform to the declared quality level, then it would be necessary to investigate a rather large sample. Therefore, in order to obtain the benefit of a moderate sample size, the procedures in this part of ISO 2859 have been devised in such a way that they allow a somewhat higher risk of failing to contradict the declared quality level when in fact the actual quality level does not conform to the declared quality level.

The wording of the result of the assessment should reflect this unbalance between the risks of reaching incorrect conclusions.

When the sample result contradicts the declared quality level *there is strong evidence of nonconformance to the declared quality level.*

When the sample result does not contradict the declared quality level, this should be understood as “we have not, in this limited sample, found strong evidence of nonconformance to the declared quality level”.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST ISO 2859-4:2010

<https://standards.iteh.ai/catalog/standards/sist/d281961e-bad2-4b9a-a946-5fe3eb60353c/sist-iso-2859-4-2010>



# Sampling procedures for inspection by attributes —

## Part 4:

## Procedures for assessment of declared quality levels

### 1 Scope

This part of ISO 2859 establishes sampling plans and procedures that can be used to assess whether the quality level of an entity (lot, process, etc) conforms to a declared value. The sampling plans have been devised so as to obtain a risk of less than 5 % of contradicting a correct declared quality level. The risk is 10 % of failing to contradict an incorrect declared quality level which is related to the limiting quality ratio (see clause 4). Sampling plans are provided corresponding to three levels of discriminatory ability.

In contrast to the procedures in the other parts of ISO 2859, the procedures in this part of ISO 2859 are not applicable to acceptance assessment of lots. Generally, the balancing of the risks of reaching incorrect conclusions in assessment procedures will differ from the balancing in the procedures for acceptance sampling.

This part of ISO 2859 may be used for various forms of quality inspection in situations where objective evidence of conformity to some declared quality level is to be provided by means of inspection of a sample. The procedures are applicable to entities such as lots, process output, etc. that allow random samples of individual items to be taken from the entity.

The sampling plans provided in this part of ISO 2859 are applicable, but not limited, to inspection of a variety of products such as

- end items;
- components and raw materials;
- operations;
- materials in process;
- supplies in storage;
- maintenance operations;
- data or records;
- administrative procedures.

The procedures are primarily intended to be used when the quantity of interest is the number or fraction of nonconforming items for which the inspected items are classified as conforming or nonconforming.

With minor changes, the procedures may also be used when the quantity of interest is the number of nonconformities or number of nonconformities per item. The necessary changes are:

- replacement of “number of nonconforming items” by “number of nonconformities”;
- replacement of “percent nonconforming items” by “nonconformities per 100 items”.

In this case the values given in Tables 2 to 7 are only approximations.

## ISO 2859-4:2002(E)

## 2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO 2859. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO 2859 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 3534-1:1993, *Statistics — Vocabulary and symbols — Part 1: Probability and general statistical terms*

ISO 3534-2:1993, *Statistics — Vocabulary and symbols — Part 2: Statistical quality control*

ISO 9000:2000, *Quality management systems — Fundamentals and vocabulary*

## 3 Terms, definitions, symbols and abbreviations

### 3.1 Terms and definitions

For the purposes of this part of ISO 2859, the terms and definitions given in ISO 3534-1, ISO 3534-2 and ISO 9000 and the following apply.

#### 3.1.1

##### limiting number of nonconforming items

*L*

largest number of nonconforming items (or nonconformities) found in the sample from the entity under investigation that does not lead to contradiction of the declared quality level

#### 3.1.2

##### quality ratio

ratio of the actual to the declared quality level of the entity under investigation

#### 3.1.3

##### limiting quality ratio

**LQR**

value of the quality ratio that is limited to a small risk (10 % in this part of ISO 2859) of failing to contradict an incorrect declared quality level

### 3.2 Symbols and abbreviated terms

The symbols and abbreviated terms used in this part of ISO 2859 are as follows:

DQL Declared quality level

*L* Limiting number of nonconforming items in the sample

LQR Limiting quality ratio

*n* Sample size

## 4 Principles

In any assessment procedure based on sampling there will be an inherent uncertainty due to possible sampling fluctuations.

The procedures in this part of ISO 2859 have been conceived so as to lead to contradiction of the declared quality level only when there is sufficient evidence to support a conclusion that the actual quality is poorer than the declared quality level.

The procedures have been devised in such a way that when the actual quality level is equal to or better than the declared quality level, the risk is less than 5 % of contradicting the declared value. Consequently, when the actual quality level is worse than the declared quality level, there is a risk that the procedures will fail to contradict an incorrect declared quality level.

This risk depends on the value of the quality ratio, i.e. the ratio between the actual and the declared quality level. The limiting quality ratio, LQR, is introduced to denote the highest quality ratio considered tolerable. When the actual quality level is LQR times worse than the declared quality level, the procedures in this part of ISO 2859 have a risk of 10 % of failing to contradict the declared quality level (corresponding to a 90 % probability of contradicting the incorrect declared quality level).

Three LQR levels I, II and III are considered. Details of the three LQR levels provided in this part of ISO 2859 are given in 6.1.

The sampling plans provided in this part of ISO 2859 are indexed by the limiting quality ratio (LQR) level and the declared quality level (DQL) and are provided in Table 1.

**Table 1 — Master table of sampling plans**

DQL % nonconforming items	LQR level I		LQR level II		LQR level III	
	$n$	$L$	$n$	$L$	$n$	$L$
0,010	3 150	1	b ←		b ←	
0,015	2 000	1	b ←		b ←	
0,025	1 250	1	3 150	2	b ←	
0,040	800	1	2 000	2	3 150	3
0,065	500	1	1 250	2	2 000	3
0,100	315	1	800	2	1 250	3
0,150	200	1	500	2	800	3
0,250	125	1	315	2	500	3
0,400	80	1	200	2	315	3
0,65	50	1	125	2	200	3
1,0	32	1	80	2	125	3
1,5	20	1	50	2	80	3
2,5	13	1	32	2	50	3
4,0	a →		20	2	32	3
6,5	a →		13	2	20	3
10,0	a →		a →		13	3

The plans are indexed by the declared quality level (DQL) of nonconforming product and limiting quality ratio (LQR) levels.

a → Use the sampling plan to the right which corresponds to a smaller limiting quality ratio as no sampling plan exist for this level of the limiting quality ratio.

b ← Use the sampling plan to the left which corresponds to a higher limiting quality ratio as no sampling plan exists for this level of the limiting quality ratio.